

Edition 1.0 2024-04

INTERNATIONAL STANDARD



Railway applications – Rolling stock – Batteries for auxiliary power supply systems –

Part 3: Lead acid batteries

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.220.20; 45.040 ISBN 978-2-8322-8567-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	DREWO	PRD	5
1	Scop	e	7
2	Norm	native references	7
3	Term	s, definitions and abbreviated terms	8
	3.1	Terms and definitions	8
	3.2	Abbreviated terms	9
4	Gene	eral requirements	9
	4.1	Definitions of components of a battery system	9
	4.2	Description of lead acid battery types	. 10
	4.2.1		. 10
	4.2.2	Lead acid batteries with valve-regulated cell design and immobilized electrolyte	11
	4.3	Environmental conditions	
	4.4	System requirements	
	4.4.1	·	
	4.4.2		
	4.4.3	Discharging performances	.16
	4.4.4	Charge retention(self-discharge)	. 17
	4.4.5	Requirements for battery sizing	. 17
	4.5	Safety and protection requirements	. 18
	4.5.1		
	4.5.2	1 3	
	4.5.3		
	4.6	Fire protection	
	4.7	Maintenance	
5	4.8	Charging characteristics	
Э	•	onal components of a battery system	
	5.1	General	
	5.2 5.3	Battery information system Battery heater	
	5.4	Thermostat or cut-off switch	
6		nanical design of battery system	
Ü	6.1	General	
	6.2	Interface mechanism	
	6.3	Shock and vibration	.21
	6.4	Ventilation of battery box	
7	Elect	rical interface	.22
	7.1	General	.22
	7.2	External electrical connections interface	.22
8	Mark	ings	. 22
	8.1	Safety signs	.22
	8.1.1	Outside the box	. 22
	8.1.2	Tray, crate or other places inside the box	.22
	8.1.3		
	8.2	Nameplate	
	8.2.1	Battery box	. 23

9 Storage and transportation conditions 23 9.1 Transportation 23 9.2 Storage 23 10 Testing 24 10.1 General 24 10.2 Type test 24 10.2.1 General 24 10.2.2 Tests for cells and monoblocs 24 10.2.3 Dielectric test 25 10.2.4 Load profile test 25
9.2 Storage 23 10 Testing 24 10.1 General 24 10.2 Type test 24 10.2.1 General 24 10.2.2 Tests for cells and monoblocs 24 10.2.3 Dielectric test 25
9.2 Storage 23 10 Testing 24 10.1 General 24 10.2 Type test 24 10.2.1 General 24 10.2.2 Tests for cells and monoblocs 24 10.2.3 Dielectric test 25
10 Testing 24 10.1 General 24 10.2 Type test 24 10.2.1 General 24 10.2.2 Tests for cells and monoblocs 24 10.2.3 Dielectric test 25
10.2 Type test
10.2 Type test
10.2.1General2410.2.2Tests for cells and monoblocs2410.2.3Dielectric test25
10.2.3 Dielectric test
10.2.4 Load profile test25
10.2.5 Shock and vibration test25
10.3 Routine test
10.3.1 General
10.3.2 Visual checks
10.3.3 Dielectric test
10.3.4 Cell and monobloc voltages
Annex A (informative) Declaration of test unit equivalence27
Annex B (normative) Dielectric test
Annex C (normative) Compliance of battery with energy demand of load profile(s)29
C.1 General29
C.2 Battery sizing29
C.3 Compliance with energy demand of load profile
C.3.1 General
C.3.2 Test facility29
C.3.3 Test batteries
C.3.4 Test procedures30
C.3.5 Energy demand compliance
C.3.6 Test report30
31 Bibliography31
Figure 1 – Definition of single cells, monobloc, crate, tray and battery box10
Figure 2 – Example of the evolution of the voltage of a VRLA cell when discharged
with multiples of the 5 h rated current versus percentage of the 5 h rated capacity12
Figure 3 – Examples of current and voltage evolution during charge13
Figure 4 – Temperature versus voltage response graph for float charge operation15
igure 5 – Temperature versus voltage response graph for boost charge operation16
Figure 6 – Examples of horizontal installation of VRLA cells and monoblocs21
Figure 7 – Typical schematic view of an electrical interface of a battery system22
Table 1 – Requirements for battery system charge operations13
Table 2 – Typical lead acid battery charge parameters14
Table 3 – Voltage and temperature reference levels for float charge operation
Table 4 – Voltage and temperature reference levels for boost charge operation16
Table 5 – Input parameters required for the sizing of the battery to be provided by the system integrator or end user

Table 6 – Output parameters provided at the conclusion of the sizing of the battery to	
be provided by the battery system manufacturer	18
Table 7 – Type tests for cells and monoblocs	25
Table B.1 – Sequence for dielectric test	28
Table B.2 – Voltages for dielectric test	28

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RAILWAY APPLICATIONS – ROLLING STOCK –
BATTERIES FOR AUXILIARY POWER SUPPLY SYSTEMS –

Part 3: Lead acid batteries

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62973-3 has been prepared by IEC technical committee 9: Electrical equipment and systems for railways. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
9/3041/FDIS	9/3066/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62973 series, published under the general title *Railway applications* – *Rolling stock* – *Batteries for auxiliary power supply systems*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

RAILWAY APPLICATIONS – ROLLING STOCK – BATTERIES FOR AUXILIARY POWER SUPPLY SYSTEMS –

Part 3: Lead acid batteries

1 Scope

This part of IEC 62973 establishes the framework for the electrical interfaces to the train, and the sizing (e.g., capacity, cell number, to meet the requested load profile) and operation of lead acid batteries of the VRLA type for auxiliary power supply systems on rolling stock of railways and complements IEC 62973-1, unless otherwise specified.

This document provides guidance and links to standards for the required battery qualification tests procedures and safety measures to be implemented.

The cited normative references for lead acid batteries provide multiple requirements and tests applicable for their qualification.

In this document, the most appropriate clauses of these cited standards have been selected and adapted as needed to reflect the intended use of these batteries as auxiliary power sources on rolling stock of railways.

The battery-specific requirements for subcomponents of battery systems such as containers, charging controls, temperature probes, nameplates and similar are covered in this document as needed.

Charging systems are excluded from the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60896-21:2004, Stationary lead-acid batteries – Part 21: Valve regulated types – Methods of test

IEC 60896-22:2004, Stationary lead-acid batteries – Part 22: Valve regulated types – Requirements

IEC 61373:2010, Railway applications – Rolling stock equipment – Shock and vibration tests

IEC TS 61430, Secondary cells and batteries – Test methods for checking the performance of devices designed for reducing explosion hazards – Lead-acid starter batteries

IEC TR 61431:2020, Guidelines for the use of monitor systems for lead-acid traction batteries

IEC 62485-2:2010, Safety requirements for secondary batteries and battery installations – Part 2: Stationary batteries

IEC 62498-1:2010, Railway applications – Environmental conditions for equipment – Part 1: Equipment on board rolling stock

IEC 62973-1:2018, Railway applications – Rolling stock– Batteries for auxiliary power supply systems – Part 1: General requirements

ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories