

Acknowledgments

This thesis was prepared within the scope of my activities as systems engineer at Airbus under the scientific supervision of Prof. Dr.-Ing. habil. Detlef Schulz, head of the Department of Electrical Power Systems at the Helmut-Schmidt-University / University of the Federal Armed Forces Hamburg.

I would like to express my deepest gratitude towards Prof. Dr.-Ing. habil. Detlef Schulz, who always made himself available to me as a contact providing competent advice, and whose cooperation gave me the faith to complete the path taken with this thesis successfully. My special thanks go to Prof. Dr.-Ing. Gerd Scholl, head of the Department of Electrical Measurement Engineering, for providing the second reviewer's opinion.

I would like to expressly thank my colleague, Dr.-Ing. Torsten Benstem, who was always by my side from the very beginning to lend a supportive hand on the path to the conferral of my doctorate, and who was so kind as to take over the role of external reviewer and industrial supervisor until the successful completion.

For taking the chair of the committee conferring the doctorate, I would like to thank Prof. Dr.-Ing. habil. Udo Zölzer, head of the Department of Signal Processing and Communications.

In addition, I would like to thank Mr. Manfred Endreß, Dipl.-Ing. (FH), Mr. Martin Frey, Dipl.-Ing. (FH), Mr. Christian Paul, Dipl.-Ing. (FH), Mr. Roland Hertz, Dipl.-Ing. (FH), Mr. Thorsten Link, Dipl.-Ing. (FH), Dr.-Ing. Markus Töppel, Mr. Hans-Achim Bauer, Dipl.-Ing. (FH), and André Zybala, Dipl.-Ing. (FH), as well as my colleagues from the Cabin Power Systems team for the great cooperation throughout the last years.

Furthermore, it is my special wish to thank my colleague Gerd Düser, Dipl.-Ing. (FH), who brought me to Airbus, without whom I never would have had the opportunity of tackling this task within the scope of the development of the so very fascinating product, the aircraft. Special thanks also go to Ms. Antje Terno, Dipl.-Ing. (FH), Ms. Ingrid Röcker, Cabin and Cargo Communication, and Ms. MS MTA Stefanie von-Linstow for the great cooperation.

I would like to thank Mr. Johannes Brombach, Dipl.-Ing., research assistant at the department of Electrical Power Systems at the Helmut-Schmidt-University / University of the Federal Armed Forces Hamburg and my colleague Dr.-Ing. Michael Oppermann for the constructive discussions. Furthermore, I would like to thank the students I supervised, who contributed to valuable partial results of this thesis with their study work and theses for obtaining Diplom, Bachelor, and Master's degrees.

I would like to thank my mother and father, who both always supported me and thereby opened the path to this thesis for me. I would also like to thank my very dear wife Meike, who has been continually encouraging me and whose understanding attitude provided me with the freedom to successfully complete this thesis.

Jork, March 2013

Torben Schröter