



INTERNATIONAL STANDARD ISO/IEC 9596-2:1993

TECHNICAL CORRIGENDUM 2

Published 1996-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — Common management information protocol: Protocol Implementation Conformance Statement (PICS) proforma

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Interconnexion de systèmes ouverts: Protocole commun d'information de gestion — PICS proforma

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to International Standard ISO/IEC 9596-2:1993 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 21, *Open systems interconnection, data management and open distributed processing*.

ICS 35.100.70

Ref. No. ISO/IEC 9596-2:1993/Cor.2:1996(E)

Descriptors: data processing, information interchange, network interconnection, open systems interconnection, communication procedure, control procedures, protocols, implementation.

© ISO/IEC 1996

Printed in Switzerland

INTERNATIONAL STANDARD**ITU-T RECOMMENDATION****INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION –
COMMON MANAGEMENT INFORMATION PROTOCOL: PROTOCOL
IMPLEMENTATION CONFORMANCE STATEMENT (PICS) PROFORMA****TECHNICAL CORRIGENDUM 2****Annex A, subclause A.1.2**

Apply the following change:

Insert the following paragraph before the paragraph starting “The following requirements are commonly used throughout the PICS proforma.”:

“In Tables A.8, A.10, A.11 (Receiver Sts column), A.30, A.32, A.34, A.36, A.38, A.40, A.42, A.44, A.46, A.48, A.50, A.52, A.54, A.56, A.58, A.60, A.62, A.64, A.66, A.68, A.70, A.72, A.74, A.76, A.78, A.80, A.82, A.84, A.86, A.88, A.90, A.92, A.94, A.96, A.98, A.100, A.102, A.104, A.106, A.108, A.110, A.112, A.114, A.116, A.118, A.120, B.2, B.4, B.6 and B.8, the value of ‘m’ in the status (Sts) column indicates that there is a minimum requirement for the implementation to receive the parameter. The TVR column shall be used to state whether the implementation provides support for more than the minimum requirement.”