



Edition 3.0 2021-07 REDLINE VERSION

# INTERNATIONAL STANDARD



Lead-acid starter batteries –
Part 4: Dimensions of batteries for heavy vehicles

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.220.20; 43.040.10

ISBN 978-2-8322-4034-2

Warning! Make sure that you obtained this publication from an authorized distributor.

## CONTENTS

FOREWORD	4
1 Scope and object	6
2 Normative references	6
3 Terms and definitions	6
4 Common features	7
4.1 Labelling	7
4.2 Marking of polarity	
4.2.1 General	7
4.2.2 Marking of positive terminals	7
4.2.3 Marking of negative terminals	7
4.2.4 Design and dimensions of marking	7
4.3 Marking of plastic material	7
4.4 Dimensions and design	9
4.5 Dimensions of terminals	9
4.6 Recommendation for new development	10
5 European types	10
5.1 General	10
5.2 Fastening	10
5.3 Dimensions	10
6 North American types	9
6.1 General	14
6.1.1 Overview	14
6.1.2 Fastening	14
6.1.3 Terminal configuration, polarity	14
6.1.4 Terminal dimensions	14
6.2 Dimensions	14
7 East Asian types	20
7.1 General	20
7.1.1 Overview	20
7.1.2 Fastening	20
7.1.3 Terminal configuration, polarity	20
7.1.4 Terminal dimensions	20
7.2 Dimensions	21
Bibliography	23
Figure 1 – Marking of polarity	7
Figure 2 – Marking of polypropylene	
Figure 2 – Marking of polypropylene-polyethylene copolymer battery components	8
Figure 3 – Dimensions of positive (on the right) and negative (on the left) terminal	
Figure 4 – EU series – Type D2	
Figure 5 – EU series – Types A, B, C	
Figure 6 – AM series – Type 4D	
Figure 7 – Dimensions ( mm) of tapered terminal	
Figure 8 – AM series – Type 8D	

Figure 9 – AM series – Type 31T	
Figure 10 – Dimensions of stud terminal	
Figure 11 – AM series – Type 31A	
Figure 12 – Dimensions (mm) of tapered terminal	
Figure 7 – AM series – Type 8D	18
Figure 8 – AM series – Type 31T	19
Figure 9 – Dimensions of stud terminal	19
Figure 10 – AM series – Type 31A	20
Figure 11 – AS series – Type E 41	22
Figure 12 – AS series – Types F51, G51 and H52	22
Table 1 – EU series – Dimensions of batteries	11
Table 2 – AM series – Dimensions of batteries	14
Table 3 – Dimensions of tapered terminal	
Table 3 – AS series – Dimensions of batteries	21

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

## LEAD-ACID STARTER BATTERIES -

### Part 4: Dimensions of batteries for heavy vehicles

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
  consensus of opinion on the relevant subjects since each technical committee has representation from all
  interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 60095-4:2008. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60095-4 has been prepared by IEC technical committee 21: Secondary cells and batteries.

This third edition cancels and replaces the second edition published in 2008. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) values of "tolerance", in particular for European batteries;
- b) update of figures for USA and Asian batteries.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
21/1087/FDIS	21/1091/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at <a href="https://www.iec.ch/members\_experts/refdocs">www.iec.ch/members\_experts/refdocs</a>. The main document types developed by IEC are described in greater detail at <a href="https://www.iec.ch/standardsdev/publications">www.iec.ch/standardsdev/publications</a>.

A list of all parts in the IEC 60095 series, published under the general title *Lead-acid starter* batteries, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- · reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

### LEAD-ACID STARTER BATTERIES -

### Part 4: Dimensions of batteries for heavy vehicles

### 1 Scope and object

This part of IEC 60095 is applicable to lead-acid batteries used for starting, lighting and ignition of heavy trucks, commercial vehicles, busses and agricultural trucks.

The object of this document is to specify global requirements of the main dimensions of starter batteries for Europe, North America and East Asia.

This document comprises 12 types of "preferred types" of batteries.

This document specifies dimensions of 4 types of batteries each for Europe (types A, B, C and D2), North America (types 4D, 8D, 31T, 31A) and East Asia (types E41, F51, G51, H52).

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482<del>:2004</del>, International Electrotechnical Vocabulary – Part 482: Primary and secondary cells and batteries

IEC 60095-1, Lead-acid starter batteries – Part 1: General requirements and methods of test

IEC 60417:2002, Graphical symbols for use on equipment

ISO/IEC 10646, Information technology – Universal coded character set (UCS)

ISO 1043-1, Plastics – Symbols and abbreviated terms – Part 1: Basic polymers and their special characteristics

ISO 7000, Graphical symbols for use on equipment - Index and synopsis

ISO 11469, Plastics - Generic identification and marking of plastics products



Edition 3.0 2021-07

# INTERNATIONAL STANDARD



Lead-acid starter batteries –
Part 4: Dimensions of batteries for heavy vehicles



## CONTENTS

F	OREWO	PRD	4
1	Scop	ne	6
2	Norn	native references	6
3	Term	s and definitions	6
4	Com	mon features	7
•	4.1	Labelling	
	4.2	Marking of polarity	
	4.2.1		
	4.2.2		
	4.2.3		
	4.2.4		
	4.3	Marking of plastic material	
	4.4	Dimensions and design	
	4.5	Dimensions of terminals	
	4.6	Recommendation for new development	
5		pean types	
J		•	
	5.1	General	
	5.2	Fastening	
_	5.3	Dimensions	
6		n American types	
	6.1	General	
	6.1.1		
	6.1.2	9	
	6.1.3	<b>3</b>	
	6.1.4		
	6.2	Dimensions	
7	East	Asian types	15
	7.1	General	15
	7.1.1	Overview	15
	7.1.2	Fastening	15
	7.1.3	Terminal configuration, polarity	15
	7.1.4	Terminal dimensions	15
	7.2	Dimensions	15
Bi	bliograp	phy	17
Fi	gure 1 -	- Marking of polarity	7
	_	- Marking of polypropylene-polyethylene copolymer battery components	
	•	- Dimensions of positive (on the right) and negative (on the left) terminal	
	•	, , , , , , , , , , , , , , , , , , , ,	
	-	- EU series – Type D2	
		- EU series - Types A, B, C	
Fi	gure 6 -	- AM series – Type 4D	12
Fi	gure 7 -	- AM series – Type 8D	13
Fi	gure 8 -	- AM series – Type 31T	13
	_	- Dimensions of stud terminal	

Figure 10 – AM series – Type 31A	14
Figure 11 – AS series – Type E 41	16
Figure 12 – AS series – Types F51, G51 and H52	16
Table 1 – EU series – Dimensions of batteries	10
Table 2 – AM series – Dimensions of batteries	
Table 3 – AS series – Dimensions of batteries	15

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### **LEAD-ACID STARTER BATTERIES -**

### Part 4: Dimensions of batteries for heavy vehicles

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60095-4 has been prepared by IEC technical committee 21: Secondary cells and batteries.

This third edition cancels and replaces the second edition published in 2008. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) values of "tolerance", in particular for European batteries;
- b) update of figures for USA and Asian batteries.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
21/1087/FDIS	21/1091/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at <a href="https://www.iec.ch/members\_experts/refdocs">www.iec.ch/members\_experts/refdocs</a>. The main document types developed by IEC are described in greater detail at <a href="https://www.iec.ch/standardsdev/publications">www.iec.ch/standardsdev/publications</a>.

A list of all parts in the IEC 60095 series, published under the general title *Lead-acid starter* batteries, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

### LEAD-ACID STARTER BATTERIES -

### Part 4: Dimensions of batteries for heavy vehicles

### 1 Scope

This part of IEC 60095 is applicable to lead-acid batteries used for starting, lighting and ignition of heavy trucks, commercial vehicles, busses and agricultural trucks.

The object of this document is to specify global requirements of the main dimensions of starter batteries for Europe, North America and East Asia.

This document comprises 12 types of "preferred types" of batteries.

This document specifies dimensions of 4 types of batteries each for Europe (types A, B, C and D2), North America (types 4D, 8D, 31T, 31A) and East Asia (types E41, F51, G51, H52).

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482, International Electrotechnical Vocabulary – Part 482: Primary and secondary cells and batteries

IEC 60095-1, Lead-acid starter batteries – Part 1: General requirements and methods of test

IEC 60417:2002, Graphical symbols for use on equipment

ISO/IEC 10646, Information technology – Universal coded character set (UCS)

ISO 1043-1, Plastics – Symbols and abbreviated terms – Part 1: Basic polymers and their special characteristics

ISO 11469, Plastics – Generic identification and marking of plastics products