



IEC 60245-3

Edition 3.0 2026-03

# INTERNATIONAL STANDARD

---

**Rubber insulated cables - Rated voltages up to and including 450/750 V -  
Part 3: Heat resistant silicone insulated cables**

## CONTENTS

FOREWORD.....	2
1 Scope.....	4
2 Normative references.....	4
3 Terms and definitions.....	4
4 Heat resistant silicone insulated cable for a conductor temperature of maximum 180 °C .....	5
4.1 Code designation.....	5
4.2 Rated voltage.....	5
4.3 Construction.....	5
4.3.1 Conductor .....	5
4.3.2 Separator.....	5
4.3.3 Insulation .....	5
4.3.4 Outer braid.....	5
4.3.5 Overall diameter .....	5
4.4 Tests.....	6
4.5 Guidance on use of the cables.....	6
Bibliography.....	8
Table 1 – Dimensions of type 60245 IEC 03 .....	6
Table 2 – Tests for type 60245 IEC 03 .....	7

INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**Rubber insulated cables -  
Rated voltages up to and including 450/750 V -  
Part 3: Heat resistant silicone insulated cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60245-3 has been prepared by IEC technical committee TC 20: Electric cables. It is an International Standard.

This third edition cancels and replaces the second edition published in 1994. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) reference to IEC 60245-2 for the tests has been deleted and replaced by IEC 63294;
- b) normative references have been updated.

The text of this International Standard is based on the following documents:

Draft	Report on voting
20/2272/FDIS	20/2281/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

This document is to be used in conjunction with IEC 60245-1:2026.

A list of all the parts in the IEC 60245 series, published under the general title *Rubber insulated cables - Rated voltages up to and including 450/750 V*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

## 1 Scope

This part of IEC 60245 defines the particular requirements for rubber heat resistant silicone insulated cables of rated voltage of 300/500 V which apply in addition to the general requirements specified in IEC 60245-1, which apply to all cables.

The tests for cables specified in the IEC 60245 series are described in IEC 63294.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60228, *Conductors of insulated cables*

IEC 60245-1:2026, *Rubber insulated cables - Rated voltages up to and including 450/750 V - Part 1: General requirements*

IEC 60719, *Calculation of the lower and upper limits for the average outer dimensions of cables with circular copper conductors and of rated voltages up to and including 450/750 V*

IEC 60811-401, *Electric and optical fibre cables - Test methods for non-metallic materials - Part 401: Miscellaneous tests - Thermal ageing methods - Ageing in an air oven*

IEC 60811-501, *Electric and optical fibre cables - Test methods for non-metallic materials - Mechanical tests - Tests for determining the mechanical properties of insulating and sheathing compounds*

IEC 60811-507, *Electric and optical fibre cables - Test methods for non-metallic materials - Mechanical tests - Hot set test for cross-linked materials*

IEC 62440, *Electric cables - Guide to use for cables with a rated voltage not exceeding 450/750 V*

IEC 63294:2021, *Test methods for electric cables with rated voltage up to and including 450/750 V*

## Bibliography

IEC 60245 (all parts), *Rubber insulated cables - Rated voltages up to and including 450/750 V*

---