

INTERNATIONAL STANDARD

CONSOLIDATED VERSION

**Methods of measurement on radio receivers for various classes of emission -
Part 4: Receivers for frequency-modulated sound broadcasting emissions**

CONTENTS

FOREWORD.....	6
1 General.....	8
1.1 Scope	8
1.2 Normative references	8
1.3 Definitions.....	9
1.4 Standard measuring conditions.....	10
1.4.1 Measurements at audio-frequency output terminals.....	10
1.4.2 Radio-frequency signal(s).....	11
1.4.3 Power supply and relevant measuring conditions	14
1.4.4 Tuning	14
1.5 General notes on measurements	15
1.5.1 Values for voltage and current.....	15
1.5.2 Audio-frequency measurement techniques.....	15
1.5.3 Presentation of radio-frequency signal level or voltage.....	15
1.5.4 Climatic and environmental conditions	16
1.5.5 Preconditioning and preliminary measurements	16
1.5.6 Test equipment and accuracy of measurements.....	16
1.5.7 Rated values.....	17
1.5.8 Presentation of measuring results.....	17
2 Sensitivity and internal noise	18
2.1 Explanation of terms	18
2.2 Signal-to-noise ratio (weighted and unweighted) and SINAD	18
2.2.1 Introduction.....	18
2.2.2 Method of measurement.....	18
2.2.3 Presentation of results	19
2.3 Noise-limited sensitivity.....	19
2.3.1 Introduction.....	19
2.3.2 Method of measurement.....	19
2.3.3 Presentation of results	19
2.4 Gain-limited sensitivity	19
2.4.1 Introduction.....	19
2.4.2 Method of measurement.....	20
2.4.3 Presentation of results	20
2.5 Usable sensitivity	20
2.5.1 Introduction.....	20
2.5.2 Method of measurement.....	20
2.5.3 Presentation of results	20
2.6 Deviation sensitivity	20
2.6.1 Introduction.....	20
2.6.2 Method of measurement.....	21
2.6.3 Presentation of results	21
2.7 Input-output characteristics	21
2.7.1 Introduction.....	21
2.7.2 Method of measurement.....	21
2.7.3 Presentation of results	22
3 Rejection of unwanted signals.....	22

3.1	Capture ratio	22
3.1.1	Introduction	22
3.1.2	Method of measurement	22
3.1.3	Presentation of results	23
3.2	Selectivity and nearby channel rejection (two-signal)	23
3.2.1	Introduction	23
3.2.2	Method of measurement	24
3.2.3	Rejection of adjacent and alternate channels	25
3.2.4	Presentation of the results	25
3.3	Rejection of intermediate and image frequencies, and spurious responses	25
3.3.1	Introduction	25
3.3.2	Methods of measurement	27
3.3.3	Presentation of results	28
3.4	Suppression of amplitude modulation	28
3.4.1	Introduction	28
3.4.2	Methods of measurement	28
3.4.3	Presentation of results	29
3.5	Rejection of r.f. signal intermodulation products	29
3.5.1	Introduction	29
3.5.2	Methods of measurement: two-signal methods	30
3.5.3	Methods of measurement: three-signal methods	31
3.6	Tuning and automatic frequency control (AFC) characteristics	33
3.6.1	Introduction	33
3.6.2	Method of measurement	33
3.6.3	Presentation of results	34
4	Interference due to internal sources	34
4.1	Single-signal whistles	34
4.1.1	Introduction	34
4.1.2	Method of measurement	34
4.1.3	Presentation of results	34
4.2	Modulation hum (interference at power supply frequency)	34
4.2.1	Introduction	34
4.2.2	Method of measurement	34
4.2.3	Presentation of results	35
4.3	Unwanted self-oscillations	35
4.3.1	Introduction	35
4.3.2	Method of measurement	35
4.3.3	Presentation of results	35
4.4	Acoustic feedback	35
4.4.1	Introduction	35
4.4.2	Method of measurement	35
4.4.3	Presentation of results	36
5	Overall audio-frequency characteristics	36
5.1	Fidelity	36
5.2	Harmonic distortion	36
5.2.1	Introduction	36
5.2.2	Method of measurement	37
5.2.3	Presentation of results	39

5.3	Intermodulation distortion	40
5.3.1	Introduction	40
5.3.2	Method of measurement	40
5.3.3	Presentation of results	41
5.4	Inter-channel characteristics	41
5.4.1	Introduction	41
5.4.2	Method of measurement	42
5.4.3	Presentation of results	42
5.5	Characteristics of the volume control	43
5.5.1	Introduction	43
5.5.2	Method of measurement	43
5.5.3	Presentation of results	43
5.6	Residual output	43
5.6.1	Introduction	43
5.6.2	Method of measurement	43
5.6.3	Presentation of the result	43
5.7	Crosstalk attenuation	43
5.7.1	Introduction	43
5.7.2	Method of measurement	44
5.7.3	Presentation of results	44
5.8	Overall audio-frequency response	44
5.8.1	Introduction	44
5.8.2	Method of measurement	44
5.8.3	Presentation of results	45
6	Effect of additional modulations of the input signal	45
6.1	Rejection of signals in the ranges 16 kHz to 22 kHz and 54 kHz to 99 kHz	45
6.1.1	Introduction	45
6.1.2	Method of measurement	45
6.1.3	Presentation of the results	45
6.2	Rejection of signals in the range 62 kHz to 73 kHz (SCA rejection)	45
6.2.1	Method of measurement	45
6.2.2	Presentation of the results	46
6.3	Measurement of interference caused by RDS signals	46
6.3.1	Introduction	46
6.3.2	Method of measurement	46
6.3.3	Presentation of results	46
6.4	Suppression of the fundamental, harmonics and sidebands of the subcarrier and the pilot-tone signal	46
6.4.1	Introduction	46
6.4.2	Method of measurement	47
6.4.3	Presentation of the results	47
6.5	Suppression of interference due to adjacent channel signals with a stereophonic receiver using the pilot-tone system	47
6.5.1	Introduction	47
6.5.2	Method of measurement	47
6.5.3	Presentation of the results	47
7	Sensitivity, antenna gain and directional response of receivers using rod, telescopic or built-in antennas	48

7.1	Introduction	48
7.2	Method of measurement of sensitivity and antenna gain for a receiver using a rod or telescopic antenna by the absorbing clamp described in CISPR 16-1	48
8	Characteristics whose methods of measurement are specified in IEC 60315-1	48
8.1	Introduction	48
8.2	List of characteristics and cross-references	48
Figure 1 – Frequency response limits of band-pass filter 200 Hz to 15 kHz		49
Figure 2 – Frequency response limits of band-pass filter 22,4 Hz to 15 kHz		50
Figure 3 – Frequency response limits of band-pass filter 200 Hz to 1,5 kHz		50
Figure 4 – Frequency response limits of the 1 kHz band-stop filter		51
Figure 5 – Weighting filter for converting white noise into special coloured noise for selectivity measurements		51
Figure 6 – Arrangement for various measurements with two r.f. input signals		52
Figure 7 – Antenna substitution networks for injecting one or two signals, for 50 Ω signal generators and 75 Ω unbalanced and 300 Ω balanced receiver inputs		53
Figure 8 – Arrangement for various measurements with one r.f. input signal		54
Figure 9 – Signal-to-noise ratio		55
Figure 10 – Noise-limited sensitivity as a function of signal frequency		55
Figure 11 – Gain-limited sensitivity as a function of signal frequency		56
Figure 12 – Output/input characteristics and noise output curves showing terms defined in 1.3		57
Figure 13 – Capture ratio		58
Figure 14a – Mono mode		59
Figure 14b – Stereo mode		59
Figure 14 – Selectivity curves		59
Figure 15 – Image and intermediate frequency rejection ratios		60
Frequency		61
Figure 16 – Spurious responses at a tuning frequency of 94 MHz (single-signal method)		61
Figure 17 – Arrangement for measuring rejection of unwanted signals simulating cable reception, using sinusoidal modulation		62
Figure 18 – Arrangement for various measurements using three r.f. input signals		63
Figure 19 – Tuning characteristics		64
Figure 20 – Tuning characteristics obtained by measuring the local oscillator frequency		65
Figure 21 – Measurement of acoustic feedback		66
Figure 22 – Arrangement for measuring fidelity		66
Figure 23 – Overall total harmonic distortion as a function of a.f. output power		67
Figure 24 – Distortion-limited output power as a function of modulation frequency		67
Figure 25 – Total harmonic distortion as a function of r.f. input signal level		68
Figure 26 – Total harmonic distortion as a function of the deviation		68
Figure 27 – Variation of distortion with detuning		69
Figure 28 – Total harmonic distortion as a function of the a.f. modulation frequency		69

Figure 29 – Cross-intermodulation between the channels of a stereo receiver (pilot-tone system).....	70
Figure A.1 – Example of a passive 1 kHz band-stop filter capable of meeting the limits shown in figure 4	71
Figure D.1 – Arrangement for r.f. signal injection into the antenna with an absorbing clamp	75
Figure D.2 – Correction curves for the insertion loss of the absorbing clamp	75
Table 1 – Audio-frequency filters	11
Table 2 – Standard values of deviation	12
Table 3 – Standard measuring frequencies	13
Table 4 – Presentation of radio-frequency signal level or voltage	16

INTERNATIONAL ELECTROTECHNICAL COMMISSION

Methods of measurement on radio receivers for various classes of emission - Part 4: Receivers for frequency-modulated sound broadcasting emissions

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60315-4 edition 2.1 contains the second edition (1997-11) [documents 100A/58/FDIS and 100A/60/RVD] and its amendment 1 (2025-12) [documents 100/4290/CDV and 100/4385/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60315-4 has been prepared by IEC subcommittee 100A: Multimedia end-user equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition published in 1982 and constitutes a technical revision.

This part of IEC 60315 shall be read in conjunction with IEC 60315-1.

The text of this standard is based on the following documents:

FDIS	Report on voting
100A/58/FDIS	100A/60/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

Annexes A, B, C and D are for information only.

IEC 60315 consists of the following parts under the general title: Methods of measurement on radio receivers for various classes of emission:

- Part 1: 1988, General considerations and methods of measurement, including audio-frequency measurements
- Part 3: 1989, Receivers for amplitude – modulated sound broadcasting emissions
- Part 4: 1997, Receivers for frequency – modulated sound broadcasting emissions
- Part 5: 1971, Specialized radio-frequency measurements – Measurement on frequency-modulated receivers of the response to impulsive interference
- Part 6: 1991, General purpose communication receivers
- Part 7: 1995, Methods of measurement on digital satellite radio (DSR) receivers
- Part 8: 1975, Radio-frequency measurements on professional receivers for frequency-modulated telegraphy systems
- Part 9: 1996, Measurement of the characteristics relevant to radio data system (RDS) reception

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

1 General

1.1 Scope

This part of IEC 60315 applies to radio receivers and tuners for the reception of frequency-modulated sound-broadcasting emissions with rated maximum system deviations of ± 75 kHz and ± 50 kHz in ITU Band 8. It deals mainly with methods of measurement using radio-frequency signals applied to the antenna terminals of the receiver. The measurements and specified conditions of test are selected to permit the comparison of results obtained by different observers and on other receivers. Performance requirements are not specified in this standard.

Radiation and immunity tests and requirements are not included since these are described in CISPR 13 and CISPR 20.

1.2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 60315. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this part of IEC 60315 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60098: 1987, *Analogue audio disk records and reproducing equipment*

IEC 60268-1: 1985, *Sound system equipment – Part 1: General*

IEC 60268-3: 1988, *Sound system equipment – Part 3: Amplifiers*

IEC 60315-1: 1988, *Methods of measurement on radio receivers for various classes of emission – Part 1: General considerations and methods of measurement, including audio-frequency measurements*

IEC 60315-3: 1989, *Methods of measurement on radio receivers for various classes of emission – Part 3: Receiver for amplitude-modulated sound-broadcasting emissions*

IEC 60315-7: 1995, *Methods of measurement on radio receivers for various classes of emission – Part 7: Methods of measurement on digital satellite radio (DSR) receivers*

IEC 60315-9: 1996, *Methods of measurement on radio receivers for various class of emission – Part 9: Measurement of the characteristics relevant to Radio Data System (RDS) reception*

IEC 60651: 1979, *Sound level meters*

IEC 61260: 1995, *Electroacoustics – Octave-band and fractional-octave-band filters*

CISPR 16-1: 1993, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1: Radio disturbance and immunity measuring apparatus*

CISPR 20: 1996, *Limits and methods of measurement of immunity characteristics of sound and television broadcast receivers and associated equipment*

ITU-R Recommendation 468-4: 1990: *Measurement of audio-frequency*

ITU-R Recommendation 559-2: 1990: *Objective measurement of radio-frequency protection ratios in LF, MF and HF broadcasting*