



IEC 60664-1

Edition 3.1 2025-05
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

BASIC SAFETY PUBLICATION

HORIZONTAL PUBLICATION

**Insulation coordination for equipment within low-voltage supply systems –
Part 1: Principles, requirements and tests**

CONTENTS

FOREWORD	7
1 Scope	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	10
3.1 Terms and definitions	10
3.2 Abbreviated terms	17
4 Basic technical characteristics for insulation coordination	17
4.1 General	17
4.2 Voltages	18
4.2.1 General aspects	18
4.2.2 Transient overvoltages	18
4.2.3 Temporary overvoltages	20
4.2.4 Recurring peak voltage	20
4.2.5 Steady-state working voltage	21
4.2.6 Steady-state peak voltage	21
4.3 Overvoltage categories	21
4.3.1 General	21
4.3.2 Equipment energized directly from the mains supply	21
4.3.3 Systems and equipment not energized directly from the mains supply	22
4.3.4 Equipment requiring specific measures	22
4.4 Frequency	23
4.4.1 General	23
4.4.2 Solid insulation	23
4.5 Pollution	23
4.5.1 General	23
4.5.2 Degrees of pollution in the micro-environment	23
4.5.3 Conditions of conductive pollution	24
4.6 Insulating material	24
4.6.1 Solid insulation	24
4.6.2 Stresses	24
4.6.3 Comparative tracking index (CTI)	25
4.7 Environmental aspects	26
4.7.1 General	26
4.7.2 Altitude	26
4.7.3 Temperature	26
4.7.4 Vibrations	27
4.7.5 Humidity	27
4.8 Duration of voltage stress	27
4.9 Electrical field distribution	27
5 Design for insulation coordination	27
5.1 General	27
5.1.1 Means of insulation coordination	27
5.1.2 Frequency above 30 kHz	28
5.1.3 Reduced distances due to coating or potting	28
5.1.4 Equipment which are not connected to public low-voltage systems.	28
5.2 Dimensioning of clearances	28

5.2.1	General	28
5.2.2	Dimensioning criteria for clearances	28
5.2.3	Other factors involving clearances	29
5.2.4	Dimensioning of clearances of functional insulation	30
5.2.5	Dimensioning of clearances of basic insulation, supplementary insulation and reinforced insulation.....	30
5.3	Dimensioning of creepage distances	31
5.3.1	General	31
5.3.2	Dimensioning criteria of creepage distances	31
5.3.3	Other factors involving creepage distances.....	32
5.3.4	Dimensioning of creepage distances of functional insulation	34
5.3.5	Dimensioning of creepage distances of basic insulation, supplementary insulation and reinforced insulation.....	34
5.4	Requirements for design of solid insulation	35
5.4.1	General	35
5.4.2	Voltage stress.....	35
5.4.3	Withstand of voltage stresses	35
5.4.4	Withstand on environmental stresses.....	37
6	Tests and measurements.....	37
6.1	General.....	37
6.2	Verification of clearances	38
6.2.1	General	38
6.2.2	Test voltages	38
6.3	Verification of creepage distances	41
6.4	Verification of solid insulation	41
6.4.1	General	41
6.4.2	Selection of tests	41
6.4.3	Conditioning	42
6.4.4	Impulse voltage test.....	43
6.4.5	AC power frequency voltage test	43
6.4.6	Partial discharge test.....	44
6.4.7	DC voltage test.....	46
6.4.8	High-frequency voltage test	46
6.5	Performing dielectric tests on complete equipment.....	46
6.5.1	General	46
6.5.2	Parts to be tested	47
6.5.3	Preparation of equipment circuits.....	47
6.5.4	Test voltage values.....	47
6.5.5	Test criteria	47
6.6	Other tests	47
6.6.1	Test for purposes other than insulation coordination	47
6.6.2	Sampling and routine tests	48
6.6.3	Measurement accuracy of test parameters.....	48
6.7	Measurement of the attenuation of the transient overvoltages.....	48
6.8	Measurement of clearances and creepage distances	48
Annex A (informative)	Basic data on withstand characteristics of clearances	54
Annex B (informative)	Nominal voltages of mains supply for different modes of overvoltage control	59

Annex C (normative) Partial discharge test methods	61
C.1 Test circuits	61
C.1.1 General	61
C.1.2 Test circuit for earthed test specimen (Figure C.1).....	61
C.1.3 Test circuit for unearthed test specimen (Figure C.2).....	62
C.1.4 Selection criteria.....	62
C.1.5 Measuring impedance.....	62
C.1.6 Coupling capacitor C_k	62
C.1.7 Filter.....	62
C.2 Test parameters.....	62
C.2.1 General	62
C.2.2 Requirements for the test voltage	63
C.2.3 Climatic conditions	63
C.3 Requirements for measuring instruments	63
C.3.1 General	63
C.3.2 Classification of PD meters.....	63
C.3.3 Bandwidth of the test circuit.....	64
C.4 Calibration	64
C.4.1 Calibration of discharge magnitude before the noise level measurement	64
C.4.2 Verification of the noise level.....	65
C.4.3 Calibration for the PD test	66
C.4.4 Calibration pulse generator.....	66
Annex D (informative) Additional information on partial discharge test methods	67
D.1 Measurement of partial discharge (PD), PD inception and extinction voltage.....	67
D.2 Description of PD test circuits (Figure D.1)	67
D.3 Precautions for reduction of noise.....	68
D.3.1 General	68
D.3.2 Sources in the non-energized test circuit	68
D.3.3 Sources in the energized test circuit	68
D.3.4 Measures for reduction of noise.....	68
D.4 Application of multiplying factors for test voltages	68
D.4.1 General	68
D.4.2 Example 1 (circuit connected to mains supply).....	69
D.4.3 Example 2 (internal circuit with maximum recurring peak voltage U_{rp}).....	69
Annex E (informative) Comparison of creepage distances specified in Table F.5 and clearances in Table A.1	70
Annex F (normative) Tables	71
Annex G (informative) Determination of clearance distances according to 5.2.....	80
Annex H (informative) Determination of creepage distances according to 5.3.....	82
Annex I (informative) Electrochemical migration of creepage distances in DC applications	84
I.1 The phenomenon of electrochemical migration	84
I.2 Effect of electrochemical migration on creepage distances in DC applications	84
Bibliography.....	86
Figure 1 – Recurring peak voltage	20
Figure 2 – Determination of the width (W) and height (H) of a rib	34
Figure 3 – Test voltages	45

Figure 4 – Across the groove	49
Figure 5 – Contour of the groove	50
Figure 6 – Contour of the groove with angle.....	50
Figure 7 – Contour of rib	50
Figure 8 – Uncemented joint with grooves less than X	51
Figure 9 – Uncemented joint with grooves equal to or more than X	51
Figure 10 – Uncemented joint with a groove on one side less than X	52
Figure 11 – Creepage distance and clearance through an uncemented joint	52
Figure 12 – Creepage distance and clearance to a head of screw more than X	52
Figure 13 – Creepage distance and clearance to a head of screw less than X	53
Figure 14 – Creepage distance and clearance with conductive floating part	53
Figure A.1 – Withstand voltage at 2 000 m above sea level.....	56
Figure A.2 – Experimental data measured at approximately sea level and their low limits for inhomogeneous field.....	57
Figure A.3 – Experimental data measured at approximately sea level and their low limits for homogeneous field	58
Figure C.1 – Earthed test specimen	61
Figure C.2 – Unearthed test specimen	62
Figure C.3 – Calibration for earthed test specimen.....	65
Figure C.4 – Calibration for unearthed test specimen.....	65
Figure D.1 – Partial discharge test circuits.....	67
Figure E.1 – Comparison between creepage distances specified in Table F.5 and clearances in Table A.1	70
Figure G.1 – Determination of clearance distances according to 5.2 (1 of 2)	80
Figure H.1 – Determination of creepage distances according to 5.3 (1 of 2).....	82
Table 1 – Dimensioning of grooves	49
Table A.1 – Withstand voltages for an altitude of 2 000 m above sea level (1 of 2)	54
Table A.2 – Altitude correction factors for clearance correction	55
Table B.1 – Inherent control or equivalent protective control	59
Table B.2 – Cases where protective control is necessary and control is provided by surge protective device having a ratio of voltage protection level to rated voltage not smaller than that specified in IEC 61643 (all parts)	60
Table F.1 – Rated impulse withstand voltage for equipment energized directly from the mains supply.....	71
Table F.2 – Clearances to withstand transient overvoltages.....	72
Table F.3 – Single-phase three-wire or two-wire AC or DC systems	73
Table F.4 – Three-phase four-wire or three-wire AC systems	74
Table F.5 – Creepage distances to avoid failure due to tracking (1 of 2)	75
Table F.6 – Test voltages for verifying clearances only at different altitudes	77
Table F.7 – Severities for conditioning of solid insulation	77
Table F.8 – Dimensioning of clearances to withstand steady-state peak voltages, temporary overvoltages or recurring peak voltages ^b	78
Table F.9 – Additional information concerning the dimensioning of clearances to avoid partial discharge	78

Table F.10 – Altitude correction factors for clearance correction 79

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INSULATION COORDINATION FOR EQUIPMENT WITHIN LOW-VOLTAGE SUPPLY SYSTEMS –

Part 1: Principles, requirements and tests

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). [IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch> [and/or] www.iso.org/patents. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60664-1 edition 3.1 contains the third edition (2020-05) [documents 109/183/FDIS and 109/186/RVD], its corrigendum 1 (2020-10) and its amendment 1 (2025-05) [documents 109/235/FDIS and 109/240/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60664-1 has been prepared by IEC technical committee 109: Insulation co-ordination for low-voltage equipment.

This third edition cancels and replaces the second edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) update of the Scope, Clauses 2 and 3,
- b) new structure for Clauses 4 and 5,
- c) addition of 1 500 V DC into tables in Annex B and F,
- d) update of distances altitude correction in a new Table F.10,
- e) addition of Annex G with a flowchart for clearances,
- f) addition of Annex H with a flowchart for creepage distances.

It has the status of a basic safety publication in accordance with IEC Guide 104.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
109/183/FDIS	109/186/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60664 series, published under the general title *Insulation coordination for equipment within low-voltage supply systems*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

In this document, the following print type is used:

– **Terms defined in Clause 3: in bold type.**

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INSULATION COORDINATION FOR EQUIPMENT WITHIN LOW-VOLTAGE SUPPLY SYSTEMS –

Part 1: Principles, requirements and tests

1 Scope

This part of IEC 60664 deals with **insulation coordination** for **electrical equipment** having a **rated voltage** up to AC 1 000 V or DC 1 500 V connected to **low-voltage supply systems**.

NOTE 1 Throughout this document, the term equipment is used with the meaning of **electrical equipment**.

This document applies to frequencies up to 30 kHz.

NOTE 12 Requirements for **insulation coordination** for equipment within **low-voltage supply systems** with rated frequencies above 30 kHz are given in IEC 60664-4.

NOTE 23 Higher voltages can exist in internal circuits of the equipment.

It applies to equipment for use up to 2 000 m above sea level and provides guidance for use at higher altitudes (See 5.2.3.4).

It provides requirements for technical committees to determine **clearances**, **creepage distances** and criteria for **solid insulation**. It includes methods of electrical testing with respect to **insulation coordination**.

The minimum **clearances** specified in this document do not apply where ionized gases are present. Special requirements for such situations can be specified at the discretion of the relevant technical committee.

This document does not deal with distances:

- through liquid insulation;
- through gases other than air;
- through compressed air.

This basic safety publication focusing on safety essential requirements is primarily intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications.

However, in case of missing specified values for **clearances**, **creepage distances** and requirements for **solid insulation** in the relevant product standards, or even missing standards, this document applies.

NOTE 4 Further explanations and examples with regard to the use of this document are provided in IEC TR 60664-2-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition

cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-2, *Environmental testing – Part 2-2: Tests – Tests B: Dry heat*

IEC 60068-2-14:2009, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-78, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60270, *High-voltage test techniques – Partial discharge measurements*

IEC 61140:2016, *Protection against electric shock – Common aspects for installation and equipment*

IEC 61180:2016, *High-voltage test techniques for low-voltage equipment – Definitions, test and procedure requirements, test equipment*

CONTENTS

FOREWORD	7
1 Scope	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	10
3.1 Terms and definitions	10
3.2 Abbreviated terms	17
4 Basic technical characteristics for insulation coordination	17
4.1 General	17
4.2 Voltages	18
4.2.1 General aspects	18
4.2.2 Transient overvoltages	18
4.2.3 Temporary overvoltages	20
4.2.4 Recurring peak voltage	20
4.2.5 Steady-state working voltage	21
4.2.6 Steady-state peak voltage	21
4.3 Overvoltage categories	21
4.3.1 General	21
4.3.2 Equipment energized directly from the mains supply	21
4.3.3 Systems and equipment not energized directly from the mains supply	22
4.3.4 Equipment requiring specific measures	22
4.4 Frequency	22
4.4.1 General	22
4.4.2 Solid insulation	22
4.5 Pollution	22
4.5.1 General	22
4.5.2 Degrees of pollution in the micro-environment	23
4.5.3 Conditions of conductive pollution	23
4.6 Insulating material	23
4.6.1 Solid insulation	23
4.6.2 Stresses	24
4.6.3 Comparative tracking index (CTI)	25
4.7 Environmental aspects	26
4.7.1 General	26
4.7.2 Altitude	26
4.7.3 Temperature	26
4.7.4 Vibrations	26
4.7.5 Humidity	26
4.8 Duration of voltage stress	26
4.9 Electrical field distribution	27
5 Design for insulation coordination	27
5.1 General	27
5.1.1 Means of insulation coordination	27
5.1.2 Frequency above 30 kHz	27
5.1.3 Reduced distances due to coating or potting	27
5.1.4 Equipment which are not connected to public low-voltage systems.	27
5.2 Dimensioning of clearances	27

5.2.1	General	27
5.2.2	Dimensioning criteria for clearances	28
5.2.3	Other factors involving clearances	28
5.2.4	Dimensioning of clearances of functional insulation	29
5.2.5	Dimensioning of clearances of basic insulation, supplementary insulation and reinforced insulation.....	29
5.3	Dimensioning of creepage distances	30
5.3.1	General	30
5.3.2	Dimensioning criteria of creepage distances	31
5.3.3	Other factors involving creepage distances.....	32
5.3.4	Dimensioning of creepage distances of functional insulation	33
5.3.5	Dimensioning of creepage distances of basic insulation, supplementary insulation and reinforced insulation.....	34
5.4	Requirements for design of solid insulation	34
5.4.1	General	34
5.4.2	Voltage stress.....	34
5.4.3	Withstand of voltage stresses	34
5.4.4	Withstand on environmental stresses.....	36
6	Tests and measurements.....	36
6.1	General.....	36
6.2	Verification of clearances	37
6.2.1	General	37
6.2.2	Test voltages	37
6.3	Verification of creepage distances	40
6.4	Verification of solid insulation	40
6.4.1	General	40
6.4.2	Selection of tests	40
6.4.3	Conditioning	41
6.4.4	Impulse voltage test.....	42
6.4.5	AC power frequency voltage test	42
6.4.6	Partial discharge test.....	43
6.4.7	DC voltage test.....	45
6.4.8	High-frequency voltage test	45
6.5	Performing dielectric tests on complete equipment.....	45
6.5.1	General	45
6.5.2	Parts to be tested	45
6.5.3	Preparation of equipment circuits.....	46
6.5.4	Test voltage values.....	46
6.5.5	Test criteria	46
6.6	Other tests	46
6.6.1	Test for purposes other than insulation coordination	46
6.6.2	Sampling and routine tests	46
6.6.3	Measurement accuracy of test parameters.....	47
6.7	Measurement of the attenuation of the transient overvoltages.....	47
6.8	Measurement of clearances and creepage distances	47
Annex A (informative)	Basic data on withstand characteristics of clearances	53
Annex B (informative)	Nominal voltages of mains supply for different modes of overvoltage control	58

Annex C (normative) Partial discharge test methods	60
C.1 Test circuits	60
C.1.1 General	60
C.1.2 Test circuit for earthed test specimen (Figure C.1).....	60
C.1.3 Test circuit for unearthed test specimen (Figure C.2).....	61
C.1.4 Selection criteria.....	61
C.1.5 Measuring impedance.....	61
C.1.6 Coupling capacitor C_k	61
C.1.7 Filter.....	61
C.2 Test parameters.....	61
C.2.1 General	61
C.2.2 Requirements for the test voltage	62
C.2.3 Climatic conditions	62
C.3 Requirements for measuring instruments	62
C.3.1 General	62
C.3.2 Classification of PD meters.....	62
C.3.3 Bandwidth of the test circuit.....	63
C.4 Calibration	63
C.4.1 Calibration of discharge magnitude before the noise level measurement	63
C.4.2 Verification of the noise level.....	64
C.4.3 Calibration for the PD test	65
C.4.4 Calibration pulse generator.....	65
Annex D (informative) Additional information on partial discharge test methods	66
D.1 Measurement of partial discharge (PD), PD inception and extinction voltage.....	66
D.2 Description of PD test circuits (Figure D.1)	66
D.3 Precautions for reduction of noise.....	67
D.3.1 General	67
D.3.2 Sources in the non-energized test circuit	67
D.3.3 Sources in the energized test circuit	67
D.3.4 Measures for reduction of noise.....	67
D.4 Application of multiplying factors for test voltages	67
D.4.1 General	67
D.4.2 Example 1 (circuit connected to mains supply).....	68
D.4.3 Example 2 (internal circuit with maximum recurring peak voltage U_{rp}).....	68
Annex E (informative) Comparison of creepage distances specified in Table F.5 and clearances in Table A.1	69
Annex F (normative) Tables	70
Annex G (informative) Determination of clearance distances according to 5.2.....	79
Annex H (informative) Determination of creepage distances according to 5.3.....	81
Annex I (informative) Electrochemical migration of creepage distances in DC applications	83
I.1 The phenomenon of electrochemical migration	83
I.2 Effect of electrochemical migration on creepage distances in DC applications	83
Bibliography.....	85
Figure 1 – Recurring peak voltage	20
Figure 2 – Determination of the width (W) and height (H) of a rib	33
Figure 3 – Test voltages	44

Figure 4 – Across the groove	48
Figure 5 – Contour of the groove	49
Figure 6 – Contour of the groove with angle.....	49
Figure 7 – Contour of rib	49
Figure 8 – Uncemented joint with grooves less than X	50
Figure 9 – Uncemented joint with grooves equal to or more than X	50
Figure 10 – Uncemented joint with a groove on one side less than X	51
Figure 11 – Creepage distance and clearance through an uncemented joint	51
Figure 12 – Creepage distance and clearance to a head of screw more than X	51
Figure 13 – Creepage distance and clearance to a head of screw less than X	52
Figure 14 – Creepage distance and clearance with conductive floating part	52
Figure A.1 – Withstand voltage at 2 000 m above sea level.....	55
Figure A.2 – Experimental data measured at approximately sea level and their low limits for inhomogeneous field.....	56
Figure A.3 – Experimental data measured at approximately sea level and their low limits for homogeneous field	57
Figure C.1 – Earthed test specimen	60
Figure C.2 – Unearthed test specimen	61
Figure C.3 – Calibration for earthed test specimen.....	64
Figure C.4 – Calibration for unearthed test specimen.....	64
Figure D.1 – Partial discharge test circuits.....	66
Figure E.1 – Comparison between creepage distances specified in Table F.5 and clearances in Table A.1	69
Figure G.1 – Determination of clearance distances according to 5.2 (1 of 2)	79
Figure H.1 – Determination of creepage distances according to 5.3 (1 of 2).....	81
Table 1 – Dimensioning of grooves	48
Table A.1 – Withstand voltages for an altitude of 2 000 m above sea level (1 of 2)	53
Table A.2 – Altitude correction factors for clearance correction	54
Table B.1 – Inherent control or equivalent protective control	58
Table B.2 – Cases where protective control is necessary and control is provided by surge protective device having a ratio of voltage protection level to rated voltage not smaller than that specified in IEC 61643 (all parts)	59
Table F.1 – Rated impulse withstand voltage for equipment energized directly from the mains supply.....	70
Table F.2 – Clearances to withstand transient overvoltages.....	71
Table F.3 – Single-phase three-wire or two-wire AC or DC systems.....	72
Table F.4 – Three-phase four-wire or three-wire AC systems.....	73
Table F.5 – Creepage distances to avoid failure due to tracking (1 of 2)	74
Table F.6 – Test voltages for verifying clearances at different altitudes.....	76
Table F.7 – Severities for conditioning of solid insulation	76
Table F.8 – Dimensioning of clearances to withstand steady-state peak voltages, temporary overvoltages or recurring peak voltages ^b	77
Table F.9 – Additional information concerning the dimensioning of clearances to avoid partial discharge	77

Table F.10 – Altitude correction factors for clearance correction	78
-------------------------------------------------------------------------	----

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INSULATION COORDINATION FOR EQUIPMENT WITHIN LOW-VOLTAGE SUPPLY SYSTEMS –

Part 1: Principles, requirements and tests

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). [IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch> [and/or] www.iso.org/patents. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60664-1 edition 3.1 contains the third edition (2020-05) [documents 109/183/FDIS and 109/186/RVD], its corrigendum 1 (2020-10) and its amendment 1 (2025-05) [documents 109/235/FDIS and 109/240/RVD].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 60664-1 has been prepared by IEC technical committee 109: Insulation co-ordination for low-voltage equipment.

This third edition cancels and replaces the second edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) update of the Scope, Clauses 2 and 3,
- b) new structure for Clauses 4 and 5,
- c) addition of 1 500 V DC into tables in Annex B and F,
- d) update of distances altitude correction in a new Table F.10,
- e) addition of Annex G with a flowchart for clearances,
- f) addition of Annex H with a flowchart for creepage distances.

It has the status of a basic safety publication in accordance with IEC Guide 104.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
109/183/FDIS	109/186/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60664 series, published under the general title *Insulation coordination for equipment within low-voltage supply systems*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

In this document, the following print type is used:

– **Terms defined in Clause 3: in bold type.**

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INSULATION COORDINATION FOR EQUIPMENT WITHIN LOW-VOLTAGE SUPPLY SYSTEMS –

Part 1: Principles, requirements and tests

1 Scope

This part of IEC 60664 deals with **insulation coordination** for **electrical equipment** having a **rated voltage** up to AC 1 000 V or DC 1 500 V connected to **low-voltage supply systems**.

NOTE 1 Throughout this document, the term equipment is used with the meaning of **electrical equipment**.

This document applies to frequencies up to 30 kHz.

NOTE 2 Requirements for **insulation coordination** for equipment within **low-voltage supply systems** with rated frequencies above 30 kHz are given in IEC 60664-4.

NOTE 3 Higher voltages can exist in internal circuits of the equipment.

It applies to equipment for use up to 2 000 m above sea level and provides guidance for use at higher altitudes (See 5.2.3.4).

It provides requirements for technical committees to determine **clearances**, **creepage distances** and criteria for **solid insulation**. It includes methods of electrical testing with respect to **insulation coordination**.

The minimum **clearances** specified in this document do not apply where ionized gases are present. Special requirements for such situations can be specified at the discretion of the relevant technical committee.

This document does not deal with distances:

- through liquid insulation;
- through gases other than air;
- through compressed air.

This basic safety publication focusing on safety essential requirements is primarily intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications.

However, in case of missing specified values for **clearances**, **creepage distances** and requirements for **solid insulation** in the relevant product standards, or even missing standards, this document applies.

NOTE 4 Further explanations and examples with regard to the use of this document are provided in IEC TR 60664-2-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition

cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-2, *Environmental testing – Part 2-2: Tests – Tests B: Dry heat*

IEC 60068-2-14:2009, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-78, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60270, *High-voltage test techniques – Partial discharge measurements*

IEC 61140:2016, *Protection against electric shock – Common aspects for installation and equipment*

IEC 61180:2016, *High-voltage test techniques for low-voltage equipment – Definitions, test and procedure requirements, test equipment*