

Edition 2.0 2023-05 REDLINE VERSION

# INTERNATIONAL STANDARD



Multicore and symmetrical pair/quad cables for digital communications – Part 11: Symmetrical single pair cables with transmission characteristics up to 600 MHz 1,25 GHz – Horizontal floor wiring – Sectional specification

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.120.20 ISBN 978-2-8322-6984-8

Warning! Make sure that you obtained this publication from an authorized distributor.

# CONTENTS

F	DREWO	RD	5
1	Scop	e	7
2	Norm	native references	7
3	Term	is and definitions	8
4		llation considerations	
	4.1	General remarks	
	4.1	Bending radius of installed cable	
	4.3	Climatic conditions	
5	-	rials and cable construction	
•	5.1	General remarks	
	5.1	Cable construction	
	5.2	Conductor	
	5.4	Insulation	
	5.4	Cable element	
	5.6	Screening of the cable element	
	5.7	Cable make-up	
	5.8	Screening of the cable core	
	5.9	Sheath	
	5.10	Identification	
	5.10	Finished cable	
6		acteristics and requirements	
U	6.1	General remarks	
	6.2	Electrical characteristics and tests	
	6.2.1		
	6.2.1		
	6.2.3		
	6.2.4	· ·	
	6.2.5		
	6.2.6	•	
	6.2.7	·	
	6.2.8	·	
	6.2.9		
	6.3	Transmission characteristics	
	6.3.1		
	6.3.2		
	6.3.3		
	6.3.4		
	6.3.5	·	
	6.3.6		
	6.3.7	, -	
	6.3.8	· · · · · · · · · · · · · · · · · · ·	
	6.3.9	·	
	6.4	Mechanical and dimensional characteristics and requirements	
	6.4.1	·	
	6.4.2	·	
	6.4.3		

6.4.4	Elongation at break of the insulation	18
6.4.5	Adhesion of the insulation to the conductor	18
6.4.6	Elongation at break of the sheath	18
6.4.7	Tensile strength of the sheath	18
6.4.8	Crush test of the cable	18
6.4.9	Impact test of the cable	18
6.4.10	Bending under tension	18
6.4.11	Repeated bending of the cable	18
6.4.12	Tensile performance of the cable	18
6.4.13	Shock-test requirements of the cable	18
6.4.14	Bump-test requirements of the cable	
6.4.15	Vibration-test requirements of a cable	
6.5 Env	ironmental characteristics	19
6.5.1	Shrinkage of the insulation	19
6.5.2	Wrapping test of the insulation after thermal ageing	
6.5.3	Bending test of insulation at low temperature	19
6.5.4	Elongation at break of the sheath after ageing	
6.5.5	Tensile strength of the sheath after ageing	
6.5.6	Sheath pressure test at high temperature	
6.5.7	Cold bend test of the cable	
6.5.8	Heat shock test	
6.5.9	Damp heat steady state	
6.5.10	Solar radiation	
6.5.11	Solvents and contaminating fluids	
6.5.12	Salt mist and sulphur dioxide	
6.5.13	Water immersion	
6.5.14	Hygroscopicity	
6.5.15	Wicking	
6.5.16	Flame propagation characteristics of a single cable	
6.5.17	Flame propagation characteristics of bunched cables	
6.5.18	Halogen gas evolution	
6.5.19	Smoke generation	
6.5.20	Toxic gas emission	
6.5.21	Integrated fire test method for cables in environmental air handling	
	spaces	
7 Bundled o	able requirements	21
	eral	
7.2 Sing	ple pairs sharing one sheath	
7.2.1	General	
7.2.2	Near-end crosstalk (NEXT)	
7.2.3	Attenuation to crosstalk ratio far-end (PS ACR-F)	
Annex A (infor	mative) Blank detail specification	23
	mative) Background information for coupling attenuation and low	
	pling attenuation requirements	
Bibliography		29
Table 1 – Tran	sfer impedance	12
Table 2 – Cou	pling attenuation	12

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 11: Symmetrical single pair cables with transmission characteristics up to 600 MHz 1,25 GHz – Horizontal floor wiring – Sectional specification

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 61156-11:2019. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

**-6-**

IEC 61156-11 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This second edition cancels and replaces the first edition published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) additional cable type in support of T1-C generic single pair cabling up to 1,25 GHz;
- b) introduction of low frequency coupling attenuation as an integral parameter describing screening efficiency at frequencies below 30 MHz.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1254/FDIS	46C/1258/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at <a href="https://www.iec.ch/members\_experts/refdocs">www.iec.ch/members\_experts/refdocs</a>. The main document types developed by IEC are described in greater detail at <a href="https://www.iec.ch/publications">www.iec.ch/publications</a>.

A list of all parts in the IEC 61156 series, published under the general title *Multicore* and symmetrical pair/quad cables for digital communications, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

# MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 11: Symmetrical single pair cables with transmission characteristics up to 600 MHz 1,25 GHz – Horizontal floor wiring – Sectional specification

# 1 Scope

This part of IEC 61156 describes cables intended to be used for transmission of 1 Gbps over a single twisted pair for office, home and industrial application. An example of existing application is 1000BASE-T1, see ISO/IEC TR 11801-9906<sup>1</sup>. The transmission characteristics of these cables are specified up to a frequency of 600 MHz and at a temperature of 20 °C. The cable type recognised is intended to be used for shielded channels with a nominal length of 40 m. Possible designs are U/FTP, X/UTP and X/FTP, where X stands for F, S or SF. This part of IEC 61156 describes cables intended to be used for single balanced pair (office, home, industrial) applications according to ISO/IEC 11801-1. An example of existing application is 1000BASE-T1, see ISO/IEC TR 11801-9906. The transmission characteristics of these cables are specified up to a frequency of 1,25 GHz and at a temperature of 20 °C. The T1-C type cable is specified up to 600 MHz, the T1-D type cable up to 1,25 GHz. Depending on the MICE environment and the installation conditions either unscreened or screened cables can be used. A blank detail specification can be found in Annex A.

These cables can comprise more than one pair in the event that several systems are operated in parallel. In this case, refer to Clause 7.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains, they are intended to be used to support the delivery of low-voltage remote powering applications.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60708<del>:2005</del>, Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath

IEC 61156-1:2007, Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification

IEC 61156-1:2007/AMD1:2009<sup>2</sup>

<sup>&</sup>lt;sup>1</sup>—Under consideration.

<sup>2</sup> A consolidated version of this publication exists, comprising IEC 61156-1:2007 and IEC 61156-1:2007/AMD1:2009.

- 8 -

IEC 61156-5:2009, Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification

IEC 62153-4-3:2013, Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method

IEC 62153-4-5:2006, Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling Screening or screening coupling attenuation – Absorbing clamp method

IEC 62153-4-9:2018, Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method IEC 62153-4-9:2018/AMD1:2020

ISO/IEC TS 29125<del>:2017</del>, Information technology – Telecommunications cabling requirements for remote powering of terminal equipment



Edition 2.0 2023-05

# INTERNATIONAL STANDARD

Multicore and symmetrical pair/quad cables for digital communications – Part 11: Symmetrical single pair cables with transmission characteristics up to 1,25 GHz – Horizontal floor wiring – Sectional specification



# CONTENTS

Ε(	DREWO	RD	5
1	Scop	e	7
2	Norm	native references	7
3		s and definitions	
4		llation considerations	
-			
	4.1	General remarks  Bending radius of installed cable	
	4.2 4.3	Climatic conditions	
5		rials and cable construction	
5			
	5.1	General remarks	
	5.2	Cable construction	
	5.3	Conductor	
	5.4	Insulation	
	5.5	Cable element	
	5.6	Screening of the cable element	
	5.7	Cable make-up  Screening of the cable core	
	5.8 5.9	Sheath	
	5.9	Identification	
	5.10	Finished cable	
6		acteristics and requirements	
O			
	6.1	General remarks	
	6.2	Electrical characteristics and tests	
	6.2.1		
	6.2.2		
	6.2.3	9	
	6.2.4		
	6.2.5	•	
	6.2.6	'	
	6.2.7	·	
	6.2.8	1 9 1 9	
	6.2.9	, , ,	
	6.3	Transmission characteristics	
	6.3.1 6.3.2	Velocity of propagation (phase velocity)	
		, , ,	
	6.3.3 6.3.4		
	6.3.5		
	6.3.6	, , , , , , , , , , , , , , , , , , , ,	
	6.3.7		
	6.3.8	, -	
	6.3.9	•	
	6.4	Mechanical and dimensional characteristics and requirements	
	6.4.1	Dimensional requirements	
	6.4.1	·	
	6.4.2	3	
	0.4.3	renaite attemptif of the maticulation	10

6.4.4	Elongation at break of the insulation	16
6.4.5	Adhesion of the insulation to the conductor	16
6.4.6	Elongation at break of the sheath	16
6.4.7	Tensile strength of the sheath	16
6.4.8	Crush test of the cable	17
6.4.9	Impact test of the cable	17
6.4.10	Bending under tension	17
6.4.11	Repeated bending of the cable	17
6.4.12	Tensile performance of the cable	17
6.4.13	Shock-test requirements of the cable	17
6.4.14	Bump-test requirements of the cable	17
6.4.15	Vibration-test requirements of a cable	17
6.5 Env	ronmental characteristics	17
6.5.1	Shrinkage of the insulation	17
6.5.2	Wrapping test of the insulation after thermal ageing	17
6.5.3	Bending test of insulation at low temperature	17
6.5.4	Elongation at break of the sheath after ageing	17
6.5.5	Tensile strength of the sheath after ageing	18
6.5.6	Sheath pressure test at high temperature	18
6.5.7	Cold bend test of the cable	18
6.5.8	Heat shock test	18
6.5.9	Damp heat steady state	18
6.5.10	Solar radiation	18
6.5.11	Solvents and contaminating fluids	18
6.5.12	Salt mist and sulphur dioxide	
6.5.13	Water immersion	18
6.5.14	Hygroscopicity	18
6.5.15	Wicking	
6.5.16	Flame propagation characteristics of a single cable	
6.5.17	Flame propagation characteristics of bunched cables	
6.5.18	Halogen gas evolution	19
6.5.19	Smoke generation	19
6.5.20	Toxic gas emission	
6.5.21	Integrated fire test method for cables in environmental air handling spaces	
7 Bundled o	:able requirements	
	eral	
	le pairs sharing one sheath	
7.2.1	General	
7.2.2	Near-end crosstalk (NEXT)	
7.2.3	Attenuation to crosstalk ratio far-end (PS ACR-F)	
	mative) Blank detail specification	
-	mative) Background information for coupling attenuation and low	
	pling aftenuation requirements	26
Bibliography		27
Table 1 – Tran	sfer impedance	11
Table 2 – Cou	pling attenuation	12

Table 3 – Low frequency coupling attenuation	. 12
Table 4 – Attenuation equation constants	. 13
Table 5 – TCL requirements	. 14
Table 6 – EL TCTL requirements	. 14
Table 7 – PS ANEXT requirements	. 15
Table 8 – PS AACR-F requirements	. 15
Table 9 – RL requirements	. 16
Table 10 – NEXT and PS NEXT requirements	. 19
Table 11 – ACR-F and PS ACR-F requirements	. 20

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

\_\_\_\_\_

# MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

# Part 11: Symmetrical single pair cables with transmission characteristics up to 1,25 GHz – Horizontal floor wiring – Sectional specification

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61156-11 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This second edition cancels and replaces the first edition published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) additional cable type in support of T1-C generic single pair cabling up to 1,25 GHz;
- b) introduction of low frequency coupling attenuation as an integral parameter describing screening efficiency at frequencies below 30 MHz.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1254/FDIS	46C/1258/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at <a href="https://www.iec.ch/members\_experts/refdocs">www.iec.ch/members\_experts/refdocs</a>. The main document types developed by IEC are described in greater detail at <a href="https://www.iec.ch/publications">www.iec.ch/publications</a>.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

# MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

# Part 11: Symmetrical single pair cables with transmission characteristics up to 1,25 GHz – Horizontal floor wiring – Sectional specification

# 1 Scope

This part of IEC 61156 describes cables intended to be used for single balanced pair (office, home, industrial) applications according to ISO/IEC 11801-1. An example of existing application is 1000BASE-T1, see ISO/IEC TR 11801-9906. The transmission characteristics of these cables are specified up to a frequency of 1,25 GHz and at a temperature of 20 °C. The T1-C type cable is specified up to 600 MHz, the T1-D type cable up to 1,25 GHz. Depending on the MICE environment and the installation conditions either unscreened or screened cables can be used. A blank detail specification can be found in Annex A.

These cables can comprise more than one pair in the event that several systems are operated in parallel. In this case, refer to Clause 7.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains, they are intended to be used to support the delivery of low-voltage remote powering applications.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60708, Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath

IEC 61156-1, Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification

IEC 61156-5, Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification

IEC 62153-4-3, Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method

IEC 62153-4-5, Metallic communication cables test methods — Part 4-5: Electromagnetic compatibility (EMC) — Screening or coupling attenuation — Absorbing clamp method

IEC 62153-4-9:2018, Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method IEC 62153-4-9:2018/AMD1:2020

 ${\tt ISO/IEC\ TS\ 29125},\ Information\ technology-Telecommunications\ cabling\ requirements\ for\ remote\ powering\ of\ terminal\ equipment$