



IEC 61156-7

Edition 2.0 2023-02  
REDLINE VERSION

# INTERNATIONAL STANDARD



---

**Multicore and symmetrical pair/quad cables for digital communications –  
Part 7: Symmetrical pair cables with transmission characteristics up to  
1 200 MHz – Sectional specification for digital and analogue communication  
cables**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.120.20

ISBN 978-2-8322-6487-4

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	5
<b>1 General .....</b>	
1 Scope .....	8
2 Normative references .....	8
3 Terms and definitions .....	9
4 Installation consideration .....	9
4.1 General remarks .....	9
4.2 Bending radius of installed cable .....	9
4.3 Climatic conditions .....	9
5 Material and cable construction .....	9
5.1 General remarks .....	9
5.2 Cable construction .....	10
5.2.1 General .....	10
5.2.2 Conductor .....	10
5.2.3 Insulation .....	10
5.2.4 Cable element .....	10
5.2.5 Cable make-up .....	10
5.2.6 Screening of the cable core .....	11
5.2.7 Sheath .....	11
5.2.8 Identification .....	11
5.2.9 Finished cable .....	11
6 Characteristics and requirements .....	12
6.1 General remarks .....	12
6.2 Electrical characteristics and tests .....	12
6.2.1 Conductor resistance .....	12
6.2.2 Resistance unbalance within a pair .....	12
6.2.3 Dielectric strength .....	12
6.2.4 Insulation resistance .....	12
6.2.5 Mutual capacitance .....	12
6.2.6 Capacitance unbalance pair to ground .....	12
6.2.7 Transfer impedance .....	12
6.2.8 Coupling attenuation .....	13
6.2.9 Current-carrying capacity .....	13
6.2.10 Resistance of the screen .....	13
6.3 Transmission characteristics .....	13
6.3.1 General remark .....	13
6.3.2 Velocity of propagation (phase velocity) .....	14
6.3.3 Phase delay and differential phase delay (delay skew) .....	14
6.3.4 Attenuation ( $\alpha$ ) .....	14
6.3.5 Unbalance attenuation near-end (TCL, EL TCTL) .....	15
6.3.6 Near-end crosstalk (NEXT) (PS NEXT, NEXT) .....	16
6.3.7 Far-end crosstalk (FEXT) (PS ACR-F, ACR-F) .....	17
6.3.8 Alien (exogenous) near-end crosstalk .....	17
6.3.9 Alien (exogenous) far-end crosstalk .....	18
6.3.10 Alien (exogenous) crosstalk of bundled cables .....	18
6.3.11 Characteristic Impedance .....	18

6.3.12	Return loss ( <i>RL</i> ).....	17
<b>3.3.8</b>	<b>Screening attenuation</b>	
6.4	Mechanical and dimensional characteristics and requirements .....	19
6.4.1	Dimensional requirements .....	19
6.4.2	Elongation at break of the conductors.....	19
6.4.3	Tensile strength of the insulation .....	19
6.4.4	Elongation at break of the insulation .....	19
6.4.5	Adhesion of the insulation to the conductor.....	19
6.4.6	Elongation at break of the sheath .....	19
6.4.7	Tensile strength of the sheath.....	19
6.4.8	Crush test of the cable.....	19
6.4.9	Impact test of the cable .....	19
6.4.10	Bending under tension.....	19
6.4.11	Repeated bending of the cable .....	20
6.4.12	Tensile performance of the cable .....	20
6.4.13	Shock-test requirements of the cable.....	20
6.4.14	Bump-test requirements of the cable .....	20
6.4.15	Vibration-test requirements of the cable.....	20
6.5	Environmental characteristics .....	20
6.5.1	Shrinkage of insulation .....	20
6.5.2	Wrapping test of insulation after thermal ageing .....	20
6.5.3	Bending test of insulation at low temperature.....	20
6.5.4	Elongation at break of the sheath after ageing .....	20
6.5.5	Tensile strength of the sheath after ageing .....	20
6.5.6	Sheath pressure at high temperature.....	20
6.5.7	Cold bend test of the cable .....	21
6.5.8	<b>Heat Hot shock test</b> .....	21
6.5.9	Damp heat steady state .....	21
6.5.10	Solar radiation (UV).....	21
6.5.11	Solvents and contaminating fluids.....	21
6.5.12	Salt mist and sulphur dioxide .....	21
6.5.13	Water immersion .....	21
6.5.14	Hygroscopicity .....	21
6.5.15	Wicking.....	21
6.5.16	Flame propagation characteristics of a single cable .....	21
6.5.17	Flame propagation characteristics of bunched cables .....	21
<b>3.5.11</b>	<b>Acid gas evolution</b> .....	
6.5.18	Resistance to fire.....	21
6.5.19	Halogen gas evolution .....	22
6.5.20	Smoke generation.....	22
6.5.21	Toxic gas emission .....	22
<b>3.5.14</b>	<b>Combined flame and smoke test</b> .....	
6.5.22	Integrated fire test .....	22
7	Introduction to the blank detail specification .....	21
Annex A (informative)	Blank detail specification .....	23
Bibliography.....		28
Table 1 – Transfer impedance .....		13

Table 2 – Coupling attenuation .....	13
Table 3 – Attenuation, constant values .....	15
Table 4 – Attenuation values.....	15
Table 5 – Near-end crosstalk, power-sum ( <i>PS NEXT</i> ).....	16
Table 6 – Far-end crosstalk- <del>FEXT</del> ( <i>PS ACR-F</i> ) .....	17
Table 7 – Return loss.....	18

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES  
FOR DIGITAL COMMUNICATIONS –****Part 7: Symmetrical pair cables with transmission  
characteristics up to 1 200 MHz –  
Sectional specification for digital and analogue  
communication cables****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 61156-7:2003+AMD1:2012 CSV. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.**

IEC 61156-7 has been prepared by subcommittee 46C: Wires and symmetrical cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This part of IEC 61156 is to be read in conjunction with IEC 61156-1:2023.

This second edition cancels and replaces the first edition published in 2003 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) restructure all text to comply with ISO/IEC Directives Part 2;
- b) align clauses with IEC 61156-1:2023;
- c) remove the clause related to screening attenuation as it is no longer a test to be performed (replaced by coupling attenuation);
- d) replace the IEC 62153-4-2 method (injection clamp) with IEC 61156-4-5 (absorbing clamp) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- e) include IEC 62153-4-9 test method (triaxial) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- f) incorporate the blank detail specification.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1228/CDV	46C/1233/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT** – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

## MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

### Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

#### 1 General

##### 1 Scope

This part of IEC 61156 specifies cables that ~~may~~ can be used for various communication systems as well as for analogue systems, such as video, that exist or are under development and which may use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems as well as to enhance present systems.

It covers a cable having four individually screened (~~STPS/FTP~~) pairs. The cable ~~may~~ can be provided with a common screen over the cable core.

The transmission characteristics are specified up to a frequency of 1 200 MHz and at a temperature of 20 °C.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems ~~and support the delivery of DC low voltage remote powering applications~~. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supply of public utility mains.

##### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60189-1:1986, Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods~~

IEC 60304, Standard colours for insulation for low-frequency cables and wires

IEC 61156-1:~~2002~~, Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification

~~IEC 61156-7-1, Multicore and symmetrical pair/quad cables for digital communications – Part 7-1: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Blank detail specification for digital and analog communication cables~~

~~IEC 62153-4-2, Metallic telecommunication cable test methods – Part 4-2: Electromagnetic compatibility (EMC) – Screening and coupling attenuation – Injection clamp method~~

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cable test methods – Part 4-5: Electromagnetic compatibility (EMC) – Screening or coupling attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

# INTERNATIONAL STANDARD

---

**Multicore and symmetrical pair/quad cables for digital communications –  
Part 7: Symmetrical pair cables with transmission characteristics up to  
1 200 MHz – Sectional specification for digital and analogue communication  
cables**



## CONTENTS

FOREWORD .....	5
1 Scope .....	7
2 Normative references .....	7
3 Terms and definitions .....	7
4 Installation consideration .....	8
4.1 General remarks .....	8
4.2 Bending radius of installed cable.....	8
4.3 Climatic conditions.....	8
5 Material and cable construction .....	8
5.1 General remarks .....	8
5.2 Cable construction .....	8
5.2.1 General .....	8
5.2.2 Conductor.....	8
5.2.3 Insulation.....	9
5.2.4 Cable element .....	9
5.2.5 Cable make-up .....	9
5.2.6 Screening of the cable core .....	9
5.2.7 Sheath.....	9
5.2.8 Identification.....	10
5.2.9 Finished cable .....	10
6 Characteristics and requirements .....	10
6.1 General remarks .....	10
6.2 Electrical characteristics and tests .....	10
6.2.1 Conductor resistance.....	10
6.2.2 Resistance unbalance within a pair.....	10
6.2.3 Dielectric strength.....	10
6.2.4 Insulation resistance.....	11
6.2.5 Mutual capacitance.....	11
6.2.6 Capacitance unbalance pair to ground.....	11
6.2.7 Transfer impedance.....	11
6.2.8 Coupling attenuation.....	11
6.2.9 Current-carrying capacity.....	12
6.2.10 Resistance of the screen .....	12
6.3 Transmission characteristics .....	12
6.3.1 General remark.....	12
6.3.2 Velocity of propagation (phase velocity).....	12
6.3.3 Phase delay and differential phase delay (delay skew) .....	12
6.3.4 Attenuation ( $\alpha$ ).....	13
6.3.5 Unbalance attenuation near-end ( $TCL$ , $EL$ $TCTL$ ).....	13
6.3.6 Near-end crosstalk ( $PS$ $NEXT$ , $NEXT$ ).....	14
6.3.7 Far-end crosstalk ( $PS$ $ACR-F$ , $ACR-F$ ) .....	15
6.3.8 Alien (exogenous) near-end crosstalk .....	16
6.3.9 Alien (exogenous) far-end crosstalk.....	16
6.3.10 Alien (exogenous) crosstalk of bundled cables .....	16
6.3.11 Impedance.....	16
6.3.12 Return loss ( $RL$ ).....	16

6.4	Mechanical and dimensional characteristics and requirements .....	17
6.4.1	Dimensional requirements .....	17
6.4.2	Elongation at break of the conductors .....	17
6.4.3	Tensile strength of the insulation .....	17
6.4.4	Elongation at break of the insulation .....	17
6.4.5	Adhesion of the insulation to the conductor.....	17
6.4.6	Elongation at break of the sheath .....	17
6.4.7	Tensile strength of the sheath.....	17
6.4.8	Crush test of the cable.....	17
6.4.9	Impact test of the cable .....	17
6.4.10	Bending under tension.....	18
6.4.11	Repeated bending of the cable .....	18
6.4.12	Tensile performance of the cable.....	18
6.4.13	Shock-test requirements of the cable.....	18
6.4.14	Bump-test requirements of the cable .....	18
6.4.15	Vibration-test requirements of the cable.....	18
6.5	Environmental characteristics .....	18
6.5.1	Shrinkage of insulation .....	18
6.5.2	Wrapping test of insulation after thermal ageing .....	18
6.5.3	Bending test of insulation at low temperature.....	18
6.5.4	Elongation at break of the sheath after ageing.....	18
6.5.5	Tensile strength of the sheath after ageing .....	18
6.5.6	Sheath pressure at high temperature .....	18
6.5.7	Cold bend test of the cable .....	19
6.5.8	Hot shock test.....	19
6.5.9	Damp heat steady state .....	19
6.5.10	Solar radiation (UV) .....	19
6.5.11	Solvents and contaminating fluids.....	19
6.5.12	Salt mist and sulphur dioxide .....	19
6.5.13	Water immersion .....	19
6.5.14	Hygroscopicity .....	19
6.5.15	Wicking.....	19
6.5.16	Flame propagation characteristics of a single cable .....	19
6.5.17	Flame propagation characteristics of bunched cables .....	19
6.5.18	Resistance to fire.....	19
6.5.19	Halogen gas evolution .....	19
6.5.20	Smoke generation.....	20
6.5.21	Toxic gas emission .....	20
6.5.22	Integrated fire test .....	20
7	Introduction to the blank detail specification .....	20
Annex A (informative)	Blank detail specification .....	21
Bibliography	.....	26
Table 1	– Transfer impedance .....	11
Table 2	– Coupling attenuation .....	11
Table 3	– Attenuation, constant values .....	13
Table 4	– Attenuation values.....	13
Table 5	– Near-end crosstalk, power-sum ( <i>PS NEXT</i> ).....	15

Table 6 – Far-end crosstalk ( <i>PS ACR-F</i> ) .....	16
Table 7 – Return loss.....	17

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES  
FOR DIGITAL COMMUNICATIONS –****Part 7: Symmetrical pair cables with transmission  
characteristics up to 1 200 MHz –  
Sectional specification for digital and analogue  
communication cables****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61156-7 has been prepared by subcommittee 46C: Wires and symmetrical cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This part of IEC 61156 is to be read in conjunction with IEC 61156-1:2023.

This second edition cancels and replaces the first edition published in 2003 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) restructure all text to comply with ISO/IEC Directives Part 2;

- b) align clauses with IEC 61156-1:2023;
- c) remove the clause related to screening attenuation as it is no longer a test to be performed (replaced by coupling attenuation);
- d) replace the IEC 62153-4-2 method (injection clamp) with IEC 61156-4-5 (absorbing clamp) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- e) include IEC 62153-4-9 test method (triaxial) for coupling attenuation measurement to be consistent with all other parts of the IEC 61156 series;
- f) incorporate the blank detail specification.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46C/1228/CDV	46C/1233/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

### Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analogue communication cables

#### 1 Scope

This part of IEC 61156 specifies cables that can be used for various communication systems as well as for analogue systems, such as video, that exist or are under development and which may use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems as well as to enhance present systems.

It covers a cable having four individually screened (S/FTP) pairs. The cable can be provided with a common screen over the cable core.

The transmission characteristics are specified up to a frequency of 1 200 MHz and at a temperature of 20 °C.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems and support the delivery of DC low voltage remote powering applications. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supply of public utility mains.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-5, *Metallic communication cable test methods – Part 4-5: Electromagnetic compatibility (EMC) – Screening or coupling attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*