TECHNICAL IEC SPECIFICATION TS 61334-5-5

First edition 2001-09

Distribution automation using distribution line carrier systems –

Part 5-5: Lower layer profiles – Spread spectrum-fast frequency hopping (SS-FFH) profile

© IEC 2001 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission 3, rue de Varembé Geneva, Switzerland Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site http://www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия

PRICE CODE



CONTENTS

FO	REW	ORD	3		
IN٦	RODI	UCTION	5		
1	Scor	e and object	6		
2	Normative references				
3	Abbreviations and definitions				
	3.1	Abbreviations			
	3.2 Definitions				
4	Physical layer				
	4.1	Purpose			
	4.2	Electrical characteristics			
	4.3	Modulation principle			
	4.4	Receiver principle			
	4.5	Synchronization			
	4.6	Frequency sets			
	4.7	Physical frame encapsulation			
	4.8	Symbol, bit and byte encoding			
	4.9	Important parameters			
	4.10	Physical layer data services			
	4.11	Physical layer management interface			
		Physical layer states			
5	Medi	16			
	5.1	Outline			
	5.2	Repeater principle	20		
	5.3	MAC layer data service definition			
	5.4	MAC layer timeout values	22		
	5.5	MAC sublayer management services			
	5.6	MAC layer states	27		
Fig	ure 1	Time representation of M = 3 SS-FFH symbol	8		
Fig	ure 2	- Coding of information symbols in sequence of carrier chips	8		
Figure 3 – Actual P_PDU representation					
Figure 4 – MAC services					
Figure 5 – Frame decomposition					
•	Figure 6 – MAC management services				
Figure 7 – Example segmentation of M SDU					
ria	ure /	- Example Segmentation of M. SDU	29		

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DISTRIBUTION AUTOMATION USING DISTRIBUTION LINE CARRIER SYSTEMS –

Part 5-5: Lower layer profiles – Spread spectrum-fast frequency hopping (SS-FFH) profile

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this technical specification may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

IEC 61334-5-5, which is a technical specification, has been prepared by IEC technical committee 57: Power system control and associated communications.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
57/489/CDV	57/518/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

The committee has decided that the contents of this publication will remain unchanged until 2004. At this date, the publication will be

- transformed into an International Standard;
- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This technical specification describes a new physical layer variant with respect to the already defined modulation techniques FSK and S-FSK within the IEC 61334 series (IEC 61334-5-1 and IEC 61334-5-2 1)).

The SS-FFH profile outlined in this technical specification basically incorporates spread spectrum modulation techniques. It offers the main advantages of very high robustness and improved EMI characteristics without sharing classical spread spectrum drawbacks such as exaggerated bandwidth demand or impractical realization.

The profile specifies the physical layer including the transmission methods and the services provided by both the physical layer and medium access sublayer entities.

¹⁾ IEC 61334-5-1, Distribution automation using distribution line carrier systems – Part 5-1: Lower layer profiles – The spread frequency shift keying (S-FSK) profile

IEC 61334-5-2, Distribution automation using distribution line carrier systems – Part 5-2: Lower layer profiles – Frequency shift keying (FSK) profile

DISTRIBUTION AUTOMATION USING DISTRIBUTION LINE CARRIER SYSTEMS –

Part 5-5: Lower layer profiles – Spread spectrum-fast frequency hopping (SS-FFH) profile

1 Scope and object

This technical specification describes the requirements of the spread spectrum-fast frequency hopping (SS-FFH) approach for distribution line carrier communication systems. It incorporates the primitives provided by the physical and MAC layer entities as well as the modulation and transmission methods.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61334. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 61334 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 61000-3-8, Electromagnetic compatibility (EMC) – Part 3: Limits – Section 8: Signalling on low-voltage electrical installations – Emission levels, frequency bands and electromagnetic disturbance levels

IEC 61334-4-1, Distribution automation using distribution line carrier systems – Part 4: Data communication protocols – Section 1: Reference model of the communication system

IEC 61334-4-32, Distribution automation using distribution line carrier systems – Part 4: Data communication protocols – Section 32: Data link layer – Logical Link Control (UC)

ITU-T Recommendation V.42, Error-correcting procedures for DCEs using asynchronous-to-synchronous conversion