

INTERNATIONAL STANDARD

IEC 61847

First edition
1998-01

Ultrasonics – Surgical systems – Measurement and declaration of the basic output characteristics

Ultrasons – Systèmes de chirurgie –

*Mesure et déclaration des caractéristiques
de sortie*

© IEC 1998 Droits de reproduction réservés — Copyright - all rights reserved

Aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'éditeur.

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission
Telefax: +41 22 919 0300

e-mail: inmail@iec.ch

3, rue de Varembe Geneva, Switzerland
IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CODE PRIX
PRICE CODE

V

*Pour prix, voir catalogue en vigueur
For price, see current catalogue*

CONTENTS

	Page
FOREWORD	3
INTRODUCTION	4
Clause	
1 Scope	5
2 Normative references	5
3 Definitions	6
4 List of symbols	9
5 General measurement requirements	9
5.1 Operating conditions	9
5.2 Load conditions	9
5.3 Preparation for measurements	10
6 Measurement procedures	10
6.1 Primary tip vibration excursion	10
6.2 Secondary tip vibration excursion	11
6.3 Drive frequency	11
6.4 Tip vibration frequency	11
6.5 Derived output acoustic power and output acoustic power	12
6.6 Directivity pattern	13
6.7 Primary tip vibration excursion modulation	13
6.8 Duty cycle	14
6.9 Quiescent electrical power	14
6.10 Maximum electrical power	14
6.11 Primary acoustic output area	15
6.12 Secondary acoustic output area	15
6.13 Power reserve index	15
7 Declaration of output characteristics	15
Figures	16
Annexes	
A Measurement methods and conditions	21
B Theory of operation of ultrasonic surgical devices	26
C Bibliography	29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ULTRASONICS – SURGICAL SYSTEMS –
Measurement and declaration of the basic output characteristics**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61847 has been prepared by IEC technical committee 87: Ultrasonics.

The text of this standard is based on the following documents:

FDIS	Report on voting
87/114/FDIS	87/117/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

Annexes A, B and C are for information only.

In this standard the following print types are used:

- Requirements: in roman type
- *Test specifications: in italic type*
- Notes: in small roman type
- Words in **bold** in the text are defined in clause 3.

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

Ultrasonic surgical systems, operating in the 20 kHz to 60 kHz range, are used widely in ophthalmology and neurosurgery to fragment or disintegrate and aspirate unwanted tissue. Their commercial use in ophthalmology started in 1970. Their application in neurosurgery followed about 10 years later. Ultrasonic surgical systems are also widely used in oncology surgery.

This International Standard defines the parameters which characterize the output and performance of open and closed site ultrasonic surgical systems, and indicates which parameters should be declared. In addition, measurement procedures are described so that technically qualified people will be able to report on the parameters in a uniform and understandable fashion. An open surgical site is one in which the incision is large relative to the size of the applicator tip being inserted thus precluding any increase in pressure of the organ due to an imbalance of irrigant flow and suction flow. An example of a closed surgical site is an eye where the incision is closely controlled.

This International Standard does not provide any guidance on what is the resultant safety or efficacy of devices described by these parameters since very little scientifically controlled data are available by which such judgements can be made.

ULTRASONICS – SURGICAL SYSTEMS – Measurement and declaration of the basic output characteristics

1 Scope

This International Standard specifies:

- the essential non-thermal output characteristics of ultrasonic surgical units;

NOTE 1 – One of the parameters of interest is output acoustic power. This standard addresses only the low-frequency (under 100 kHz) component of the total delivered energy. The high-frequency component, which probably relates to cavitation developed at the tip, is not addressed (see A.4).

- methods of measurement of these output characteristics;
- those characteristics which should be declared by the manufacturers of such equipment.

NOTE 2 – In the interest of clarity, this standard does not address all of the complex surfaces and shapes possible for **applicator tips**. A straight tubular shape is used in the description of the parameters and measurements to be made. It is left to the user of this standard to adapt the basic methodology described to more complex designs if required.

This International Standard is applicable to equipment which meets the requirements of a, b and c below:

- ultrasonic surgical systems operating in the frequency range 20 kHz to 60 kHz; and
- ultrasonic surgical systems, whose use is the fragmentation or cutting of human tissue, whether or not those effects are delivered in conjunction with tissue removal or coagulation; and
- ultrasonic surgical systems, in which an acoustic wave is conducted by means of a specifically designed wave guide to deliver energy to the surgical site.

NOTE 3 – Examples of these types of systems are surgical aspirators, intracorporeal lithotripters, end-cutting devices etc.

This International Standard is not applicable to:

- lithotripsy equipment which uses extracorporeally induced pressure pulses, focussed through liquid conducting media and the soft tissues of the body;
- surgical devices used as part of the therapeutic process (hyperthermia systems);
- surgical devices whose acoustic application areas are not at the end of a longitudinally vibrating applicator tip and therefore would not fit the monopole model used in this standard.

This International Standard does not deal with the effectiveness or safety of ultrasonic surgical systems.

NOTE 4 – Throughout this standard, the term accuracy means the overall uncertainty expressed at the 95 % confidence level.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60500:1974, *IEC standard hydrophone*

IEC 61205:1993, *Ultrasonics – Dental descaler systems – Measurement and declaration of the output characteristics*