# TECHNICAL SPECIFICATION

### IEC TS 61895

First edition 1999-10

# Ultrasonics – Pulsed Doppler diagnostic systems – Test procedures to determine performance

Ultrasons – Systèmes de diagnostic à effet Doppler pulsés – Procédures d'essai pour déterminer la performance

© IEC 1999 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission 3, rue de Varembé Geneva, Switzerland Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site http://www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия

PRICE CODE



#### CONTENTS

				Page		
FO	REWO	)RD		4		
IN	rodu	JCTION		6		
Cla	use					
1	Scop	e		7		
2	Norm	ative re	ferences	7		
3	Defin	itions		7		
4	Symb	ools		12		
5	Over	all tests	of complete systems	12		
	5.1	General considerations				
	0.1	5.1.1	Types of pulsed <b>Doppler ultrasound systems</b>			
		5.1.2	Worst-case conditions			
		5.1.3	Doppler beam axes			
		5.1.4	Probe/target distance variation and measurement			
	5.2		conditions			
	0	5.2.1	Power supply			
		5.2.2	Target movement direction			
		5.2.3	Propagation medium			
		5.2.4	Penetration depth			
		5.2.5	Working depth			
		5.2.6	Focusing			
		5.2.7	Working Doppler angle			
		5.2.8	Wall-thump filter cut-off frequency			
		5.2.9	Transmitter output power			
		5.2.10	Working pulse repetition frequency (PRF)			
		5.2.11	Doppler (receiver) gain			
		5.2.12	Test frequency	17		
		5.2.13	Working sample volume length	17		
			Doppler signal power measurement			
	5.3	Zero si	gnal noise level	17		
	5.4	Dopple	er frequency response	18		
		5.4.1	Frequency response range	18		
		5.4.2	Deviation from flat response	18		
		5.4.3	Large signal performance	18		
	5.5	Spatial	response	19		
		5.5.1	Sample volume response	19		
	5.6	Sample	e volume position registration error	20		
	5.7	5.7 Beam position and orientation				
	5.8	5.8 Intrinsic broadening				
	5.9	Dead z	zone	22		
	5.10	Acoust	ic working frequency	22		
	5.11	Flow direction separation				
	5.12	.12 Velocity estimation accuracy				

	5.13	Volume flow estimation accuracy	. 22	
	5.14	Maximum, mean, mode and median frequency estimation accuracy	. 23	
	5.15	Velocity waveform indices estimation accuracy	. 25	
6	Doppler test objects			
	6.1	Test objects	. 26	
	6.2	Electronic test object	26	
Anr	ex A	(normative) Description of pulsed <b>Doppler ultrasound systems</b>	. 28	
A.1	Sin	gle-channel system	. 28	
A.2	Multi-channel system2			
A.3	Aliasing			
A.4	Dup	lex and triplex scanners	. 29	
		·		
Ribl	ioarai	phy	32	

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

\_\_\_\_\_

## ULTRASONICS – PULSED DOPPLER DIAGNOSTIC SYSTEMS – TEST PROCEDURES TO DETERMINE PERFORMANCE

#### **FOREWORD**

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this technical specification may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 61895, which is a technical specification, has been prepared by IEC technical committee 87: Ultrasonics.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting	
87/151/CDV	87/168/RVC	

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

Annex A forms an integral part of this technical specification.

The committee has decided that this publication remains valid until 2005. At this date, in accordance with the committee's decision, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

#### INTRODUCTION

Pulsed ultrasonic Doppler flowmeters and velocimeters are widely used in clinical practice, usually in combination with real-time **B-mode** imaging and colour-flow imaging instruments. The device periodically transmits pulses of ultrasound from an ultrasound transducer and measures the Doppler shift in the frequency of ultrasound reflected and scattered from moving tissues. This Doppler shift is proportional to the component of reflector or scatterer velocity along the ultrasound beam. By looking for Doppler shifts in the received signal at specific times after transmission (range-gating), the device can be used to determine the variation of tissue velocity with distance along the ultrasound beam. The device is sensitive to movement only within a region of the beam called the sample volume. The position of the sample volume along the beam may be adjusted by altering the delay between transmission and range-gating. Multichannel devices have a number of sample volumes operating simultaneously.

The pulsed ultrasonic device is most commonly used to investigate blood flow when the ultrasound is scattered from red blood cells.

This technical specification describes a range of tests which may be used to measure performance and the test objects required. In many cases, the test method and test object have been described in IEC 61206 and in these cases reference is simply made to this document. Other tests and test objects are described in [1] and [2]. The test methods may be considered as falling into one of the following three categories. The first is routine quality control tests that can be carried out by a clinician or technologist to ensure that the system is working adequately or has adequate sensitivity. The second is more elaborate test methods, conducted less frequently, when, for example, the system is suspected of malfunctioning. The third represents tests that would be carried out by a manufacturer on complete systems in order to guarantee compliance with specification.

### ULTRASONICS – PULSED DOPPLER DIAGNOSTIC SYSTEMS – TEST PROCEDURES TO DETERMINE PERFORMANCE

#### 1 Scope

This technical specification describes

- test methods for measuring the performance of pulsed **Doppler ultrasound systems**;
- Doppler test objects for carrying out these tests;

and applies to

- tests made on an overall pulsed **Doppler ultrasound system**, a system which is not disassembled or disconnected;
- tests made on pulsed **Doppler ultrasound systems** whether they are stand-alone or as part of another ultrasound instrument.

Electrical safety, acoustic output and electromagnetic compatibility (EMC) are not covered in this technical specification.

The workload to perform all described tests is, in general, prohibitive. It is intended that a subset of the described tests is adopted for regular use. However, experience to give guidance for selection has still to be gathered and will be the subject of ongoing work.

#### 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this technical specification. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this technical specification are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 61102:1991, Measurement and characterisation of ultrasonic fields using hydrophones in the frequency range 0,5 MHz to 15 MHz

IEC 61206:1993, Ultrasonics - Continuous-wave Doppler systems - Test procedures

IEC 61390:1996, Ultrasonics – Real-time pulse-echo systems – Test procedures to determine performance specifications