

Edition 2.0 2008-05

INTERNATIONAL STANDARD

Mobile and portable DVB-T/H radio access – Part 1: Interface specification

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE XB

ICS 33.170 ISBN 2-8318-9750-5

CONTENTS

FO	REWO	ORD	6		
1	Scop	pe	8		
2	Normative references				
3	Abbreviations				
4	Term	ninal categories	11		
5	Defin	nition of receiving conditions	12		
	5.1	Portable reception			
	5.2	Mobile reception			
6	Frequ	uencies and channel bandwidths	13		
	6.1	Channel frequencies	13		
	6.2	Supported frequency ranges	13		
	6.3	Supported bandwidths	14		
7	DVB-	-T/H modes	14		
	7.1	Supported DVB-T/H modes	14		
	7.2	Change of modulation parameters	14		
	7.3	Tuning procedure			
8	Trans	smitter performance			
	8.1	Transmitter noise-like impairments	15		
		8.1.1 Noise-like processes			
	8.2	Further transmitter impairments			
		8.2.1 Group delay errors			
		8.2.2 Phase noise in OFDM systems			
	0.0	8.2.3 OFDM clock frequency			
	8.3	Spectrum masks			
		8.3.1 DVB-T signals (general)			
		8.3.2 DVB-T signals (critical cases)			
9	Rece	eiver antenna characteristics			
5	9.1	Antennas for terminal category a			
	9.2	Antennas for terminal category b1			
	9.3	Antennas for terminal category b2 and c			
	9.4	External antennas			
	•	9.4.1 General			
		9.4.2 External antennas for terminal category b2 and c			
		9.4.3 External antenna connector			
10	Rece	eiver performance	21		
	10.1	Reference model	21		
	10.2	Noise model	22		
	10.3	Degradation criteria	24		
	10.4	Diversity receivers	25		
		DVB-H receivers			
	10.6	Channel models			
		10.6.1 DVB-T Rayleigh channel (P ₁)			
		10.6.2 Portable indoor (PI) and outdoor (PO) channels			
		10.6.3 Mobile reception	29		

10.7 <i>C/N</i> performance	34
10.7.1 C/N performance in Gaussian channel	34
10.7.2 C/N performance in DVB-T Rayleigh channel (P ₁)	34
10.7.3 C/N Performance in portable indoor (PI) and portable outdoor (PO)	
channels	
10.7.4 DVB-T <i>C/N</i> performance in mobile channels for terminal class a	
10.7.5 DVB-H <i>C/N</i> performance in mobile channels	
10.8 Receiver minimum and maximum signal input levels	
10.8.1 Noise floor	
10.8.2 Minimum input levels (sensitivity)	
10.8.3 Total maximum power for wanted and unwanted signals	
10.8.4 Maximum input levels for wanted and unwanted signals	
10.9 Immunity to analogue and/or digital signals in other channels	
10.9.1 General	
10.9.2 Interfering signal definitions	
10.9.3 Selectivity patterns	
10.9.4 Linearity patterns	
10.9.5 Immunity to pattern S1	
10.9.6 Immunity to pattern S2	
10.9.7 Immunity to pattern L1	
10.9.8 Immunity to pattern L2	
10.9.9 Immunity to pattern L3	
10.9.10 Immunity to pattern L4	
10.10 Immunity to co-channel interference from analogue TV signals	
10.11.1 Performance with echo within guard interval	
10.11.2 Performance with echo outside guard interval	
10.12 Tolerance to impulse interference	
10.12.1 General	
10.12.2 Test patterns	
10.13 EMC characteristics	
10.13.1 Terminal category c	
10.13.2 Terminal category a and b	
11 Interoperability with other radio systems	
11.1 Cellular radios	
11.1.1 General	
11.1.2 Cellular radio uplink wanted signal interference to DVB-T/H receiver	-
11.1.3 Cellular radio uplink wanted signal interference to DVB-T/H	30
receiver	57
11.2 DVB-RCT	
Annex A (informative) Active external antennas and system noise floor	
Annex B (informative) An example of C/N -performance with a practical transmitter	
Annex C (informative) Multipath reception in a DVB-T system	
Bibliography	ังช
Figure 1 – Reference model	
Figure 2 – Noise model	23
Figure 3 – Antenna diversity receiver	26

Figure 4 – Receiver behaviour in a mobile channel	30
Figure 5 – DVB-H reference receiver C/N behaviour in mobile channel	31
Figure 6 – Mobile SFN synchronisation test channel for weak long echo	32
Figure 7 – Mobile SFN synchronisation test channel for strong long echo	33
Figure 8 – Mobile SFN synchronisation test channel for strong short echo	33
Figure 9 – PAL interfering signals	41
Figure 10 – SECAM L interfering signal	42
Figure 11 – Pattern S1 in case of N+1 or N-1	43
Figure 12 – Pattern S2 in case of N + 1 or N – 1	44
Figure 13 – Pattern L1	45
Figure 14 – Pattern L2	46
Figure 15 – Pattern L3	47
Figure 16 – Pattern L4	49
Figure 17 – Echo outside guard interval mask	50
Figure 18 – Mask for echo outside GI for GI = 1/4	52
Figure 19 – Definition of the impulse interference test pattern	
Figure 20 – Terminal architectures	
Figure 21 – Frequency bands	
Figure 22 – GSM Tx block diagram	57
Figure 23 – Tx PA-noise mask in DVB-T/H receiver input	58
Figure A.1 – System noise floor versus receiver noise figure for different levels of manmade-noise $F_{\mathbf{a}}$ relative to T_{0}	62
Figure C.1 – Theoretical limits of out of guard delay	64
Figure C.2 – DVB-T model – Splitting of the signal power into contributing and interfering components	65
Figure C.3 – Theoretical echo power profile for 8k, 64QAM, 2/3	67
Table 1 – Supported frequency ranges	14
Table 2 – Conversion of MER to END	16
Table 3 – Typical antenna gain for terminal category b2 and c	19
Table 4 – Specification for optional antenna supply	
Table 5 – Modulation versus implementation margin	23
Table 6 – Delta values between picture failure point and reference BER	25
Table 7 – Approximation of the DVB-T specified Rayleigh channel	27
Table 8 – Doppler spectrum definitions for PI and PO channels	
Table 9 – Definition of PI channel	
Table 10 – Definition of PO channel	
Table 11 – Typical urban profile (TU6) constitution	
Table 12 – Mobile SFN synchronisation test channel for weak long echo	
Table 13 – Mobile SFN synchronisation test channel for strong long echo	
Table 14 – Mobile SFN synchronisation test channel for strong short echo	
Table 15 – DVB-T <i>C/N</i> (dB) for reference <i>BER</i> in Gaussian channel	
Table 16 – DVB-H C/N (dB) for 5% MFER in Gaussian channel	
Table 17 – C/N (dB) for reference RER in DVB-T Rayleigh channel (P ₄)	35

Table 18 – C/N (dB) for 5 % MFER in portable channel	35
Table 19 - C/N (dB) for 5 % ESR in PI and PO channel	35
Table 20 – C/N (dB) for 5 % MFER in PI and PO channel	36
Table 21 – C/N (dB) for 5 % ESR in mobile channels for single antenna receiver	37
Table 22 – C/N (dB) for ESR 5 % in mobile channels for diversity receiver	37
Table 23 – DVB-H <i>C/N</i> (dB) in mobile channel for 5 % <i>MFER</i>	38
Table 24 – Maximum input levels for terminal category a and b1	40
Table 25 – Maximum input levels for terminal category b2 and c	40
Table 26 – Immunity to pattern S1 for DVB-T	43
Table 27 – Immunity to pattern S1 for DVB-H	43
Table 28 – Immunity to pattern S2 for DVB-T	44
Table 29 – Immunity to pattern S2 for DVB-H	45
Table 30 – Immunity to pattern L1 for DVB-T	45
Table 31 – Immunity to pattern L1 for DVB-H	46
Table 32 – Immunity to pattern L2 for DVB-T	46
Table 33 – Immunity to pattern L2 for DVB-H	47
Table 34 – Immunity to pattern L3 for DVB-T	47
Table 35 – Immunity to pattern L3 for DVB-H	48
Table 36 – Immunity to Pattern L4 for DVB-T	
Table 37 – Immunity to Pattern L4 for DVB-H	48
Table 38 – Immunity to co-channel interference from analogue signals for DVB-T	49
Table 39 – Immunity to co-channel interference from analogue signals for DVB-H	49
Table 40 – C/N for echo within guard interval	50
Table 41 – Timing of the corner point <i>Tc</i>	51
Table 42 – Definition of the value ${\it \Delta}$	51
Table 43 – Definition of the inflection point	51
Table 44 – Impulse interference test patterns	53
Table 45 – Cellular interferer frequency ranges	56
Table A.1 – Noise floor values	61
Table B.1 – C/N (dB) for reference BER	63

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MOBILE AND PORTABLE DVB-T/H RADIO ACCESS -

Part 1: Interface specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
 consensus of opinion on the relevant subjects since each technical committee has representation from all
 interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62002-1 has been prepared by technical area 1: Terminals for audio, video and data services and content, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition, published in 2005 and constitutes a technical revision.

The main changes with respect to the previous edition are listed below.

- DVB-H has been included as a part of the main specification.
- All the performance figures have bee revised as new simulation results have been made available as well as new reference receivers for DVB-H have been developed.
- DVB-H now includes all the different MPE-FEC code rates.
- New portable indoor and portable outdoor channel models have been included as well as performance figures for those.
- A new 2x TU-6 mobile SFN test channel has been included.

- A new L4 linearity pattern has been added.
- Dedicated performance figures for DVB-H for S1, S2, L1 to L4 interference patterns have been included.
- A new GSM-interference measurement method has been added.

The text of this standard is based on the following documents:

CDV	Report on voting
100/1289/CDV	100/1381/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62002 series, under the general title *Mobile and portable DVB-T/H radio access*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed;
- · withdrawn:
- replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later date.

MOBILE AND PORTABLE DVB-T/H RADIO ACCESS -

Part 1: Interface specification

1 Scope

This part of IEC 62002 is a radio access specification for mobile, portable and hand-held portable devices capable of receiving DVB-T/H services. It includes informative system aspects as well as specifications for minimum RF-performance. It covers terminals in three main classes, namely integrated car terminals, portable digital TV sets and hand-held portable convergence terminals. Interoperability with integrated cellular radios is also considered. The specification covers the following areas.

- Frequency ranges
- Supported modes
- Definition of receiving conditions
- Definition of the receiver RF-reference model
- · Definition of degradation criteria
- Antenna characteristics
- · Channel models
- *C/N*-performance with different channels
- Minimum and maximum input levels
- Immunity to interfering signals
- Definition of an ensemble of interference patterns
- Tolerance to impulse interference
- SFN-performance
- Transmitter minimum performance
- Interoperability of cellular radios
- EMC aspects

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 13, Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement

CISPR 20, Sound and television broadcast receivers and associated equipment – Immunity characteristics – Limits and methods of measurement

IEC 60169-2, Radio-frequency connectors - Part 2: Coaxial unmatched connector

ETSI EN 300 744:2007, Digital Video Broadcasting (DVB); Framing structure, Channel coding and modulation for digital terrestrial television, V1.5.2

ETSI ETS 300 342-1, Radio Equipment and Systems (RES); ElectroMagnetic Compatibility (EMC) for European digital cellular telecommunications system (GSM 900 MHz and DCS 1 800 MHz); Part 1: Mobile and portable radio and ancillary equipment

ETSI EN 300 607-1, Digital cellular telecommunications system (Phase 2+) (GSM) – Mobile Station (MS) conformance specification – Part 1: Conformance specification

ETSI EN 302 304:2004, Digital Video Broadcasting (DVB); Transmission System for Handheld Terminals (DVB-H), V1.1.1

ETSI TR 101 190 V1.2.2, Digital Video Broadcasting (DVB); Implementation guidelines for DVB terrestrial services; Transmission aspects

ITU-R BT.1701-1, Characteristics of radiated signals of conventional analogue television systems