

Edition 3.0 2015-07

# INTERNATIONAL STANDARD

**Characteristics of DAB receivers** 

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.060.20 ISBN 978-2-8322-2812-8

Warning! Make sure that you obtained this publication from an authorized distributor.

# CONTENTS

Ε(	DREWORL	J	6
1	Scope.		8
2	Normat	ive references	8
3		and definitions	
4		mplementation and functional performance requirements	
•		utomatic mode selection	
	4.1.1	General	
	4.1.2	Requirements	
		requency bands	
		hannel decoder	
	4.3.1	Standard receiver	
	4.3.2	Multimedia receiver	
	4.4 S	ervice selection	
	4.4.1	General	13
	4.4.2	Requirements	14
	4.5 R	eceiver reactions to a multiplex reconfiguration	14
	4.6 A	udio decoder	14
	4.6.1	General	14
	4.6.2	DAB services	15
	4.6.3	DAB+ services	15
	4.7 A	utomatic switching to another ensemble	15
	4.8 R	esponse to conditional access (CA) services	15
	4.8.1	General	
	4.8.2	Requirements for DAB receivers without CA capabilities	
		utput for audio and other services	
	4.9.1	General	
	4.9.2	Requirements	
		isplay	
	4.10.1	Standard receiver	
	4.10.2	Multimedia receiver	
		ext labels	
	4.11.1	Standard receiver	
	4.11.2	Multimedia receiver	
		ata applications	
	4.12.1 4.12.2	Standard receiver	
5		ces	
J		eneral	
		F input	
	5.2 R	General	
	5.2.1	Domestic and portable receivers	
	5.2.3	Automotive receivers	
		nalogue audio interface (see IEC 61938)	
		igital audio interface (see IEC 60958-3)	
6		S	
•	•	eneral	
	J. 1 G	0110101	19

	6.2	Service lists	19
	6.3	Display	20
	6.3.1	General	20
	6.3.2	Service labels and service component labels	20
	6.3.3	Dynamic label	20
	6.3.4	Signal quality indicator	20
	6.3.5	Audio coding information	20
	6.4	Other receiver features	21
	6.4.1	Time and date	21
	6.4.2	Service following	21
	6.4.3	Announcements	21
	6.4.4	Dynamic range control (DRC)	21
	6.5	Data features	21
	6.5.1	Journaline	21
	6.5.2	Broadcast website (BWS)	22
	6.5.3	TPEG services	22
7	Minin	num performance levels and measuring methods	22
	7.1	General conditions	22
	7.1.1	General – Published specifications for receivers	22
	7.1.2	Power supply	22
	7.1.3	Atmospheric conditions	22
	7.1.4	BER measurement conditions	22
	7.1.5	Acoustic onset of impairment (OOI) measurement conditions	23
	7.1.6	DAB signal	23
	7.1.7	Receiver classification	23
	7.2	Audio part – Performance requirements	24
	7.2.1	General	24
	7.2.2	DAB services	24
	7.2.3	DAB+ services	24
	7.3	RF part – Sensitivity test methods	24
	7.3.1	General	24
	7.3.2	Baseband stream and RF conditions for BER and OOI testing	24
	7.3.3	Baseband stream and listening conditions for acoustic OOI testing	24
	7.4	Sensitivity requirement using a conducted signal at node "A"	25
	7.4.1	General	25
	7.4.2	Method of measurement (Gaussian channel) using BER	25
	7.4.3	Presentation of results using BER	25
	7.4.4	Requirements – Receiver types A2, C2, D, E2 using BER	26
	7.4.5	Method of measurement (Gaussian channel) using acoustic OOI	
	7.4.6	Presentation of results using acoustic OOI	26
	7.4.7	Requirements – Receiver types A2, C2, D, E2 using acoustic OOI	26
	7.5	Sensitivity using radiated electromagnetic wave at node "N"	27
	7.5.1	General	27
	7.5.2	Link budget transmission assumption – Non-automotive receivers	27
	7.5.3	Method of measurement – Non-automotive types A1, B, C1. C2 and A2 with optional antenna	27
	7.5.4	Presentation of results	29
	7.5.5	Requirements – Types A1, B, C1, C2 and A2 with optional antenna	29
	7.5.6	·	

7.6	RF part – Maximum input power	29
7.6.1	General	29
7.6.2	Method of measurement (Gaussian channel)	29
7.6.3	Presentation of results	29
7.6.4	Requirements	29
7.7	RF part – Selectivity	30
7.7.1	General	
7.7.2	- 1	
7.7.3	Rejection of unwanted signals (far-off selectivity)	
7.8	RF part – Performance in a Rayleigh channel	
7.8.1	General	
7.8.2	Sensitivity	
7.8.3	Method of measurement – Conducted input signal only	
7.8.4	Presentation of results	
7.8.5	Requirements	
7.9	RF part – Acquisition time after synchronization loss	
7.9.1	General	
7.9.2	Method of measurement	
7.9.3	Presentation of results	
7.9.4	Requirements	
	informative) Recommended centre frequencies	
,	normative) Characteristics of a Rayleigh channel	
B.1	Simulation of the mobile radio channel	
B.2	Doppler spectrum types	
B.2.1	General	
B.2.2	• • • • • • • • • • • • • • • • • • • •	
B.2.3		
B.2.4	• • • • • • • • • • • • • • • • • • • •	
B.2.5	• • • • • • • • • • • • • • • • • • • •	
B.2.6	•••	
B.3	Propagation models	
B.3.1	General	
B.3.2		
B.3.3 B.4	Typical urban (non-hilly) area (TU)	
	informative) Basic characteristics and functionality for accessibility for blind	42
,	ly impaired users	44
	hy	
Dionog. up	.,	
Eiguro 1	Example of a functional block diagram of a DAP receiver	10
•	Example of a functional block diagram of a DAB receiver	1 2
	Block diagram for the measurement of the sensitivity and the maximum er, using BER	25
	Block diagram for the measurement of the sensitivity and the maximum	20
	er, using acoustic OOI	26
	Block diagram for the measurement of free field sensitivity	
_	Free field screened chamber measurement – Features and setup	
•	·	
-	Spectrum mask of the DAB signal for selectivity measurements	
Figure 7 –	Block diagram for BER method selectivity measurements	31

Figure 8 – Block diagram for OOI method selectivity measurements	32
Figure 9 – Block diagram for measuring the performance in a Rayleigh channel	34
Figure 10 – Block diagram for measuring acquisition time after synchronization loss	35
Figure B.1 – Continuous delay power profile $P(\tau)$ for RA	41
Figure B.2 – Continuous delay power profile $P(\tau)$ for TU	41
Table 1 – Performance requirement for an automotive active antenna	18
Table 2 – Classification of receiver types	23
Table 3 – Conditions for BER and OOI testing	24
Table 4 – Conditions for acoustic OOI testing	25
Table 5 – Conditions for uniform signal level	28
Table 6 – Minimum requirements for maximum input power (conducted)	30
Table 7 – Difference between the centre frequencies of the DAB ensembles	31
Table 8 – Minimum requirement for adjacent channel selectivity	32
Table 9 – Channel simulation profiles related to frequency band and mode	34
Table A.1 – Recommended centre frequencies for DAB (1 of 2)	37
Table B.1 – Four tap setting for typical rural (non-hilly) area (RA)	42
Table B.2 – Six tap setting for typical rural (non-hilly) area (RA)	42
Table B.3 – Twelve tap setting for typical urban (non-hilly) area (TU)	43
Table B.4 – Six tap setting for typical urban (non-hilly) area (TU)	43
Table B.5 – Tap setting for single-frequency networks (SFN) in VHF bands	43

# INTERNATIONAL ELECTROTECHNICAL COMMISSION

# CHARACTERISTICS OF DAB RECEIVERS

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62104 has been prepared by technical area 1, Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition cancels and replaces the second edition published in 2003. This edition constitutes a technical revision.

The main changes with respect to the previous edition are as follows.

- The document has been updated in line with the development of the DAB system, and in particular the introduction of DAB+ audio services (see ETSI TS 102 563).<sup>1</sup>
- Requirements for displays, text and data applications have been introduced to reflect market trends.

<sup>1</sup> For an overview of the DAB standards, see ETSI TR 101 495.

- Additional test methods have been introduced to allow R.F. measurements to be made on receivers with integrated antennas and/or no external BER indicators by using an acoustic impairment method.
- Clause 6 has been updated to reflect the development of the market and to provide better guidance for the implementation of optional features.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/2502/FDIS	100/2541/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

# CHARACTERISTICS OF DAB RECEIVERS

#### 1 Scope

This International Standard describes the digital audio broadcasting (DAB) receiver characteristics for consumer equipment intended for terrestrial and cable reception operating in VHF band III. Dedicated receivers for specific applications are not within the scope of this standard. This standard describes the characteristics for different classes and categories of DAB receivers such as standard and multimedia receivers and domestic, automotive and adapter receivers.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60169-10, Radio-frequency connectors – Part 10: R.F. coaxial connectors with inner diameter of outer conductor 3 mm (0,12 in) with snap-on coupling – Characteristic impedance 50 ohms (Type SMB)

IEC 60315-1, Methods of measurement on radio receivers for various classes of emission – Part 1: General considerations and methods of measurement, including audio-frequency measurements

IEC 60315-4, Methods of measurement on radio receivers for various classes of emission – Part 4: Receivers for frequency-modulated sound-broadcasting emissions

IEC 60958-3, Digital audio interface – Part 3: Consumer applications

IEC 61169-2:2007, Radio-frequency connectors – Part 2: Sectional specification – Radio frequency coaxial connectors of type 9,52

IEC 61169-24, Radio-frequency connectors — Part 24: Sectional specification — Radio frequency coaxial connectors with screw coupling, typically for use in 75 ohm cable networks (type F)

IEC 61606 (all parts), Audio and audiovisual equipment – Digital audio parts – Basic measurement methods of audio characteristics

IEC 61938, Multimedia systems – Guide to the recommended characteristics of analogue interfaces to achieve interoperability

IEC 62106:2009, Specification of the radio data system (RDS) for VHF/FM sound broadcasting in the frequency range from 87,5 MHz to 108,0 MHz

ISO/IEC 10646, Information technology – Universal Coded Character Set (UCS)

ISO/IEC 11172-3, Information technology – Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s – Part 3: Audio

ISO/IEC 13818-3, Information technology – Generic coding of moving pictures and associated audio information – Part 3: Audio

ISO/IEC 14496-3 Information technology – Coding of audio-visual objects – Part 3: Audio

ISO/IEC 23003-1:2007, Information technology – MPEG audio technologies – Part 1: MPEG Surround

ISO 20860-1, Road vehicles – 50 ohms impedance radio frequency connection system interface – Part 1: Dimensions and electrical requirements

ETSI EN 300 401:2006, Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers

ETSI EN 301 234, Digital Audio Broadcasting (DAB); Multimedia Object Transfer (MOT) protocol

ETSI TS 101 498, Digital Audio Broadcasting (DAB); Broadcast Website

ETSLTS 101 499, Digital Audio Broadcasting (DAB); SlideShow; User Application Specification

ETSLTS 101 756, Digital Audio Broadcasting (DAB); Registered Tables

ETSLTS 101 757, Digital Audio Broadcasting System (DAB); Conformance Testing for DAB Audio

ETSITS 102 371, Digital Audio Broadcasting (DAB); Digital Radio Mondiale (DRM); Transportation and Binary Encoding Specification for Service and Programme Information (SPI)

ETSLTS 102 428, Digital Audio Broadcasting (DAB); DMB video service; User Application Specification

ETSLTS 102 563, Digital Audio Broadcasting (DAB); Transport of Advanced Audio Coding (AAC) audio

ETSI TS 102 652, Digital Audio Broadcasting (DAB); Intellitext; Application specification

ETSLTS 102 818, Hybrid Digital Radio (DAB, DRM, RadioDNS); XML Specification for Service and Programme Information (SPI)

ETSLTS 102 979, Digital Audio Broadcasting (DAB); Journaline; User application specification

ETSLTS 102 980, Digital Audio Broadcasting (DAB); Dynamic Label Plus (DL Plus); Application specification

ETSLTS 103 176, Digital Audio Broadcasting (DAB); Rules of implementation; Service information features

COST 207, *Digital Land Mobile Radio Communications* – COST 207, Commission of the European Communities, Final Report, 14 March 1984 – 13 September 1988, Office for Official Publications of the European Communities, Luxembourg, 1989