



IEC 62106-1

Edition 1.0 2018-10

# INTERNATIONAL STANDARD

---

**Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range  
from 64,0 MHz to 108,0 MHz –  
Part 1: Modulation characteristics and baseband coding**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.160.40

ISBN 978-2-8322-6066-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms, definitions and abbreviated terms .....	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	8
3.3 Notation and conventions.....	8
3.3.1 Hexadecimal notation .....	8
3.3.2 Nomenclature for group types.....	8
3.3.3 Capitalized RDS terms.....	8
4 Modulation characteristics of the data channels.....	8
4.1 General.....	8
4.2 Subcarrier generation .....	9
4.3 Data-stream subcarrier frequencies for all possible streams .....	10
4.4 Subcarrier phase requirements .....	11
4.5 Subcarrier level requirements .....	11
4.6 Data-stream modulation requirements.....	11
4.7 Clock-frequency and data-rate .....	11
4.8 Differential coding on all data-streams .....	11
4.9 Data-channel spectrum shaping on all data-streams .....	12
4.10 Symbol phase shifts of data across data-streams.....	15
5 Baseband coding.....	16
5.1 Data-stream baseband coding structure .....	16
5.2 Data-stream error protection .....	16
5.3 Synchronization of blocks and groups across all streams.....	17
6 Transmission options on data-streams 1, 2 and 3 .....	18
Annex A (normative) Offset words to be used for group and block synchronization .....	19
Annex B (informative) Theory and implementation of the modified shortened cyclic code .....	20
B.1 General.....	20
B.2 Encoding procedure .....	20
B.2.1 Theory .....	20
B.2.2 Shift-register implementation of the encoder.....	22
B.3 Decoding procedure.....	23
B.3.1 Theory .....	23
B.3.2 Implementation of the decoder.....	24
Annex C (informative) Implementation of group and block synchronization using the modified shortened cyclic code .....	26
C.1 Theory .....	26
C.1.1 Acquisition of group and block synchronization.....	26
C.1.2 Detection of loss of synchronization.....	26
C.2 Shift register arrangement for deriving group and block synchronization information.....	26
Bibliography.....	29

Figure 1 – Block diagram of data-stream 0 radio-data equipment at the transmitter .....	9
Figure 2 – Block diagram of a typical data-stream 0 radio-data receiver/decoder .....	10
Figure 3 – Subcarriers for RDS data-stream 0 and additional RDS2 data-streams 1, 2 and 3 .....	10
Figure 4 – Amplitude response of the specified transmitter or receiver data-shaping filter.....	13
Figure 5 – Amplitude response of the combined transmitter and receiver data-shaping filters .....	14
Figure 6 – Spectrum of biphase coded radio-data signals .....	14
Figure 7 – Time-function of a single biphase symbol .....	15
Figure 8 – 57 kHz modulated data-signal .....	15
Figure 9 – Structure of the baseband coding.....	16
Figure B.1 – Generator matrix of the basic shortened cyclic code in binary notation .....	21
Figure B.2 – Shift-register implementation of the encoder .....	22
Figure B.3 – Parity-check matrix of the basic shortened cyclic code.....	24
Figure B.4 – Shift-register implementation of the decoder .....	25
Figure C.1 – Group and block synchronization detection circuit.....	27
Table 1 – Encoding rules .....	12
Table 2 – Decoding rules .....	12
Table 3 – Phase shifts of data across data-streams 1-3 with respect to data-stream 0 .....	16
Table A.1 – Offset word codes .....	19
Table B.1 – Offset word syndromes using matrix of Figure B.3 .....	24
Table C.1 – Offset word syndromes for group and block synchronization .....	28

# INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

## **RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –**

### **Part 1: Modulation characteristics and baseband coding**

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106-1 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition, together with IEC 62106-2, IEC 62106-3, IEC 62106-4, IEC 62106-5 and IEC 62106-6, cancels and replaces IEC 62106:2015, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106:2015:

- Provision has been made to carry RDS on multiple data-streams (RDS2).

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/2907/CDV	100/3055/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

Since the mid-1980s a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, specifically for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA [1, 2, 3, 4, 5].<sup>1</sup>

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

The following future parts are planned:

Part 7: RBDS

Part 8: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

Obsolete or unused functions from the original RDS standard IEC 62106:2015 have been deleted. The presentation in Parts 1, 2 and 3 follows the OSI basic reference model for information processing systems [6].

---

<sup>1</sup> Numbers in square brackets refer to the Bibliography.

**RADIO DATA SYSTEM (RDS) –  
VHF/FM SOUND BROADCASTING IN THE FREQUENCY  
RANGE FROM 64,0 MHz TO 108,0 MHz –**

**Part 1: Modulation characteristics and baseband coding**

## **1 Scope**

This part of IEC 62106 defines the basic layer of the Radio Data System (RDS) intended for application to VHF/FM sound broadcasts in the range 64,0 MHz to 108,0 MHz, which can carry either stereophonic (pilot-tone system) or monophonic programmes (as stated in ITU-R Recommendation BS.450-3 and ITU-R Recommendation BS.643-3).

## **2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*

ITU-R Recommendation BS.450-3, *Transmission standards for FM sound broadcasting at VHF*

ITU-R Recommendation BS.643-3, *Radio data system for automatic tuning and other applications in FM radio receivers for use with pilot-tone system*