



Edition 1.0 2011-02

# TECHNICAL REPORT



Environmental conditions – Vibration and shock of electrotechnical equipment – Part 4: Equipment transported in road vehicles

INTERNATIONAL ELECTROTECHNICAL COMMISSION



ICS 19.040

ISBN 978-2-88912-389-6

# CONTENTS

FO	REWC	)RD	5
1	Scop	e	7
2	Norm	ative references	7
3	Data	source and quality	7
	3.1	SRETS road and test track measurements	7
	3.2	CEEES 'round robin' 10 tonne truck measurements	8
	3.3	Various vehicle measurements by Hoppe and Gerock	9
	3.4	Millbrook measurements on Landrover Defender	10
	3.5	Millbrook measurements on Ford transit van	
	3.6	Millbrook measurements on Renault Magnum	
	3.7	Supplementary data	
4	Intra	data source comparison	
	4.1	General remark	
	4.2	SRETS road and test track measurements	
	4.3	CEEES 'round robin' 10 tonne truck measurements	
	4.4	Various vehicle measurements by Hoppe and Gerock	14
	4.5	Millbrook measurements on Landrover Defender, Ford Transit Van and Renault Magnum	15
	4.6	Renault Trafic (1,9 tonne) and TRM 1000 (20 Tonne)	
	4.7	Various US road vehicles circa 1970 and circa mid 1980's	
5	Inter	data source comparison	. 15
6	Ident	ified test severities	17
7		onmental description	
8		parison with IEC 60721 and IEC 60068	
9	•	mmendations	
		bhy	
טום	nogra	אויל אויל אויל אויל אויל אויל אויל אויל	. 00
<b>-</b> :		Ochemotic of ODETO uchicles	07
Ŭ		- Schematic of SRETS vehicles	
Ŭ		- Effective values of all runs from covert SRETS measurements	
-			28
Ŭ		<ul> <li>Comparison of SRETS amplitudes in the 3 axis</li> </ul>	
Fig	ure 5 -	<ul> <li>Comparison of SRETS measurements made with driver's knowledge</li> </ul>	29
		<ul> <li>Comparison of SRETS PSDs of different vehicles (v1, v2,v3) and road s made with driver's knowledge</li> </ul>	30
		<ul> <li>Comparison of SRETS measurements made without driver's knowledge and with driver's knowledge (overt) on different roads</li> </ul>	30
		<ul> <li>Comparison of different SRETS vehicles at the load platform – nents made with driver's knowledge</li> </ul>	31
		<ul> <li>Comparison of SRETS measurements with different road categories          — Made</li></ul>	31
		<ul> <li>Comparison of vertical SRETS time and signal triggered data made without nowledge</li> </ul>	32
		<ul> <li>Power spectral density of SRETS time and signal triggered data made river's knowledge</li> </ul>	33
		<ul> <li>Peak hold PSD of SRETS time and signal triggered data made without nowledge</li> </ul>	33

Figure 14 – APD of the SRETS measured data made without driver's knowledge	. 34
Figure 15 – Fitting of SRETS APD with multiple gaussian distributions	. 34
Figure 16 – Vertical SRS of SRETS measured amplitudes greater than 5 g – Made without driver's knowledge	. 35
Figure 17 – Lateral SRS of SRETS measured amplitudes greater than 5 g – Made	
without driver's knowledge	
Figure 18 Vibration r.m.s. against time for CEEES analysis	
Figure 19 – Vibration r.m.s. against vehicle velocity for CEEES analysis	
Figure 20 – Acceleration peaks against vehicle velocity for CEEES analysis	
Figure 21 – Vibration PSD analysis from CEEES 'round robin' exercise	
Figure 22 – Shock SRS analysis from CEEES 'round robin' exercise	
Figure 23 – Vibration test severities from CEEES 'round robin' exercise	
Figure 24 – Composite vibration PSD of CEEES measurements	
Figure 25 – Composite vibration APD from CEEES measurements	
Figure 26 – Vibration PSD from degraded roads on CEEES measurements	
Figure 27 – Shocks from CEEES measurements	.40
Figure 28 – Typical vibration PSD from Hoppe and Gerock measurements	.41
Figure 29 – Envelope of vibration PSD from Hoppe and Gerock measurements	.43
Figure 30 – Number of shocks per 100 km FROM Hoppe and Gerock measurements	.43
Figure 31 – Vibration r.m.s. from Millbrook measurements on landrover	.44
Figure 32 – Shock peaks from Millbrook measurements on landrover	.44
Figure 33 – Vibration PSD from Millbrook measurements on landrover	.45
Figure 34 – Vibration r.m.s. from Millbrook measurements on transit van	.45
Figure 35 – Maximum PSD values FROM Millbrook measurements on transit van	.46
Figure 36 – Shock amplitudes from Millbrook measurements on transit van	.46
Figure 37 – Vibration r.m.s. from Millbrook measurements on Renault Magnum	.47
Figure 38 – Maximum PSD values from Millbrook measurements on Renault Magnum	.47
Figure 39 – Shock amplitudes from Millbrook measurements on Renault Magnum	.48
Figure 40 – Maximum PSD values from Millbrook measurements on Renault Magnum	.48
Figure 41 – Vibration PSD from GAM EG 13 measurements on Renault Traffic	.49
Figure 42 – Vibration PSD from GAM EG 13 measurements on RVI TRM 1000	. 50
Figure 43 – Vibration severities from Mil Std 810 (Foley)	.51
Figure 44 – Vibration severities from Mil Std 810 (Connon)	.51
Figure 45 – Data from ASTM 4728-91	. 52
Figure 46 – Data from ASTM D4278-95	. 52
Figure 47 – Data from EXACT DK 1 – 237	. 53
Figure 48 – Data from reference 15	
Figure 49 – Data from ASTM D 4728-95	
Figure 50 – Data from reference 16	
Figure 51 – SRETS test severity from PSD	
Figure 52 – SRETS test severity from PSD	
Figure 53 – SRETS test severity from r.m.s. (including shocks)	
Figure 54 – SRETS test severity from r.m.s. (including shocks)	
Figure 55 – Test severities from UK defence standard	
G	

Figure 56 – Test severities from NATO STANAG	58
Figure 57 – Test severities from ASTM D 4728-95	59
Figure 58 – Test severity from ETA	59
Figure 59 – Test severities from CEN and ISO	60
Figure 60 – Test severities from ETS	60
Figure 61 – IEC 60721-2-2:1997 [26] – Random vibration severity	61
Figure 62 – IEC 60721-4-2:1997 – Random vibration severity	61
Figure 63 – IEC 60721-3-2:1997 – Sinusoidal vibration severity	62
Figure 64 – IEC 60721-4-2:1997 – Sinusoidal vibration severity	62
Figure 65 – IEC 60721-3-2:1997 – Shock severity	63
Figure 66 – IEC 60721-4-2:1997 – Shock severity	63
Figure 67 – IEC 60721-4-2:1997 – Recommended repeated shock severity	64
Figure 68 – Comparison of the effects of IEC 60721-2-2:1997 – Random and sinusoidal vibration severities	64
Figure 69 – Comparison of the effects of IEC 607212-2:1997 – Random and sinusoidal vibration severities	65
Figure 70 – Comparison of the effects of IEC 60721-2-2:1997 – Random and sinusoidal vibration severities	65
Table 1 – Summary of SRETS journeys	26
Table 2 – Summary of measurements made by Bosch using a number of vehicles and under different test conditions	26
Table 3 – Vehicles included in Hoppe and Gerock measurements	41
Table 4 – Shock occurrences from Hoppe and Gerock measurements	42
Table 5 – Probable" shock durations from Hoppe and Gerock measurements	42
Table 6 – Vibration r.m.s. from GAM EG 13 measurements on Renault Traffic	49
Table 7 – Vibration r.m.s. from GAM EG 13 measurements on RVI TRM 1000	50

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# ENVIRONMENTAL CONDITIONS – VIBRATION AND SHOCK OF ELECTROTECHNICAL EQUIPMENT –

#### Part 4: Equipment transported in road vehicles

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC/TR 62131-4, which is a technical report, has been prepared by IEC technical committee 104: Environmental conditions, classification and methods of test.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
104/509/DTR	104/538/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table. This publication has been drafted in accordance with the ISO/IEC Directives, Part 2. A list of all the parts in the IEC 62131 series, under the general title *Environmental conditions – Vibration and shock of electrotechnical equipment,* can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

# ENVIRONMENTAL CONDITIONS – VIBRATION AND SHOCK OF ELECTROTECHNICAL EQUIPMENT –

## Part 4: Equipment transported in road vehicles

#### 1 Scope

IEC/TR 62131-4, which is a technical report, reviews the available dynamic data relating to electrotechnical equipment transported by road vehicles. The intent is that from all the available data an environmental description will be generated and compared to that set out in IEC 60721 [25]<sup>1</sup>.

For each of the sources identified the quality of the data is reviewed and checked for self consistency. The process used to undertake this check of data quality and that used to intrinsically categorize the various data sources is set out in IEC/TR 62131-1.

This technical report primarily addresses data extracted from a number of different sources for which reasonable confidence exists as to the quality and validity. The report also presents data for which the quality and validity cannot realistically be reviewed. These data are included to facilitate validation of information from other sources. The report clearly indicates when utilizing information in this latter category.

This technical report addresses data from a number of data gathering exercises. The quantity and quality of data in these exercises varies considerably as does the range of road (and test track) conditions covered. The vast majority of the road conditions are from Western Europe. It is believed that one of the data sources considered is that used to set the current IEC 60721 severities. However, review of that data indicates the inclusion of some quite old vehicles.

Relatively little of the data reviewed were made available in electronic form. To permit comparison to be made in this assessment, a quantity of the original (non-electronic) data have been manually digitized.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60721-3-2:1997, Classification of environmental conditions – Part 3: Classification of groups of environmental parameters and their severities – Section 2: Transportation

<sup>1</sup> References in square brackets refer to the bibliography.