INTERNATIONAL STANDARD

IEC 62289

First edition 2002-07

Video recording – Helical-scan digital video cassette recording format using 12,65 mm magnetic tape and incorporating MPEG-2 compression – Format D-10

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



CONTENTS

FOI	REWO	ORD	5
1	Scop	e	6
2	Norm	native references	6
3	Abbr	eviations and acronyms	7
4	Environment and test conditions		
	4.1	Calibration tape	7
	4.2	Record locations and dimensions	
5	Таре	and cassette physical specifications	7
	5.1	Magnetic tape specifications	7
	5.2	Cassette specifications	8
6	Таре	record physical parameters	28
	6.1	Tape speed	28
	6.2	Helical record physical parameters	28
	6.3	Longitudinal record physical parameters	28
7	Long	itudinal track signal and magnetic parameters	31
	7.1	Longitudinal track record parameters	31
	7.2	Control track record parameters	
	7.3	Time and control code record parameters	
8	Helic	al track signal parameters and magnetization	34
	8.1	General	
	8.2	Helical track data parameters	
	8.3	Scrambling and channel coding	
	8.4	Magnetization	
	8.5	Data arrangement in video sectors	
۸	8.6	Data arrangement in audio data sectors	
		(normative) Video shuffling tables	
Anr		(normative) Digital interfaces	
	B.1	Introduction	
	B.2	Video interface	
		Audio interface	
۸ ۳۰	B.4	Serial data interface(informative) Tape transport and scanner	
		· · · · ·	91
Anr		(informative) Compatibility with the other digital formats using type-L ative cassettes	94
Δnr		(informative) Compatibility with analog Type-L	
		(normative) SMPTE 356M, "D-10 Type Stream Specifications: MPEG-2	
AIII	4:2:2	P@ML for 525/60 and 625/50"	96
	F.1	Scope	96
	F.2	Specification of the D-10 type MPEG-2 4:2:2P@ML elementary stream	96
	F.3	Interfaces	98
	F.4	D-10 type ES Stream operating points	98
	F.5	D-10 recording format compression model	
	F.6	D-10 recording format digital interfaces	
Anr	nex G	(informative) D-10 document reference tree	101

Figure 1 – Top and side view (S-cassette)	10
Figure 2 – Bottom view (S-cassette)	11
Figure 3 – Datum areas, supporting areas, tape guides and associated dimensions (S-cassette)	13
Figure 4 – Reel location in the unlocked position (S-cassette)	13
Figure 5 – Protecting lid dimensions (S-cassette)	14
Figure 6 – Reel dimensions (S-cassette)	15
Figure 7 – Reel height in the unlocked position (S-cassette)	15
Figure 8 – Unlocking lever insertion area (S-cassette)	16
Figure 9 – Lid unlocking force (S-cassette)	17
Figure 10 – Lid opening force (S-cassette)	17
Figure 11 – Reelspring force (S-cassette)	18
Figure 12 – Safety plug strength (S-cassette)	18
Figure 13 – Extraction force (F1, F2) and friction torque (S-cassette)	19
Figure 14 – Top and side view (L-cassette)	19
Figure 15 – Bottom view (L-cassette)	20
Figure 16 – Datum areas, supporting areas and tape guides (L-cassette)	22
Figure 17 – Reel location in unlocked position (L-cassette)	22
Figure 18 – Protecting lid (L-cassette)	23
Figure 19 – Reel dimensions (L-cassette)	24
Figure 20 – Reel height in unlocked operation (L-cassette)	24
Figure 21 – Unlocking lever insertion area (L-cassette)	25
Figure 22 – Lid unlocking force (L-cassette)	26
Figure 23 – Lid opening force (L-cassette)	26
Figure 24 – Reel spring force (L- cassette)	26
Figure 25 – Safety plug strength (L-cassette)	27
Figure 26 – Extraction force (F1, F2) and friction torque (L-cassette)	27
Figure 27 – Locations and dimensions of recorded tracks	30
Figure 28 – Locations and dimensions of tolerance zones of helical track records	31
Figure 29 – Recorded control code waveform for the 525/60 system	33
Figure 30 – Recorded control code waveform for the 625/50 system	33
Figure 31 – Helical recording block diagram	34
Figure 32 – Helical playback block diagram	35
Figure 33 – Sector arrangement on a helical track	36
Figure 34 – Sector arrangement on a helical track (525/60 system)	37
Figure 35 – Sector arrangement on a helical track (625/50 system)	38
Figure 36 – Video sync block format	39
Figure 37 – Audio sync block format (525/60 system)	39
Figure 38 – Audio sync block format (625/50 system)	39
Figure 39 – Sync block identification bytes	40
Figure 40 – ID ₀ : sync block number (525/60 system)	41
Figure 41 – ID0: sync block number (625/50 system)	42
Figure 42 – Track, segment and frame/field counts	45

Figure 43 – Re-ordering of coefficient data	50
Figure 44 – Length information for video data	53
Figure 45 – Example of packing 10 slices into 10 sync blocks	55
Figure 46 – Video AUX sync block	57
Figure 47 – Block interleave (525/60 system)	58
Figure 48 – Block interleave (625/50 system)	58
Figure 49 – Video outer ECC (525/60 system)	60
Figure 50 – Video outer ECC (625/50 system)	62
Figure 51 – Audio video timing	63
Figure 52 – Audio data word assignment	64
Figure 53 – Audio auxiliary data words	65
Figure 54 – Audio data block layout (525/60 system)	66
Figure 55 – Audio data block layout (625/50 system)	67
Figure 56 – Sync block shuffling	67
Figure 57 – Channel sector shuffling	68
Figure C.1 – Possible scanner configuration (525/60 and 625/50 systems)	92
Figure C.2 – Possible longitudinal head location and tape wrap (525/60 and 625/50 systems)	93
Figure F.3 – Digital recorder compression model	99
Figure G.1 – D-10 document reference tree	101
Table 1 – Record location and dimensions for the 525/60 and 625/50 systems	29
Table 2 – ID ₀ : sync block number	43
Table A.1 – Shuffling pattern (525/60 system)	69
Table A.2 – Shuffling pattern (625/50 system)	78
Table C.1 – Parameters for a possible scanner design	91
Table C.2 – Data rate and wavelength	91
Table F.1 – Basic bit stream constraints	96
Table F.2 – Operating points	99

INTERNATIONAL ELECTROTECHNICAL COMMISSION

VIDEO RECORDING – HELICAL-SCAN DIGITAL VIDEO CASSETTE RECORDING FORMAT USING 12,65 MM MAGNETIC TAPE AND INCORPORATING MPEG-2 COMPRESSION – FORMAT D-10

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62289 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

CDV	Report on voting
100/416A/CDV	100/481/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

The committee has decided that the contents of this publication will remain unchanged until 2007. At this date, the publication will be

- reconfirmed;
- withdrawn;
- · replaced by a revised edition, or
- · amended.

VIDEO RECORDING – HELICAL-SCAN DIGITAL VIDEO CASSETTE RECORDING FORMAT USING 12,65 MM MAGNETIC TAPE AND INCORPORATING MPEG-2 COMPRESSION – FORMAT D-10

1 Scope

This standard specifies the formatting for the recording of data blocks containing MPEG-2 compressed video, multiple channels of AES3 audio and associated data which form helical records on 12,65 mm tape in cassettes. This standard also defines the helical track record parameters, the content and format of the longitudinal records and the cassette physical specifications.

The compressed video uses the MPEG-2 compression which is defined by ISO/IEC 13818-2 with constraints as defined by Annex F. The compressed video channel supports frame frequencies of 30/1,001 Hz (hereafter referred to as 525/60 system) and 25 Hz (hereafter referred to as 625/50 system).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61213:1993, Analogue audio recording on video tape – Polarity of magnetization

IEC 61237-1:1994, Broadcast video tape recorders – Methods of measurement – Part 1: Mechanical measurements

ISO/IEC 13818-2:2001, Information technology – Generic coding of moving pictures and associated audio information: Video

ITU-R BT.601-5, Studio encoding parameters of digital television for standard 4:3 and wide-screen 16:9 aspect ratios

SMPTE 12M:1999, Time and Control Code

SMPTE 259M:1997, 10-Bit 4:2:2 Component and 4 $f_{\rm sc}$ NTSC Composite Digital Signals – Serial Digital Interface

SMPTE 305M, Television - Serial Data Transport Interface

SMPTE 326M, SDTI Content Package Format (SDTI-CP)

SMPTE 328M, MPEG-2 Video Elementary Stream Editing Information

SMPTE 331M, Element and Metadata Definitions for the SDTI-CP

SMPTE RP 204, SDTI-CP MPEG Decoder Templates

AES3-1992, Serial transmission format for two-channel linearly represented digital audio data