

This is a preview - click here to buy the full publication



IEC/TR 62627-03-02

Edition 1.0 2011-12

TECHNICAL REPORT



**Fibre optic interconnecting devices and passive components –
Part 03-02: Reliability – Report of high power transmission test of specified
passive optical components**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

U

ICS 33.180.20

ISBN 978-2-88912-825-9

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Samples for transmission test.....	7
3 High power damage threshold test.....	8
3.1 Test conditions.....	8
3.2 Apparatus and measurement conditions.....	8
3.3 Test results.....	9
3.4 Ferrule endfaces of the attenuators.....	12
3.5 Change of characteristics in the backward direction incidence for optical isolators.....	13
4 Thermal simulation of passive optical components.....	16
4.1 Thermal simulation in the high power light.....	16
4.1.1 General.....	16
4.1.2 Fixed optical attenuator.....	16
4.1.3 Optical isolator.....	18
4.1.4 Optical splitter.....	19
4.2 Temperature rise simulation in the medium power light.....	19
5 Long-term test of high power light.....	21
6 Assumption of failure mode.....	24
7 Conclusion.....	25
7.1 General.....	25
7.2 Fixed optical attenuator.....	25
7.3 Optical isolator.....	25
7.4 Optical splitter.....	25
7.5 Conclusion.....	25
Bibliography.....	26
Figure 1 – Measurement setup.....	9
Figure 2 – Results for high power transmission test of 10 dB attenuator.....	11
Figure 3 – Pictures of ferrule endfaces in the input side of 30 dB attenuator.....	13
Figure 4 – High power test result for backward direction for optical isolator (example).....	15
Figure 5 – Measurement result for the ferrule point of reflection in the optical isolator.....	15
Figure 6 – Thermal distribution of fixed optical attenuator by thermal simulation (10 dB attenuator, input power: 1 W).....	16
Figure 7 – Maximum internal temperature of fixed optical attenuator by thermal simulation (input power: 1 W).....	17
Figure 8 – Thermal simulation of fixed optical attenuator (input power: 2 W).....	18
Figure 9 – Thermal simulation of optical isolator (forward direction, input power: 5 W).....	18
Figure 10 – Maximum internal temperature of optical splitter by thermal simulation (forward direction, input power: 5 W).....	19
Figure 11 – Ambient temperature dependency of maximum temperature in the thermal simulation of fixed optical attenuator.....	20
Figure 12 – Relationship between input light power and maximum temperature in the thermal simulation of fixed optical attenuator.....	20

Figure 13 – Change of IL and RL of fixed optical attenuator	22
Figure 14 – Change of IL and RL of optical isolator	22
Figure 15 – Change of IL and RL of optical splitter.....	23
Table 1 – Specifications of the passive optical components use for the high power damage threshold test	7
Table 2 – Manufacturer names and product codes of samples	7
Table 3 – Test details	8
Table 4 – Measurement requirements	8
Table 5 – Measurement conditions in the test	9
Table 6 – Results of high power damage threshold test	10
Table 7 – Characteristics changes before and after the test.....	12
Table 8 – Fibre protrusion and withdrawal in the fixed optical attenuator before and after the high power test	12
Table 9 – Test result in the backward direction	14
Table 10 – Conditions of optical attenuator for simulation	19
Table 11 – Conditions of long-term test.....	21
Table 12 – Measurement result of optical characteristics and protrusion before and after the test of fixed optical attenuator	23
Table 13 – Measurement result of optical characteristics before and after the test of optical isolator	23
Table 14 – Measurement result of optical characteristics before and after the test of optical splitter	24

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS –

Part 03-02: Reliability – Report of high power transmission test of specified passive optical components

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62627-03-02, which is a technical report, has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86B/3228/DTR	86B/3277/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Optical transmission power has increased in recent years due to the growing demands for ultra-long haul transmission systems and more applications of fibre optic amplifiers for cable television broadcasting systems. In view of these advances, concerns arise about optical fibres, fibre optic connectors and passive optical components installed in fibre optic communication systems due to the fact that these components may harm human beings due to a leakage of high-power light and the possibility of fire caused by melting and damage of these components. However, mechanisms, conditions, and factors that cause such accidents have not yet been clearly identified. Furthermore, industry standards on the reliability and long-term evaluation of optical components do not include testing with high optical power.

This technical report is based on the Optoelectronic Industry and Technology Development Association (OITDA) – Technical Paper (TP), TP04/SP_PD-2008, "Technical paper of investigation of high-power reliability for passive optical components for optical communication application".

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS –

Part 03-02: Reliability – Report of high power transmission test of specified passive optical components

1 Scope

This part of IEC 62627 describes test data relating to high power damage of fixed optical attenuators, optical isolators and optical splitters (non-wavelength selective branching devices). It also describes the test of thermal simulation and failure mechanism analysis for the above passive optical components on high power transmission.