

Edition 1.0 2017-05

INTERNATIONAL STANDARD



Flexible display devices – Part 5-3: Visual assessment of image quality and defects

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 31.120 ISBN 978-2-8322-4298-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

		KU	
IN	TRODU	CTION	6
1	Scop	e	7
2	Norm	ative references	7
3	Term	s and definitions	7
4	Procedures of visual assessment [2][3]		
•	4.1	General	
	4.2	Setup of displays and driving conditions	
	4.3	Observers for visual assessment [4][5]	
	4.4	Ambient conditions for visual assessment	
	4.4.1		
	4.4.2		
	4.5	Viewing geometry	
	4.5.1	General	
	4.5.2		
	4.5.3		
	4.5.4		
5		charts (test signals)	
J		General	
	5.1		_
	5.2	Full-screen patterns	
	5.3	Periodic patterns	
	5.4	Tone and colour gradation patterns	
	5.5	Test chart for cross-talk	
	5.6	Test chart for electro-optical defects	
	5.7	Test chart for static image resolution	
_	5.8	Natural and synthetic images	
6	9		
	6.1	General	
	6.2	Number of duplicate and reference DUTs	
	6.3	Procedures of visual assessment after exposure to environmental stress	
	6.4	Procedures of visual assessment after exposure to mechanical stress	
7	Criteria for judgments		
	7.1	General concept	22
	7.2	Judgment using a limit sample	22
	7.3	Ranking using a set of grade samples	22
	7.4	Preparation of a limit sample or a set of grade samples	23
	7.4.1	General	23
	7.4.2	Procedures	23
	7.4.3	Affirmation of end-user true needs	23
	7.5	Judgments without a limit sample or a set of grade samples	24
	7.5.1	General	24
	7.5.2	Procedures	24
	7.6	Assessment using an ND (neutral density) filter	24
	7.6.1	General	24
	7.6.2	Procedures	24
	7.7	Assessment method for mechanical defects	25

8 R	porting	25
8.1	Requirements for reporting	25
8.2	Recommendations for reporting	
Annex	A (informative) Ranking of mura defect using ND filter	26
Bibliog	raphy	27
Figure	1 – Illustrative viewing geometries of flexible display devices	11
Figure	2 – Example test patterns	15
Figure	3 – Examples of periodic patterns	16
Figure	4 – Example test charts for tone and colour reproduction	18
Figure	5 - Examples of a test chart displayed on the screen of deformed DUTs	19
	6 – Cross-talk patterns window boxes on grey background diagonal from the n at P ₀	20
Figure	7 – Monoscopic pattern for assessment of ultra high definition screen	21
Table ²	1 – Example of the set of input signal levels for an 8-bit system	13
Table 2	2 – Other input signal levels for an 8-bit system	14
Table /	A.1 – Example of ranking of mura defect using an ND filter	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FLEXIBLE DISPLAY DEVICES -

Part 5-3: Visual assessment of image quality and defects

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62715-5-3 has been prepared by IEC technical committee 110: Electronic display devices.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
110/844/FDIS	110/867/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62715 series, published under the general title *Flexible display devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- · reconfirmed,
- · withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 62715 was developed in response to demands for the standardization of the general rules and detailed procedures that are used in the visual assessment of flexible display devices.

Visual assessment is an essential means for evaluating flexible display devices and is intended to complement objective display measurements [1] 1. The advantages of visual assessment are as follows:

- a) It is speedy, e.g. defects are instantly recognized by a human observer.
- b) It allows the evaluation of various device shapes and allows evaluation from various directions and distances, which can lead to higher sensitivity for detecting defects.
- c) It completely covers the area of even the largest display, allowing identification and selection of regions of interest for objective measurements.
- d) It is sensitive, e.g. for some defects, visual assessment is the most sensitive means of detection.
- e) It corresponds to the perception of humans.
- f) It can detect unexpected changes or defects that can be overlooked by predetermined measurements with equipment.

Visual assessment is a necessary first step for specifying types of measurements and the regions of interest for measurements.

Evaluation results from visual assessment depend on the observer, region of interest for the assessment, lighting and geometrical conditions of the assessment, criteria in making judgments, and various other factors. Therefore, it is important to standardize the general rules, including the terms, conditions, criteria and reporting of results from visual assessments.

Regarding the procedures for visual assessment of electronic display devices, the following standards can be consulted: IEC 62341-6-2 [6] and IEC 61747-20-3 [7].

Visual assessment is usually performed by comparing a test sample with a limit sample or a set of grade samples. This document stipulates the framework and procedures to be used in the assessments; it also describes the preparation of a limit sample or a set of grade samples.

This document also applies when a limit sample or a set of grade samples are not available for the same type of defect. Concerning defects of flexible display devices, many kinds of defects can be observed. Even within the same category of defect, factors, such as the shape, size, luminance, colour, gradation of the edge, width of the edge, solitary or repetitive, position in the display area, can differ. Therefore, in most cases, it is practically impossible to prepare the same type of limit sample or comparison samples for visual assessment.

¹ Numbers in square brackets refer to the Bibliography.

FLEXIBLE DISPLAY DEVICES -

Part 5-3: Visual assessment of image quality and defects

1 Scope

This part of IEC 62715 provides the framework and procedures for performing the visual assessment of flexible display devices.

Visual assessment stipulated in this document is applicable to flexible display modules in the following states:

- initial states and ageing states under standard ambient conditions,
- mechanically or environmentally stressed conditions,
- states after mechanical endurance test(s), after environmental endurance test(s) and after a combination of mechanical and environmental endurance tests.

NOTE Visual assessment under the mechanical or environmental stress is usually difficult to do, but this document can be applied when it is possible.

Visual assessment is performed by comparing a test sample to a limit sample or to a set of grade samples. This document provides the framework and procedures for visual assessments that use a limit sample or a set of grade samples. This document describes the framework and procedure that are followed while preparing limit samples and a set of grade samples. This document also describes visual assessment when limit samples and grade samples are not available for the same type of defect.

This document provides sets of test patterns that can be used in visual assessments.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61747-30-1, Liquid crystal display devices – Part 30-1: Measuring methods for liquid crystal display modules – Transmissive type

IEC 62715-1-1, Flexible display devices – Part 1-1: Terminology and letter symbols

IEC 62715-6-1, Flexible display devices – Part 6-1: Mechanical stress test methods

IEC 62715-6-22, Flexible display devices – Part 6-2: Environmental testing methods

² Under preparation. Stage at the time of publication: IEC/AFDIS 62715-6-2:2017.