



IEC 62977-3-4

Edition 1.0 2023-03

# INTERNATIONAL STANDARD



---

**Electronic displays –  
Part 3-4: Evaluation of optical performances – High dynamic range displays**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 31.120; 31.260

ISBN 978-2-8322-6701-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions and abbreviated terms .....	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	11
4 Standard measuring equipment .....	12
4.1 Video signal generator .....	12
4.2 Conditions of measuring equipment .....	12
4.3 Measuring equipment block diagram .....	12
5 Standard measuring conditions.....	13
5.1 Standard measuring environmental conditions .....	13
5.2 Power supply .....	13
5.3 Warm-up time .....	13
5.4 Standard darkroom conditions.....	13
5.5 Adjustment of HDR display .....	13
6 Measuring methods of optical characteristics.....	14
6.1 HDR peak luminance .....	14
6.1.1 HDR peak luminance variation by black and white pattern .....	14
6.1.2 APL by the window and background level .....	15
6.1.3 Test pattern for HDR peak luminance .....	16
6.1.4 Measuring method .....	16
6.2 Black luminance and contrast ratio.....	17
6.2.1 Test patterns for black luminance .....	17
6.2.2 Contrast ratio.....	18
6.2.3 Local contrast ratio .....	19
6.2.4 Measuring method .....	19
6.2.5 Contrast ratio with ambient illumination .....	20
6.3 Luminance loading.....	20
6.3.1 General .....	20
6.3.2 Measuring method .....	21
6.4 Transition times and duration of peak luminance.....	21
6.4.1 Test pattern for transition time .....	21
6.4.2 Measurement of rise and fall times .....	21
6.4.3 Measuring method of duration time and interval.....	22
6.5 Tone reproduction.....	23
6.5.1 General .....	23
6.5.2 Information on the evaluation of tone reproduction .....	23
6.6 HDR tone mapping.....	24
6.6.1 General .....	24
6.6.2 Information on the evaluation of tone mapping.....	24
6.7 Chromaticity gamut area and colour reproduction .....	25
6.7.1 Chromaticity gamut area evaluation.....	25
6.7.2 Information on the evaluation of colour reproduction.....	26
7 Reporting.....	27

7.1	Reporting requirements.....	27
7.2	Reporting of measurement results.....	27
Annex A	(informative) Example of tone reproduction measurement and evaluation .....	29
A.1	General.....	29
A.2	Test pattern for tone reproduction with constant APL .....	29
A.3	Example inputs for tone reproduction measurement.....	30
A.4	Measuring method of tone reproduction .....	31
A.5	Grey scale tracking accuracy .....	32
Annex B	(informative) Example of tone mapping evaluation .....	33
B.1	Inputs of tone mapping test patterns .....	33
B.2	Evaluation method of tone mapping input value outside of the display luminance range .....	33
B.3	Supplemental measurement.....	35
Annex C	(informative) Example of colour reproduction measurement and evaluation .....	36
C.1	General.....	36
C.2	Test pattern for colour reproduction with constant APL .....	36
C.3	Example inputs for colour reference pattern .....	37
C.4	Measuring method of colour reproduction .....	41
C.5	Colour reproduction accuracy .....	42
Bibliography	.....	43
Figure 1	– Measuring layout for non-contact measurement .....	12
Figure 2	– Measuring layout for close-up type LMD.....	14
Figure 3	– Example of white luminance curve as function of the white window area, expressed by its APL (%).....	15
Figure 4	– General window pattern with $A$ % area .....	16
Figure 5	– $A$ % APL pattern with $A$ % area white .....	16
Figure 6	– Input patterns for black luminance.....	18
Figure 7	– Graphical example of rise time and fall time of peak luminance.....	22
Figure 8	– OETF and EOTF curves .....	23
Figure 9	– Example of tone mapping for PQ curve .....	24
Figure 10	– BT.2020 and DCI-P3 chromaticity gamut in $xy$ chromaticity diagram.....	25
Figure A.1	– Multi-colour pattern for grey scale measurement.....	30
Figure B.1	– Black-to-colour image for PQ HDR with saturation .....	34
Figure B.2	– Black-to-colour image for PQ HDR with no saturation .....	34
Figure B.3	– Colour-to-white image for PQ HDR with saturation.....	35
Figure B.4	– Colour-to-white image for PQ HDR with no saturation .....	35
Figure C.1	– Multi-colour pattern with centre reference colour for colour reproduction measurement.....	36
Table 1	– Primary colours of BT.2020 and DCI-P3 .....	25
Table A.1	– Examples of measuring range for PQ grey scale measurement.....	31
Table B.1	– Code values for tone mapping test patterns .....	33
Table C.1	– Conversion matrix between $XYZ$ and $RGB$ for BT.2020 colorimetry .....	37
Table C.2	– Conversion matrix between $XYZ$ and $RGB$ for DCI-P3@D65 colorimetry .....	37

Table C.3 – Example of the colour reference pattern target values ..... 38

Table C.4 – Example RGB inputs of colour reference pattern for BT.2020 colorimetry ..... 39

Table C.5 – Example RGB inputs of colour reference pattern for DCI-P3@D65  
colorimetry ..... 40

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRONIC DISPLAYS –****Part 3-4: Evaluation of optical performances –  
High dynamic range displays****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62977-3-4 has been prepared by IEC technical committee 110: Electronic displays. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
110/1493/FDIS	110/1509/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts in the IEC 62977 series, published under the general title *Electronic displays*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

High dynamic range (HDR) systems enable more natural images that contain wider variations in brightness. For the wider dynamic range, newly designed electro-optical transfer function (EOTF) replaces the BT.1886 function of standard dynamic range (SDR) HDTV. High dynamic range (HDR) systems utilize non-linear signal encoding that enables reproduction over a wider range of light levels, from subtle grey differences at very low luminance levels up to very bright highlights. This very wide range of light levels occurs in both natural as well as synthetic imagery. In particular, in order to render the native image according to the intent of the content creator, signal codewords of SMPTE ST 2084 [2]<sup>1</sup> HDR EOTF, also known as the perceptual quantizer (PQ), are mapped to absolute luminance values within the mastering peak luminance as specified in metadata of the HDR content, versus an SDR signal level which indicates relative brightness according to the display luminance. In this case, tone mapping would be necessary when the display luminance cannot make the darker and the brighter luminance because HDR content preserves details in the darkest and brightest areas of a picture that are lost when using SDR standards (see 3.1.4) [20] such as Recommendation ITU-R BT.709 [12]. The tone mapping curve can depend upon the display manufacturer.

This document intends to describe the measurement and evaluation of the optical performance of HDR displays as a reference for forthcoming standards to make the work of the involved experts more efficient and to avoid duplication of efforts.

There are unique requirements to evaluate HDR displays, and particular attention is given to the measurements, so that they are done properly. For example,

- 1) very low luminance levels will be measured, with careful control of stray light from both the display as well as ambient light sources;
- 2) to measure high light output levels, measurements timing and test pattern need to be carefully controlled to correctly and accurately capture peak or high luminance levels since HDR displays can have a peak luminance time limit, and many HDR displays have luminance loading limits;
- 3) for HDR content, 10 bits or higher bit-depth should be used for sufficient luminance quantization;
- 4) the HDR test signal has SMPTE ST 2086 [3] HDR static metadata assigned to fixed values. Other metadata is not used in this document.

Proper source content is critical to evaluating HDR performance of the displays including the driver (and interface). In SDR displays, it is possible to separate these issues from the evaluation of “panels”, but for HDR displays it is not possible to separate these issues because HDR displays include one or more internal blocks that process the HDR video signal, such as EOTF and tone mapping, etc., in addition to essential driving stages for the display panel.

---

<sup>1</sup> Numbers in square brackets refer to the Bibliography.

## ELECTRONIC DISPLAYS –

### Part 3-4: Evaluation of optical performances – High dynamic range displays

#### 1 Scope

This part of IEC 62977 specifies the standard evaluation methods for determining the optical characteristics of HDR electronic display modules and systems. These methods apply to emissive and transmissive direct-view displays that render real 2D images on a flat panel or on a curved panel with a local radius of curvature larger than 1 500 mm. This document evaluates the optical characteristics of these displays under darkroom conditions. This document applies to the testing of display performance in response to HDR digital input signals that are absolute luminance encoded such as the HDR signal comprising RGB component values of Recommendation ITU-R BT.2020 colorimetry with SMPTE ST 2084 [2] PQ luminance encoding and SMPTE ST 2086 [3] metadata.

NOTE A flat panel or flat panel display is a display with a planar surface that emits light from the surface. The display can consist of light valves modulating a backlight or be self-luminous. Emissive/transmissive/reflective hybrid displays can be non-planar panels or non-planar panel displays.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62977-2-1:2021, *Electronic displays – Part 2-1: Measurements of optical characteristics – Fundamental measurements*

IEC 62977-2-2:2020, *Electronic displays – Part 2-2: Measurement of optical characteristics – Ambient performance*

CIE 015:2004, *Colorimetry*

Recommendation ITU-R BT.2020-2, *Parameter values for ultra-high definition television systems for production and international programme exchange*

Recommendation ITU-R BT.2100-2, *Image parameter values for high dynamic range television for use in production and international programme exchange*