

PRE-STANDARD

Symmetrical pair/quad cables for digital communications with transmission characteristics up to 600 MHz –

**Horizontal floor wiring –
Sectional specification**

Withhold

PUBLICLY AVAILABLE SPECIFICATION



INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

Reference number
IEC/PAS 61156-5

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS WITH
TRANSMISSION CHARACTERISTICS UP TO 600 MHZ –
HORIZONTAL FLOOR WIRING – SECTIONAL SPECIFICATION**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

This PAS Pre-Standard has been published using a rapid procedure as a result of technical consensus at the level of experts working on the subject within the IEC. The normal IEC procedure for the preparation of an International Standard is pursued in parallel and this Pre-Standard will be withdrawn upon publication of the corresponding International Standard.

IEC-PAS 61156-5 has been processed by subcommittee 46C, Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors and accessories for communication and signalling.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document:

Draft PAS	Report on voting
46C/462/PAS	46C/474/RVD

Full information on the voting for the approval of this PAS Pre-Standard can be found in the report on voting indicated in the above table.

SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS WITH TRANSMISSION CHARACTERISTICS UP TO 600 MHz –

HORIZONTAL FLOOR WIRING - SECTIONAL SPECIFICATION

1 Scope

This sectional specification relates to IEC 61156-1: Multicore and symmetrical pair/quad cables for digital communications - Part 1: Generic specification. The cables described herein are specifically intended for horizontal floor wiring in class D, E and F channels, as defined in ISO/IEC 11801 (2001): *Information technologies - Generic cabling for customer premises cabling* (see Table 1).

1.1 General

This sectional specification covers individually screened (STP), common screened (FTP) and unscreened (UTP) pairs or quads having a pair count of four pairs or less. The transmission characteristics of the cables are specified at 20 °C. See Annex A for a discussion of cable performance at temperatures higher than 20 °C.

The designation "Category 5e" is used herein to describe an enhanced Category 5 cable and is used in the same context as "Category 5" in ISO/IEC 11801 (2001). This enhanced cable is designated Category 5e to differentiate it from the Category 5 cables described in IEC 61156-2, -3, and -4. Although both Category 5 and 5e cables are characterised to 100 MHz and can be used in Class D channels, Category 5e has additional requirements, as compared to Category 5, which make it preferred for use in systems utilizing four pairs transmitting simultaneously in both directions.

Table 1

Cable Designation	Maximum reference frequency [MHz]	Channel Designation
Category 5e	100 ¹⁾	D
Category 6	250	E
Category 7	600	F
NOTE 1 Some characteristics are measured up to 125 MHz in order to comply with IEEE's request to specify the electrical performances up to a frequency 25 % higher than the referenced frequency.		

These cables can be used for various communication systems that are under development and which use as many as 4 pairs simultaneously. In this sense, this specification provides the cable characteristics required by system developers to evaluate new systems.

Under static conditions, the cables should operate in the temperature range from –40 °C to +60 °C. The temperature dependence of the cables is specified for screened and unscreened cables, and should be taken into account for the design of an actual cabling systems.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems. These cables are not intended to be used in conjunction with low impedance sources, for example, the electric power supplies of public utility mains.

The recommended temperature range during installation should be indicated in the detail specification.

1.2 Reference documents

IEC 60189-1:1986, *Low-frequency cables and wires with PVC insulation and PVC sheath. Part 1: General test and measuring methods*

IEC 60304:1982, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1:2000, *Multicore and symmetrical pair/quad cables for digital communications - Part 1: Generic specification*

ISO/IEC 11801:2001, *Information technology - Generic cabling for customer premises*