

# PUBLICLY AVAILABLE SPECIFICATION



---

**Maritime navigation and radiocommunication equipment and systems – Bridge  
alert management  
Part 101: Guideline on implementation**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 47.020; 47.020.70

ISBN 978-2-8322-5618-3

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	4
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	6
4 Purpose .....	7
4.1 Bridge alert management – Implementation .....	7
4.2 Structure of document .....	7
5 Implementing BAM in an equipment standard .....	8
5.1 Implementing a concept .....	8
5.2 Implementation process .....	8
5.3 Subjects for consideration when developing/modifying an individual equipment standard .....	10
5.3.1 General .....	10
5.3.2 Description of subjects .....	10
5.4 Role of a Central Alert Management system (CAM system) .....	11
6 Alert properties .....	12
6.1 Harmonization of alert sound vs legacy alarm sounds .....	12
6.1.1 General .....	12
6.1.2 Emergency alarms .....	13
6.1.3 Sounds in standards where MSC.302(87) does not take precedence .....	14
6.2 Priority .....	14
6.3 Category .....	16
6.4 Functional vs technical alerts .....	19
6.5 Alert management using context information .....	21
6.5.1 General .....	21
6.5.2 Different operational modes – Different alert requirements .....	21
6.5.3 Other operational sectors .....	22
7 Pre-BAM power failures and alarm-outputs .....	23
7.1 General .....	23
7.2 Pre-BAM alerts .....	23
7.2.1 Applying ALR sentences .....	23
7.2.2 Pre-BAM alert ‘alarm condition’ .....	23
7.2.3 Applying dry contacts to inform about abnormal conditions (e.g. system failure) .....	24
7.2.4 Pre-BAM alert ‘power failure’ .....	24
7.3 Alerting on power problems .....	24
7.3.1 General .....	24
7.3.2 Description .....	25
7.3.3 Discussion .....	25
7.3.4 Resolution .....	26
8 Alert Identifiers .....	27
8.1 General .....	27
8.2 Application .....	28
9 Clarification regarding presentation of alerts in the list of active alerts .....	29
10 WG16 assistance .....	29
Bibliography .....	31

Figure 1 – BAM is a concept applied to equipment rather than a piece of equipment .....	8
Figure 2 – Role of a CAM system in Bridge Alert Management.....	12
Figure 3 – Typical decision tree for the classification of alert priority.....	15
Figure 4 – Typical decision tree for the classification of alert priority after escalation of a warning .....	16
Figure 5 – EUT scope with one or two power inputs with one or two power sources .....	26
Table 1 – Blocks of alert identifier end numbers in each 10 consecutive alert identifiers above 300.....	28

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT  
AND SYSTEMS – BRIDGE ALERT MANAGEMENT****Part 101: Guideline on implementation****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 62923-101 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

<b>Draft PAS</b>	<b>Report on voting</b>
80/1041/DPAS	80/1044/RVDPAS

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

# MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – BRIDGE ALERT MANAGEMENT

## Part 101: Guideline on implementation

### 1 Scope

This document primarily provides support to other workgroups to include alert requirements in standards in line with Bridge Alert Management (BAM), and additionally provides support to designers to implement alert properties so that they conform with the BAM requirements.

This document is applicable, and is intended to provide guidance, when the intention is to implement BAM according to IMO Resolution MSC.302(87).

Based on the IMO decision to adopt the BAM Performance Standard MSC.302(87) as a high level leading umbrella standard for intended implementation of BAM, IMO resolved in MSC.302(87), 3.6, that in case of conflict with alert requirements in existing performance standards, MSC.302(87) takes precedence.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 62923-1:2018, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results*

IEC 62923-2:2018, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 2: Alert and cluster identifiers and other additional features*

IMO A.1021(26), *Code on alerts and indicators*, 2009

IMO MSC.302(87), *Performance standards for Bridge Alert Management (BAM)*