

Edition 1.0 2020-10

# PUBLICLY AVAILABLE SPECIFICATION



**Zhaga interface specification Book 1 and Book 12** 

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.140.99 ISBN 978-2-8322-8944-0

Warning! Make sure that you obtained this publication from an authorized distributor.

# CONTENTS

| Г  | JREWU      |  | 10 |
|----|------------|--|----|
| IN | ITRODU     | JCTION   | 12 |
| Sı | ubdivis    | ion 1  | 13 |
|    | Zhaga      | Interface Specification Book 12                            | 13 |
|    | _          | ary (informative)  |    |
|    |            | ound   |    |
|    | •          | nts  |    |
|    | Intende    | ed Use   | 13 |
| 1  |            | eral   |    |
|    | 1.1        | Introduction   | 14 |
|    | 1.2        | Scope  |    |
|    | 1.3        | Conformance and references                                 |    |
|    | 1.3.1      |  |    |
|    | 1.3.2      |  |    |
|    | 1.4        | Definitions  |    |
|    | 1.5        | Acronyms   | 15 |
|    | 1.6        | Symbols  |    |
|    | 1.7        | Conventions  |    |
|    | 1.7.1      | Precedence   | 15 |
|    | 1.7.2      | Cross references   | 15 |
|    | 1.7.3      | Informative text   | 15 |
|    | 1.7.4      | Terms in capitals  | 15 |
|    | 1.7.5      | Units of physical quantities                               | 15 |
|    | 1.7.6      | Decimal separator  | 15 |
|    | 1.7.7      | Limits   | 16 |
| 2  | Over       | view (Informative)   | 16 |
|    | 2.1        | General  | 16 |
|    | 2.2        | Description of the LED Array and the Holder                | 16 |
|    | 2.3        | Outline of this Book                                       |    |
| Ра | art 1: Int | terface Definition   | 18 |
| 3  | Mech       | nanical interface  | 18 |
| _  | 3.1        | Drawing principles   |    |
|    | 3.2        | Mechanical references and definitions                      |    |
|    | 3.3        | Mechanical interface of the LED Array                      |    |
|    | 3.3.1      | •  |    |
|    | 3.3.2      | ·  |    |
|    | 3.3.3      |  |    |
|    | 3.4        | Mechanical interface of the Holder                         |    |
|    | 3.4.1      |  |    |
|    | 3.4.2      |  |    |
|    | 3.4.3      | Dimensions depending on LED Array category and maximum LES |    |
| 4  | Dhat       | Categoryometric interface                                  |    |
| 4  |            |  |    |
|    | 4.1        | Light Emitting Surface                                     |    |
|    | 4.2        | Operating conditions                                       |    |
|    | 4.3        | Luminous flux  | 31 |

|    | 4.4         | Luminous intensity distribution  | 31 |
|----|-------------|--|----|
|    | 4.5         | Luminance uniformity   | 32 |
|    | 4.6         | Correlated color temperature   | 33 |
|    | 4.7         | Color rendering index  | 33 |
| 5  | Elect       | rical interface of the LED Array   | 33 |
|    | 5.1         | Electrical interface of the LED Array  | 33 |
|    | 5.2         | Electrical insulation of the LED Array (informative)   |    |
| 6  | Theri       | mal interface  |    |
|    | 6.1         | Background information (informative)   | 33 |
|    | 6.2         | Generic thermal interface model  |    |
|    | 6.2.1       |  |    |
|    | 6.2.2       |  |    |
|    | 6.2.3       |  |    |
|    | 6.2.4       | Thermal compatibility check  | 34 |
|    | 6.2.5       | Thermal Interface Material   | 34 |
|    | 6.2.6       | Surface planarity and roughness  | 34 |
|    | 6.2.7       | Aging of LED Array (informative)   | 34 |
| Ра | art 2: Co   | ompliance Tests  | 35 |
| 7  | Com         | oliance test tools   | 36 |
|    | 7.1         | LED Array test tools   | 36 |
|    | 7.1.1       | •  |    |
|    | 7.2         | Holder test tools  |    |
|    | 7.2.1       | Gauges for Holder cavity test  | 36 |
|    | 7.2.2       | •  |    |
| 8  | LED         | Array Compliance Tests   |    |
|    | 8.1         | LED Array mechanical interface tests   | 38 |
|    | 8.1.1       | •  |    |
|    | 8.1.2       | mounting holes   | 39 |
|    | 8.1.3       | Test of the demarcation of the LED Array C20x24, C19x19, C13.5x13.5 or C12x15 with mouse bites | 39 |
|    | 8.1.4       | Test of the electrical contact areas (+) and (-) of the LED Array                              | 40 |
|    | 8.1.5       | ·  |    |
|    | 8.1.6       | ,  |    |
|    | 8.2         | LED Array photometric interface tests  |    |
|    | 8.2.1       |  |    |
|    | 8.2.2       | i v  |    |
|    | 8.2.3       | , ,  |    |
|    | 8.2.4       | ŭ  |    |
|    | 8.2.5       | ,  |    |
|    | 8.3         | LED Array thermal interface tests  |    |
|    | 8.3.1       |  |    |
|    | 8.3.2       | •  |    |
|    | 8.3.3       | ·  |    |
|    | 8.4         | LED Array Product Data Set test  |    |
| 9  | 8.5<br>Hold | LED Array Product Data Set tester Compliance Tests   |    |
| J  |             | Unider machanical interface tests  | 42 |

|    | 9.1.1    | Test of the outline of the cavity of the Holder                         | 42 |
|----|----------|---|----|
|    | 9.1.2    | Test of the electrical contacts (+) and (-) of the Holder               | 43 |
|    | 9.1.3    | Test of the keep-out zone of the Holder                                 | 44 |
|    | 9.2      | Holder Product Data Set test  | 45 |
| Αı | nnexes . |   | 46 |
| Αı | nnex A F | Product Data Set requirements   | 47 |
|    |          | LED Array Product Data Set  |    |
|    | A.2      | Holder Product Data Set   |    |
| Αı |          | Definition of the cavity outline and mechanical reference of the Holder |    |
|    |          | Guidelines for LES and Luminance measurements (informative)             |    |
|    | C.1      | Test equipment  |    |
|    | C.2      | Test conditions   |    |
|    | C.3      | Test procedure  |    |
| Αı |          | History of Changes  |    |
|    |          | on 2  |    |
| J. |          | Interface Specification Book 1  |    |
|    | _        | ary (informative)   |    |
|    |          | ound  |    |
|    | •        | ts  |    |
|    |          | ed Use  |    |
| 1  |          | eral  |    |
| '  | 1.1      | Introduction  |    |
|    | 1.1      | Scope   |    |
|    | 1.2      | Conformance and references  |    |
|    | 1.3.1    | Conformance and references  |    |
|    | 1.3.1    | Normative references  |    |
|    | 1.3.2    | Informative references  |    |
|    | 1.3.3    | Common definitions  |    |
|    | 1.4      | Common acronyms   |    |
|    | 1.6      | Common symbols  |    |
|    | 1.7      | Common conventions  |    |
|    | 1.7.1    | Cross references  |    |
|    | 1.7.1    | Informative text  |    |
|    | 1.7.2    | Terms in capitals   |    |
|    | 1.7.4    | Units of physical quantities  |    |
|    | 1.7.5    | Decimal separator   |    |
| 2  |          | view of Zhaga (informative)   |    |
| _  | 2.1      | About Zhaga   |    |
|    | 2.1      | Zhaga building blocks and interfaces                                    |    |
|    | 2.3      | Compatibility and Interchangeability                                    |    |
|    | 2.4      | Product Data Set  |    |
|    | 2.5      | Compliance testing  |    |
|    | 2.5.1    | Certification   |    |
|    | 2.5.1    | Market surveillance   |    |
|    | 2.6      | Compatibility check   |    |
|    | 2.7      | Zhaga product certification   |    |
| 3  |          | anical interface  |    |
| -  |          | wing principles   |    |
|    | J D. C   | p   |    |

|    | 3.2     | Mechanical interface between Separate ECG and Luminaire         | .63  |
|----|---------|---|------|
|    | 3.3     | Thermal expansion   | . 63 |
|    | 3.4     | Demarcation (Informative)                                       | . 63 |
| 4  | Photo   | ometric interface   | . 65 |
|    | 4.1     | Light Emitting Surface  | .65  |
|    | 4.1.1   | LES categories  | . 66 |
|    | 4.2     | Operating conditions for measuring photometric parameters       | .66  |
|    | 4.3     | Luminous flux   | . 67 |
|    | 4.4     | Luminous intensity distribution                                 | .68  |
|    | 4.4.1   | Beam angle and beam angle categories                            | .69  |
|    | 4.5     | Luminance uniformity  | . 69 |
|    | 4.6     | Correlated color temperature (CCT)                              | .69  |
|    | 4.7     | Color rendering index (CRI)                                     | .70  |
|    | 4.8     | Luminaire Optics (informative)                                  | .70  |
| 5  | Elect   | rical interface   | . 70 |
|    | 5.1     | Electrical insulation (informative)                             | .70  |
| 6  | Therr   | nal interface   | .70  |
|    | 6.1     | Background information (informative)                            | .70  |
|    | 6.2     | Generic thermal interface model                                 |      |
|    | 6.2.1   | General case  |      |
|    | 6.2.2   | Test Fixture TPTF   | .72  |
|    | 6.2.3   | Rated Operating Temperature and safety (informative)            | .73  |
|    | 6.2.4   | Thermal overload protection (Informative)                       |      |
|    | 6.2.5   | Ambient Temperature   |      |
|    | 6.2.6   | Luminaires with multiple LLEs or multiple LED Modules           | .74  |
|    | 6.2.6.1 | Separate heat sinks   | .74  |
|    | 6.2.6.2 | One heat sink   | .74  |
|    | 6.2.7   | Thermal compatibility check                                     | .74  |
|    | 6.2.8   | Thermal uniformity  | .75  |
|    | 6.2.9   | Thermal Interface Material                                      | .76  |
|    | 6.2.10  | Surface planarity and roughness                                 | .76  |
|    | 6.2.11  | Aging of LED Light Engine or LED Module/LED Array (informative) | .76  |
|    | 6.2.12  | Empty   | . 76 |
|    | 6.2.13  | Ambient Temperature and thermal resistance (Rth)                | .76  |
|    | 6.3     | Simplified thermal interface model                              | .77  |
|    | 6.3.1   | General case  | . 77 |
|    | 6.3.2   | Rated Operating Temperature and safety (informative)            | .77  |
|    | 6.3.3   | Thermal overload protection (informative)                       | .77  |
|    | 6.3.4   | Thermal compatibility check                                     |      |
|    | 6.3.5   | Thermal Interface Material                                      | .78  |
|    | 6.3.6   | Surface planarity and roughness                                 | .78  |
|    | 6.3.7   | Aging of LED Light Engine or LED Module/LED Array (informative) | .78  |
| 7  | Contr   | ol interface  | .78  |
| Ar | nex A   | Compliance tests  | .79  |
|    |         | Module/LED Array compliance tests                               |      |
|    |         | LED Module/LED Array mechanical interface test                  |      |
|    | A.0.1.1 |   |      |
|    |         | 1 Test equipment  |      |

| A.0.1.1.3 Test procedure  A.0.1.1.4 Pass criteria  A.0.2 LED Module/LED Array photometric interface tests  A.0.2.1 Test on Luminous Flux  A.0.2.1.1 Test equipment  A.0.2.1.2 Test conditions  A.0.2.1.3 Test procedure  A.0.2.1.4 Pass criteria |                                  |
|--|----------------------------------|
| A.0.2 LED Module/LED Array photometric interface tests  A.0.2.1 Test on Luminous Flux  A.0.2.1.1 Test equipment  A.0.2.1.2 Test conditions  A.0.2.1.3 Test procedure  A.0.2.1.4 Pass criteria  | 79<br>79<br>79<br>79<br>80<br>80 |
| A.0.2.1 Test on Luminous Flux A.0.2.1.1 Test equipment A.0.2.1.2 Test conditions A.0.2.1.3 Test procedure A.0.2.1.4 Pass criteria  |                                  |
| A.0.2.1.1 Test equipment  A.0.2.1.2 Test conditions  A.0.2.1.3 Test procedure  A.0.2.1.4 Pass criteria   | 79<br>79<br>80<br>80             |
| A.0.2.1.2 Test conditions  A.0.2.1.3 Test procedure  A.0.2.1.4 Pass criteria   | 79<br>80<br>80                   |
| A.0.2.1.3 Test procedure   | 79<br>80<br>80                   |
| A.0.2.1.4 Pass criteria  | 80<br>80<br>80                   |
|  | 80<br>80                         |
| A 0 0 0 T 1  | 80                               |
| A.0.2.2 Test on Relative Partial Luminous Flux and beam angle  |                                  |
| A.0.2.2.1 Test equipment   | 80                               |
| A.0.2.2.2 Test conditions  |                                  |
| A.0.2.2.3 Test procedure   | 80                               |
| A.0.2.2.4 Pass criteria  | 80                               |
| A.0.2.3 Test on correlated color temperature (CCT)   | 81                               |
| A.0.2.3.1 Test equipment   | 81                               |
| A.0.2.3.2 Test conditions  | 81                               |
| A.0.2.3.3 Test procedure   | 81                               |
| A.0.2.3.4 Pass criteria  | 81                               |
| A.0.2.4 Test on color rendering index  | 81                               |
| A.0.2.4.1 Test equipment   | 81                               |
| A.0.2.4.2 Test conditions  | 82                               |
| A.0.2.4.3 Test procedure   | 82                               |
| A.0.2.4.4 Pass criteria  | 82                               |
| A.0.2.5 Test on Luminance Uniformity   | 82                               |
| A.0.3 LED Module/LED Array thermal interface tests   | 82                               |
| A.0.3.1 Test on thermal power (Pth)  | 82                               |
| A.0.3.1.1 Test equipment   | 82                               |
| A.0.3.1.2 Test conditions  | 82                               |
| A.0.3.1.3 Test procedure   | 82                               |
| A.0.3.1.4 Pass criteria  |                                  |
| A.0.4 LED Module/LED Array electrical interface tests  | 83                               |
| A.0.5 LED Module/LED Array Product Data Set test   | 83                               |
| A.0.5.1 Test   | 83                               |
| A.0.5.2 Pass criteria  | 83                               |
| A.1 LLE compliance tests   | 83                               |
| A.1.1 LLE mechanical interface tests   | 83                               |
| A.1.1.1 Test of the mechanical interface of the Integrated LLE   | 83                               |
| A.1.1.1.1 Test equipment   | 83                               |
| A.1.1.1.2 Test conditions  | 83                               |
| A.1.1.1.3 Test procedure   | 83                               |
| A.1.1.1.4 Pass criteria  | 84                               |
| A.1.2 LLE photometric interface tests  | 84                               |
| A.1.2.1 Test on Luminous Flux  | 84                               |
| A.1.2.1.1 Test equipment   | 84                               |
| A.1.2.1.2 Test conditions  | 84                               |
| A.1.2.1.3 Test procedure   | 84                               |
| A.1.2.1.4 Pass criteria  |                                  |
| A.1.2.2 Test on Relative Partial Luminous Flux and beam angle  | 84                               |

|     | A.1.2.2.1   | Test equipment   | 84 |
|-----|-------------|--|----|
|     | A.1.2.2.2   | Test conditions  | 85 |
|     | A.1.2.2.3   | Test procedure   | 85 |
|     | A.1.2.2.4   | Pass criteria  | 85 |
|     | A.1.2.3     | Test on correlated color temperature (CCT)                             | 85 |
|     | A.1.2.3.1   | Test equipment   | 85 |
|     | A.1.2.3.2   | Test conditions  | 85 |
|     | A.1.2.3.3   | Test procedure   | 86 |
|     | A.1.2.3.4   | Pass criteria  | 86 |
|     | A.1.2.4     | Test on color rendering index  | 86 |
|     | A.1.2.4.1   | Test equipment   | 86 |
|     | A.1.2.4.2   | Test conditions  | 86 |
|     | A.1.2.4.3   | Test procedure   | 86 |
|     | A.1.2.4.4   | Pass criteria  |    |
|     | A.1.2.5     | Test on Luminance Uniformity   |    |
|     | A.1.3 LLE   | thermal interface tests  |    |
|     | A.1.3.1     | Test on thermal power (Pth)  | 87 |
|     | A.1.3.1.1   | Test equipment   |    |
|     | A.1.3.1.2   | Test conditions  |    |
|     | A.1.3.1.3   | Test procedure   |    |
|     | A.1.3.1.4   | Pass criteria  |    |
|     | A.1.3.2     | Test on Thermal power through the Thermal Interface Surface (Pth,rear) |    |
|     | A.1.3.2.1   | Test equipment   |    |
|     | A.1.3.2.2   | Test conditions  |    |
|     | A.1.3.2.3   | Calibration of <i>P</i> th,rear test setup                             |    |
|     | A.1.3.2.4   | Measurement of Pth,rear of the LLE                                     |    |
|     | A.1.3.2.5   | Pass criteria  |    |
|     | A.1.3.3     | Empty  |    |
|     | A.1.3.4     | Empty  |    |
|     | A.1.3.5     | Temperature stabilization  |    |
|     | A.1.3.6     | Position of measurement point for the temperature <i>t</i> r           |    |
|     |             | electrical interface tests   |    |
|     |             | control interface tests  |    |
|     | A.1.6 LLE   | Product Data Set test  |    |
|     | A.1.6.1     | Test   |    |
|     | A.1.6.2     | Pass criteria  |    |
| A.2 | 2 Luminaire | compliance tests   | 92 |
|     | A.2.1 Lum   | inaire mechanical interface tests                                      | 92 |
|     | A.2.1.1     | Test of the mechanical dimensions of the Luminaire                     |    |
|     | A.2.1.1.1   | Test equipment   | 92 |
|     | A.2.1.1.2   | Test conditions  | 92 |
|     | A.2.1.1.3   | Test procedure   |    |
|     | A.2.1.1.4   | Pass criteria  |    |
|     |             | inaire photometric interface tests                                     |    |
|     | A.2.3 Lum   | inaire thermal interface tests   |    |
|     | A.2.3.1     | Empty  |    |
|     |             | inaire electrical interface tests                                      |    |
|     |             | inaire control interface tests   |    |
|     | 1 2 6 I     | ingire Product Date Set test   | വാ |

| A.2.6.1 Test  | 93 |
|---|----|
| A.2.6.2 Pass criteria   |    |
| Annex B Guidelines for Demarcation measurement  |    |
| Annex C History of changes  | 96 |
|   |    |
| Figure 2-1 – 3D-drawings of a Book 12 LED Array and Holder (informative)  |    |
| Figure 3-1 – Positions of the reference point and the reference plane of the LED Array  |    |
| Figure 3-2 – Definition of the LED Array Border and mechanical references   | 19 |
| Figure 3-3 – Demarcation model for the outline of the LED Array without mounting holes and without mouse bites  | 20 |
| Figure 3-4 – Demarcation model – top view for the outline and mounting holes of the   |    |
| LED Array in one of the categories C28x28 or C24x24   | 21 |
| Figure 3-5 – Demarcation model – top view for the outline of the LED Array with mouse bites in one of the categories C20x24, C19x19, C16x19, C13.5x13.5 or C12x15 | 22 |
| Figure 3-6 – Definition of the minimum electrical contact area for the (+) and (-)  | ∠∠ |
| contacts – top view   | 23 |
| Figure 3-7 – Requirement on the minimum size contact area for the (+) and (-) contacts  | 23 |
| Figure 3-8 – Requirement on the overlap area for the (+) and (-) contacts – top view  | 24 |
| Figure 3-9 – Definition of the keep-in zone   | 25 |
| Figure 3-10 – Definition of the maximum electrical contact area – top view  | 26 |
| Figure 3-11 – Definition of the Cavity Border and mechanical references   | 27 |
| Figure 3-12 – Demarcation model for the outline of the cavity for the LED Array   | 28 |
| Figure 3-13 – Definition of the position of the electrical contacts of the Holder   | 29 |
| Figure 3-14 – Definition of the keep-out zone   | 30 |
| Figure 4-1 – Luminance property evaluation areas  | 33 |
| Figure 7-1 – Definition of the gauges for the holder cavity compliance test   | 36 |
| Figure 7-2 – Definition of the gauges for the holder contacts compliance test   | 37 |
| Figure 9-1 – LED array in 'Concept 1' Holder  | 43 |
| Figure 9-2 – LED array in 'Concept 2' Holder  | 44 |
| Figure B-1 – Examples of cavity outlines in a Holder  | 48 |
| Figure B-2 – Definition of the effective cavity outline of a Holder   | 48 |
| Figure C-1 – Set-up for measurement of luminance uniformity and LES diameter  | 49 |
| Figure 2-1 – Schematic overview of a Luminaire and one or more non-integrated LED Light Engines   | 59 |
| Figure 2-2 – Schematic overview of a Luminaire and one or more integrated LED Light   |    |
| Engines   |    |
| Figure 2-3 – Schematic overview of a LED Light Engine with Integrated ECG   |    |
| Figure 2-4 – Schematic overview of a LED Light Engine with Separate ECG   |    |
| Figure 2-5 – Overview of test and certification of Zhaga products   |    |
| Figure 2-6 – Compatibility check  |    |
| Figure 3-1 – Example of a Demarcation Model (2-dimensional)   |    |
| Figure 3-2 – Example of a product which is compliant with the Demarcation Model   |    |
| Figure 3-3 – Example of a product which is not compliant with the Demarcation Model   |    |
| Figure 3-4 – Example of a product which is not compliant with the Demarcation Model   | 65 |

| Figure 4-1 – Rotationally symmetric solid angle bounded by the polar angles $\gamma 1$ and $\gamma 2$ which is used to define the Relative Partial Luminous Flux | 69 |
|--|----|
| Figure 6-1 – Thermal model of a LLE – Luminaire or a LED Module – Luminaire combination  | 71 |
| Figure 6-2 – Power conversion  | 72 |
| Figure 6-3 – Position of the Thermal Interface Surface in case of a configuration with TIM   | 76 |
| Figure A-1 – Heat sensor equipment with Test Fixture and LLE-under-test  |    |
| Figure A-2 – Calibration of the heat flux measurement setup  | 89 |
| Figure A-3 – Position of measurement point for the temperature <i>t</i> r  | 91 |
| Figure B-1 – Example of a LED Array  | 94 |
| Figure B-2 – Example of a LED Array with sections  | 94 |
| Figure B-3 – Example of a LED Array with measurement points  | 95 |
| Table 3-1 – Values of dimensions for the Book 12 LED Array categories  | 25 |
| Table 3-2 – Values of dimension Økeep-in depending on the LED Array category and the LES Category  | 26 |
| Table 3-3 – Values of Holder dimensions depending on the Book 12 LED Array categories  | 29 |
| Table 3-4 – Values of dimension Økeep-out depending on the LED Array category and the maximum LES Category   |    |
| Table 4-1 – Relative partial luminous flux requirements  |    |
| Table 7-1 – Values of dimensions of the gauges for the Holder cavity compliance test   |    |
| Table 7-2 – Values of dimensions of the gauges for the Holder contacts compliance  |    |
| test   | 38 |
| Table D-1 – Changes from Edition 1.1 to Edition 1.2  |    |
| Table 4-1 – Definition of circular LES categories  | 66 |
| Table 4-2 – Test voltages for different Rated input voltages of the LLE  |    |
| Table 4-3 – Definition of luminous flux categories   | 68 |
| Table 4-4 – Definition of beam angle categories  |    |
| Table C-1 – Changes from Edition 1.7 to Edition 1.8  | 96 |

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# **ZHAGA INTERFACE SPECIFICATION BOOK 1 AND BOOK 12**

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 63328 has been processed by subcommittee 34A: Electric light sources, of IEC technical committee 34: Lighting.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

| Draft PAS     | Report on voting |
|---------------|------------------|
| 34A/2195/DPAS | 34A/2205/RVDPAS  |

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

# INTRODUCTION

This PAS is a reproduction of Zhaga Book 1 Edition 1.8 and Book 12 Edition 1.2 with no changes introduced.

The document layout, terms and definitions, etc within this PAS therefore do not follow the normal IEC drafting rules that would be applied for an International Standard.

Subdivision 1 comprises Zhaga Book 12 Edition 1.2 – Rectangular LED arrays with circular LES and corresponding holders.

Subdivision 2 comprises Zhaga Book 1 Edition 1.8 – Overview and common information, which is essential to the interpretation of Zhaga Book 12 (and future Zhaga books).

The future intention is for the content of this PAS to be incorporated within one or more International Standards and at this time any conflict with IEC Directives and drafting rules will be addressed.

#### **Subdivision 1**

#### **Zhaga Interface Specification Book 12**

### **Summary (informative)**

#### **Background**

The Zhaga Consortium is a global lighting-industry organization that aims to standardize components of LED luminaires, including LED light engines, LED modules, LED arrays, holders, electronic control gear (LED drivers) and connectivity fit systems.

Zhaga has created a set of interface specifications, known as Books. Each Book defines one or more components of an LED luminaire by means of the mechanical, photometric, electrical, thermal, and control interfaces of the component to its environment. This makes such products interchangeable in the sense that it is easy to replace one product with another, even if they have been made by different manufacturers.

#### **Contents**

This Book 12 defines LED arrays with a rectangular shape and a circular light emitting surface. For each LED array, this Book 12 also defines the mechanical interface between the LED array and the corresponding holder. The mechanical interface between the holder and the luminaire is defined in another Zhaga book.

This book should be read together with Zhaga Book 1.

#### Intended Use

The LED arrays defined in this specification are intended to be mounted on a heat sink by means of a holder and to be connected to a separate electronic control gear. The light output is essentially Lambertian to enable the luminaire optics to shape the application's desired light distribution from a defined input.

The LED arrays and holders defined in this Book 12 are intended to be installed and replaced by luminaire manufacturers only.

#### 1 General

#### 1.1 Introduction

The Zhaga Consortium is a global organization that aims to standardize components of LED Luminaires. A LED Luminaire is a lighting fixture for general lighting that contains a light source based on solid-state technology. Such light sources, including LED Modules and LED Light Engines, typically consist of one or more LEDs combined with an Electronic Control Gear (LED driver). Other components of LED Luminaires include LED Arrays, Holders, and connectivity fit systems.

Zhaga has created a set of interface specifications, known as Books, which define the interfaces between a component and its environment. Book 1 is a special Book in the sense that it provides common information, which is relevant to all other Books in the series. In addition, Book 1 defines requirements and compliance tests, which are applicable across multiple Zhaga books. Such Books refer to those requirements and compliance tests as applicable.

# 1.2 Scope

This Book 12 defines LED Arrays with a rectangular shape and a circular light emitting surface. For each LED Array, this Book 12 also defines the mechanical interface between the LED Array and the corresponding Holder. The mechanical interface between the Holder and the Luminaire (e.g. outline, OCA and mounting holes) is defined in [Book-10].

The LED Arrays defined in this specification are intended to be mounted on a heat sink by means of a Holder and to be connected to a separate Electronic Control Gear. The light output is essentially Lambertian to enable the Luminaire Optics to shape the application's desired light distribution from a defined input. The LED Arrays and Holders defined in this Book 12 are intended to be installed and replaced by Luminaire manufacturers only.

Although this Book 12 has been developed with "Chip-on-board" in mind, the specification is in no way limited to this technology.

#### 1.3 Conformance and references

## 1.3.1 Conformance

All provisions in the Zhaga interface Specifications are mandatory, unless specifically indicated as recommended, optional or informative. Verbal expressions of provisions in the Zhaga interface specifications follow the rules provided in Clause 7 of ISO/IEC Directives, Part 2:2018. For clarity, the word "shall" indicates a requirement that is to be followed strictly in order to conform to the Zhaga interface specifications, and from which no deviation is permitted. The word "should" indicates that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others, or that a certain course of action is preferred but not necessarily required, or that (in the negative form) a certain possibility or course of action is deprecated but not prohibited.

#### 1.3.2 References

For references which are not listed in this section, see [Book 1]. For undated references, the most recently published edition applies.

- [Book 1] Zhaga Interface Specification, Book 1: Overview and Common Information.
- [Book 10] Zhaga Interface Specification, Book 10: Circular LED modules for spot lighting.