



Edition 1.0 2021-10

TECHNICAL REPORT



Packaging of components for automatic handling – Part 3-3: Packaging of surface mount components on continuous paper tapes for Auto Loading Feeder

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 31.020; 31.240

ISBN 978-2-8322-1041-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWOR	RD	4
INTRODUC	CTION	6
1 Scope		7
2 Norma	ative references	7
3 Terms	, definitions and symbols	7
	rerms and definitions	
	Symbols	
4 Requir	rements and required dimensions for paper taping for Auto Loading Feeder	8
4.1 (General	8
4.2 F	Required dimensions for the cover tape sealed positions	9
	Required dimensions for the distance between the upper side of the carrier	
	ape and the top surface of a component	
	Required specifications for the sealing method for the cover tape	
	Requirements about fluff generated at removal of cover tape	
	Required specifications for the maximum trailer length nformative) Overview and features of Auto Loading Feeder	
· ·		
	nformative) Methods and mechanisms of automatically exposing the ts in using Auto Loading Feeder	12
	General	
	Single-door method	
	Double-door method	
	nformative) Discussion for paper taping for Auto Loading Feeder	
C.1 (General	14
C.2 [Discussion items	14
C.2.1	Necessity of M_1 and M_2 as the cover tape sealed positions	14
C.2.2	Necessity of K_1 as the distance between the upper side of the carrier	
	tape and the top surfaces of a component	15
C.2.3	Sealing method for the cover tape	15
C.2.4	Dent of the cover tape over the pockets	16
C.2.5	Lower limit of peel-off strength of the cover tape	
C.2.6	Adhesion of components on the cover tape	
C.2.7	Bending stiffness of the carrier tape	
C.2.8	Fluff entering the pockets at removal of the cover tape	
C.2.9 C.2.10	Maximum trailer length	
C.2.10 C.2.11	5	
	nformative) Glossary	
ывподгарт	ıy	22
Figure 4		~
Figure 1 – Specified dimensions for paper taping for Auto Loading Feeder		
•	Leader part and trailer part	10
	 Operation and features when another tape is re-supplied automatically by pading Feeder 	11

Figure B.1 – Overview of the single-door method	.12
Figure B.2 – Overview of the double-door method	.13

Figure C.1 – Example dent of the cover tape over the pocket (embossed tape)	16
Figure C.2 – Example of fluff entering the pocket possible in using Auto Loading Feeder	17
Figure C.3 – Examples of cut shapes available/unavailable for Auto Loading Feeder and a tape deformed at its top end	19
Table 1 – Symbols used in figures and tables	8
Table 2 – The cover tape sealed positions required for paper taping for Auto Loading Feeder	9
Table 3 – Distance between the upper side of the carrier tape and top surface of a component required for paper taping for Auto Loading Feeder	9
Table D.1 – Glossary of mounter and feeder related terms	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING -

Part 3-3: Packaging of surface mount components on continuous paper tapes for Auto Loading Feeder

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 60286-3-3 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
40/2843/DTR	40/2865/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available

IEC TR 60286-3-3:2021 © IEC 2021 - 5 -

at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60286 series, published under the general title *Packaging of components for automatic handling*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This Technical Report was developed by the technical committee 40 working group 36 on components packaging, in which the members, such as mounter manufacturers, component manufacturers and packaging material manufacturers, had proposed, considered and discussed the possible standardization of the application of Auto Loading Feeder to enable automatically exchange SMD continuous tapes, using paper carrier tape during mounter operation, aiming to support IEC 60286-3, Edition 6, issued in 2019.

This document includes data expressed in the form of provisions, such as requirements or recommendations. These data, however, do not claim to be provisions and are just suggested as the results of the discussion.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a trademark concerning Auto Loading Feeder given in 3.1.1.

- Trademark ... AUTO LOADING FEEDER™
- Trademark registration number ... No.5983611 (Japan)

IEC takes no position concerning the evidence, validity and scope of this trademark right.

The holder of this trademark right has assured the IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this trademark right is registered with IEC. Information may be obtained from:

• Name of holder of trademark right ... Yamaha Motor Co., Ltd.

Address ... 2500 Shingai, Iwata, Shizuoka, Japan

- Name of holder of trademark right ... FUJI CORPORATION
 Address ... 19 Chausuyama., Yamamachi, Chiryu, Aichi, Japan
- Name of holder of trademark right ... Panasonic Corporation

Address ... 2-7, Matsuba-cho, Kadoma, Osaka, Japan

Attention is drawn to the possibility that some of the elements of this document may be the subject of trademark rights other than those identified above. IEC shall not be held responsible for identifying any or all such trademark rights.

PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING -

Part 3-3: Packaging of surface mount components on continuous paper tapes for Auto Loading Feeder

1 Scope

This part of IEC 60286 describes the possible requirements for paper taping for the Auto Loading Feeder mechanism to mount electronic components without leads or with stump type leads used for electric circuits. This document is applicable to the punched carrier tape with the bottom cover tape (nominal tape width: 8 mm only) among the tapes of Type 1a, and the pressed carrier tape (nominal tape width: 8 mm) of Type 1b in IEC 60286-3.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60286-3:2019, Packaging of components for automatic handling – Part 3: Packaging of surface mount components on continuous tapes