

TECHNICAL REPORT

Guidelines for the use of monitor systems for lead-acid traction batteries

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.220.20

ISBN 978-2-8322-8854-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	4
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Desirable characteristics and features	6
4.1 General.....	6
4.2 Physical location of the monitoring device	6
4.3 State of charge indication or "fuel gauge"	7
4.4 Battery temperature information	7
4.5 High battery temperature warning	7
4.6 Low temperature warning	7
4.7 Electrolyte level indication	7
4.8 Electrolyte level maintenance log.....	7
4.9 Uniformity of cell properties in a battery	8
4.10 Battery commissioning date	8
4.11 Battery configuration	8
5 Evaluation and analysis	8
5.1 State of charge indication or "fuel gauge"	8
5.2 Battery temperature information	8
5.3 Water consumption	9
5.4 Uniformity of cell properties	10
5.5 Electrolyte density	10
5.6 Capacity throughput.....	11
5.7 Battery age	11
5.8 Battery data sheet.....	11
5.9 Communication interfaces.....	12
5.10 Ground faults	12
5.11 Human factors	12
6 Data monitoring – Recommended list of parameters to be monitored.....	13
7 Analysis and evaluation of gathered battery data	14
7.1 Data flow	14
7.2 Prediction of residual operational life	14
Annex A (informative) Example determination of the residual service life of lead-acid traction batteries.....	15
A.1 General.....	15
A.2 Lost capacity due to stress factors	15
A.2.1 Evaluation of the impact of a deep discharge	15
A.2.2 Evaluation of impact of the battery temperature	16
A.2.3 Evaluation of the impact of very high discharge currents.....	17
A.2.4 Evaluation of the impact of the battery being in idle state	17
A.2.5 Calculation of the residual capacity.....	17
A.2.6 Residual number of cycles	18
Figure 1 – Potential data flow in a monitor system	14
Figure A.1 – Example of interrelation between discharge voltages and discharge currents indicating a deep discharge condition.....	16

Table 1 – Residence times and related temperature ranges	9
Table 2 – Temperature warning levels	9
Table 3 – Units and value resolution of measured characteristics	13
Table A.1 – Derating factor due to ageing on standby and idling	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**GUIDELINES FOR THE USE OF MONITOR SYSTEMS
FOR LEAD-ACID TRACTION BATTERIES****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 61431, which is a Technical Report, has been prepared by IEC technical committee 21: Secondary cells and batteries.

This second edition cancels and replaces the first edition, published in 1995. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) The guidelines have been streamlined in terms of technical content and focussed for automatic monitoring systems.

The text of this Technical Report is based on the following documents:

Enquiry draft	Report on voting
21/1044/DTR	21/1053A/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

GUIDELINES FOR THE USE OF MONITOR SYSTEMS FOR LEAD-ACID TRACTION BATTERIES

1 Scope

This document is an informative document relating to aspects of automatic monitor systems as utilized in lead-acid traction battery applications. It lists the characteristics and features that need to be monitored and evaluated to properly assess the operative status of a traction battery. Guidance concerning the accuracy and reliability of the generated information is also provided.

2 Normative references

There are no normative references in this document.