



Edition 2.0 2021-08

TECHNICAL REPORT



Selection guidelines for polymeric materials for outdoor use under HV stress

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.035.20; 29.080.10

ISBN 978-2-8322-4533-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWO	RD	4	
INTRODUCTION			
1 Scop	e	7	
2 Norm	native references	7	
3 Term	is and definitions	8	
	rtant material properties		
4.1	General		
4.2	Resistance to tracking and erosion		
4.3	Arc resistance		
4.4	Water diffusion test (resistance of material to chemical and physical		
	degradation by water)	10	
4.4.1	General	10	
4.4.2	Test specimens	10	
4.4.3	Test procedure	10	
4.4.4	1		
4.5	Tear strength		
4.6	Volume resistivity		
4.7	Breakdown field strength		
4.8	Stress corrosion test (resistance to chemical attack)		
4.8.1	-		
4.8.2			
4.8.3			
4.8.4	•		
4.9	Resistance to weathering and UV procedure		
4.10 4.11	Resistance to flammability procedure Glass transition temperature		
4.11	Hydrophobicity		
4.12			
4.12.			
4.12.			
	rtant properties and minimum requirements of polymeric insulation materials		
	utdoor use under HV stress		
Annex A ((informative) Additional measuring methods	25	
A.1	General		
A.2	Resistance to corona and ozone		
A.3	Resistance to acid attack generated by partial discharge under wet,		
	contaminated, and energization condition	25	
Annex B ((informative) Water immersion test	26	
B.1	General	26	
B.2	Test procedure	26	
Bibliograp	bhy	28	
Figure 1 -	- Example of boiling container for water diffusion test	11	
Figure 2 -	Figure 2 – Electrodes for voltage test		
-	- Voltage test circuit		
Figure 4 – Example of permanent load application for stress corrosion test			

Figure 5 – Definition of glass transition temperature T_{g}	16
Figure 6 – Specimen with adhesive foil	18
Figure 7 – Specimen with pollution layer	19
Figure 8 – Area for the drop application for measurement according to IEC TS 62073 (example for Method A)	21
Figure B.1 – Example of water uptake of two different kinds of materials (MFRP and UFRP)	27

Table 1 – Important properties and minimum requirements of polymeric insulation	
materials for outdoor use under HV stress	22
Table B.1 – Example of dielectric properties in dry conditions and after water	07
immersion for 100 days	27

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SELECTION GUIDELINES FOR POLYMERIC MATERIALS FOR OUTDOOR USE UNDER HV STRESS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 62039 has been prepared by IEC technical committee 112: Evaluation and qualification of electrical insulating materials and systems. It is a Technical Report.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of hydrophobicity definitions and hydrophobicity transfer test;
- b) addition of stress corrosion test.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
112/526/DTR	112/535/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

There is a need within utilities and industry for material standards that define the physical properties of the polymers applied for outdoor insulation. This requirement was identified during discussions in IEC TC 36 and IEC TC 112. As a consequence, in 2001, CIGRE formed the working group D1.14 and later on working groups D1.27, C4.303 and D1.58 with the specific task of defining the physical parameters which are important for the polymeric materials applied in outdoor insulation and developing the relevant test methods, where necessary. As a first step, a state-of-the-art report was issued by CIGRE in Technical Brochure 255. Thirteen properties were identified; standardized test methods and minimum requirements were available for eleven of them. For the remaining property of hydrophobicity retention and recovery, test methods and minimum requirements still need to be defined. This will be the future task of SC D1. This document presents, as a conclusion of the CIGRE report, the important material properties for polymeric materials used in outdoor insulation, where they are applicable, and lists standardized test methods reported in literature (references in the bibliography) are summarized.

SELECTION GUIDELINES FOR POLYMERIC MATERIALS FOR OUTDOOR USE UNDER HV STRESS

1 Scope

This document presents the important material properties of polymeric materials used in outdoor insulation and, where applicable, lists standardized test methods including minimum requirements. If no standardized tests are available, the test methods reported in literature are summarized.

This document is valid for insulating materials having polymeric insulation, which are used in outdoor high voltage electrical applications with a system voltage greater than 1 000 V AC and 1 500 V DC (several tests are only defined for alternating current, which are not applicable for direct current). Such applications are relevant where the housing is an integral part of the device, for example in surge arresters and cable terminations. The scope of this document is limited to the insulation materials only and is not generally intended for coating materials (coating materials are, for example, thin layers applied on toughened glass and ceramic). Some tests mentioned in this document are applicable for coating and are under consideration by CIGRE. The performance of insulators in service depends on several factors such as the type of material, the design and environmental conditions. Consequently, the choice of materials that fulfil the requirements listed in Table 1 is a necessary condition but does not guarantee satisfactory performance when used in outdoor insulation.

In Annex A and Annex B different test methods for testing additional properties are given, which are not standardized.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60243-1, *Electric strength of insulating materials – Test methods – Part 1: Tests at power frequencies*

IEC 60243-2, Electric strength of insulating materials – Test methods – Part 2: Additional requirements for tests using direct voltage

IEC 60455-2, Resin based reactive compounds used for electrical insulation – Part 2: Methods of test

IEC 60587, Electrical insulating materials used under severe ambient conditions – Test methods for evaluating resistance to tracking and erosion

IEC 60695-11-10, Fire hazard testing – Part 11-10: Test flames – 50 W horizontal and vertical flame test methods

IEC 61621, Dry, solid insulating materials – Resistance test to high-voltage, low-current arc discharges

IEC TS 62073, Guidance on the measurement of hydrophobicity of insulator surfaces

IEC 62631-3-1, Dielectric and resistive properties of solid insulating materials – Part 3-1: Determination of resistive properties (DC methods) – Volume resistance and volume resistivity – General method

ISO 34-1, Rubber, vulcanized or thermoplastic – Determination of tear strength – Part 1: Trouser, angle and crescent test pieces

ISO 483, Plastics – Small enclosures for conditioning and testing using aqueous solutions to maintain the humidity at a constant value

ISO 4892-2, Plastics – Methods of exposure to laboratory light sources – Part 2: Xenon-arc lamps

ISO 6721-11, Plastics – Determination of dynamic mechanical properties – Part 11: Glass transition temperature

ISO 11357-2, *Plastics – Differential scanning calorimetry (DSC) – Part 2: Determination of glass transition temperature and step height*

ISO 11359-2, Plastics – Thermomechanical analysis (TMA) – Part 2: Determination of coefficient of linear thermal expansion and glass transition temperature