

TECHNICAL REPORT



Performance of voltage sourced converter (VSC) based high-voltage direct current (HVDC) transmission – Part 1: Steady-state conditions

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.200; 29.240.01

ISBN 978-2-8322-2198-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	10
3.1 Terms and definitions.....	10
3.2 Abbreviated terms.....	11
4 Classifications of VSC HVDC systems	12
4.1 General.....	12
4.2 Symmetrical monopolar HVDC system	12
4.3 Asymmetrical monopolar HVDC system	13
4.3.1 General	13
4.3.2 ASMP with earth return.....	13
4.3.3 ASMP with metallic return.....	13
4.4 Bipolar HVDC system	14
4.4.1 General	14
4.4.2 Bipolar HVDC with earth return.....	14
4.4.3 Rigid bipolar configuration	14
4.4.4 Bipolar HVDC with dedicated metallic return.....	15
4.5 Back-to-back HVDC system	15
4.6 Interface transformer arrangements	15
4.7 Switching and reconfiguration	16
4.7.1 Converter station and DC yard switching	16
4.7.2 Transition station switching.....	17
4.7.3 Connecting multiple converters.....	18
4.7.4 DC gas-insulated metal enclosed switchgear (DC GIS).....	22
5 Environmental information	22
6 Rated power, current and voltage	24
6.1 Rated power	24
6.2 Rated DC current.....	24
6.3 Rated DC voltage.....	25
7 Steady-state operation	25
7.1 General.....	25
7.2 PQ diagram.....	25
7.3 UQ diagram	26
7.4 Reactive power exchange	27
8 Overload and equipment capability	28
8.1 Overload.....	28
8.2 Equipment capability.....	28
8.2.1 General	28
8.2.2 Converter valve capability.....	29
8.2.3 Capability of oil-cooled transformers and dry type reactors	29
8.2.4 Capability of other converter station equipment	29
9 Converter station types and operation modes	29
9.1 Converter station types	29
9.2 Operation modes	31

9.2.1	Reduced direct voltage operation	31
9.2.2	Full direct voltage operation.....	31
9.2.3	Operating sequences.....	31
10	AC system.....	33
10.1	General.....	33
10.2	AC voltage	34
10.2.1	Steady-state voltage range	34
10.2.2	Negative sequence voltage.....	34
10.3	Frequency.....	34
10.3.1	Rated frequency	34
10.3.2	Steady-state frequency range	34
10.3.3	Short-term frequency variation.....	34
10.3.4	Frequency variation during emergency	35
10.4	AC voltage and frequency operation ranges.....	35
10.5	System impedance.....	35
10.6	Positive and zero-sequence surge impedance.....	36
10.7	Other sources of harmonics	36
11	Reactive power.....	36
11.1	General.....	36
11.2	VSC HVDC systems.....	36
12	HVDC transmission line, earth electrode line and earth electrode	37
12.1	General.....	37
12.2	Overhead line(s)	37
12.2.1	General	37
12.2.2	Electrical parameters	37
12.3	Cable(s).....	38
12.3.1	General	38
12.3.2	Electrical parameters	38
12.4	Transmission line combined with overhead line and cable section.....	39
12.5	Electrode line.....	39
12.6	Earth electrode	39
12.7	Gas insulated line	39
13	Reliability	39
14	HVDC control	39
14.1	General.....	39
14.2	Control objectives	40
14.3	Control structure	40
14.3.1	General	40
14.3.2	HVDC bipole/station control.....	41
14.3.3	HVDC pole control	42
14.3.4	Converter and valve control	43
14.4	Measurement.....	43
15	Telecommunication.....	44
15.1	Types of telecommunication links.....	44
15.2	Classification of data to be shared	44
15.3	Fast response telecommunication	44
16	Auxiliary systems.....	45
16.1	General.....	45

16.2	Electrical auxiliary system	45
16.2.1	General	45
16.2.2	Auxiliary power supplies	45
16.2.3	Batteries and uninterruptible power supplies (UPS)	46
16.2.4	Emergency supply	46
16.3	Mechanical auxiliary system.....	47
17	Audible noise.....	48
17.1	General.....	48
17.2	Public nuisance.....	48
17.2.1	Valves and valve coolers	48
17.2.2	Interface transformers	48
17.2.3	Reactors.....	48
17.3	Noise in working areas.....	49
18	AC side harmonics	49
18.1	General.....	49
18.2	Harmonic sources	50
18.2.1	General	50
18.2.2	Converter generated harmonics.....	50
18.2.3	Pre-existing network harmonics	50
18.3	Total harmonic distortion.....	51
19	DC side harmonics	51
19.1	General.....	51
19.2	Coupling between parallel AC and DC circuits	52
20	Power line carrier (PLC) interference.....	53
20.1	General.....	53
20.2	Performance specification	54
21	Radio frequency interference	54
21.1	General.....	54
21.2	RFI from HVDC systems	54
21.2.1	RFI sources	54
21.2.2	RFI propagation.....	55
22	Power losses	55
	Annex A (informative) Fundamental PQ equations of the VSC converter station.....	56
	Annex B (informative) Reactive power exchange of the VSC converter station.....	58
	Bibliography.....	59
	Figure 1 – Symmetrical monopolar VSC HVDC system	13
	Figure 2 – Asymmetrical monopolar VSC HVDC system with earth return	13
	Figure 3 – Asymmetrical monopolar VSC HVDC system with metallic return	13
	Figure 4 – Bipolar VSC HVDC system with earth return	14
	Figure 5 – Rigid bipolar VSC HVDC system	15
	Figure 6 – Bipolar HVDC system with dedicated metallic return	15
	Figure 7 – DC switching of line conductors	17
	Figure 8 – DC switching – Overhead line to cable	18
	Figure 9 – Examples of VSC HVDC system with two converter units per pole	19
	Figure 10 – Example of PQ diagram of the VSC converter	26

Figure 11 – Example of UQ diagram of the VSC converter	27
Figure 12 – Reactive power exchanges of the VSC converter station at PCC	28
Figure 13 – AC/DC converter station types in the U/I diagram	30
Figure 14 – Operating sequence transitions of the VSC HVDC system	32
Figure 15 – Example of the AC grid voltage and frequency operation ranges	35
Figure 16 – Hierarchical structure of an HVDC control system	41
Figure 17 – HVDC pole control	43
Figure 18 – Harmonic contribution by the VSC converter	50
Figure 19 – Amplification of the pre-existing network harmonics	51
Figure 20 – Example of separate AC and DC tower configurations	52
Figure 21 – Example of hybrid AC and DC tower configuration	53
Figure A.1 – Simple configuration of the VSC converter station to AC grid	56
Figure A.2 – Example of power-circle diagrams of the VSC converter	57
Figure B.1 – Simplified equivalent AC grid at PCC of the VSC converter station	58
Table 1 – Information supplied for HVDC substation	22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PERFORMANCE OF VOLTAGE SOURCED CONVERTER (VSC) BASED HIGH-VOLTAGE DIRECT CURRENT (HVDC) TRANSMISSION –

Part 1: Steady-state conditions

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes permitted International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 63363-1 has been prepared by IEC technical committee 115: High Voltage Direct Current (HVDC) transmission for DC voltages above 100 kV and IEC subcommittee 22F: Power electronics for electrical transmission and distribution systems. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
115/281/DTR	115/298/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

A list of all parts in the IEC 63363 series, published under the general title *Performance of voltage sourced converter (VSC) based high-voltage direct current (HVDC) transmission*, can be found on the IEC website.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

High-voltage direct current (HVDC) is an established technology that has been in commercial use for more than 60 years. With the changes in demands due to evolving environmental needs, installation of HVDC systems has increased dramatically in the last 30 years and almost half of the world's HVDC projects were commissioned after the year 2000. HVDC has become a common tool in the design of future global transmission systems.

An HVDC system transmits more electrical power over longer distances than a similar alternating current (AC) transmission system, which means fewer transmission lines are needed, saving both money and land and simplifying approvals. In addition to significantly lowering electrical losses over long distances, HVDC transmission is also very stable and easily controlled, and can stabilize and interconnect AC power networks that are otherwise incompatible. Typically, an HVDC system provides unique or superior capabilities in the following aspects:

- long distance bulk power transmission;
- asynchronous interconnections;
- long distance cable;
- controllability;
- lower losses;
- environmental concerns;
- limitation of short-circuit currents.

The voltage sourced converter (VSC) HVDC transmission system is a new generation of HVDC transmission technology, which can increase the reliability of power grids and provide an alternative to connecting wind farms or solar farms to power grids, providing power to islands, connecting asynchronous grids and building direct current (DC) grids. VSC HVDC can provide:

- independent decoupled control of active and reactive power;
- power supply for weak or even passive networks without a need for AC network to provide commutating voltage;
- simultaneous support of both active and reactive power to the AC power systems, which is beneficial for enhancing system reliability and improving power quality.

Simply due to these technical merits, the market demand for VSC HVDC transmission technology is spreading widely over the world. VSC HVDC has been selected for a number of transmission projects aimed at exchanging energy between areas and connection of remote renewable energy sources such as offshore wind farms to onshore.

With the fast development of the VSC HVDC power transmission industry, IEC standardization work has been carried out accordingly. Up to the time of writing, more than four IEC documents, related to VSC DC equipment and systems have been published. Among these, IEC 62747, IEC TR 62543, IEC 62501, and the IEC TS 62751 series provide essential information for the design and operation of VSC HVDC transmission systems.

This document provides, as a supplement to above publications, a basic guide in VSC HVDC transmission system design and operation.

This document is part one of a series of three intended technical reports, covering steady-state performance, while parts two and three (yet to be published) are intended to cover transient performance and dynamic performance, respectively.

PERFORMANCE OF VOLTAGE SOURCED CONVERTER (VSC) BASED HIGH-VOLTAGE DIRECT CURRENT (HVDC) TRANSMISSION –

Part 1: Steady-state conditions

1 Scope

The objective of this Technical Report is to present the "state of the art" with respect to general guidance on the steady-state performance demands of VSC HVDC transmission systems. It concerns the steady-state performance of two-terminal VSC HVDC transmission systems utilizing converters with power flow capability in both directions.

Different configurations of a VSC HVDC transmission system are covered in this document, including the symmetrical monopolar, asymmetrical monopolar, bipolar with earth return, bipolar with dedicated metallic return and rigid bipolar configurations.

There are many variations between different VSC HVDC transmission systems. This document does not consider these in detail; consequently, it cannot be used directly as a specification for a particular project, but rather to provide the general basis for the system steady-state performance demands.

Normally, the performance specifications are based on a complete system including two VSC HVDC converter stations. However, sometimes a VSC HVDC transmission system can also be separately specified and purchased from multiple vendors instead of single turnkey vendor. In such cases, due consideration can be given to the coordination of each part with the overall VSC HVDC system performance objectives and the interface of each with the system can be clearly defined. The major components of the VSC HVDC transmission system are presented in IEC 62747.

Referring to IEC 62747, an HVDC substation/converter station is defined as that part of the VSC HVDC transmission system which consists of one or more VSC converter units installed in a single location together with buildings, reactors, filters, reactive power supply, control, monitoring, protective, measuring and auxiliary equipment. The AC substations are not covered in this document.

This document provides guidance and supporting information on the procedure for system design and the technical issues involved in the system design of VSC HVDC transmission projects for both owners and contractors. This document can be used as the basis for drafting a procurement specification and as a guide during project implementation.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62747:2014, *Terminology for voltage-sourced converters (VSC) for high-voltage direct current (HVDC) systems*
IEC 62747:2014/AMD1:2019