



Edition 1.0 2023-06

TECHNICAL SPECIFICATION



Fire hazard testing – Part 2-21: Glowing/hot-wire based test methods – Fire containment test on finished units

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 13.220.40

ISBN 978-2-8322-7122-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOR	FOREWORD4				
INTF	INTRODUCTION				
1	Scop	e	7		
2	Norn	native references	7		
3	Term	is and definitions	8		
4	Test	specimen	9		
4	.1	General	9		
4	.2	Verification of potential ignition sources	9		
4	.3	Test conditions	. 10		
5	Test	apparatus	. 10		
5	.1	Nickel-Chromium wire (NiCr wire)	. 10		
5	.2	Test circuit	. 10		
5	.3	Connections	. 10		
5	.4	Cheesecloth	. 10		
5	.5	Test chamber	. 10		
5	.6	Timing device	.11		
6	Verif	ication of the NiCr wire	.11		
7	Cond	Jitioning	.11		
7	.1	Conditioning of the test specimen	.11		
7.	.2	Conditioning of the cheesecloth	.11		
7.	.3	Testing condition	.11		
8	Test	procedure	.11		
8	.1	Flow chart	.11		
8	.2	Identification of potential ignition sources	.13		
8	.3	Factors affecting test	. 14		
8	.4	Application of NiCr wire	. 14		
8	.5	Selection of NiCr wire application methodology	. 15		
8	.6	Potential ignition source verification	.16		
-	.7	Test specimen fire containment verification			
9	Obse	ervations and measurements	.18		
9	.1	Initial observations	. 18		
-	.2	Test observations			
10	Eval	uation of test results	. 18		
11	Test	report	. 19		
12	Infor	mation to be given in the relevant product standard	.19		
Anne	ex A	(normative) Interpretations of the location of the cylindrical volume	.20		
Anne	ex B	(normative) NiCr wire application methods – Internal coil winding method	.21		
В	.1	General	.21		
В	.2	Insulating material cavity preparation	.21		
В	.3	NiCr wire coil preparation	.21		
Annex C (normative) NiCr wire application methods – External winding method					
С	.1	General	.24		
С	.2	Insulated connections winding method	.24		
С	.3	Non-insulated connections winding method	.25		
С	.4	Examples of electrical connections applying the external winding method	.26		

IEC TS 60695-2-21:2023 © IEC 2023 - 3 -

C.4.1	General	26
C.4.2	Insulated terminals providing mechanical support function	
C.4.3	Insulated terminals with one side not accessible	
Annex D (ir	nformative) Examples of supply wires fixation methodologies	28
D.1 C	General	28
D.2 F	ixation over existing electrical connection supply harness	28
D.3 F	ixation over surrounding parts	28
Bibliograph	y	. 30
Figure 1 –	Test procedure flow-chart	. 12
•	' Insulating material cavity cross sectional dimensions	
	NiCr wire application methodology selection flow-chart	
-	– Examples of the location of the cylindrical volume	
Figure B.1	– Winding tool	. 22
Figure B.2	– Example 1 of NiCr wire coil application	23
Figure B.3	 Example 2 of NiCr wire coil application 	.23
Figure B.4	 Example 3 of NiCr wire coil application 	.23
Figure C.1	 Single connection insulating material external winding – Side View 	24
Figure C.2	 Single connection insulating material external winding – Front view 	25
Figure C.3	 Example of non-insulated single terminal electrical connection 	26
Figure C.4	 Example of insulated terminals providing mechanical support function 	26
Figure C.5	 Example of insulated terminal with one side not accessible 	27
Figure D.1	 Fixation over existing harness by stripe 	. 28
Figure D.2	 Fixation over surrounding parts by adhesive tape – Side view 	29
Figure D.3	 Fixation over surrounding parts by adhesive tape – Top view 	29
Table B.1 -	- Drill bit and winding tool dimensions	22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIRE HAZARD TESTING –

Part 2-21: Glowing/hot-wire based test methods – Fire containment test on finished units

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 60695-2-21 has been prepared by IEC technical committee 89: Fire hazard testing. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
89/1554/DTS	89/1561A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

IEC TS 60695-2-21:2023 © IEC 2023 - 5 -

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This publication has the status of a Technical Specification in accordance with IEC Guide 104 and ISO/IEC Guide 51.

NOTE The following print types are used:

• terms defined in Clause 3: in **bold** type.

A list of all parts in the IEC 60695 series, published under the general title *Fire hazard testing*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Fires might create hazards to life and property as a result of the generation of heat (emission of heat on fire hazard), and also as a result of the production of toxic effluent, corrosive effluent and smoke (fire effluents on the fire hazard). Fires start with ignition and then can grow, leading in some cases to flash-over and a fully developed fire. Resistance to ignition is therefore one of the most important parameters of a material to be considered in the assessment of a fire hazard.

Most current fire hazard assessment techniques evaluate the resistance to ignition characteristics of a single material or component. These assessment techniques are able to drive the preselection and validation of materials and components but are not able to evaluate the possible interaction of materials or components in a complex environment such as in a finished unit, once a fire event is initiated.

In a fault condition, a finished unit might be subject to the overheating of electrical connections and contacts. Such overheating can be caused by corrosion, poor crimp connections, incorrect assembly, erosion of contact surfaces, or mechanical fatigue. Insulating materials that are overheated can ignite and cause fire.

It is difficult to simulate the actual conditions of potential faults in finished units; therefore all possible fire hazards should be taken into account at the design stage and subsequently during the preselection of materials and components.

This fire containment test has been developed to verify if a finished unit is able to contain an internal fire event, generated by combustible parts ignited by a simulated overheated electrical connection.

FIRE HAZARD TESTING –

Part 2-21: Glowing/hot-wire based test methods – Fire containment test on finished units

1 Scope

This part of IEC 60695, which is a Technical Specification, specifies a **fire** containment test method for **finished units**. It is intended to verify the capability of containing of a fire event generated by an **effective ignition source** inside a **finished unit**.

Unless otherwise specified by the relevant product standard, determination of the **fire** containment described in this document does not apply to any of the following:

- A single electrical component;
- A single electrical component when incorporated into a finished unit;
- Electrical installation products such as distribution boards, circuit protection devices, switchgear, controlgear, cable management system and electrical accessories (wiring devices).

The test method described in this document does not apply to the following electrical connections:

- Low-power electrical connections contained in **finished units**, where the maximum power through the connection does not exceed 15 W.
- Soldered and welded electrical connections are exempted from the evaluations of this document.

This document is intended to be used for evaluating the capability of **fire** containment of **finished units**, during the selection of **finished units** and in the design of **finished units**.

The requirements, test method or test conditions of this document will not apply unless specifically referred to or included in the relevant publications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62368-1:2018, Audio/video, information and communication technology equipment – Part 1: Safety requirements

ISO 13943:2017, Fire safety – Vocabulary