

Edition 1.0 2021-08

TECHNICAL SPECIFICATION

Opportunity charging of lead-acid traction batteries

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.220.20; 29.220.99

ISBN 978-2-8322-4760-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOF	REWO	PRD	3
INTI	RODU	JCTION	5
1	Scop	pe	6
2	Norm	native references	6
3	Terms and definitions		
4	Plan	ning the implementation of opportunity charging	7
5	Oper	rational procedures	8
5	5.1	General	8
5	5.2	Charging conditions	8
5	5.3	Regular charges	8
5	5.4	Ventilation	9
5	5.5	Temperature	9
5	5.6	Examples of discharge and charge profiles	9
Bibl	iograp	phy	12
Figu	ıre 1 -	- Examples of discharge and charge profiles of vented lead-acid batteries	10
		- Example of discharge and charge profiles of valve regulated lead-acid	11

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPPORTUNITY CHARGING OF LEAD-ACID TRACTION BATTERIES

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61044 has been prepared by IEC technical committee 21: Secondary cells and batteries. It is a Technical Specification.

This first edition cancels and replaces the second edition of IEC TR 61044 published in 2002. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the recommended depth of discharge for opportunity charging has been adjusted;
- b) a distinction is made between valve regulated lead-acid batteries (VRLA) and vented lead-acid batteries.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
21/1081/DTS	21/1088/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

Lead-acid traction batteries find a widespread application in industrial transportation vehicles because of their particular properties of providing a reliable power supply source with a very low environmental impact.

In such applications, both monitoring and power management by electronic means have made great strides not only on the discharge side of the energy balance but during charging as well.

This progress permits refuelling, i.e., charging of a lead-acid traction battery in a well-controlled manner during idle periods in the course of a working schedule.

As a result, the total capacity or ampere-hour output of the lead-acid battery increases per working day substantially beyond the manufacturer's maximum recommended value.

However, such opportunity charging will provide improved capital efficiency only if adequate precautions are taken to prevent premature deterioration of the state of the lead-acid traction battery caused by such a practice.

This document is intended to present requirements, derived from the field experience of battery manufacturers in general and from opportunity charging of lead-acid traction batteries in particular, with the aim of preventing detrimental effects on batteries and industrial equipment.

OPPORTUNITY CHARGING OF LEAD-ACID TRACTION BATTERIES

1 Scope

This document covers opportunity charging of lead-acid traction batteries, i.e., the use of idle time during a working period to increase the state of charge (SoC) so as to extend the daily working period of a lead-acid traction battery while at the same time avoiding an excessive depth of discharge.

This document specifies requirements for the use of opportunity charging of lead-acid traction batteries of vented and valve regulated types when the battery manufacturer has not provided alternative specific operating procedures.

This document is only applicable for lead-acid traction batteries of vented and valve regulated design for which the battery manufacturer has not provided specific operating procedures.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62485-3:2014, Safety requirements for secondary batteries and battery installations – Part 3: Traction batteries