

TECHNICAL SPECIFICATION



**Electric vehicles conductive charging system –
Part 3-7: DC EV supply equipment where protection relies on double or
reinforced insulation – Battery system communication**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 43.120

ISBN 978-2-8322-5736-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|---|----|
| FOREWORD..... | 8 |
| INTRODUCTION..... | 10 |
| 1 Scope..... | 11 |
| 2 Normative references | 11 |
| 3 Terms and definitions | 11 |
| 4 Symbols and abbreviated terms..... | 12 |
| 5 Operating principles | 12 |
| 5.1 General..... | 12 |
| 5.2 Battery system specific FSA..... | 12 |
| 5.3 State definitions | 13 |
| 5.4 Transitions in the FSA for battery systems | 13 |
| 6 Object dictionary..... | 14 |
| 6.1 General..... | 14 |
| 6.2 Additional definitions to general application objects | 15 |
| 6.2.1 General | 15 |
| 6.2.2 Object 6001 _h : Control word | 15 |
| 6.2.3 Object 6002 _h : Status word..... | 15 |
| 6.3 Detailed complex data type specifications | 15 |
| 6.3.1 General | 15 |
| 6.3.2 Object 0081 _h to 0082 _h : Reserved..... | 16 |
| 6.3.3 Object 0083 _h : Ni-MH charging rules parameter record..... | 16 |
| 6.4 Produced application objects | 16 |
| 6.4.1 General | 16 |
| 6.4.2 Object 6100 _h : Type of battery cells..... | 16 |
| 6.4.3 Object 6102 _h : Battery system rated Wh capacity (optional) | 20 |
| 6.4.4 Object 6105 _h : Battery system temperature | 22 |
| 6.4.5 Object 6126 _h : Battery system maximum cell voltage (optional, mandatory for rental/swap battery systems)..... | 25 |
| 6.4.6 Object 6127 _h : Battery system minimum cell voltage (optional, mandatory for rental/swap battery systems)..... | 27 |
| 6.4.7 Object 6160 _h : Actual battery system Wh capacity | 28 |
| 6.4.8 Object 6162 _h : Full EMS output battery system Wh capacity (optional, mandatory for rental/swap battery systems)..... | 30 |
| 6.4.9 Object 6164 _h : Relative battery system Wh capacity (SOC) (optional) | 32 |
| 6.4.10 Object 6192 _h : Reserved | 34 |
| 6.4.11 Object 6193 _h : Threshold time of the battery system maximum charging time | 34 |
| 6.5 Produced application objects (optional)..... | 35 |
| 6.5.1 General | 35 |
| 6.5.2 Object 6101 _h : Battery system connecting status (optional) | 35 |
| 6.5.3 Object 6103 _h : Battery system rated Ah capacity (optional) | 38 |
| 6.5.4 Object 6104 _h : Battery system number of cells (optional)..... | 39 |
| 6.5.5 Object 6106 _h : Battery system lifetime (optional) | 41 |

| | | |
|--------|---|----|
| 6.5.6 | Object 6107 _h : Battery system lifetime in cycles (optional)..... | 42 |
| 6.5.7 | Object 6108 _h : Battery system lifetime EMS input capacity (optional) | 44 |
| 6.5.8 | Object 6109 _h : Battery system manufacturer (optional)..... | 45 |
| 6.5.9 | Object 610A _h : Battery system cell manufacturer (optional) | 47 |
| 6.5.10 | Object 610B _h : Battery system cell notation (optional) | 48 |
| 6.5.11 | Object 6120 _h : Battery system maximum charge start temperature (optional)..... | 49 |
| 6.5.12 | Object 6121 _h : Battery system minimum charge start temperature (optional)..... | 51 |
| 6.5.13 | Object 6122 _h : Battery system maximum discharge temperature (optional)..... | 53 |
| 6.5.14 | Object 6123 _h : Battery system minimum discharge temperature (optional)..... | 54 |
| 6.5.15 | Object 6124 _h : Battery system maximum temperature for storage (optional)..... | 56 |
| 6.5.16 | Object 6125 _h : Battery system minimum temperature for storage (optional)..... | 58 |
| 6.5.17 | Object 6161 _h : Actual battery system Ah capacity (optional) | 59 |
| 6.5.18 | Object 6163 _h : Full EMS output battery system Ah capacity (optional) | 61 |
| 6.5.19 | Object 6165 _h : Battery system VDN 1 actual cell voltage (optional) | 62 |
| 6.5.20 | Object 6166 _h to 6174 _h : Battery system VDN 2 to 16 actual cell voltage (optional)..... | 64 |
| 6.5.21 | Object 6175 _h : Battery system balance (optional) | 64 |
| 6.5.22 | Object 6176 _h : Battery system SOH (optional) | 65 |
| 6.5.23 | Object 6177 _h : Battery system EMS output time (optional)..... | 67 |
| 6.5.24 | Object 6178 _h : Battery system EMS input time (optional)..... | 69 |
| 6.5.25 | Object 6179 _h : Battery system EMS output Ah counter (optional) | 70 |
| 6.5.26 | Object 617A _h : Battery system EMS input Ah counter (optional) | 72 |
| 6.5.27 | Object 617B _h : Battery system EMS output Wh counter (optional) | 74 |
| 6.5.28 | Object 617C _h : Battery system EMS input Wh counter (optional) | 75 |
| 6.5.29 | Object 617D _h : Battery system EMS output counter (optional) | 77 |
| 6.5.30 | Object 617E _h : Battery system EMS input counter (optional) | 79 |
| 6.5.31 | Object 617F _h : Battery system deep discharging counter (optional) | 80 |
| 6.5.32 | Object 6180 _h : Battery system short-circuit counter (optional) | 82 |
| 6.5.33 | Object 6181 _h : Battery system over-temperature counter (optional) | 83 |
| 6.5.34 | Object 6182 _h : Temperature dependent average EMS output current (optional)..... | 85 |
| 6.5.35 | Object 6183 _h : Temperature dependent peak EMS output current (optional)..... | 86 |
| 6.5.36 | Object 6184 _h : Temperature dependent average EMS input current (optional)..... | 87 |
| 6.5.37 | Object 6185 _h : Temperature dependent peak EMS input current (optional)..... | 88 |
| 6.5.38 | Object 6186 _h : Temperature dependent capacity correction (optional) | 89 |

| | | |
|----------|--|-----|
| 6.5.39 | Object 6187 _h : Battery system capacity dependent current correction (optional) | 90 |
| 6.5.40 | Object 6188 _h : Battery system temperature dependent self-discharge rate (optional) | 92 |
| 6.5.41 | Object 6189 _h : Temperature dependent cell charge maximum voltage (optional) | 93 |
| 6.5.42 | Object 618A _h : Battery system 100 % to 90 % capacity dependent voltage correction (optional) | 94 |
| 6.5.43 | Object 618B _h : Battery system 0 % to 10 % capacity dependent voltage correction (optional) | 95 |
| 6.5.44 | Object 618C _h : Battery system point of cell balancing (optional) | 96 |
| 6.6 | Consumed application objects | 98 |
| 6.6.1 | General | 98 |
| 6.6.2 | Object 618F _h : EMS output rules for Ni-MH battery system (optional) | 98 |
| 6.6.3 | Object 618D _h : Battery system go to deep sleep mode timing (optional) | 101 |
| 6.6.4 | Object 618E _h : Battery system minimal SOC for go to deep sleep mode (optional) | 103 |
| 6.6.5 | Object 6190 _h : Battery system specific controls (optional) | 104 |
| | | |
| Figure 1 | – FSA for battery system | 13 |
| Figure 2 | – Value structure | 16 |
| Figure 3 | – Object structure | 36 |
| Figure 4 | – Object structure | 39 |
| | | |
| Table 1 | – States behaviour | 13 |
| Table 2 | – Transitions, events and actions | 14 |
| Table 3 | – Value definition | 15 |
| Table 4 | – Value definition for VD specific FSA control | 15 |
| Table 5 | – Value definition for virtual device FSA state | 15 |
| Table 6 | – Ni-MH charging rules parameter record | 16 |
| Table 7 | – Value definition | 17 |
| Table 8 | – Object description | 18 |
| Table 9 | – Entry description | 19 |
| Table 10 | – Object description | 20 |
| Table 11 | – Entry description | 21 |
| Table 12 | – Grouping of sub-indices | 22 |
| Table 13 | – Object description | 23 |
| Table 14 | – Entry description | 23 |
| Table 15 | – Object description | 25 |
| Table 16 | – Entry description | 26 |
| Table 17 | – Object description | 27 |
| Table 18 | – Entry description | 27 |
| Table 19 | – Object description | 29 |
| Table 20 | – Entry description | 29 |
| Table 21 | – Object description | 30 |

Table 22 – Entry description 31

Table 23 – Value definition 32

Table 24 – Object description 32

Table 25 – Entry description 33

Table 26 – Entry description 34

Table 27 – Entry description 35

Table 28 – Value definition 36

Table 29 – Object description 36

Table 30 – Entry description 37

Table 31 – Object description 38

Table 32 – Entry description 38

Table 33 – Value definition for the parallel and series cell number fields..... 40

Table 34 – Object description 40

Table 35 – Entry description 40

Table 36 – Object description 41

Table 37 – Entry description 42

Table 38 – Object description 43

Table 39 – Entry description 43

Table 40 – Object description 44

Table 41 – Entry description 44

Table 42 – Object description 46

Table 43 – Entry description 46

Table 44 – Object description 47

Table 45 – Entry description 47

Table 46 – Object description 48

Table 47 – Entry description 49

Table 48 – Object description 50

Table 49 – Entry description 50

Table 50 – Object description 51

Table 51 – Entry description 52

Table 52 – Object description 53

Table 53 – Entry description 53

Table 54 – Object description 55

Table 55 – Entry description 55

Table 56 – Object description 56

Table 57 – Entry description 56

Table 58 – Object description 58

Table 59 – Entry description 58

Table 60 – Object description 59

Table 61 – Entry description 60

Table 62 – Object description 61

Table 63 – Entry description 61

Table 64 – Object description 63

| | |
|---|----|
| Table 65 – Entry description | 63 |
| Table 66 – Index assignments for battery system 2 to 16 | 64 |
| Table 67 – Value definition | 64 |
| Table 68 – Object description | 64 |
| Table 69 – Entry description | 65 |
| Table 70 – Value definition | 66 |
| Table 71 – Object description | 66 |
| Table 72 – Entry description | 66 |
| Table 73 – Object description | 67 |
| Table 74 – Entry description | 68 |
| Table 75 – Object description | 69 |
| Table 76 – Entry description | 69 |
| Table 77 – Object description | 71 |
| Table 78 – Entry description | 71 |
| Table 79 – Object description | 72 |
| Table 80 – Entry description | 73 |
| Table 81 – Object description | 74 |
| Table 82 – Entry description | 74 |
| Table 83 – Object description | 76 |
| Table 84 – Entry description | 76 |
| Table 85 – Object description | 77 |
| Table 86 – Entry description | 77 |
| Table 87 – Object description | 79 |
| Table 88 – Entry description | 79 |
| Table 89 – Object description | 80 |
| Table 90 – Entry description | 81 |
| Table 91 – Object description | 82 |
| Table 92 – Entry description | 82 |
| Table 93 – Object description | 84 |
| Table 94 – Entry description | 84 |
| Table 95 – Object description | 85 |
| Table 96 – Entry description | 86 |
| Table 97 – Object description | 86 |
| Table 98 – Entry description | 87 |
| Table 99 – Object description | 87 |
| Table 100 – Entry description | 88 |
| Table 101 – Object description..... | 88 |
| Table 102 – Entry description | 89 |
| Table 103 – Object description..... | 89 |
| Table 104 – Entry description | 90 |
| Table 105 – Sub-index relation to capacity range..... | 90 |
| Table 106 – Value definition..... | 91 |
| Table 107 – Object description..... | 91 |

Table 108 – Entry description 91

Table 109 – Object description..... 92

Table 110 – Entry description 92

Table 111 – Object description..... 93

Table 112 – Entry description 93

Table 113 – Value definition..... 94

Table 114 – Object description..... 94

Table 115 – Entry description 94

Table 116 – Value definition..... 95

Table 117 – Object description..... 95

Table 118 – Entry description 96

Table 119 – Object description..... 96

Table 120 – Entry description 97

Table 121 – Object description..... 99

Table 122 – Entry description 99

Table 123 – Object description..... 102

Table 124 – Entry description 102

Table 125 – Value definition..... 103

Table 126 – Object description..... 103

Table 127 – Entry description 103

Table 128 – Value definition..... 105

Table 129 – Object description..... 105

Table 130 – Entry description 106

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –**Part 3-7: DC EV supply equipment where protection
relies on double or reinforced insulation –
Battery system communication**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61851-3-7 has been prepared by IEC technical committee 69: Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

| | |
|------------|-------------------------------|
| Draft | Report on voting |
| 69/653/DTS | 69/674/RVDTS 69/674A/RVDTS |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The following print types are used:

- requirements: in roman type;
- notes: in small roman type;
- **text formatted in bold and using mixed capital and underline are used as state names and are not to be translated.**

A list of all parts in the IEC 61851 series, published under the general title *Electric vehicles conductive charging system*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This document is published in separate parts according to the following structure:

IEC TS 61851-3-1, *Electric vehicles conductive charging system – Part 3-1: DC EV supply equipment where protection relies on double or reinforced insulation – General rules and requirements for stationary equipment*

IEC TS 61851-3-2, *Electric vehicles conductive charging – Part 3-2: DC EV supply equipment where protection relies on double or reinforced insulation – Particular requirements for portable and mobile equipment*

IEC TS 61851-3-4, *Electric vehicles conductive charging system – Part 3-4: DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

IEC TS 61851-3-5, *Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects*

IEC TS 61851-3-6, *Electric vehicles conductive charging system – Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication*

IEC TS 61851-3-7, *Electric vehicles conductive charging system – Part 3-7: DC EV supply equipment where protection relies on double or reinforced insulation – Battery system communication*

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-7: DC EV supply equipment where protection relies on double or reinforced insulation – Battery system communication

1 Scope

This part of IEC 61851, which is a Technical Specification, applies to CANopen communication for the conductive transfer of electric power between the supply network and an electric road vehicle or a removable RESS or traction-battery of an electric road vehicle.

This document specifies application objects provided by the battery system.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 61851-3-4:2023 *Electric vehicles conductive charging system – DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

IEC TS 61851-3-5:2023 *Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects*

EN 50325-4:2002, *Industrial communications subsystem based on ISO 11898 (CAN) for controller- device interfaces – Part 4: CANopen*

EN 50604-1:2016, *Secondary lithium batteries for light EV (electric vehicle) applications – Part 1: General safety requirements and test methods*