



TECHNICAL SPECIFICATION

**Nanomanufacturing – Key control characteristics –
Part 7-2: Nano-enabled photovoltaics – Device evaluation method for indoor
light**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 07.120; 07.030; 27.160

ISBN 978-2-8322-7255-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Abbreviated terms	9
5 Methods for measuring current-voltage characterization	10
5.1 General.....	10
5.2 Requirements	10
5.2.1 Device under test (DUT).....	10
5.2.2 Illumination adjustment.....	10
5.2.3 Measurement procedure	11
5.3 Important additional information.....	13
6 Indoor reference photovoltaic cells	14
6.1 Requirements	14
6.1.1 Selecting indoor reference photovoltaic cells	14
6.1.2 Calibrating indoor reference photovoltaic cells.....	14
6.2 Important notes.....	15
7 Standard indoor light – Requirements.....	16
7.1 Standard indoor illuminance.....	16
7.2 Standard indoor light.....	16
7.3 Spectral irradiance of standard indoor light	16
8 Traceability.....	19
8.1 Description – General	19
8.2 Calibration chain example.....	19
9 Temperature correction	20
9.1 Requirements	20
9.2 Temperature of the DUT	20
10 Spectral-mismatch correction	20
10.1 Requirements	20
10.1.1 Indoor reference photovoltaic-cell method	20
10.1.2 Recording results.....	21
10.2 Important additional information.....	21
11 Spectral responsivity	21
11.1 Requirements	21
11.1.1 Spectral responsivity, $S(\lambda)$	21
11.1.2 Measurement methods	21
11.2 Important notes.....	21
12 Illumination sources.....	22
12.1 Requirements	22
12.1.1 Indoor spectral coincidence	22
12.1.2 Illuminance non-uniformity.....	22
12.1.3 Temporal stability	23
12.1.4 Light source classification.....	23
12.1.5 Indoor standard relative spectral responsivity	23

12.2	Illuminance non-uniformity	35
13	Nonlinearity	35
13.1	Requirements	35
13.2	Important notes	35
Annex A (informative) Explanations of the provisions, descriptions, and other content in the standard main body of this document		36
A.1	Purpose of this document	36
A.2	Target of this document	36
A.3	Issues discussed during deliberation.....	36
A.3.1	Adjusting light intensity with an illuminometer	36
A.3.2	Indoor spectral coincidence	36
A.3.3	Stability of a DUT (5.2.2)	37
A.3.4	Maximum power (P_{max}).....	37
A.4	Supplemental remarks on requirements	38
A.4.1	Requirements for the DUTs (5.2.1)	38
A.4.2	Standard indoor light (Clause 7)	38
A.4.3	Methods for adjusting illuminance (5.2.2).....	39
A.4.4	Quasi-reference photovoltaic cell.....	42
A.4.5	Standard indoor light (7.1, 7.2)	42
A.4.6	Spectral responsivity (11.1.2)	42
A.4.7	Illumination source and indoor spectral coincidence (12.1.1)	43
A.4.8	Illumination sources and non-uniformity of brightness (12.1.2).....	44
A.4.9	Temporal stability (12.1.3)	44
A.4.10	Classification of illumination sources (12.1.5)	44
A.4.11	Nonlinearity (13.1)	45
A.5	Correspondence between this document and the IEC 60904 series	45
Bibliography.....		47
Figure 1 – Spectral irradiance of standard indoor light at 1 000 lx		19
Figure 2 – Calibration chain example		20
Figure 3 – Standard relative spectral responsivity		34
Figure A.1 – Configurations of illuminance adjusting methods described in a) A.4.3.2, b) A.4.3.3 and c) A.4.3.4		39
Figure A.2 – PRISM or spectroradiometer method		40
Figure A.3 – Measurement laboratories.....		41
Figure A.4 – Temporal fluctuation of illuminance of a fluorescent lamp		44
Table 1 – Standard indoor illuminance		12
Table 2 – Result record.....		13
Table 3 – Calibration record.....		15
Table 4 – Spectral irradiance ($mW/m^2/nm$) of standard indoor light at 1 000 lx		16
Table 5 – Light source classification		23
Table 6 – Indoor standard relative spectral responsivity (%)		24
Table A.1 – Spectral coincidence of F to reference spectrum CIE FL10		42
Table A.2 – Spectral coincidence of L to reference spectrum CIE LED-B4		42
Table A.3 – Correspondence between clauses of this document and IEC 60904		46
Table A.4 – New concepts in this document derived from IEC 60904		46

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**NANOMANUFACTURING –
KEY CONTROL CHARACTERISTICS –**
**Part 7-2: Nano-enabled photovoltaics –
Device evaluation method for indoor light**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 62607-7-2 has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
113/710/DTS	113/737/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC TS 62607 series, published under the general title *Nanomanufacturing – Key control characteristics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- transformed into an International Standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

Commercialization of nano-enabled solar cells, such as organic solar cells, is being promoted by utilizing their advantages over conventional solar cells, such as light weight, flexibility, colour, transparency, and coating processability. Energy harvesting applications that generate power using indoor light have been recognized as important applications for nano solar cells in conjunction with recent advances in the Internet of Things. In general, nano solar cells have a large band gap and are suitable for power generation under indoor lighting whose spectra are localized in the visible light region. In addition, since the low illuminance characteristics can be improved by devising the configuration, it is expected to be suitable for energy harvesting using indoor light.

The IEC 60904 series specifies evaluation methods for sunlight. In IEC 60904, the most important factors in evaluating a solar cell are the selection of a light source and the method of adjusting its irradiance for measurement. By changing the light source from sunlight to indoor light, an evaluation method under indoor light can be obtained. The clause structure of this document corresponds to that of IEC 60904. While light sources are limited to sunlight in the outdoor environment, various light sources are used indoors, such as fluorescent lamps and LED lamps in addition to sunlight. The indoor brightness is expressed by illuminance in lux (lx), which takes into account the sensitivity of the human eye. Strictly speaking, since the spectral characteristics of the eyes are different from those of solar cells, there is not always a correlation between the illuminance and the power generation of solar cells. For example, a crystalline Si solar cell could generate power using only near-infrared light which is invisible to human eyes, i.e. zero lux. However, high-efficiency lighting other than incandescent lamps has a spectrum concentrated in the visible light region, thus expressing the efficiency of an indoor solar cell based on the spectrum of sunlight is not appropriate.

In this document, such uncertainties due to the use of illuminance instead of irradiance are eliminated by setting a reference spectrum for indoor light sources. The reference indoor light spectra are representatives of the spectrum of light sources used for indoor lighting, are defined only between 380 nm and 780 nm, and have no component outside of this wavelength range. Therefore, this document provides a method to evaluate solar cells with illuminance. Since the illuminance is obtained by the overlap integral of the spectral irradiance of the light source and the luminosity, there could be an infinite number of spectral irradiances that give the same illuminance. A large error could arise due to light in the wavelength region with low luminosity. In an extreme case, invisible light has a finite output even at zero illuminance. In this document, however, the output by zero lux illuminance is supposed to be zero, that is, the output is not guaranteed.

The target of this document is to define the output of a solar cell in a bright (finite illuminance) indoor environment. The output with light other than the reference spectrum is out of this target. If it is necessary to include such cases, they will be treated as individual cases. In that case, one would extend the reference spectrum and build an evaluation technique that uses irradiance instead of illuminance. Special illumination conditions can be used by using a user-defined reference spectrum. In this case, however, illuminance can be meaningless if the illumination contains a significant amount of invisible light.

Illumination includes not only the light that the eyes of humans are sensitive to, but also the infrared energy contained in incandescent lighting and sunlight that enters from outdoors. But because incandescent lighting is used less and less due to its poor energy efficiency, this document defines measurement methods with two standard indoor light sources specified by CIE: FL10 and LED-B4, corresponding to the fluorescent lamp and the white LED lamp, respectively, the correlated colour temperatures (CCT) of which are approximately 5 000 K. Other light sources such as sunlight or incandescent lamps are not appropriate because they contain much invisible infrared light and illuminance is not a good measure for performance evaluation of photovoltaic devices, because they contain a significant amount of invisible light.

This document, along with FL10 and LED-B4, establishes methods for evaluating photovoltaic cells under indoor conditions. This document assumes that an arbitrary photovoltaic cell will be measured under indoor lighting. For requirements not listed in this document, refer to the relevant normative references.

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 7-2: Nano-enabled photovoltaics – Device evaluation method for indoor light

1 Scope

This Technical Specification specifies the efficiency testing of photovoltaic cells (excluding multi-junction cells) under indoor light. Although it is primarily intended for nano-enabled photovoltaic cells (organic thin-film, dye-sensitized solar cells (DSC), and Perovskite solar cells), it can also be applied to other types of photovoltaic cells, such as Si, CIGS, GaAs cells, and so on.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

JIS C 1609-1, *Illuminance meters – Part 1: General measuring instruments*

DIN 5032-7, *Photometry – Part 7: Classification of illuminance meters and luminance meters*

ISO/CIE 19476, *Characterization of the performance of illuminance meters and luminance meters*