



TECHNICAL SPECIFICATION



**Flexible display devices –
Part 5-4: Measuring method of blur in flexible transparent displays**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120

ISBN 978-2-8322-6928-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms, definitions and abbreviated terms	5
3.1 Terms and definitions.....	5
3.2 Abbreviated terms.....	5
4 Measuring conditions.....	6
4.1 Standard measuring environmental conditions	6
4.2 Standard darkroom conditions.....	6
4.3 Standard setup conditions.....	6
4.3.1 Display mounting	6
4.3.2 Measuring configuration	6
4.3.3 Starting conditions of measurements	7
4.3.4 Conditions of measuring equipment.....	7
5 Blur caused by a flexible transparent display	8
5.1 Purpose	8
5.2 Measuring conditions	9
5.3 Measuring method	9
Annex A (informative) Example of blur measurement configuration	13
A.1 Purpose	13
A.2 Examples of parameters in blur measurement.....	13
Bibliography.....	16
Figure 1 – Geometric configuration of measuring system	7
Figure 2 – Layout diagram of measurement setup.....	8
Figure 3 – Examples of test pattern with and without blur and luminance measurements	9
Figure 4 – Schematic diagram to illustrate the method of calculating the standard deviation specifying the Gaussian blur model.....	11
Figure A.1 – Examples of different levels of blur	13
Table 1 – Example of test report for blur measure.....	12
Table A.1 – Examples of the maximum measurement field diameter for different values of blur width.....	14
Table A.2 – Examples of the maximum measurement field diameter for different values of blur width.....	14
Table A.3 – Examples of PPI for different configurations of a reference display device	14
Table A.4 – Examples of combinations of measurement field diameter and corresponding distance from the LMD to the reference display device yielding a measurement field angle of 1°	15

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FLEXIBLE DISPLAY DEVICES –

Part 5-4: Measuring method of blur in flexible transparent displays

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62715-5-4, which is a technical specification, has been prepared by IEC technical committee 110: Electronic displays.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
110/1055/DTS	110/1084/RVTDS

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62715 series, published under the general title *Flexible display devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

FLEXIBLE DISPLAY DEVICES –

Part 5-4: Measuring method of blur in flexible transparent displays

1 Scope

This part of IEC 62715 specifies the measuring conditions and measuring methods for determining the blur of objects when viewed through a flexible transparent display. This document mainly applies to flexible transparent display modules that have a constant radius curvature about a single axis. The display is measured in a static mechanical state.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62715-1-1, *Flexible display devices – Part 1-1: Terminology and letter symbols*

IEC 62715-5-1, *Flexible display devices – Part 5-1: Measuring methods of optical performance*