

INTERNATIONAL STANDARD

Information technology – Generic cabling for customer premises

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

Warning! Make sure that you obtained this publication from an authorized distributor.

Contents

Foreword	viii
Introduction	ix
1 Scope	1
2 Normative references	2
3 Definitions and abbreviations	4
3.1 Definitions	4
3.2 Abbreviations	7
4 Conformance	8
5 Structure of the generic cabling system	9
5.1 Structure	9
5.1.1 Functional elements	9
5.1.2 Cabling subsystems	9
5.1.3 Campus backbone cabling subsystem	10
5.1.4 Building backbone cabling subsystem	10
5.1.5 Horizontal cabling subsystem	10
5.1.6 Work area cabling	10
5.2 Overall structure	11
5.3 Location of distributors	13
5.4 Interfaces to the generic cabling system	14
5.4.1 Public network interface	14
5.5 Dimensioning and configuring	15
5.5.1 Floor distributor	15
5.5.2 Preferred cable types for pre-cabling and recommended use	15
5.5.3 Telecommunications outlets	15
5.5.4 Telecommunications closets and equipment rooms	16
5.5.5 Building entrance facilities	16
5.6 Electromagnetic compatibility	16
5.7 Earthing and bonding	16
6 Implementation	17
6.1 Horizontal cabling	18
6.1.1 Horizontal distances	18
6.1.2 Choosing cable types	19
6.1.3 Configuring TOs	20
6.2 Backbone cabling	21
6.2.1 Physical topology	21
6.2.2 Choosing cable types	21
6.2.3 Backbone cabling distances	22
7 Link specifications	23
7.1 Classification of applications and links	24
7.1.1 Application classification	24
7.1.2 Link classification	24
7.2 Balanced cabling links	25
7.2.1 Characteristic impedance	25
7.2.2 Return loss	26
7.2.3 Attenuation	26

7.2.4	Near-end crosstalk loss	27
7.2.5	Attenuation to crosstalk loss ratio	27
7.2.6	DC resistance	28
7.2.7	Propagation delay	29
7.2.8	Longitudinal to differential conversion loss (balance)	29
7.2.9	Transfer impedance of shield	29
7.3	Optical fibre links	30
7.3.1	Optical attenuation	30
7.3.2	Multimode modal bandwidth	31
7.3.3	Return loss	31
7.3.4	Propagation delay	31
8	Cable requirements	32
8.1	General requirements for 100 Ω and 120 Ω balanced cable	33
8.1.1	Additional requirements for 100 Ω balanced cable	35
8.1.2	Additional requirements for 120 Ω balanced cable	36
8.2	General requirements for 150 Ω balanced cable	37
8.3	Additional crosstalk considerations for balanced cables	39
8.3.1	Power summation	39
8.3.2	Hybrid and multi-unit cables and cables connected to multiple TOs	39
8.4	Multimode optical fibre cables	40
8.5	Singlemode optical fibre cables	40
9	Connecting hardware requirements	41
9.1	General requirements	41
9.1.1	Location	41
9.1.2	Design	42
9.1.3	Operating environment	42
9.1.4	Mounting	42
9.1.5	Cross-connect jumpers and patch cords	42
9.1.6	Installation practices	43
9.1.7	Marking and colour coding	43
9.2	Connecting hardware for 100 Ω and 120 Ω cabling	43
9.2.1	General requirements	43
9.2.2	Performance marking	44
9.2.3	Mechanical characteristics	44
9.2.4	Electrical characteristics	45
9.2.5	Telecommunications outlet requirements	46
9.2.6	Installation practices	46
9.3	Connecting hardware for 150 Ω cabling	47
9.3.1	General requirements	47
9.3.2	Performance marking	47
9.3.3	Mechanical characteristics	47
9.3.4	Electrical characteristics	48
9.3.5	Telecommunications outlet requirements	48
9.3.6	Installation practices	49
9.4	Optical fibre connecting hardware	49
9.4.1	General requirements	49
9.4.2	Marking and colour coding	49
9.4.3	Mechanical and optical characteristics	49

9.4.4	Telecommunications outlet requirements	50
9.4.5	Cross-connect jumpers and patch cords	50
9.4.6	Optical fibre connectivity	50
10	Shielding practices	51
10.1	EMC	51
10.2	Grounding	51
11	Administration	53
11.1	Scope of administration	53
11.2	Identifiers	53
11.3	Records	53
11.3.1	Documentation	53
Annexes		
A	Test procedures	54
A.1	Link performance testing	54
A.1.1	Testing balanced cabling links	54
A.1.2	Testing optical fibre cabling links	57
A.1.3	Link tests	58
A.2	Transmission testing of connecting hardware for balanced cabling	59
A.2.1	Purpose and scope	59
A.2.2	Applicability	59
A.2.3	Test parameters	60
A.2.4	Transmission testing of connecting hardware for balanced cables	61
A.3	Termination procedure and setup verification for modular jack and plug testing	64
A.3.1	Test plug termination	64
A.3.2	Balun and test plug qualification	66
A.3.3	Typical TO measurement procedure	67
B	Reliability testing of connecting hardware for balanced cabling	69
B.1	Introduction	69
B.2	Contact resistance measurement	70
B.3	Insulation resistance	70
B.4	Durability	70
B.5	Vibration	70
B.6	Stress relaxation	71
B.7	Thermal shock	71
B.8	Humidity/temperature cycle	71
B.9	Corrosion testing	72
C	Requirements for flexible 100 Ω, 120 Ω and 150 Ω balanced cables	73
C.1	General requirements	73
C.2	Additional requirements for 150 Ω flexible cables	73
D	Topology	75
D.1	Common topologies	75
D.1.1	Network topology	75
D.2	Configurations	76
D.3	Application of the structured framework	77
E	Acronyms for balanced cables	79

F	Tutorial on link performance	80
F.1	Balanced cable transmission	80
F.1.1	Link parameters	80
F.1.2	Link parameter values	82
F.2	Optical cabling.....	82
G	Supported applications	83
H	Fibre optic connectivity planning guide	86
H.1	Introduction	86
H.2	General recommendations.....	86
H.3	Connectivity options at the TO.....	87
H.3.1	Duplex SC connectivity configuration	87
H.3.2	Simplex BFOC/2,5 connectivity configuration	88
H.3.3	Duplexable BFOC/2,5-to-SC (hybrid) connectivity configuration	88
H.4	Connectivity options at distributors	88
J	Bibliographical references	89

Figures

1	- Structure of generic cabling	9
2	- Inter-relationship of functional elements	11
3	- Example of the generic cabling system	12
4	- Typical accommodation of functional elements	13
5	- Potential interfaces to generic cabling	14
6	- Maximum cable lengths	17
7a	- Horizontal link model-copper	18
7b	- Horizontal cabling model-fibre	19
8	- Typical horizontal and work area cabling.....	20
9	- Backbone star topology	21
10	- Maximum backbone distances.....	22
11	- Example of a system showing the location of cabling interfaces and the extent of associated links.....	23
12	- Eight position jack pin and pair grouping assignments.....	46
A.1	- Measurement configuration	55
A.2	- Calibration configuration	55
A.3	- Calibration	57
A.4	- Test setup	57
A.5	- Balun and test lead attenuation measurement	63
A.6	- Attenuation measurement using resistors	63
A.7	- Balanced test leads and jacket prior to untwisting.....	64
A.8	- Balanced test leads and jacket prior to plug termination	65
A.9	- Completed test plug	65
A.10	- Test plug qualification measurement.....	67
A.11	- Typical TO NEXT measurement setup.....	68
B.1	- Reliability test programme	69
D.1	- Common topologies.....	75
D.2	- Accomodating star cabling topology in a bus pathway topology	76
D.3	- Star cabling topology.....	76
D.4	- Ring system topology realised from a star cabling topology	76
D.5	- Bus system topology realised from a star cabling topology.....	77
D.6	- Example of voice services over generic cabling	77
D.7	- Inter-relationship of functional elements in an installation with diversity for protection against failure.....	78
E.1	- Cable types	79
H.1	- Duplex SC connectivity configuration	87
H.2	- Simplex BFOC/2,5 connectivity configuration.....	88
H.3	- Duplexable BFOC/2,5-to-SC (hybrid) connectivity configuration.....	88

Tables

1	- Recommended media for pre-cabling.....	15
2	- Channel lengths achievable with different categories and types of cabling	25
3	- Minimum return loss at each cabling interface	26
4	- Maximum attenuation values	26
5	- Minimum NEXT loss.....	27
6	- Minimum ACR values.....	28
7	- Maximum d.c. loop resistance.....	28
8	- Maximum propagation delay	29
9	- Longitudinal to differential conversion loss	29
10	- Attenuation of fibre optic cabling subsystems.....	30
11	- Wavelength windows for multimode fibre optic cabling	30
12	- Wavelength windows for singlemode fibre optic cabling	31
13	- Minimum optical modal bandwidth.....	31
14	- Minimum optical return loss	31
15	- Mechanical characteristics of 100 Ω and 120 Ω balanced cables.....	33
16	- Electrical characteristics of 100 Ω and 120 Ω balanced cables	34
17	- Additional electrical characteristics of 100 Ω balanced cables.....	35
18	- Alternative limits for attenuation and NEXT loss.....	35
19	- Additional electrical characteristics of 120 Ω balanced cables.....	36
20	- Mechanical characteristics of 150 Ω balanced cables.....	37
21	- Electrical characteristics of 150 Ω balanced cables	38
22	- Cable transmission performance parameters.....	40
23	- Mechanical characteristics of connecting hardware intended for use with 100 Ω or 120 Ω cabling.....	44
24	- Electrical characteristics of connecting hardware intended for use with 100 Ω or 120 Ω cabling.....	45
25	- Mechanical characteristics of connecting hardware intended for use with 150 Ω cabling.....	47
26	- Electrical characteristics of connecting hardware intended for use with 150 Ω cabling	48
27	- Mechanical and optical characteristics of optical fibre connecting hardware	49
A.1	- Parameters for testing cabling links	58
A.2	- Test balun performance characteristics (1 - 100 MHz).....	61
A.3	- Test plug NEXT loss requirements	66
C.1	- Different mechanical characteristics for 150 Ω flexible cables	73
C.2	- Different electrical characteristics for 150 Ω flexible cables	74
E.1	- Naming of balanced cables.....	79
G.1	- Supported applications.....	83
G.2	- Application standards and balanced cabling	85
G.3	- Application standards and optical fibre cabling.....	85

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialised system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 11801 was prepared by the Joint Technical Committee ISO/IEC JTC 1/SC 25, Interconnection of Information Technology Equipment.

This International Standard has taken into account requirements specified in application standards listed in annex G. It refers to International Standards for components and test methods whenever an appropriate International Standard was available.

Annexes A, B and C form an integral part of this International Standard.
Annexes D, E, F, G, H and J are for information only.

Introduction

Within customer premises, the importance of the cabling infrastructure is similar to that of other fundamental building utilities such as heating, lighting and mains power. As with other utilities, interruptions to service can have serious impact. Poor quality of service due to lack of design foresight, use of inappropriate components, incorrect installation, poor administration or inadequate support can threaten an organisation's effectiveness.

Historically, the cabling within a premises comprised both application specific and multipurpose networks. Appropriate use of this International Standard will enable a controlled migration to generic cabling. Certain circumstances may warrant the introduction of application specific cabling; these instances should be minimised.

This International Standard provides:

- a) users with an application independent generic cabling system and an open market for cabling components;
- b) users with a flexible cabling scheme such that modifications are both easy and economical;
- c) building professionals (for example, architects) with guidance allowing the accommodation of cabling before specific requirements are known; that is, in the initial planning either for construction or refurbishment;
- d) industry and applications standardisation bodies with a cabling system which supports current products and provides a basis for future product development.

This International Standard specifies a multi-vendor cabling, and is related to:

- a) International Standards for cabling components developed by committees of the IEC; for example, copper cables IEC/TC 46 ¹⁾, copper connectors IEC/TC 48, optical fibre cables and connectors IEC/TC 86;
- b) applications developed by the sub-committees of ISO/IEC JTC 1 ²⁾ and study groups of ITU-T ³⁾: for example, LANs: ISO/IEC JTC 1/SC 6 and SC 25/WG 4 ⁴⁾; ISDN: ITU-T SG13 ⁵⁾;
- c) planning and installation guides for the implementation and use of generic cabling systems;

The applications listed in annex G have been analysed to determine the requirements for a generic cabling system. These requirements, together with statistics concerning premises geography from different countries and the model described in 6.1.1, have been used to develop the requirements for cabling components and to stipulate their arrangement into cabling systems. As a result, generic cabling defined within this International Standard is targeted at, but not limited to, the general office environment.

It is anticipated that the generic cabling system defined by this International Standard will have a life expectancy in excess of 10 years.

¹⁾ International Electrotechnical Commission - Technical Committee 46

²⁾ International Organization for Standardization/International Electrotechnical Commission - Joint Technical Committee 1

³⁾ International Telecommunication Union - Telecommunications

⁴⁾ Sub Committee 25 - Working Group 4

⁵⁾ Study Group 13

INTERNATIONAL STANDARD

Information technology -

Generic cabling for customer premises

1 Scope

International Standard ISO/IEC 11801 specifies generic cabling for use within commercial premises, which may comprise single or multiple buildings on a campus.

The International Standard is optimised for premises having a geographical span of up to 3 000 m, with up to 1 000 000 m² of office space, and a population between 50 and 50 000 persons. It is recommended that the principles of this International Standard be applied to installations that do not fall within this range.

Cabling defined by this International Standard supports a wide range of services including voice, data, text, image and video.

This International Standard specifies:

- a) the structure and minimum configuration for generic cabling ¹⁾,
- b) implementation requirements,
- c) performance requirements for individual cabling links and
- d) conformance requirements and verification procedures

Although safety (electrical, fire, etc.) and Electromagnetic Compatibility (EMC) requirements are outside the scope of this International Standard, and may be covered by other standards and regulations, information given in this International Standard may be of assistance in meeting these requirements.

¹⁾ Cables and cords used to connect application specific equipment to the generic cabling system are outside of the scope of this standard. Since they have significant effect on the transmission characteristics of the channel, assumptions and guidance are provided on their performance and length.

2 Normative references

The following normative documents contain provisions that, through reference in this text, constitute provisions of ISO/IEC 11801. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 68-1:1988,	Basic environmental testing procedures - Environmental testing - Part 1: General and guidance
IEC 68-2-2:1974,	Basic environmental testing procedures - Part 2: Tests - Tests B: Dry heat
IEC 68-2-6:1982,	Basic environmental testing procedures - Part 2: Tests - Tests Fc and guidance: Vibration (sinusoidal)
IEC 68-2-14:1984,	Basic environmental testing procedures - Part 2: Tests - Test N: Change of temperature
IEC 68-2-38:1974,	Basic environmental testing procedures - Part 2: Tests - Test Z/AD: Composite temperature/humidity cyclic test
IEC 68-2-60 TTD:1990,	Basic environmental testing procedures - Part 2: Tests - Test Ke: Corrosion tests in artificial atmosphere at very low concentration of polluting gas(es) [Technical Trend Document]
IEC 96-1:1986,	Radio-frequency cables - Part 1: General requirements and measuring methods
IEC 189-1:1986,	Low-frequency cables and wires with p.v.c. insulation and p.v.c. sheath - Part 1: General test and measuring methods
IEC 227-2:1979,	Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V - Part 2: Test methods
IEC 512-1:1994,	Electromechanical components for electronic equipment; basic testing procedures and measuring methods - Part 1: General
IEC 512-2:1985,	Electromechanical components for electronic equipment; basic testing procedures and measuring methods - Part 2: General examination, electrical continuity and contact resistance tests, insulation tests and voltage stress tests Amendment 1 (1988)
IEC 603-7:1990,	Connectors for frequencies below 3 MHz for use with printed boards - Part 7: Detail specification for connectors, 8 way, including fixed and free connectors with common mating features
IEC 708-1:1981,	Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath - Part 1: General design details and requirements
IEC 793-1:1992,	Optical fibres - Part 1: Generic specification Amendment 3 (1988)
IEC 793-2:1992,	Optical fibres - Part 2: Product specifications
IEC 794-1:1993,	Optical fibre cables - Part 1: Generic specification
IEC 794-2:1989,	Optical fibre cables - Part 2: Product specifications

IEC 807-8:1992,	Rectangular connectors for frequencies below 3 MHz - Part 8: Detailed specification for connectors, four signal contacts and earthing contacts for cable screen
IEC 811-1-1:1993,	Common test methods for insulating and sheathing materials of electric cables - Part 1: Methods for general application - Section 1: Measurement of thickness and overall dimensions - Tests for determining the mechanical properties
IEC 874-1:1993,	Connectors for optical fibres and cables - Part 1: Generic specification
IEC 874-10:1992,	Connectors for optical fibres and cables - Part 10: Sectional specification for fibre optic connector - Type BFOC/2,5
IEC 874-14:1993,	Connectors for optical fibres and cables - Part 14: Sectional specification for fibre optic connector - Type SC
IEC 1073-1:1994,	Splices for optical fibres and cables - Part 1: Generic specification - Hardware and accessories
IEC 1156-1:1994,	Multicore and symmetrical pair/quad cables for digital communications - Part 1: Generic specification
ISO/IEC 8802-5:1992,	Information processing systems - Local and metropolitan area networks - Part 5: Token ring access method and physical layer specifications
CISPR 22:1993,	Limits and methods of measurement of radio disturbance characteristics of information technology equipment.
ITU-T Rec. G.117:1988,	Transmission aspects of unbalance about earth (definitions and methods)
ITU-T Rec. G.650:1993,	Transmission media characteristics. Definition and test methods for the relevant parameters of single-mode fibres
ITU-T Rec. G.651:1993,	Characteristics of a 50/125 µm multimode graded index optical fibre cable
ITU-T Rec. G.652:1993,	Characteristics of a single-mode optical fibre cable
ITU-T Rec. O.9:1988,	Measuring arrangements to assess the degree of unbalance about earth