



ISO/IEC 14165-151

Edition 1.0 2017-11

INTERNATIONAL STANDARD




**Information technology –Fibre channel –
Part 151: Fibre Channel BaseT (FC-BaseT)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200


ISBN 978-2-8322-5100-3

Warning! Make sure that you obtained this publication from an authorized distributor.



Information Technology — Fibre Channel — Part 151: BaseT

Technologies de l'information — Fibre Channel — Partie 151 (FC-BaseT)



Contents	Page
FOREWORD	7
INTRODUCTION	9
1 Scope	10
2 Normative references	10
3 Terms, definitions, abbreviations, symbols, and conventions	11
3.1 Terms and definitions	11
3.2 Editorial conventions	14
3.3 Abbreviations, acronyms, and symbols	14
3.4 Keywords	15
3.5 State Diagram notation	16
3.5.1 State Diagram conventions	16
3.5.2 State Diagram variables	17
3.5.3 State Diagram timers	17
3.5.4 State transitions	17
3.5.5 Operators	18
4 Structure and concepts	19
4.1 Overview	19
4.2 Relationship with other standards	20
4.3 FC-BaseT PHY logical model	21
4.4 FC-BaseT usage of XGMII	22
4.5 Operation of FC-BaseT	23
4.5.1 Overview	23
4.5.2 PCS overview	24
4.5.3 PMA overview	25
4.6 FC-BaseT service primitives and interfaces	25
4.6.1 Overview	25
4.6.2 PMA service interface	25
4.6.3 Management function interface	30
4.7 FC-BaseT Nomenclature	31
5 Physical Coding Sublayer (PCS)	32
5.1 Overview	32
5.2 PCS reset function	32
5.3 PCS transmit function	33
5.3.1 Overview	33
5.3.2 36/33 transcoding	34
5.3.3 Error detecting code	36
5.3.4 PCS scrambling	37
5.3.5 Schläfli Lattice coding	39
5.3.6 Trellis coding	40
5.3.7 Generation of PMA training sequences	41
5.4 PCS receive function	42
5.4.1 Overview	42
5.4.2 Decoding	43
5.4.3 PCS descrambling	44
5.4.4 33/36 transcoding	45
5.4.5 PCS synchronization	46
5.5 State Diagrams	46

6	PMA Sublayer and Medium Dependent Interface	48
6.1	PMA Overview	48
6.2	PMA Functions	49
6.2.1	PMA Reset function	49
6.2.2	PMA Transmit function	49
6.2.3	PMA Receive Function	49
6.2.4	PHY Control Function	50
6.2.5	Link Monitor Function	53
6.2.6	Clock Recovery Function	53
6.2.7	State Diagrams	53
6.3	PMA Electrical Specification	56
6.3.1	Isolation and EMC Requirements	56
6.3.2	Test Modes	56
6.3.3	Transmitter Electrical Specifications	59
6.3.4	Receiver Electrical Specifications	64
6.4	MDI Specification	66
6.4.1	Overview	66
6.4.2	MDI Mechanical Specification	66
6.4.3	Automatic MDI/MDI-X Configuration	67
6.4.4	MDI Electrical Specification	67
6.4.5	MDI Fault tolerance	67
6.5	Link Segment Characteristics	67
6.5.1	Overview	67
6.5.2	FC-BaseT Link Topology	68
6.5.3	FC-BaseT Cable Plant Requirements	68
7	Elasticity FIFO	69
7.1	Overview	69
7.2	Ordered sets processing	70
7.3	Clock skew compensation	71
8	PHY startup procedure	73
8.1	Overview	73
8.2	Host speeds determination	73
8.3	Host synchronization	73
8.4	FC-BaseT auto-negotiation	74
8.4.1	Overview	74
8.4.2	FC-BaseT support	75
8.4.3	Master-Slave relationship	76
8.4.4	Cable length estimation	77
8.4.5	Tentative Operating Speed Determination	78
8.4.6	Configuration resolution	79
8.5	Speed downshift function	80
8.6	State diagrams	80
9	Port management	86
9.1	Overview	86
9.2	FC-BaseT management registers	86
9.3	Control Register	88
9.4	Status Register	91
9.5	Speed Downshift Register	93
9.6	Test Register	94
9.7	SNR Margin Registers	94
9.8	Auto-Negotiation Pages Registers	95

Annex A (informative) Additional 36/33 Mappings	98
A.1 Overview	98
A.2 Notation	98
A.3 Additional mappings	98
Annex B (informative) Schläfli Lattice coding	100
Annex C (informative) Recommended 4GFC-BaseT power schedule	102
Bibliography	103

Figure	Page
Figure 1	State diagram notation example 16
Figure 2	FC-BaseT topology 19
Figure 3	FC-BaseT relationship to the OSI Reference Model, the Fibre Channel Levels, and the IEEE 802.3 LAN Model. 20
Figure 4	An FC-BaseT PHY logical model 21
Figure 5	PCS and PMA functional block diagram 24
Figure 6	PCS and PMA service interfaces 26
Figure 7	FC-BaseT nomenclature 31
Figure 8	PCS reference diagram 32
Figure 9	PCS transmit bit ordering 33
Figure 10	Side-stream scrambler for the Master PHY 37
Figure 11	Side-stream scrambler for the Slave PHY 38
Figure 12	4D PAM-8 Schläfli Lattice encoder. 39
Figure 13	4D PAM-8 Trellis encoder 40
Figure 14	Generation of PMA training PAM-2 sequences 41
Figure 15	PCS receive bit ordering 42
Figure 16	4D PAM-8 Schläfli Lattice decoder. 43
Figure 17	Side-stream descrambler for the Master PHY 44
Figure 18	Side-stream descrambler for the Slave PHY 44
Figure 19	PCS synchronization state diagram 47
Figure 20	PMA Reference Diagram 48
Figure 21	Example of Link Establishment 52
Figure 22	PHY Control State Diagram 55
Figure 23	Link Monitor State Diagram 56
Figure 24	Transmitter Test Fixture A 58
Figure 25	Transmitter Test Fixture B 58
Figure 26	Test Mode 1 Output (not to scale) 59
Figure 27	4GFC-BaseT Transmitter PSD at 5dBm 61
Figure 28	2GFC-BaseT Transmitter PSD at 5dBm 62
Figure 29	1GFC-BaseT Transmitter PSD at 5dBm 63
Figure 30	MDI Jack Connector. 66
Figure 31	Balanced Cabling Plug Connector 66
Figure 32	FC-BaseT Link Topology 68
Figure 33	FC-BaseT elasticity FIFO. 69
Figure 34	Example of E-FIFO implementation 70
Figure 35	FC-BaseT clock skew compensation 71
Figure 36	Base page encoding. 75
Figure 37	Unformatted page encoding 76
Figure 38	Clock detect state diagram. 84
Figure 39	Clock loopback state diagram 85
Figure B.1	4D symbol error rate in function of SNR. 100

Table	Page
Table 1 ISO and American Conventions	14
Table 2 State Diagram Operators.	18
Table 3 FC-BaseT design goals for data rates and cable reaches for the cabling channels specified by ISO/IEC 11801:2002/AMD2:2010	20
Table 4 XGMII frequencies for FC-BaseT	22
Table 5 XGMII characters.	22
Table 6 FC-BaseT symbol and data rates	23
Table 7 Fibre Channel words	34
Table 8 XGMII representation of Fibre Channel words	35
Table 9 36/33 transcoding	35
Table 10 36/33 transcoding examples	35
Table 11 Bit to symbols mapping	40
Table 12 PMA training sequences	41
Table 13 PCS synchronization state variables.	46
Table 14 Idle2 and Idle3 Ordered Sets.	51
Table 15 PHY Control and Link Monitor State Variables	53
Table 16 PHY Control and Link Monitor Timers.	54
Table 17 Management Register Settings for Test Modes	57
Table 18 Disturbing Signal Frequency	59
Table 19 Droop Requirements	59
Table 20 Transmitter Power Schedule	64
Table 21 Transmitter Frequency Requirements.	64
Table 22 Receiver Frequency Requirements.	65
Table 23 Alien Noise Requirements	65
Table 24 Assignment of PMA Signals to MDI and MDI-X Contacts	67
Table 25 FC-BaseT MDI Electrical Requirements	67
Table 26 FC-BaseT Cable Plant Requirements	68
Table 27 Extended Fill Words	70
Table 28 Technology Ability Field.	75
Table 29 Unformatted code field of the first unformatted page	76
Table 30 Master-Slave seed assignment.	77
Table 31 Unformatted code field of the second unformatted page.	78
Table 32 Unformatted code field of the third unformatted page	79
Table 33 Cable length estimation state variables.	81
Table 34 Cable length estimation timers	83
Table 35 FC-BaseT registers	86
Table 36 FC-BaseT control register bits.	88
Table 37 FC-BaseT status register bits	91
Table 38 FC-BaseT speed downshift register bits	93
Table 39 FC-BaseT test register bits	94
Table 40 FC-BaseT SNR margin registers bits	94
Table 41 FC-BaseT auto-negotiation pages registers bits	96
Table A.1 Additional 36/33 mappings.	98
Table A.2 6-bit encoding of XGMII control characters	99
Table C.1 Recommended transmitter power schedule	102

INFORMATION TECHNOLOGY – FIBRE CHANNEL –

Part 151: Fibre Channel BaseT (FC-BaseT)

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14165-151 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 14165 series, under the general title *Information technology – Fibre Channel*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies and the voting results may

be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT - The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of ISO/IEC 14165 describes extensions to the Fibre Channel signaling and physical layer requirements defined in ANSI INCITS 404-2005, Fibre Channel - Physical Interfaces 2, to transport Fibre Channel over the commonly available 4-pair balanced copper cabling specified in ISO/IEC 11801:2002 and TIA/EIA-568-B.2-2001. This document is one of the Fibre Channel family of standards.

INFORMATION TECHNOLOGY — FIBRE CHANNEL —

Part 151: Fibre Channel BaseT (FC-BaseT)

1 Scope

This part of ISO/IEC 14165 describes extensions to the Fibre Channel signaling and physical layer requirements defined in ISO/IEC 14165-142, Fibre Channel - Physical Interfaces 2, to transport Fibre Channel over the commonly available 4-pair balanced copper cabling specified in ISO/IEC 11801:2002 and TIA/EIA-568-B.2-2001. This standard is one of the Fibre Channel family of standards.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60603-7-2, *Connectors for electronic equipment – Part 7-2: Detail specification for 8-way, unshielded, free and fixed connectors, for data transmissions with frequencies up to 100 MHz*

IEC 60603-7-3, *Connectors for electronic equipment – Part 7-3: Detail specification for 8-way, shielded, free and fixed connectors, for data transmission with frequencies up to 100 MHz*

IEC 60603-7-4, *Connectors for electronic equipment – Part 7-4: Detail specification for 8-way, unshielded, free and fixed connectors, for data transmissions with frequencies up to 250 MHz*

IEC 60603-7-5, *Connectors for electronic equipment – Part 7-5: Detail specification for 8-way, shielded, free and fixed connectors, for data transmissions with frequencies up to 250 MHz*

ISO/IEC 14165-122, *Information technology - Fibre Channel - Part 122: Arbitrated Loop - 2 (FC-AL-2)* [ANSI INCITS 332-1999 including ANSI INCITS 332-1999/AM1-2003 and ANSI INCITS 332-1999/AM2-2006]

ISO/IEC 11801:2002, *Information technology - Generic cabling for customer premises*

ISO/IEC 11801:2002/AMD1:2008

ISO/IEC 11801:2002/AMD2:2010

ISO/IEC TR 24750, *Information technology - Assessment and mitigation of installed balanced cabling channels in order to support 10GBASE-T*

ANSI INCITS 404-2006, *Information technology - Fibre Channel - Part 142: Physical Interfaces - 2 (FC-PI-2)*

ANSI INCITS 424-2007, *Information technology - Fibre Channel - Framing and Signaling - 2 (FC-FS-2)*

IEEE Std 802.3-2005, *Standard for information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

IEEE Std 802.3an-2006, *Physical Layer and Management Parameters for 10 Gb/s Operation, Type 10GBASE-T*