

ISO/IEC 14543-3-6

Edition 1.0 2007-01

INTERNATIONAL STANDARD

Information technology – Home electronic system (HES) architecture – Part 3-6: Media and media dependent layers – Twisted pair for network based control of HES Class 1

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ISBN 2-8318-8991-X

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FO	REW	ORD		6			
INT	TRODUCTION8						
1	Scop	e		9			
2	Normative references						
3	Term	ıs, defin	nitions and abbreviations	10			
	3.1	Definit	ions	10			
	3.2		viations				
4	-		e				
5	Requirements for HES Class 1, Twisted Pair Type 0 (TP0)						
	5.1	Datagram service					
	0.1	5.1.1	Transmission method				
		5.1.2	Transceiver characteristics				
		5.1.3	Physical layer services – Physical data service				
		5.1.4	Physical layer protocol				
	5.2		m definition				
		5.2.1	Topology	18			
		5.2.2	Line	18			
		5.2.3	Line connection	18			
		5.2.4	Repeater	18			
		5.2.5	Medium installation requirements	18			
		5.2.6	General hardware requirements	19			
	5.3	Power	feeding service	19			
		5.3.1	General	19			
		5.3.2	Power feeding device types	19			
		5.3.3	Factor C (current consumption)	19			
		5.3.4	Line power supply general requirements	20			
		5.3.5	Power supply voltage				
		5.3.6	Dynamic characteristics	21			
		5.3.7	Distributed power supply (DPS)				
	5.4	Data link layer type Twisted Pair Type 0					
		5.4.1	Frame formats				
		5.4.2	Medium access control				
		5.4.3	L_Data service and protocol				
		5.4.4	L_Busmon service				
		5.4.5	L_Service_Information service				
_	5.5		wisted Pair Type 0 frame structure				
6	•		ts for HES Class 1, Twisted Pair Type 1 (TP1-64 & TP1-256)				
	6.1 Physical layer requirements – Overview						
	6.2	•	rements for analogue bus signals				
		6.2.1	General				
		6.2.2	Specification of logical "1"				
		6.2.3	Specification of logical "0" (Single)				
		6.2.4	Specification of logical "0" (overlapping)				
		6.2.5	Analogue requirements within a transmitted character				
	0.0	6.2.6	Simultaneous sending / collision behaviour				
	6.3	S.3 Medium attachment unit (MAU)					

	6.3.1	General	45
	6.3.2	Requirements within a physical segment	45
	6.3.3	Remote powered devices (RPD)	52
6.4	Twiste	d Pair Type 1 bus cable	53
	6.4.1	Requirements	53
	6.4.2	Measurement of continuous magnetic and electrical interference, respectively transient induced differential voltages	54
6.5	Topolo	gy	55
	6.5.1	Physical segment	55
	6.5.2	Bridge	55
	6.5.3	Router, sub-line, main line and zone	
	6.5.4	Gateways to other networks	
6.6		es of the physical layer type Twisted Pair Type 1	
	6.6.1	General	
	6.6.2	Physical_Data service	
	6.6.3	Physical_Reset service	
6.7		our of the physical layer type Twisted Pair Type 1 entity	
6.8		nk layer type Twisted Pair Type 1	
	6.8.1	General	
	6.8.2	Frame formats	
	6.8.3	Medium access control	
	6.8.4	Data link layer services	
	6.8.5	Data link layer protocol	
	6.8.6	State machine of data link layer	
	6.8.7	Parameters of data link layer	/6
	6.8.8	Reflections on the system behaviour in case of L_Poll_Data configuration faults	76
	6.8.9	Data link layer of a bridge	77
	6.8.10	Data link layer of a router	77
	6.8.11	Externally accessible bus monitor and data link layer interface	77
•		ine codecter format	
•		mitter rising and falling edges	
-			
•	•	ater maximum transition timeower supply gauge	
•		supply dynamic internal resistor measuring test set-up	
•		g edge and over-current measurements	
•		letwork with distributed power supply	
•		pe/Current gauge of one node	
-	_	age/Current gauge of entire distributed power supply with 6 to 8 supply	24
nodes			
•		mon part of frame structure	
Figure 12	2 – Cont	rol field	29
Figure 13	B – CTR	LE field	30

Figure 14 – Format1s, L_Data_Standard frame format with standard field-name abbreviations	30
Figure 15 – Format 1e, L_Data_Extended frame format with standard fieldname abbreviations	
Figure 16 – EFF field	
Figure 17 – Format 2, Short acknowledgement frame format	
Figure 18 – Transmission definition	
Figure 19 – Format 1s, Full L_Data_Standard request frame format	
Figure 20 – Format 1e, Full L_Data_Extended request frame format	
Figure 21 – Logical structure of physical layer type TP1	
Figure 22 – Octet mapped to a serial character	
Figure 23 – "1"-Bit frame	
Figure 24 – "0"-Bit frame	
Figure 25 – Delayed logical "0"	43
Figure 26 – Overlapping of two logical "0" (example)	44
Figure 27 – Method of transmitting	
Figure 28 – Example of transmitter characteristics	
Figure 29 – Example of a diagram of a TP1-64 transmitter	49
Figure 30 – Example of a diagram of a TP1-256 transmitter (I_{limit} 0,4 A)	49
Figure 31 – Relation between framed data and asynchronous signal	50
Figure 32 – Relation between digital signal and serial bit stream	51
Figure 33 – Example of light dimmer	52
Figure 34 – Physical segments	55
Figure 35 – Physical segments combined to a line	56
Figure 36 – Lines combined to a zone	56
Figure 37 – Network topology	58
Figure 38 – Control field	62
Figure 39 – Frame fields with standard fieldname abbreviations	62
Figure 40 – Format 1s, L_Data_Standard frame format	63
Figure 41 – Check octet	63
Figure 42 – Frame fields with standard fieldname abbreviations	64
Figure 43 – Format 1e, L_Data_Extended frame format	
Figure 44 – Extended control field	65
Figure 45 – Format 3 - L_Poll_Data request frame format	65
Figure 46 – L_Poll_Data response frame format	66
Figure 47 – Format 2 - Short acknowledgement frame format	67
Figure 48 – Character timing	67
Figure 49 – Priority operation	68
Figure 50 – Guarantee of access fairness	70
Figure 51 – State machine of data link layer	76

Table 1 – Electrical data encoding	15
Table 2 – Transceiver characteristics – Sending part	16
Table 3 – Transceiver characteristics – Receiving part	16
Table 4 – Mandatory and optional requirements for physical layer services	16
Table 5 – Physical-Result parameter	17
Table 6 – Requirements for the TP0 line	18
Table 7 – General hardware requirements	19
Table 8 – Current consumption requirements	20
Table 9 – Power supply voltage	20
Table 10 – Requirements for one supplying DPS device	24
Table 11 – Requirements for entire DPS	26
Table 12 – Possible cable lengths depending on number of DPS devices connected (for a typical cable)	27
Table 13 – Priority of frames – IFT	34
Table 14 – Requirements for acknowledgement wait time, frame re-transmission	36
Table 15 – Requirements for full wait time, frame re-transmission	36
Table 16 – System parameters of physical layer Type TP1-64 and TP1-256	39
Table 17 – Analogue and digital signal of a logical "1"	41
Table 18 – Analogue and digital signal of logical "0"	42
Table 19 – Limits within a character	44
Table 20 – Unit currents for standard devices	46
Table 21 – Dynamic requirements of a TP1-64 transmitter	48
Table 22 – Dynamic requirements of a TP1-256 transmitter	48
Table 23 – Requirements for the receiver	50
Table 24 – Requirements for bit coding	51
Table 25 – Requirements for the bit decoding unit	52
Table 26 – Requirements for TP1 cable	53
Table 27 – Requirements for character coding	68
Table 28 – Requirements for character decoding	68
Table 29 - Priority sequence, in descending order of importance	69

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 3-6: Media and media dependent layers – Twisted pair for network based control of HES Class 1

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC Publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC Publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC Publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC Publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent primarily concerning activities as described in clause 5: Requirements for HES Class 1, Twisted Pair Type 0 (TP0).

Schneider Electric Industries SAS has informed IEC and ISO that they have the patent applications or granted patents as listed below:

EP 0370 921 B1, EP 0911 777 A1.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent primarily concerning activities as described in 6.2: Requirements for analogue bus signals and 6.3: Medium attachment unit (MAU).

Siemens AG (Regensburg) has informed IEC and ISO that they have the patent applications or granted patents as listed below:

EP 0365 696 B1, EP 0487 759 B1, EP 0489 194 B1, EP 0643 893 B1, EP 0770 285 B1, EP 0854 587 A1, EP 0858 142 A1, EP 0858 194 A1, WO 00/42694 A1.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent primarily concerning activities as described in 5.3.7: Distributed power supply (DPS).

Siemens Schweiz AG has informed IEC and ISO that they have the patent applications or granted patents as listed below:

EP-B-0'749'070

ISO and IEC take no position concerning the evidence, validity and scope of these putative patent rights. The holders of these putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these putative patent rights are registered with IEC and ISO. Information may be obtained from:

Schneider Electric Industries SAS Systems and Architectures – EDA (Electrical Distribution Architecture) PLM-A Plant – 2 chemin des sources - Meylan F-38050 Grenoble cedex 9 France

Siemens AG A and D ET BC Siemensstr. 10 D-93055 Regensburg Germany Siemens Schweiz AG Building Technologies Group Intellectual Property Gubelstr. 22 CH-6300 Zug Switzerland

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14543-3-6 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This International Standard is a product family standard. It shall be used in conjunction with ISO/IEC 14543-2-1, 14543-3-3, 14543-3-4, 14543-3-5 and 14543-3-7.

The list of all currently available parts of ISO/IEC 14543 series, under the general title Information technology – Home electronic system (HES) architecture, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

INTRODUCTION

The reference model for Open System Interconnection (OSI), specified in ISO/IEC 7498, assigns the functions that are needed for communications between two entities that are connected by medium to seven logical layers. This International Standard specifies interconnection of entities used for home and building control via the medium twisted pair. It specifies the medium and medium dependent functions such as the cable, the connectors and the transmission technology in terms of the Physical Layer and the Data Link Layer according to ISO/IEC 7498.

Currently, ISO/IEC 14543, Information technology - Home Electronic System (HES) architecture, consists of the following parts:

- Part 2-1: Introduction and device modularity
- Part 3-1:
- Communication layers Application layer for network based control of HES Class 1 Communication layers Transport, network and general parts of data link layer for Part 3-2: network based control of HES Class 1
- Part 3-3: User process for network based control of HES Class 1
- Part 3-4: System management – Management procedures for network based control of HES Class 1
- Part 3-5: Media and media dependent layers - Powerline for network based control of HES Class 1
- Media and media dependent layers Twisted pair for network based control of Part 3-6: HES Class 1
- Part 3-7: Media and media dependent layers - Radio frequency for network based control of HES Class 1
- Part 4: Home and building automation in a mixed-use building (technical report)
- Part 5-1: Intelligent grouping and resource sharing for HES Class 2 and Class 3 - Core protocol (under consideration)
- Part 5-2: Intelligent grouping and resource sharing for HES Class 2 and Class 3 - Device certification (under consideration) Additional parts may be added later.

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 3-6: Media and media dependent layers – Twisted pair for network based control of HES Class 1

1 Scope

This part of ISO/IEC 14543 defines the mandatory and optional requirements for the medium specific physical and data link layer for twisted pair for network based control of HES Class 1 in its two variations called TP0 and TP1.

NOTE Data link layer interface and general definitions, which are media independent, are specified in ISO/IEC 14543-3-2.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 14543-2-1, Information technology – Home Electronic System (HES) architecture – Part 2-1: Introduction and device modularity

ISO/IEC 14543-3-2, Information technology – Home electronic system (HES) architecture – Part 3-2: Communication layers – Transport, network and general parts of data link layer for network based control of HES Class 1

ISO/IEC 14543-3-3, Information technology – Home Electronic System (HES) architecture – Part 3-3: User process for network based control of HES Class 1

ISO/IEC 14543-3-4, Information technology – Home Electronic System (HES) architecture – Part 3-4: System management – Management procedures for network based control of HES Class 1

ISO/IEC 14543-3-5, Information technology – Home Electronic System (HES) architecture – Part 3-4: Media and media dependent layers – Powerline for network based control of HES Class 1

ISO/IEC 14543-3-7, Information technology – Home Electronic System (HES) architecture – Part 3-6: Media and media dependent layers – Radio frequency for network based control of HES Class 1

IEC 60189-2, Low-frequency cables and wires with PVC insulation and PVC sheath – Part 2: Cables in pairs, triples, guads and guintuples for inside installations

IEC 60227-2, Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V – Part 2: Test methods

IEC 60245-2, Rubber insulated cables – Rated voltages up to and including 450/750 V – Part 2: Test methods

IEC 60332-1 (all subparts), Tests on electric and optical fibre cables – Part 1: Test for a vertical flame propagation for a single insulated wire or cable

IEC 60754-2, Test on gases evolved during combustion of electric cables – Part 2: Determination of degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity

IEC 61000-4-5, Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test

IEC 61000-6-1, Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments

IEC 61000-6-2, Electromagnetic compatibility (EMC) – Part 6-2: Generic standards – Immunity for industrial environments

EN 50090-2-2, Home and Building Electronic Systems (HBES) – Part 2-2: System overview – General technical requirements