



ISO/IEC 14776-326

Edition 2.0 2015-09

INTERNATIONAL STANDARD

**Information technology – Small computer system interface (SCSI) –
Part 326: Reduced block commands (RBC)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-2861-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|--|----|
| FOREWORD | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms, definitions, abbreviations, keywords, and conventions | 7 |
| 3.1 Terms and definitions | 7 |
| 3.2 Abbreviations | 8 |
| 3.3 Keywords | 8 |
| 3.4 Conventions | 9 |
| 3.4.1 Non-numeric values | 9 |
| 3.4.2 Numeric values | 10 |
| 4 RBC device model | 10 |
| 4.1 General | 10 |
| 4.2 Removable medium device | 10 |
| 4.3 Command usage | 11 |
| 4.3.1 General | 11 |
| 4.3.2 Using the INQUIRY command | 11 |
| 4.3.3 Using the REQUEST SENSE command | 11 |
| 4.3.4 FORMAT UNIT command progress determination | 11 |
| 4.4 Using the PREVENT ALLOW MEDIUM REMOVAL command | 12 |
| 4.4.1 General | 12 |
| 4.4.2 START STOP UNIT command state restrictions | 12 |
| 4.5 Logical Blocks | 12 |
| 4.6 Reservations | 13 |
| 5 Reduced Block Commands | 14 |
| 5.1 General | 14 |
| 5.2 FORMAT UNIT command | 16 |
| 5.3 READ(10) Command | 17 |
| 5.4 READ CAPACITY command | 17 |
| 5.5 START STOP UNIT command | 18 |
| 5.5.1 General | 18 |
| 5.5.2 Power conditions | 19 |
| 5.5.3 Enable/Disable bits | 20 |
| 5.6 SYNCHRONIZE CACHE command | 21 |
| 5.7 VERIFY command | 21 |
| 5.8 WRITE(10) command | 22 |
| 5.9 Mode parameters | 23 |
| 5.9.1 General | 23 |
| 5.9.2 Mode parameter list | 23 |
| 5.9.3 Mode Parameter header | 23 |
| 5.9.4 RBC Device Parameter's page | 23 |
| 6 SPC-2 implementation requirements for RBC devices | 25 |
| 6.1 General | 25 |
| 6.2 INQUIRY command | 25 |
| 6.2.1 Standard INQUIRY data | 25 |
| 6.2.2 INQUIRY vital product data pages | 26 |
| 6.3 MODE SELECT(6) command | 27 |

- 6.4 MODE SENSE(6) command 27
- 6.5 PREVENT ALLOW MEDIUM REMOVAL 28
- 6.6 REQUEST SENSE command 28
- 6.7 TEST UNIT READY command 28
- 6.8 WRITE BUFFER Command 29
 - 6.8.1 General 29
 - 6.8.2 Download microcode and save mode (101b) 30
 - 6.8.3 Download microcode with offsets and save mode (111b) 30
- 7 Asynchronous event notification for RBC devices 30
 - 7.1 General 30
 - 7.2 Unit attention 31
 - 7.2.1 General 31
 - 7.2.2 Power condition change notification 31
 - 7.3 Deferred errors 31
 - 7.4 Information exception condition notification 31
 - 7.5 Event status notification 31
 - 7.5.1 General 31
 - 7.5.2 Event Status sense information 32
 - 7.5.3 Power Management CLASS event INFORMATION field 32
 - 7.5.4 MEDIA CLASS EVENT INFORMATION field 33
 - 7.5.5 DEVICE BUSY CLASS EVENT INFORMATION field 34
 - 7.5.6 Event status retention 35
 - 7.5.7 Removable medium device initial response 35
- Annex A (normative) RBC device implementation requirements for SBP-2 36
 - A.1 SBP-2 terms and definitions 36
 - A.1.1 Terms and definitions 36
 - A.1.2 Abbreviations 38
 - A.2 SBP-2 storage model 38
 - A.2.1 General 38
 - A.2.2 Model configuration 38
 - A.2.3 Reconnect/Power reset support 40
 - A.3 Configuration ROM support 40
 - A.3.1 General 40
 - A.3.2 Unit Directory – Command_Set_Spec_ID 40
 - A.3.3 Unit Directory – Command_Set 41
 - A.3.4 Unit Directory – Logical_Unit_Number 41
 - A.4 Security support 41
 - A.5 Status block support 41
 - A.6 Unsolicited Status support 42
 - A.6.1 General 42
 - A.6.2 Unit attention condition 42
 - A.6.3 Event Status retention 42

Figure A.1 – Mass storage interface block diagram 39

Figure A.2 – Status block for RBC 42

Table 1 – RBC direct access commands that are allowed in the presence of various reservations 14

| | |
|--|----|
| Table 2 – Reduced Block Command set..... | 15 |
| Table 3 – FORMAT UNIT command | 16 |
| Table 4 – READ (10) Command Descriptor Block..... | 17 |
| Table 5 – READ CAPACITY Command Descriptor Block..... | 18 |
| Table 6 – READ CAPACITY data | 18 |
| Table 7 – START STOP UNIT Command Descriptor Block..... | 19 |
| Table 8 – POWER CONDITIONS | 19 |
| Table 9 – START STOP control bit definitions..... | 21 |
| Table 10 – SYNCHRONIZE CACHE Command Descriptor Block..... | 21 |
| Table 11 – VERIFY Command Descriptor Block | 22 |
| Table 12 – WRITE(10) Command Descriptor Block | 22 |
| Table 13 – Mode parameter list..... | 23 |
| Table 14 – RBC Device Parameters page format | 24 |
| Table 15 – Required SPC-2 commands..... | 25 |
| Table 16 – Standard Inquiry data format | 26 |
| Table 17 – MODE SELECT(6) Command Descriptor Block..... | 27 |
| Table 18 – MODE SENSE(6) Command Descriptor Block | 28 |
| Table 19 – FAILURE PREDICTION ASCQ XY definitions | 29 |
| Table 20 – WRITE BUFFER Command Descriptor Block..... | 29 |
| Table 21 – Asynchronous Event conditions | 30 |
| Table 22 – Power condition sense code and qualifier values | 31 |
| Table 23 – Event status ASCQ values..... | 32 |
| Table 24 – Event Status INFORMATION field format | 32 |
| Table 25 – POWER MANAGEMENT CLASS EVENT INFORMATION field format | 32 |
| Table 26 – POWER MANAGEMENT CLASS EVENT EVENT field | 33 |
| Table 27 – POWER MANAGEMENT CLASS EVENT STATUS field..... | 33 |
| Table 28 – MEDIA CLASS EVENT INFORMATION field format | 33 |
| Table 29 – MEDIA CLASS EVENT EVENT field | 34 |
| Table 30 – DEVICE BUSY CLASS EVENT information field format | 34 |
| Table 31 – DEVICE BUSY CLASS EVENT EVENT field | 34 |
| Table 32 – DEVICE BUSY CLASS STATUS field | 35 |

INFORMATION TECHNOLOGY – SMALL COMPUTER SYSTEM INTERFACE (SCSI) –

Part 326: Reduced block commands (RBC)

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14776-326 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This second edition cancels and replaces the first edition published in 2002 and constitutes a minor revision.

This second edition provides additional explanations and corrects mistakes with respect to the first edition.

A list of all parts in the ISO/IEC 14776 series, published under the general title *Information technology – Small computer system interface (SCSI)*, can be found on the IEC website.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

INFORMATION TECHNOLOGY – SMALL COMPUTER SYSTEM INTERFACE –

Part 326: Reduced block commands (RBC)

1 Scope

This part of ISO/IEC 14776 defines a Reduced Block Command set for logical block devices. The Reduced Block Commands along with the required SPC-2 commands and their restrictions described in this standard, fully specify the complete command set for RBC logical block devices.

The purpose of this part of ISO/IEC 14776 is to provide a command set of reduced requirements and options from SCSI Block Commands (SBC) (ISO/IEC 14776-321) for block devices. The reduced command set is intended to more closely match the functionality required for simple block logical units. The specified commands place no restrictions on device performance. The initial focus of this command set was to enable rigid disks and removable media devices attached to Serial Bus and utilizing SBP-2 (ISO/IEC 14776-232) for command and control.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 13213:1994, *Information technology – Microprocessor systems – Control and Status Registers (CSR) Architecture for microcomputer buses*

ISO/IEC 14776-232:2001, *Information technology – Small computer system interface (SCSI) – Part 232: Serial Bus Protocol 2 (SBP-2)*

ISO/IEC 14776-321:2001, *Information technology – Small Computer System Interface (SCSI-3) – Part 321: Block commands (SBC)*

ISO/IEC 14776-362:2006, *Information technology – Small computer system interface (SCSI) – Part 362: Multimedia commands-2 (MMC-2)*

ISO/IEC 14776-412, *Information technology – Small computer system interface (SCSI) – Part 412: SCSI, Architecture model-2 (SAM-2)*

ISO/IEC 14776-452:2005, *Information technology – Small computer system interface (SCSI) – Part 452: Primary commands-2 (SPC-2)*

IEEE Standard 1394-1995, *High Performance Serial Bus*

IEEE Standard 1394A-2000, *High Performance Serial Bus Amendment 1*