

INTERNATIONAL
STANDARD

ISO/IEC
15041

First edition
1997-04-15

**Information technology — Data
interchange on 90 mm optical disk
cartridges — Capacity: 640 Mbytes per
cartridge**

*Technologies de l'information — Échange de données sur cartouches de
disque optique de 90 mm — Capacité: 640 Mbytes par cartouche*



Reference number
ISO/IEC 15041:1997(E)

Contents

	Page
Section 1 - General	1
1 Scope	1
2 Conformance	2
2.1 Optical disk cartridge (ODC)	2
2.2 Generating system	2
2.3 Receiving system	2
2.4 Compatibility statement	2
3 Normative reference	2
4 Definitions	2
4.1 band	2
4.2 case	2
4.3 Channel bit	2
4.4 clamping zone	2
4.5 control track	2
4.6 Cyclic Redundancy Check (CRC)	2
4.7 defect management	2
4.8 DOW disk	2
4.9 disk reference plane	2
4.10 embossed mark	2
4.11 entrance surface	2
4.12 Error Correction Code (ECC)	2
4.13 field	2
4.14 format	2
4.15 fully embossed disk	3
4.16 fully rewritable disk	3
4.17 groove	3
4.18 hub	3
4.19 interleaving	3
4.20 Kerr rotation	3
4.21 land and groove	3
4.22 logical track	3
4.23 logical ZCAV	3
4.24 mark	3

©ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office · Case Postale 56 · CH-1211 Genève 20 · Switzerland

Printed in Switzerland

4.25 optical disk	3
4.26 optical disk cartridge (ODC)	3
4.27 partially embossed disk	3
4.28 physical track	3
4.29 physical track group	3
4.30 pitch	3
4.31 polarization	3
4.32 read power	3
4.33 recording layer	3
4.34 Reed-Solomon code	3
4.35 sector	3
4.36 space	3
4.37 spindle	4
4.38 substrate	4
4.39 zone	4
5 Conventions and notations	4
5.1 Representation of numbers	4
5.2 Names	4
6 List of acronyms	4
7 General description of the optical disk cartridge	5
8 General requirements	5
8.1 Environments	5
8.1.1 Testing environment	5
8.1.2 Operating environment	5
8.1.3 Storage environment	6
8.1.4 Transportation	6
8.2 Temperature shock	6
8.3 Safety requirements	6
8.4 Flammability	6
9 Reference Drive	6
9.1 Optical system	6
9.2 Optical beam	8
9.3 Read channels	8
9.4 Tracking	8
9.5 Rotation of the disk	9
Section 2 - Mechanical and physical characteristics	9
10 Dimensional and physical characteristics of the case	9
10.1 General description of the case	9
10.2 Reference planes of the case	9
10.3 Dimensions of the case	9
10.3.1 Overall dimensions	9
10.3.2 Location hole	10
10.3.3 Alignment hole	10
10.3.4 Reference surfaces	10
10.3.5 Detents	11
10.3.6 Functional Areas	11
10.3.7 Spindle and head windows	12

10.3.8 Shutter	13
10.3.9 Path for shutter opener and shutter sensor notch	13
10.3.10 Mis-insert protections	14
10.3.11 Gripper slots	14
10.3.12 Label area	15
10.4 Mechanical characteristics	15
10.4.1 Material	15
10.4.2 Mass	15
10.4.3 Edge distortion	15
10.4.4 Compliance	15
10.4.5 Shutter opening force	15
11 Dimensional, mechanical and physical characteristics of the disk	27
11.1 General description of the disk	27
11.2 Reference axis and plane of the disk	27
11.3 Dimensions of the disk	27
11.3.1 Hub dimensions	27
11.3.2 Clamping zone	28
11.4 Mechanical characteristics	28
11.4.1 Material	28
11.4.2 Mass	29
11.4.3 Moment of inertia	29
11.4.4 Imbalance	29
11.4.5 Axial deflection	29
11.4.6 Axial acceleration	30
11.4.7 Radial runout	30
11.4.8 Radial acceleration	30
11.4.9 Tilt	30
11.5 Optical Characteristics	31
11.5.1 Index of refraction	31
11.5.2 Thickness of the substrate	31
11.5.3 Birefringence	31
11.5.4 Vertical Birefringence	31
11.5.5 Reflectance	31
12 Interface between cartridge and drive	32
12.1 Clamping method	32
12.2 Clamping force	32
12.3 Capture cylinder	32
12.4 Disk position in operating condition	32
Section 3 - Format of information	34
13 Geometry of physical tracks	34
13.1 Physical track shape	34
13.2 Direction of track spiral	34
13.3 Physical track pitch	34
14 Track format	34
14.1 Logical Track number	34
14.2 Logical Track layout	34
14.3 Clock frequencies and periods	34
14.4 Radial alignment	35

14.5 Sector number	35
15 Sector format	35
15.1 Sector layout	35
15.2 Sector Mark (SM)	36
15.3 VFO fields	38
15.4 Address Mark (AM)	38
15.5 ID fields	39
15.6 Postambles (PA)	39
15.7 Gap	39
15.8 Sync	40
15.9 Data field	40
15.9.1 User data bytes	40
15.9.2 CRC and ECC bytes	40
15.9.3 Resync bytes	40
15.10 Buffer field	40
16 Recording code	41
17 Format of the Information Zone	42
17.1 General description of the Information Zone	42
17.2 Division of the Information Zone	42
17.2.1 Initial Zone	42
17.2.2 Acquire Zone	42
17.2.3 Test Zones	42
17.2.4 Control Zone	44
17.2.5 Data Zone	44
17.2.6 Buffer Zones	45
18 Format of the Data Zone	45
18.1 Buffer tracks and Test tracks in the Data Zone	46
18.2 Defect Management Areas (DMAs)	46
18.3 Disk Definition Structure (DDS)	47
18.3.1 Fully rewritable disks	49
18.3.2 Fully embossed disks	49
18.3.3 Partially embossed disks	50
18.4 Partitioning	50
18.4.1 Fully rewritable disks	50
18.4.2 Partially embossed disks	50
18.4.3 Fully embossed disks	50
19 Defect management	52
19.1 Rewritable groups: Spare sectors	52
19.1.1 Initialization of the disk	52
19.1.2 Certification	52
19.1.3 Disks not certified	52
19.1.4 Write procedure	53
19.1.5 Primary Defect List (PDL)	53
19.1.6 Secondary Defect List (SDL)	53
19.2 Embossed groups: Parity sectors	54

Section 4 - Characteristics of embossed information	56
20 Method of testing	56
20.1 Environment	56
20.2 Use of the Reference Drive	56
20.2.1 Optics and mechanics	56
20.2.2 Read power	56
20.2.3 Read channels	56
20.2.4 Tracking	56
20.3 Definition of signals	56
21 Signals from grooves	58
21.1 Cross-track signal	58
21.2 Cross-Track minimum signal	58
21.3 Push-pull signal	58
21.4 Divided push-pull signal	59
21.5 Phase depth	59
21.6 Track location	59
22 Signals from Headers	60
22.1 Sector Mark	60
22.2 VFO1 and VFO2	60
22.3 Address Mark, ID field and Postamble	60
22.4 Timing jitter	60
23 Signals from embossed Recording fields	60
23.1 Signal amplitude	60
23.2 Modulation method offset	61
23.3 Timing jitter	61
Section 5 - Characteristics of the recording layer	62
24 Method of testing	62
24.1 Environment	62
24.2 Reference Drive	62
24.2.1 Optics and mechanics	62
24.2.2 Read power	62
24.2.3 Read channel	62
24.2.4 Tracking	62
24.2.5 Signal detection for testing purposes	62
24.3 Write conditions	62
24.3.1 Write pulse and power	62
24.3.2 Write magnetic field	65
24.3.3 2 T and 4 T pulse power determination	65
24.3.4 Media power sensitivity	65
24.4 Erase conditions	65
24.4.1 Erase power	66
24.4.2 Erase magnetic field	66
24.5 Definition of signals	66
25 Magneto-optical characteristics	66
25.1 Figure of merit	66
25.2 Imbalance of the magneto-optical signal	66

26	Write characteristics	67
26.1	Resolution	67
26.2	Narrow-band signal-to-noise ratio	67
26.3	Cross-talk ratio	68
26.3.1	Rewritable track test method	68
26.4	Timing Jitter	68
26.5	Media thermal interaction	68
27	Erase power determination	69
Section 6	- Characteristics of user data	70
28	Method of testing	70
28.1	Environment	70
28.2	Reference Drive	70
28.2.1	Optics and mechanics	70
28.2.2	Read power	70
28.2.3	Read amplifiers	70
28.2.4	Mark Quality	70
28.2.5	Channel bit clock	71
28.2.6	Binary-to-digital converters	71
28.2.7	Error correction	71
28.2.8	Tracking	71
29	Minimum quality of a sector	71
29.1	Headers	71
29.1.1	Sector Mark	71
29.1.2	ID fields	71
29.2	User-written data	71
29.2.1	Recording field	71
29.2.2	Byte errors	71
29.2.3	Modulation method offset	71
29.2.4	Timing jitter	72
29.3	Embossed data	72
29.3.1	Byte errors	72
30	Data interchange requirements	72
30.1	Tracking	72
30.2	User-written data	72
30.3	Embossed data	72
30.4	Quality of disk	72
Annexes		
A	- Edge distortion test	73
B	- Compliance test	75
C	- CRC for ID fields	77
D	- Interleave, CRC, ECC, Resync for the data field	78
E	- Contents of the Control Zone	84
F	- Determination of the Resync patterns	91
G	- Measurement of the figure of merit	96

H - Read Channel for measuring NBSNR and jitter	97
J - Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media	100
K - Air cleanliness class 100 000	102
L - Position of the cartridge relative to the reference planes	103
M - Relaxation by zones of the requirements for signals	104
N - Test method for measuring the adsorbent force of the hub	105
P - Measurement implementation for Cross-track signal	107
Q - Track deviation measurement	108
R - Derivation of the operating climatic environment	112
S - Transportation	117
T - Office environment	118
U - Values to be implemented in existing and future standards	119
V - Measurement of the vertical birefringence of the substrate	120
W - Sector retirement guidelines	122
X - Laser power calibration for evaluation of media power sensitivity	123

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 15041 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Optical disk cartridges for information interchange*.

Annexes A to P form an integral part of this International Standard. Annexes Q to X are for information only.

Information technology — Data interchange on 90 mm optical disk cartridges — Capacity: 640 Mbytes per cartridge

Section 1 - General

1 Scope

This International Standard defines the characteristics of 90 mm Optical Disk Cartridges (ODC) with a capacity of 640 Mbytes per Cartridge. The Standard specifies five related, but different implementations of such cartridges, viz.

Type R/W Provides for data to be written, read and erased many times over the whole recording surface of the disk using the thermo-magnetic and magneto-optical effects.

Type DOW Provides for data to be written and read many times over the whole recording surface of the disk, using the direct overwrite thermo-magnetic and magneto-optical effects requiring a single external magnetic field.

Type P-ROM Provides for a part of the disk surface to be embossed by stamping or other means. This part of the disk is read without recourse to the magneto-optical effect. All parts which are not embossed provide for data to meet the requirements of Type R/W.

Type P-DOW Provides for a part of the disk surface to be embossed by stamping or other means. This part of the disk is read without recourse to the magneto-optical effect. All parts which are not embossed provide for data to meet the requirements of Type DOW.

Type O-ROM Provides for the whole of the disk surface to be embossed and reproduced by stamping or other means. This type of disk is read without recourse to the magneto-optical effect.

Type R/W and Type DOW are also referred to as "fully rewritable", Type P-ROM and Type P-DOW as "partially embossed" and Type O-ROM as "fully embossed".

For each Type, this International Standard provides for 512-byte and 2 048-byte sectors. All sectors on a disk are of the same size.

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the environments in which the cartridges are to be operated and stored;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written; including the physical disposition of the tracks and sectors, the error correction codes, and the modulation method used;
- the characteristics of the embossed information on the disk;
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

This International Standard provides for interchange between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical disk cartridge (ODC): A claim of conformance with this International Standard shall specify the Type of the ODC. It shall be in conformance if it meets all mandatory requirements specified herein for that Type.

2.2 Generating system: A claim of conformance with this International Standard shall specify which Type(s) is (are) supported. A system generating an ODC for interchange shall be in conformance with this International Standard if it meets the mandatory requirements of this International Standard for the Type(s) specified.

2.3 Receiving system: A claim of conformance with this International Standard shall specify which Type(s) is (are) supported. A system receiving an ODC for interchange shall be in conformance with this International Standard if it is able to process any recording made on the cartridge in accordance with 2.1 on the Type(s) specified.

2.4 Compatibility statement: A claim of conformance with this International Standard shall include a statement listing any other International Standard supported by the system for which conformance is claimed. This statement shall specify the number of the Standard(s), the ODC type(s) supported (where appropriate) and whether support includes reading or both reading and writing.

3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 950:1991, *Safety of information technology equipment, including electrical business equipment.*