INTERNATIONAL STANDARD

150/IEC 17417

First edition 2011-12-01

Information technology —
Telecommunications and information
exchange between systems — Short
Distance Visible Light Communication
(SDVLC)

Technologies de l'information — Téléinformatique — Communication à courte distance utilisant la lumière visible (SDVLC)





COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Forewordv				
Introductionvi				
1	Scope	1		
2	Conformance	1		
3	Normative references	1		
4	Terms,definitions and abbreviations	2		
5	Conventions and notations	6		
6	General	6		
7	Physical Layer			
8	Transmitter and Receiver Block Diagram	7		
8.1	Transmitter to Receiver Link			
8.2 8.2.1	Data Encoding			
8.2.2	2B4B Data Encoding			
8.3	Modulation			
8.4	Bit Order	8		
9	Frame Formats	8		
9.1	Frame Structure overview			
9.2	Frame Structure Detail	_		
9.2.1	Start Indicator Structure			
9.2.2 9.3	Control Header Structure			
9.3 9.3.1	MAC PD0 Structure			
9.3.2	Payload			
9.3.3	Payload CRC			
9.4	Visible Frame			
9.4.1	Visible Pattern			
9.5	Cyclic Redundancy Check (CRC)	16		
10	Connection Procedure	16		
11	Association Operation Messages	17		
11.1	Association Request (AS-REQ)			
11.2	Association Response (AS-RSP)			
11.3	Association Acknowledge (AS-ACK)			
11.4	Disassociation Request (DAS-REQ)			
11.5	Disassociation Response (DAS-RSP)			
11.6	Disassociation Acknowledge (DAS-ACK)			
12	Data Burst Modes Operation			
12.1	Periodic Burst Mode			
12.1.1 12.1.2	Burst Request Message (BR-REQ)			
12.1.2	Aperiodic Burst Mode			
	Aperiodic Burst Request Message (ABR-REQ)			
	Aperiodic Burst Response Message (ABR-RSP)			
13	Data Encoding Change			
13.1	ENC-REQ (Data Encoding Change Request)			

ISO/IEC 17417:2011(E)

13.2	ENC-RSP (Data Encodin	ng Change Response	9)28
	Lito itoi (Data Liicoan	ig onlange response	// ···································

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 17417 was prepared by Ecma International (as ECMA-397) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Introduction

Short Distance Visible Light Communication (SDVLC) uses visible light LEDs for data communication. In most cases, LEDs with the primary purpose of illumination will take on the secondary purpose of acting as a digital data communication source; in other cases the LED's primary purpose will be data communication while the secondary purpose will be to communicate visible status to the user. With the extension of the application of LEDs from the primary purpose of illumination to the secondary purpose of data communication, VLC can be also applied to short range data communication.

With SDVLC, "what you see is what you send". One possible application of SDVLC is high speed mobile-to-mobile communication.

Information technology — Telecommunications and information exchange between systems — Short Distance Visible Light Communication (SDVLC)

1 Scope

This International Standard specifies a phsical layer (PHY) and medium access control (MAC) for communication of up to 10 cm distance with an f_m of 120 MHz using visual light with the wavelength between 380 nm and 780 nm.

In addition it specifies human-detectable brightness control that is independent of the modulation for the data transfer.

2 Conformance

Conformant implementations:

- have both a Transmitter and a Receiver;
- use 8B10B encoding and may use 2B4B encoding;
- use an f_m of 120 MHz as specified in 8.3.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 18092:2004, Information technology — Telecommunications and information exchange between systems — Near Field Communication — Interface and Protocol (NFCIP-1)

ISO/IEC 7498-1, Information technology — Open Systems Interconnection — Basic Reference Model: The Basic Model

ISO/IEC 14165-251, Information technology — Fibre Channel — Part 251: Framing and Signaling (FC-FS)

ITU-T Z.100, Specification and Description Language (SDL)

RFC 791, Internet Protocol — DARPA Internet Program — Protocol Specification