



ISO/IEC 17760-101

Edition 1.0 2015-06

INTERNATIONAL STANDARD



**Information technology – AT attachment 8 –
Part 101: ATA/ATAPI Command Set (ACS)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-2695-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	14
INTRODUCTION	16
1 Scope	17
2 Normative references	17
3 Terms, definitions and conventions	18
3.1 Terms and definitions	18
3.2 Conventions	25
3.2.1 Overview	25
3.2.2 Precedence	25
3.2.3 Lists	26
3.2.4 Keywords	26
3.2.5 Numbering	27
3.2.6 Bit conventions	28
3.2.7 State diagram conventions	28
3.2.8 Byte, word, DWord, and QWord Relationships	29
3.2.9 ATA string convention	31
4 Feature set definitions	32
4.1 Overview	32
4.2 General feature set	32
4.3 The PACKET feature set	33
4.3.1 Overview	33
4.3.2 Identification of PACKET feature set devices	34
4.3.3 Signature for ATAPI devices	34
4.3.4 The PACKET command	34
4.4 48-bit Address feature set	34
4.5 Advanced Power Management (APM) feature set	35
4.6 Automatic Acoustic Management (AAM) feature set	35
4.7 CompactFlash Association (CFA) feature set	35
4.8 Device Configuration Overlay (DCO) feature set	36
4.9 Free-fall Control feature set	38
4.10 General Purpose Logging (GPL) feature set	38
4.11 Host Protected Area (HPA) feature set	39
4.11.1 HPA overview	39
4.11.2 HPA security extensions	39
4.11.3 28-bit and 48-bit HPA commands interactions	39
4.11.4 IDENTIFY DEVICE data	41
4.11.5 Determination of SET MAX security extension status	41
4.11.6 HPA State Transition Diagrams	41
4.12 Long Logical Sector (LLS) feature set	56
4.13 Long Physical Sector (LPS) feature set	58
4.14 Media Card Pass Through Command feature set	60
4.15 Native Command Queuing (NCQ) feature set	60
4.15.1 Overview	60
4.15.2 Command Phases	61

4.16 NV Cache feature set	61
4.16.1 Overview	61
4.16.2 Pinning	61
4.16.3 NV Cache Management	62
4.16.4 Rotating media state after power-on event	62
4.17 NV Cache Power Management feature set	62
4.18 Power Management feature set	63
4.18.1 Overview	63
4.18.2 Power management commands	63
4.18.3 Standby timer	64
4.18.4 Power modes	64
4.19 Power-Up In Standby (PUIS) feature set	66
4.20 Security feature set	66
4.20.1 Overview	66
4.20.2 Passwords	67
4.20.3 Master Password Capability	67
4.20.4 Frozen Mode	67
4.20.5 Commands	67
4.20.6 IDENTIFY DEVICE data	67
4.20.7 Security initial setting	68
4.20.8 Password rules	68
4.20.9 Password attempt counter	68
4.20.10 Security states	69
4.20.11 Master Password Identifier feature	78
4.21 Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set	79
4.21.1 Overview	79
4.21.2 Device SMART data structure	79
4.21.3 Background data collection	79
4.21.4 Off-line/Captive mode data collection	79
4.21.5 Threshold exceeded condition	79
4.21.6 SMART feature set commands	79
4.21.7 SMART operation with power management modes	79
4.21.8 SMART device error log reporting	80
4.22 Software Settings Preservation (SSP) feature set	80
4.23 Streaming feature set	81
4.23.1 Streaming feature set overview	81
4.23.2 Streaming commands	81
4.24 Tagged Command Queuing (TCQ) feature set	82
4.24.1 Overview	82
4.24.2 Queueing	83
4.25 Trusted Computing feature set	83
4.26 Write-Read-Verify feature set	84
5 ATA protocols	86
6 Normal and Error Output field descriptions	87
6.1 Overview	87
6.2 Status field	87
6.2.1 Overview	87
6.2.2 Busy bit	87
6.2.3 Check Condition bit	87

6.2.4 Data Request bit	87
6.2.5 Deferred Write Error bit	87
6.2.6 Device Fault bit	88
6.2.7 Device Ready bit	88
6.2.8 Error bit	88
6.2.9 Service bit	88
6.2.10 Stream Error bit	88
6.2.11 Transport Dependent (TD)	88
6.3 Error field	89
6.3.1 Overview	89
6.3.2 Abort bit	89
6.3.3 Attempted Partial Range Removal bit	89
6.3.4 Command Completion Time Out bit	89
6.3.5 End of Media bit	89
6.3.6 ID Not Found bit	89
6.3.7 Illegal Length Indicator bit	90
6.3.8 Insufficient LBA Range Entries Remaining bit	90
6.3.9 Insufficient NV Cache Space bit	90
6.3.10 Interface CRC bit	90
6.3.11 Media Error bit	90
6.3.12 Sense Key field	90
6.3.13 Uncorrectable Error bit	90
6.4 Interrupt Reason field	90
6.4.1 Overview	90
6.4.2 Command/Data bit	90
6.4.3 Input/Output (I/O) bit	90
6.4.4 Release bit	91
6.4.5 Tag field	91
6.5 Count field	91
6.5.1 Overview	91
6.5.2 NCQ Tag field	91
6.6 SActive field	91
6.7 SATA Status	91
7 Command descriptions	92
7.1 Command description introduction	92
7.1.1 Overview	92
7.1.2 Command Name - Command Code [/Subcommand Code], Command Protocol	92
7.1.3 Feature Set	92
7.1.4 Inputs	93
7.1.5 Normal Outputs	93
7.1.6 Error Outputs	94
7.1.7 Input From the Device to the Host Data Structure	94
7.1.8 Output From the Host to the Device Data Structure	95
7.1.9 Unsupported commands	95
7.2 CFA ERASE SECTORS - C0h, Non-Data	95
7.3 CFA REQUEST EXTENDED ERROR CODE - 03h, Non-Data	96
7.4 CFA TRANSLATE SECTOR - 87h, PIO Data-In	98
7.5 CFA WRITE MULTIPLE WITHOUT ERASE - CDh, PIO Data-Out	99
7.6 CFA WRITE SECTORS WITHOUT ERASE - 38h, PIO Data-Out	100

7.7 CHECK MEDIA CARD TYPE - D1h, Non-Data	101
7.8 CHECK POWER MODE - E5h, Non-Data	102
7.9 CONFIGURE STREAM - 51h, Non-Data	103
7.10 Device Configuration Overlay (DCO)	104
7.10.1 DCO Overview	104
7.10.2 DEVICE CONFIGURATION FREEZE LOCK - B1h/C1h, Non-Data	105
7.10.3 DEVICE CONFIGURATION IDENTIFY - B1h/C2h, PIO Data-In	106
7.10.4 DEVICE CONFIGURATION RESTORE - B1h/C0h, Non-Data	110
7.10.5 DEVICE CONFIGURATION SET - B1h/C3h, PIO Data-Out	111
7.11 DEVICE RESET - 08h, Device Reset	118
7.12 DOWNLOAD MICROCODE - 92h, PIO Data-Out/Non-Data	119
7.13 EXECUTE DEVICE DIAGNOSTIC - 90h, Execute Device Diagnostic	121
7.14 FLUSH CACHE - E7h, Non-Data	122
7.15 FLUSH CACHE EXT - EAh, Non-Data	124
7.16 IDENTIFY DEVICE - EC _h , PIO Data-In	125
7.17 IDENTIFY PACKET DEVICE - A1h, PIO Data-In	163
7.18 IDLE - E3h, Non-Data	181
7.19 IDLE IMMEDIATE - E1h, Non-Data	182
7.20 Non-Volatile Cache	183
7.20.1 NV Cache Overview	183
7.20.2 NV Cache Power Management Overview	184
7.20.3 ADD LBA(S) TO NV CACHE PINNED SET - B6h/10h, DMA.....	184
7.20.4 FLUSH NV CACHE - B6h/14h, Non-Data	186
7.20.5 NV CACHE DISABLE- B6h/16h, Non-Data.....	187
7.20.6 NV CACHE ENABLE - B6h/15h, Non-Data.....	188
7.20.7 QUERY NV CACHE MISSES - B6h/13h, DMA	189
7.20.8 QUERY NV CACHE PINNED SET - B6h/12h, DMA	191
7.20.9 REMOVE LBA(S) FROM NV CACHE PINNED SET - B6h/11h, DMA/Non-Data.....	192
7.20.10 RETURN FROM NV CACHE POWER MODE - B6h/01h, Non-Data	194
7.20.11 SET NV CACHE POWER MODE - B6h/00h, Non-Data.....	195
7.21 NOP - 00h, Non-Data	196
7.22 PACKET - A0h, Packet	197
7.23 READ BUFFER - E4h, PIO Data-In	199
7.24 READ DMA - C8h, DMA	200
7.25 READ DMA EXT - 25h, DMA	201
7.26 READ DMA QUEUED - C7h, DMA Queued	202
7.27 READ DMA QUEUED EXT- 26h, DMA Queued	203
7.28 READ FPDMA QUEUED - 60h, DMA Queued	205
7.29 READ LOG EXT - 2Fh, PIO Data-In	206
7.30 READ LOG DMA EXT - 47h, DMA	207
7.31 READ MULTIPLE - C4h, PIO Data-In	208
7.32 READ MULTIPLE EXT - 29h, PIO Data-In	209
7.33 READ NATIVE MAX ADDRESS - F8h, Non-Data	210
7.34 READ NATIVE MAX ADDRESS EXT - 27h, Non-Data	211
7.35 READ SECTOR(S) - 20h, PIO Data-In	212
7.36 READ SECTOR(S) EXT - 24h, PIO Data-In	213
7.37 READ STREAM DMA EXT - 2Ah, DMA	214

7.38 READ STREAM EXT - 2Bh, PIO Data-In	216
7.39 READ VERIFY SECTOR(S) - 40h, Non-Data	217
7.40 READ VERIFY SECTOR(S) EXT - 42h, Non-Data	218
7.41 SECURITY DISABLE PASSWORD - F6h, PIO Data-Out	219
7.42 SECURITY ERASE PREPARE - F3h, Non-Data	220
7.43 SECURITY ERASE UNIT - F4h, PIO Data-Out	221
7.44 SECURITY FREEZE LOCK - F5h, Non-Data	223
7.45 SECURITY SET PASSWORD - F1h, PIO Data-Out	224
7.46 SECURITY UNLOCK - F2h, PIO Data-Out	225
7.47 SERVICE - A2h, DMA Queued	227
7.48 SET FEATURES - EFh, Non-Data	228
7.48.3 Enable/disable 8-bit PIO data transfer	230
7.48.4 Enable/disable volatile write cache	230
7.48.5 Set transfer mode	230
7.48.6 Enable/disable the APM feature set	231
7.48.7 Enable/disable the PUIS feature set	232
7.48.8 PUIS feature set device spin-up	232
7.48.9 Enable/disable CFA power mode 1	232
7.48.10 Enable/Disable Write-Read-Verify feature set	233
7.48.11 Enable/disable the AAM feature set	233
7.48.12 Set Maximum Host Interface Sector Times	234
7.48.13 Enable/disable read look-ahead	234
7.48.14 Enable/disable release interrupt	235
7.48.15 Enable/disable SERVICE interrupt	235
7.48.16 Enable/disable reverting to defaults	235
7.48.17 Enable/Disable the Free-fall Control feature set	235
7.48.18 Enable/Disable SATA feature	235
7.49 SET MAX	237
7.49.2 SET MAX ADDRESS - F9h, Non-Data	238
7.49.3 SET MAX FREEZE LOCK - F9h/04h, Non-Data	240
7.49.4 SET MAX LOCK - F9h/02h, Non-Data	241
7.49.5 SET MAX SET PASSWORD - F9h/01h, PIO Data-Out	242
7.49.6 SET MAX UNLOCK - F9h/03h, PIO Data-Out	243
7.50 SET MAX ADDRESS EXT - 37h, Non-Data	245
7.51 SET MULTIPLE MODE - C6h, Non-Data	246
7.52 SLEEP - E6h, Non-Data	247
7.53 SMART	248
7.53.2 SMART DISABLE OPERATIONS - B0h/D9h, Non-Data	249
7.53.3 SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE - B0h/D2h, Non-Data	250
7.53.4 SMART ENABLE OPERATIONS - B0h/D8h, Non-Data	251
7.53.5 SMART EXECUTE OFF-LINE IMMEDIATE - B0h/D4h, Non-Data	253
7.53.6 SMART READ DATA - B0h/D0h, PIO Data-In	257
7.53.7 SMART READ LOG - B0h/D5h, PIO Data-In	262
7.53.8 SMART RETURN STATUS - B0h/DAh, Non-Data	263
7.53.9 SMART WRITE LOG - B0h/D6h, PIO Data-Out	264
7.54 STANDBY - E2h, Non-Data	265
7.55 STANDBY IMMEDIATE - E0h, Non-Data	266
7.56 TRUSTED NON-DATA - 5Bh, Non-Data	267

7.57 TRUSTED RECEIVE - 5Ch, PIO Data-In	268
7.58 TRUSTED RECEIVE DMA - 5Dh, DMA	271
7.59 TRUSTED SEND - 5Eh, PIO Data-Out	273
7.60 TRUSTED SEND DMA - 5Fh, DMA	275
7.61 WRITE BUFFER - E8h, PIO Data-Out	276
7.62 WRITE DMA - CAh, DMA	277
7.63 WRITE DMA EXT - 35h, DMA	278
7.64 WRITE DMA FUA EXT - 3Dh, DMA	279
7.65 WRITE DMA QUEUED - CCh, DMA Queued	279
7.66 WRITE DMA QUEUED EXT - 36h, DMA Queued	282
7.67 WRITE DMA QUEUED FUA EXT - 3Eh, DMA Queued	284
7.68 WRITE FPDMA QUEUED - 61h, DMA Queued	285
7.69 WRITE LOG EXT - 3Fh, PIO Data-Out	286
7.70 WRITE LOG DMA EXT - 57h, DMA	287
7.71 WRITE MULTIPLE - C5h, PIO Data-Out	288
7.72 WRITE MULTIPLE EXT - 39h, PIO Data-Out	289
7.73 WRITE MULTIPLE FUA EXT - CEh, PIO Data-Out	290
7.74 WRITE SECTOR(S) - 30h, PIO Data-Out	291
7.75 WRITE SECTOR(S) EXT - 34h, PIO Data-Out	292
7.76 WRITE STREAM DMA EXT - 3Ah, DMA	293
7.77 WRITE STREAM EXT - 3Bh, PIO Data-Out	295
7.78 WRITE UNCORRECTABLE EXT - 45h, Non-Data	296
8 SCT Command Transport	298
8.1 Overview	298
8.1.1 General	298
8.1.2 SCT command nesting and interspersing with standard commands	298
8.1.3 Resets	298
8.2 Processing SCT commands	299
8.2.1 Processing SCT commands overview	299
8.2.2 SCT capability identification	299
8.2.3 SCT command transfer	299
8.2.4 SCT data transfer	303
8.2.5 SCT status	305
8.3 SCT Command Set	309
8.3.1 Overview	309
8.3.2 SCT Read/Write Long command	310
8.3.3 SCT Write Same command	312
8.3.4 SCT Error Recovery Control command	315
8.3.5 SCT Feature Control command	317
8.3.6 SCT Data Table command	320
9 Normal and Error Outputs	324
9.1 Overview	324
9.2 Normal Outputs	324
9.3 Error Outputs	344
Annex A (normative) – Log definitions	386

Annex B (informative) – Command Set summary.....	407
Annex C (informative) – Design and programming considerations for large physical sector devices	432
Annex D (informative) – How to use SCT commands	434
Annex E (informative) – Implementation Guidelines For 1 024/4 096 Byte Sector Sizes	442
Bibliography	448

FIGURES

Figure 1 – ATA document relationships	16
Figure 2 – State diagram convention	28
Figure 3 – Byte, word, DWord and QWord relationships	29
Figure 4 – Device Configuration Overlay state diagram	37
Figure 5 – HPA Not Set	42
Figure 6 – HPA Set (28).....	43
Figure 7 – HPA Set (48).....	44
Figure 8 – HPA Locked (28)	45
Figure 9 – HPA Locked (48)	46
Figure 10 – LLS and LPS Example.....	59
Figure 11 – Alignment 0.....	59
Figure 12 – Alignment 1	59
Figure 13 – Alignment 3	59
Figure 14 – Power management state diagram.....	64
Figure 15 – Security state diagram	73
Figure 16 – Selective self-test span example	255
Figure C.1 – Unaligned Write Example.....	433
Figure D.1 – Example flowchart for SCT commands	435
Figure D.2 – Example sequence for foreground write same with a repeating pattern	436
Figure D.3 – Example sequence for foreground write same with a repeating sector	436
Figure D.4 – Example sequence for writing data using an SCT command with no background activity	436
Figure D.5 – Example sequence for reading data using an SCT command with no background activity	437
Figure D.6 – Example Sequence for a Non-Data SCT command with no background activity	437
Figure D.7 – Example sequence for writing data using an SCT command with background activity	438
Figure D.8 – Example sequence for a Non-Data SCT command with background activity	439
Figure E.1 – System Dependency Chain	442
Figure E.2 – Mapping Proposals	443
Figure E.3 – Logical to Physical Mapping	443
Figure E.4 – Uncorrectable Error Handling	445
Figure E.5 – Typical HDD Layout Using A Master Boot Record	446

TABLES

Table 1 – Numbering conventions examples	28
Table 2 – ATA string byte swapping	31
Table 3 – ATA firmware revision example	31
Table 4 – Feature Set Summary	32
Table 5 – Block Size By Command	57
Table 6 – Media Card type references	60
Table 7 – Summary of Security States and Characteristics	69
Table 8 – Security Command Actions	70
Table 9 – IDENTIFY settings for Security state SEC1	74
Table 10 – IDENTIFY settings for Security state SEC2	75
Table 11 – IDENTIFY settings for Security state SEC4	76
Table 12 – IDENTIFY settings for Security state SEC5	77
Table 13 – IDENTIFY settings for Security state SEC6	78
Table 14 – Preserved Feature Sets and Settings	80
Table 15 – Status field	87
Table 16 – Error field	89
Table 17 – Interrupt Reason Field	90
Table 18 – Count field	91
Table 19 – Example Inputs	93
Table 20 – Example Normal Output	93
Table 21 – Example Error Output	94
Table 22 – Extended error codes	96
Table 23 – CFA TRANSLATE SECTOR data	98
Table 24 – Device Configuration Overlay Feature field values	104
Table 25 – Device Configuration Identify data structure	107
Table 26 – Device Configuration Overlay (DCO) data structure	112
Table 27 – Count field output for DOWNLOAD MICROCODE requesting the offset transfer method	120
Table 28 – Diagnostic codes	122
Table 29 – IDENTIFY DEVICE data	126
Table 30 – Specific Configuration	143
Table 31 – Minor version number	149
Table 32 – Normal Erase Mode Time	155
Table 33 – Enhanced Erase Mode Time	155
Table 34 – IDENTIFY DEVICE data World Wide Name field (word-based view)	158
Table 35 – IDENTIFY DEVICE data World Wide Name field (byte-based view)	158
Table 36 – Device Nominal Form Factor	160
Table 37 – Nominal Media Rotation Rate	161
Table 38 – Transport minor version number	162
Table 39 – IDENTIFY PACKET DEVICE data	164
Table 40 – Standby timer periods	181
Table 41 – NV Cache Commands	184
Table 42 – NV Cache Power Management Commands	184
Table 43 – Request Pin Data	186
Table 44 – Cache Miss Data	190
Table 45 – Pin Set Data	191
Table 46 – Remove Pin Data	193
Table 47 – NOP Subcommand Code	196

Table 48 – SECURITY DISABLE PASSWORD data content.....	220
Table 49 – SECURITY ERASE UNIT data content	222
Table 50 – SECURITY SET PASSWORD data content	225
Table 51 – SECURITY UNLOCK data content	226
Table 52 – SET FEATURES Feature field definitions.....	228
Table 53 – Transfer modes	231
Table 54 – APM levels	231
Table 55 – Write-Read-Verify Modes.....	233
Table 56 – AAM levels	234
Table 57 – SATA Features	235
Table 58 – SET MAX Feature field values.....	237
Table 59 – SET MAX SET PASSWORD data content	242
Table 60 – SMART Feature field values	248
Table 61 – SMART EXECUTE OFF-LINE IMMEDIATE Subcommands	253
Table 62 – Device SMART data structure	258
Table 63 – Off-line data collection status byte values.....	259
Table 64 – Self-test execution status values	259
Table 65 – Offline Data Collection Capabilities.....	260
Table 66 – TRUSTED RECEIVE Security Protocol field description	269
Table 67 – Security Protocol 00h - SP Specific field descriptions for Protocol 00h	270
Table 68 – TRUSTED RECEIVE parameter data for SP Specific=0000h	270
Table 69 – TRUSTED RECEIVE parameter data for SP Specific=0001h	271
Table 70 – TRUSTED SEND - Security Protocol field description.....	274
Table 71 – Fields to issue an SCT command using SMART WRITE LOG.....	299
Table 72 – Fields to issue an SCT command using WRITE LOG (DMA) EXT.....	300
Table 73 – Successful SCT command response	301
Table 74 – SCT command error response.....	302
Table 75 – Extended Status codes	303
Table 76 – SCT data transfer using SMART READ LOG or SMART WRITE LOG	304
Table 77 – SCT data transfer using the GPL feature set.....	305
Table 78 – SCT status request using SMART READ LOG	306
Table 79 – SCT status request using the GPL feature set	307
Table 80 – Format of SCT status response	307
Table 81 – SCT command format.....	309
Table 82 – SCT Action Codes	309
Table 83 – SCT Read/Write Long command	310
Table 84 – SCT Read/Write Long command status response.....	310
Table 85 – SCT Read/Write Long command Format.....	311
Table 86 – SCT Write Same command	313
Table 87 – SCT Write Same command status response.....	314
Table 88 – SCT Error Recovery Control command	315
Table 89 – SCT Error Recovery Control command status response.....	316
Table 90 – SCT Feature Control command	317
Table 91 – Feature Code List	318
Table 92 – SCT Feature Control command status response.....	319
Table 93 – SCT Data Table command	320
Table 94 – SCT Data Tables (by Table Identifier)	320
Table 95 – Absolute HDA Temperature.....	321
Table 96 – SCT Data Table command status response	323
Table 97 – Error Bit Defined For Normal Output.....	324
Table 98 – Extended Error Code for Normal Output.....	325

Table 99 – Generic Normal Output (No LBA Return Value) for Normal Output.....	326
Table 100 – CFA Normal Output	327
Table 101 – Media Card Type Normal Output	328
Table 102 – Check Power Mode Normal Output	329
Table 103 – Stream Normal Output	330
Table 104 – Device Signatures for Normal Output	331
Table 105 – IDLE Unload Normal Output	332
Table 106 – ATAPI Normal Output	333
Table 107 – Queued Normal Output.....	334
Table 108 – HPA Normal Output	335
Table 109 – SMART Off-Line Immediate Normal Output	336
Table 110 – SMART Return Status Normal Output.....	337
Table 111 – Generic Extended Normal Output.....	338
Table 112 – SETMAX Extended Normal Output.....	339
Table 113 – Queued Extended Normal Output.....	340
Table 114 – NV Cache Normal Output	341
Table 115 – NV Cache Flush Normal Output	342
Table 116 – NCQ Command Acceptance Normal Output	343
Table 117 – NCQ Normal Outputs.....	343
Table 118 – Unsupported Command Error.....	344
Table 119 – CFA Erase Error	345
Table 120 – CFA Write Error	346
Table 121 – CFA & Check Power Mode Abort Error	347
Table 122 – Generic Abort wo/ICRC Error	348
Table 123 – Generic Abort Error.....	349
Table 124 – Trusted Abort Error	350
Table 125 – Generic SET MAX Error.....	351
Table 126 – SET MAX Unlock Error	352
Table 127 – Configure Stream Error.....	353
Table 128 – Flush Cache Error.....	354
Table 129 – Flush Cache Ext Error.....	355
Table 130 – Read DMA Error	356
Table 131 – Read DMA Ext Error	357
Table 132 – Read Log Ext Error	358
Table 133 – Read PIO Error	359
Table 134 – Read Stream Error.....	360
Table 135 – HPA Error.....	361
Table 136 – Write Log Error.....	362
Table 137 – Write Log Ext Error	363
Table 138 – SMART Error	364
Table 139 – Write Extended Error	365
Table 140 – Write Stream Error	366
Table 141 – DCO Set Error.....	367
Table 142 – NOP Error	368
Table 143 – PACKET command Error	369
Table 144 – Read DMA Queued Error.....	370
Table 145 – Read DMA Queued Extended Error	371
Table 146 – SMART Read Log/SMART Read Data Error	372
Table 147 – Read PIO Extended Error	373
Table 148 – Read Native Max Extended Error	374
Table 149 – SETMAX Extended Error	375

Table 150 – Write Error.....	376
Table 151 – Write DMA Error.....	377
Table 152 – Write DMA Queued Error.....	378
Table 153 – NV Cache Add Abort Error.....	379
Table 154 – NV Cache Remove Abort Error.....	380
Table 155 – NV Cache Abort Error	381
Table 156 – NV Cache Abort with Data Transfer Error.....	382
Table 157 – NCQ Command Acceptance Error.....	383
Table 158 – NCQ Write Command Aborted Error	384
Table 159 – NCQ Read Command Aborted Error	385
Table A.1 – Example Log Structure	386
Table A.2 – Log address definition	387
Table A.3 – General Purpose Log Directory	388
Table A.4 – SMART Log Directory.....	388
Table A.5 – Comprehensive error log	389
Table A.6 – General Statistics	390
Table A.7 – Extended Comprehensive SMART error log	391
Table A.8 – Extended Error log data structure.....	392
Table A.9 – Command data structure	392
Table A.10 – Error data structure.....	393
Table A.11 – State field values	393
Table A.12 – Extended Self-test log data structure	394
Table A.13 – Extended Self-test log descriptor entry.....	395
Table A.14 – NCQ Command Error Log	396
Table A.15 – Read Stream Error Log	397
Table A.16 – Stream Error Log Entry.....	398
Table A.17 – SATA Phy Event Counters Format.....	399
Table A.18 – Selective self-test log.....	400
Table A.19 – Selective self-test feature flags.....	401
Table A.20 – Self-test log data structure.....	401
Table A.21 – Self-test log descriptor entry.....	402
Table A.22 – Summary SMART Error log.....	403
Table A.23 – Error log data structure	404
Table A.24 – Command data structure	404
Table A.25 – Error data structure.....	405
Table A.26 – State field values	405
Table A.27 – Write Stream Error Log.....	406
Table B.1 – Command Matrix	407
Table B.2 – Command codes (sorted by command code).....	408
Table B.3 – Command codes (sorted by command name)	412
Table B.4 – Historical Command Assignments.....	415
Table B.5 – Historical SET FEATURE Code Assignments.....	423
Table D.1 – SCT command using SMART WRITE LOG command	440
Table D.2 – SCT command using WRITE LOG EXT command	440

INFORMATION TECHNOLOGY –

AT ATTACHMENT 8 –

Part 101: ATA/ATAPI Command Set (ACS)

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 17760-101 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 17760 series, under the general title *Information technology – ATA attachment 8*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2, as far as was practicable.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

INTRODUCTION

This International Standard standard encompasses the following:

- Clause 1 describes the scope.
- Clause 2 provides normative references for the entire standard.
- Clause 3 provides terms and definitions, abbreviations, and conventions used within the entire standard.
- Clause 4 describes the general operating requirements of the command layer.
- Clause 5 describes the ATA protocols used by the commands in this standard.
- Clause 6 describes Normal and Error Output fields.
- Clause 7 describes commands.
- Clause 8 describes the SCT Command Transport.
- Clause 9 describes command normal and error outputs.
- Annex A describes logs.
- Annex B provides command summaries.
- Annex C describes considerations for using devices with non-512 byte sectors.
- Annex D provides a tutorial on how to use SCT.
- Annex E provides implementation guidelines for 1 024/4 096 byte sectors.

Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.

ATA document relationships

The set of AT Attachment standards consists of this standard and the ATA implementation standards described in AT Attachment – 8 ATA/ATAPI Architecture Model (ATA8-AAM). Figure 1 shows the relationship of this standard to the other standards and related projects in the ATA and SCSI families of standards and specifications.




Figure 1 — ATA document relationships

INFORMATION TECHNOLOGY – AT ATTACHMENT 8 –

Part 101: ATA/ATAPI Command Set (ACS)

1 Scope

This part of ISO/IEC 17760 (ATA8-ACS) specifies the command set host systems use to access storage devices. It provides a common command set for systems manufacturers, system integrators, software suppliers, and suppliers of intelligent storage devices.

This International Standard maintains compatibility with the AT Attachment with Packet Interface - 7 standard (ATA/ATAPI-7), ISO/IEC 24739, while providing additional functions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 14776-453, *Information technology - SCSI Primary Commands - 3 (SPC-3)*¹

ISO/IEC 24739 (all parts), *Information technology – AT Attachment with Packet Interface - 7 (ATA/ATAPI-7 V1 to V3)*²

ISO 7779:1999, *Acoustics - Measurement of airborne noise emitted by information technology and telecommunications equipment*

ANSI INCITS.397-2005/AM 1-2006, *ATA/ATAPI-7 Amendment 1*

ANSI INCITS.452-2008, *AT Attachment-8 - ATA/ATAPI Architecture Model (ATA8-AAM)*

INCITS T13/1697D, *AT Attachment-8 - ATA Serial Transport (ATA8-AST)*

INCITS T13/1698D, *AT Attachment-8 - Parallel Transport (ATA8-APT)*

Serial ATA 2.6 (SATA 2.6) specification. February 2007

Serial ATA 2.5 (SATA 2.5) specification. October 2005

NOTE 1 - For information on the current status of Serial ATA documents, see the Serial ATA International Organization at <http://www.sata-io.org>.

NOTE 2 - For more information on the current status of T10 documents, contact the INCITS Secretariat at 202-737-8888 (phone), 202-638-4922 (fax) or via e-mail at incits@itic.org. To obtain copies of this document, contact Global Engineering at 15 Inverness Way, East Englewood, CO 80112-5704 at 303-792-2181 (phone), 800-854-7179 (phone), or 303-792-2192 (fax), or see <http://www.incits.org>.

CompactFlash Association Specification, Revision 4.1

NOTE 3 - For the CompactFlash Association Specification published by the CompactFlash Association, contact the CompactFlash Association at <http://www.compactflash.org>.

RFC 3280, *Internet X.509 Public Key Infrastructure: Certificate and Certificate Revocation List (CRL) Profile, IETF, 2002*

RFC 3281, *An Internet Attribute Certificate: Profile for Authorization, IETF, 2002*

NOTE 4 - For RFCs contact the Internet Engineering Task Force at <http://www.ietf.org>.

1. ANSI INCITS 408-2005
2. ANSI INCITS 397-2005