
**Information technology — Radio
frequency identification for item
management —**

**Part 3:
Parameters for air interface
communications at 13,56 MHz**

*Technologies de l'information — Identification par radiofréquence
(RFID) pour la gestion d'objets —*

*Partie 3: Paramètres de communications d'une interface d'air à
13,56 MHz*

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	vi
Introduction.....	vii
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions	2
5 Symbols and abbreviated terms	3
5.1 Symbols	3
5.2 Abbreviated terms	4
5.3 Notation	5
6 Requirements: Physical layer, collision management system and protocol values for 13,56 MHz systems	6
6.0 General and applicable to All Modes	6
6.0.1 Presentation as determined in ISO/IEC 18000-1	6
6.0.2 ISO/IEC 18000-3 Interoperability	6
6.0.3 ISO/IEC 18000-3 interrogator conformance/compliance	6
6.0.4 ISO/IEC 18000-3 tag compliance	6
6.0.5 Command structure and extensibility	6
6.0.6 Mandatory commands	6
6.0.7 Optional commands	7
6.0.8 Custom commands	7
6.0.9 Proprietary commands	7
6.1 Physical layer, collision management system and protocols for MODE 1	7
6.1.1 Read/Write system	7
6.1.2 Normative Aspects	7
6.1.3 Conformance and performance measurement aspects	7
6.1.4 Physical Layer	7
6.1.5 Protocol and collision management operating method	7
6.1.6 Commands	8
6.1.7 Parameter tables for interrogator to tag link	8
6.1.8 Parameter tables for tag to interrogator link	11
6.2 MODE 2: Physical layer, collision management system and protocols for MODE 2	14
6.2.1 Normative aspects: physical and media access control (MAC) parameters: interrogator to tag link	15
6.2.2 Tag to interrogator link	17
6.2.3 Description of operating method	20
6.2.4 Protocol parameters	25
6.2.5 Description of protocol operating method	25
6.2.6 Collision management parameters	41
6.2.7 Description of collision management parameters operating method (informative)	41
6.2.8 Tag order sequencing	49
6.2.9 Commands	49
6.2.10 Air interface application layer	49
6.2.11 Optional Functionality	49
6.3 MODE 3: Physical layer, collision management system and protocols for MODE 3	52
6.3.1 Protocol overview	52
6.3.2 General	52
6.3.3 Physical layer, collision management system and protocols	53

7	Marking of equipment	124
Annex A	(informative) MODE 1: mandatory and optional commands required to support the ISO/IEC 15962 data protocol.....	125
Annex B	(informative) MODE 2 and MODE 3: Phase Jitter Modulation	126
Annex C	(normative) MODE3: State transition tables	129
C.1	Present state: Ready	129
C.2	Present state: Arbitrate	130
C.3	Present state: Reply	131
C.4	Present state: Acknowledged.....	132
C.5	Present state: Open	133
C.6	Present state: Secured.....	134
C.7	Present state: Killed (optional).....	136
Annex D	(normative) MODE 3: Command Response Tables	137
D.1	Command response: Power-up.....	137
D.2	Command response: <i>BeginRound</i>.....	137
D.3	Command response: <i>NextSlot</i>	138
D.4	Command response: <i>ResizeRound</i>	138
D.5	Command response: <i>ACK</i>	138
D.6	Command response: <i>NAK</i>	139
D.7	Command response: <i>Req_RN</i>	139
D.8	Command response: <i>Select</i>	139
D.9	Command response: <i>Read</i>	140
D.10	Command response: <i>Write</i>.....	140
D.11	Command response: <i>Kill</i>	141
D.12	Command response: <i>Lock</i>.....	141
D.13	Command response: <i>Access</i>	142
D.14	Command response: <i>BlockWrite</i>	142
D.15	Command response: <i>BlockErase</i>	142
D.16	Command response: <i>BlockPermalock</i>.....	143
D.17	Command response: T₂ timeout	143
D.18	Command response: Invalid command	144
Annex E	(normative) MODE 3: Error codes	145
Annex F	(normative) MODE 3: Slot counter	146
F.1	Slot-counter operation	146
Annex G	(informative) MODE 3: Example slot-count (Q) selection algorithm	147
G.1	Example algorithm an interrogator might use to choose Q.....	147
Annex H	(informative) MODE 3: Example of tag inventory and access.....	148
H.1	ASK Method: Example inventory and access of a single tag	148
H.2	PJM Method: Example inventory and access of a single or multiple tags.....	149
Annex I	(informative) MODE 3: Calculation of 5-bit and 16-bit cyclic redundancy checks	150
I.1	Example CRC-5 encoder/decoder	150
I.2	Example CRC-16 calculations	151
I.3	Example CRC-16c encoder/decoder	151
Annex J	(informative) MODE 3: ASK Method: Interrogator-to-tag link modulation	152
J.1	Baseband waveforms, modulated RF, and detected waveforms	152
Annex K	(informative) MODE 3: Example data flow exchange.....	153
K.1	Overview of the data-flow exchange.....	153
K.2	Tag memory contents and lock-field values.....	153
K.3	Data-flow exchange and command sequence.....	154
Annex L	(informative) MODE 3: Tag Features	155
L.1	Optional Tag passwords	155
L.2	Optional Tag memory banks and memory-bank sizes	155
L.3	Optional Tag commands.....	155
L.4	Optional Tag error-code reporting format.....	155

L.5	Optional Tag functionality	156
L.6	Optional Tag Feature.....	156
Annex M	(informative) Cyclic Redundancy Check (CRC) (16 bit)	157
M.1	The CRC error detection method.....	157
M.2	CRC calculation example.....	157
Annex N	(informative) Cyclic redundancy check (CRC) mode 2 (32 bit).....	159
N.1	The CRC 32 error detection method.....	159
N.2	CRC 32 calculation example	159
N.3	Practical example of CRC 32 calculation	161
Annex O	(informative) Known possible interferences between the MODES determined in this part of ISO/IEC 18000	162
Bibliography	163

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 18000-3 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This third edition cancels and replaces the second edition (ISO/IEC 18000-3:2008), which has been technically revised.

ISO/IEC 18000 consists of the following parts, under the general title *Information technology — Radio frequency identification for item management*:

- *Part 1: Reference architecture and definition of parameters to be standardized*
- *Part 2: Parameters for air interface communications below 135 kHz*
- *Part 3: Parameters for air interface communications at 13,56 MHz*
- *Part 4: Parameters for air interface communications at 2,45 GHz*
- *Part 6: Parameters for air interface communications at 860 MHz to 960 MHz*
- *Part 7: Parameters for active air interface communications at 433 MHz*

Introduction

ISO/IEC 18000 has been developed in order to

- provide a framework to define common communications protocols for Internationally useable frequencies for radio frequency identification (RFID), and, where possible, to determine the use of the same protocols for all frequencies such that the problems of migrating from one to another are diminished;
- minimise software and implementation costs;
- enable system management and control and information exchange to be common as far as is possible.

This part of ISO/IEC 18000 was prepared in accordance with the requirements determined in ISO/IEC 18000-1.

ISO/IEC 18000-1 provides explanation of the concepts behind this part of ISO/IEC 18000.

This part of ISO/IEC 18000 has 3 MODES of operation, intended to address different applications. The detailed technical differences between the MODES are shown in the parameter tables.

This part of ISO/IEC 18000 relates solely to systems operating at 13,56 MHz.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents.

The ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured the ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with the ISO and IEC. Information may be obtained from the following companies.

Contact details	Patent number
EM Microelectronic SA	EP 97 115772.2
Mr Marc Degrauwe, IP manager	EP 0 902 546
Rue des Sors 3	US 151803
CH-2074 Marin, Switzerland	
(T) +41 32 755 51 11	
(F) +41 32 755 54 03	
info@emmicroelectronic.com	
www.emmicroelectronic.com	

Contact details	Patent number
<p>Impinj, Inc. Chris Diorio, CTO 701 N 34th Street, suite 300 Seattle, WA 98103, USA (T) +1 206 834 1115 (F) +1 206 517 5262 diorio@impinj.com www.impinj.com</p>	
<p>Intermec IP Corporation Phyllis T. Turner-Brim, Esq. Legal Department 6001 – 36th Avenue West Everett, WA 98203, USA (T) +1 425-265-2480 (F) +1 425-501-6587 phyllis.turnerbrim@intermec.com</p>	<p>US 5673037 DE 69530547.6 EP 0702323 FR EP0702323 GB EP0702323 KR 204748 TW 318306 US 6172596 US 6400274 (claims 1-10 only) US 6404325 US 5550547 TW 307079 KR 210830 US 5521601 US 5777561 US 5828318 EP 1020044 US 5912632 US 5942987 TW 352492 KR 244844 US 5995019 US 6400274 (claims 11 et. Seq.) US 6288629 US 6812841 US 6812852 US 7427912</p>

Contact details	Patent number
Magellan Technology Pty. Limited IP Manager 65 Johnston St Annandale, NSW 2038, Australia (T) +61 2 9562 9800 (F) +61 2 9518 7620 info@magellan-technology.com	US5302954 SG37971 DE3854478D EP0390822 US5485154 US10/927,957 US6967573 JP2002500465T JP2006-180816 DE69835452 EP1048126 AU2006202886 AU785098 US7248145 US7259654 US11/538,271 US11/538/242 JP2003 526148 JP2006 344227 DE60119910 EP1266458 EP07013773 EP1544782 EP1544788 EP1679635
NXP B.V. Marc Schouten Intellectual Property & Licensing High Tech Campus 32 5656 AE Eindhoven The Netherlands (T) +31 40 27 26951 (F) +31 40 27 42640 marc.schouten@nxp.com	

Contact details	Patent number
TAGSYS, SA Alastair McArthur, CTO 180. Chemin de Saint Lambert 13821 La Penne sur Huveaune FRANCE +33 491 27 57 00 +33 491 27 57 01 alastair.mcarthur@tagsysrfd.com.au www.tagsysrfd.com	US 6,641,036 EP 1232471 US 6992567 EP 1256083 US 6946951 EP 1358644 US 6538564 EP 953181
Texas Instruments Inc. Robby Holland, Licensing Manager P.O. Box 655464, MS 3999 Dallas TX 75256 (T) +1 972 917 4367 (F) +1 972 917 4418 r-holland3@ti.com	EP1 038257 US 09/315708 JP 00-560700 EP 1 034644 US 6442215 CN 1273730A WO00/04686 EP 0669591B AT-PS 401127
Zebra Technologies Corporation Eric McAlpine, IP Counsel Legal Department 333 Corporate Woods Parkway Vernon Hills, IL 60061-3109 (T) +1 847 793 5640 (F) +1 847 955 4514 emcalpine@zebra.com	US 6784787 EP 1031046 EP 1291671 EP 05017862.3 US 5680459 US 5557280 US 5699066 EP 0585132 US 6198381 JP 10-272945 US 5537105 US 5966083 US 5995017

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights. The latest IP submissions to ISO can be found at:

<http://www.iso.org/patents>

Information technology — Radio frequency identification for item management —

Part 3: Parameters for air interface communications at 13,56 MHz

1 Scope

This part of ISO/IEC 18000 provides physical layer, collision management system and protocol values for RFID systems for item identification operating at 13,56 MHz in accordance with the requirements of ISO/IEC 18000-1.

This part of ISO/IEC 18000 provides definitions for systems for each MODE determined in Clause 6 below.

This part of ISO/IEC 18000 defines three non-interfering MODES.

- The MODES are not interoperable.
- The MODES, whilst not interoperable, are non-interfering.

2 Conformance

In order to claim conformance with this part of ISO/IEC 18000, it is necessary to comply with all of the relevant clauses of this part of ISO/IEC 18000 except those marked “optional”. It is also necessary to operate within the local national radio regulations (which may require further restrictions).

Relevant conformance test methods are defined in ISO/IEC TR 18047-3.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 13239, *Information technology — Telecommunications and information exchange between systems — High-level data link control (HDLC) procedures*

ISO/IEC 7816-6, *Identification cards — Integrated circuit cards — Part 6: Interindustry data elements for interchange*

ISO/IEC 15693 (all parts), *Identification cards — Contactless integrated circuit cards — Vicinity cards*

ISO/IEC 15961, *Information technology — Radio frequency identification (RFID) for item management — Data protocol: application interface*

ISO/IEC 18000-3:2010(E)

ISO/IEC 15962, *Information technology — Radio frequency identification (RFID) for item management — Data protocol: data encoding rules and logical memory functions*

ISO/IEC 15963, *Information technology — Radio frequency identification for item management — Unique identification for RF tags*

ISO/IEC 18000-1, *Information technology — Radio frequency identification for item management — Part 1: Reference architecture and definition of parameters to be standardized*

ISO/IEC TR 18046, *Information technology — Automatic identification and data capture techniques — Radio frequency identification device performance test methods*

ISO/IEC TR 18047-3, *Information technology — Radio frequency identification device conformance test methods — Part 3: Test methods for air interface communications at 13,56 MHz*

ISO/IEC 19762 (all parts), *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary*

EPCglobal *Tag Data Standards (Version 1.3 and above)*