



**International
Standard**

ISO/IEC 18000-6

**Information technology — Radio
frequency identification for item
management —**

**Part 6:
General parameters for air
interface communications at 860
MHz to 930 MHz**

*Technologies de l'information — Identification par
radiofréquence (RFID) pour la gestion d'objets —*

*Partie 6: Paramètres de communications d'une interface radio
entre 860 MHz et 960 MHz*

**Fourth edition
2025-10**



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	2
3.1	Terms and definitions	2
3.2	Symbols.....	2
3.3	Abbreviated terms.....	2
4	Conformance	3
4.1	Claiming conformance.....	3
4.2	Interrogator conformance and obligations.....	3
4.3	Tag conformance and obligations.....	3
5	Overview	4
Bibliography		9

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This fourth edition cancels and replaces the third edition (ISO/IEC 18000-6:2013), which has been technically revised.

The main changes are as follows:

- the frequency range has been changed from “860 MHz to 960 MHz” to “860 MHz to 930 MHz”;

ISO/IEC 18000-65 has been added as an optional extension for streaming sensors.

A list of all parts in the ISO/IEC 18000 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

This document describes a passive backscatter radio frequency identification (RFID) system that supports the following system capabilities:

- identification and communication with multiple tags in the field;
- selection of a subgroup of tags for identification or with which to communicate;
- reading from and writing to or rewriting data many times to individual tags;
- user-controlled permanently lockable memory;
- data integrity protection;
- interrogator-to-tag communications link with error detection;
- tag-to-interrogator communications link with error detection;
- support for both passive back-scatter tags with or without batteries.

This document provides an overview for a passive-backscatter, RFID system operating in the 860 MHz to 930 MHz frequency range. The system comprises interrogators, also known as readers, and tags, also known as labels. The general overview describes four types called Type A, Type B, Type C and Type D. Details for each type are defined in the following documents and described in detail in the following paragraphs:

- Type A: ISO/IEC 18000-61
- Type B: ISO/IEC 18000-62
- Type C: ISO/IEC 18000-63
- Type D: ISO/IEC 18000-64

This document, together with ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64, specifies the physical and logical requirements for a passive-backscatter, RFID system operating in the 860 MHz to 930 MHz frequency range.

NOTE The titles of ISO/IEC 18000-61, ISO/IEC 18000-62 and ISO/IEC 18000-64 list an upper frequency range of 960 MHz, which is intended to be modified at their next revision.

An interrogator transmits information to a tag by modulating an RF signal in the given frequency range. The tag receives both information and operating energy from this RF signal. Passive tags are those which receive all of their operating energy from the interrogator's RF waveform. If tags maintain a battery then they may operate using some passive principles; however, they do not necessarily get all their operating energy from the interrogator's RF waveform.

An interrogator receives information from a tag by transmitting a continuous-wave (CW) RF signal to the tag; the tag responds by modifying the reflection coefficient of its antenna, thereby backscattering and modulating an information signal to the interrogator. The system is Interrogator-Talks-First (ITF) for Types A, B and C, meaning that a tag modulates its antenna reflection coefficient with an information signal only after being directed to do so by an interrogator, or TOTAL, meaning that a tag modifies its antenna reflection coefficient with an information signal upon entering an interrogator's field after first listening for interrogator modulation in order to determine if the system is ITF or not. Interrogators and tags are not required to talk simultaneously; rather, communications are half-duplex, meaning that interrogators talk and tags listen, or vice versa.

This document further contains an optional “tag only talks after listening” Type D, an enhanced Tag Talks Only (TTO) technique. Type D uses Pulse-Position Encoding (PPE) or Miller encoding in the return link and does not define a dedicated forward link. In fact, tags may implement one of the types defined in this document (A, B, or C) besides Type D in order to allow enhanced tag access techniques.

Types A, B and C are ITF. Type A uses Pulse-Interval Encoding (PIE) in the forward link and an adaptive ALOHA collision-arbitration algorithm. Type B uses Manchester in the forward link and an adaptive binary-tree collision-arbitration algorithm. Type C uses PIE in the forward link and a random slotted collision-arbitration algorithm.

Type D is TOTAL based on Pulse Position Encoding or Miller $M = 2$ encoded subcarrier.

Information technology — Radio frequency identification for item management —

Part 6:

General parameters for air interface communications at 860 MHz to 930 MHz

1 Scope

This document specifies the air interface for radio frequency identification (RFID) devices operating in the 860 MHz to 930 MHz Industrial, Scientific, and Medical (ISM) band used in item management applications. This document is intended to allow for compatibility and to encourage inter-operability of products for the growing RFID market in the international marketplace.

This document defines the forward and return link parameters for technical attributes including, but not limited to, operating frequency, operating channel accuracy, occupied channel bandwidth, maximum effective isotropic radiated power (EIRP), spurious emissions, modulation, duty cycle, data coding, bit rate, bit rate accuracy, bit transmission order, and, where appropriate, operating channels, frequency hop rate, hop sequence, spreading sequence and chip rate. It further defines the communications protocol used in the air interface.

This document specifies the physical and logical requirements for a passive-backscatter, Interrogator-Talks-First (ITF) or tag-only-talks-after-listening (TOTAL) RFID system.

This document, together with ISO/IEC 18000-61, ISO/IEC 18000-62, ISO/IEC 18000-63 and ISO/IEC 18000-64 specifies the following for the 860 MHz to 930 MHz range:

- physical interactions (the signalling layer of the communication link) between interrogators and tags;
- interrogator and tag operating procedures and commands;
- the collision-arbitration scheme used to identify a specific tag in a multiple-tag environment.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 18000-61, *Information technology — Radio frequency identification for item management — Part 61: Parameters for air interface communications at 860 MHz to 960 MHz Type A*

ISO/IEC 18000-62, *Information technology — Radio frequency identification for item management — Part 62: Parameters for air interface communications at 860 MHz to 960 MHz Type B*

ISO/IEC 18000-63, *Information technology — Radio frequency identification for item management — Part 63: Parameters for air interface communications at 860 MHz to 930 MHz Type C*

ISO/IEC 18000-64, *Information technology — Radio frequency identification for item management — Part 64: Parameters for air interface communications at 860 MHz to 960 MHz Type D*

ISO/IEC 19762, *Information technology — Automatic identification and data capture (AIDC) techniques — Vocabulary*