
**Information technology — JPEG XS
low-latency lightweight image coding
system —**

**Part 2:
Profiles and buffer models**

Technologies de l'information — Système de codage d'images léger à faible latence JPEG XS —

Partie 2: Profils et modèles tampons





COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions.....	1
3.2 Abbreviated terms.....	4
3.3 Symbols.....	4
4 Conventions	6
4.1 Conformance language.....	6
4.2 Operators.....	6
4.2.1 Arithmetic operators.....	6
4.2.2 Logical operators.....	6
4.2.3 Relational operators.....	6
4.2.4 Precedence order of operators.....	6
4.2.5 Mathematical functions.....	7
5 Buffer model	7
5.1 General system block diagram.....	7
5.2 Influencing variables on the required buffer sizes.....	8
5.3 Role of the buffer model.....	9
6 Interpretation of Bayer data	9
Annex A (normative) Profiles, levels and sublevels	11
Annex B (normative) Packet-based JPEG XS decoder model	25
Annex C (normative) Packet-based constant bit rate buffer model	31
Annex D (informative) Encoder model, latency bounds and codestream conformance properties for the packet-based constant bit rate buffer model	37
Annex E (informative) JPEG XS latency analysis	42
Bibliography	49

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This second edition cancels and replaces the first edition (ISO/IEC 21122-2:2019), which has been technically revised.

The main changes are as follows:

- addition of new profiles to compress colour filter array images (CFA images), to allow mathematically lossless image compression, and to compress 4:2:0 colour sampled images.

A list of all parts in the ISO/IEC 21122 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

This document is part of a series of standards for a low-latency lightweight image coding system, denoted as JPEG XS.

While ISO/IEC 21122-1 specifies a full set of compression coding tools needed to satisfy all of the requirements of JPEG XS, a targeted application can often work with a simpler and reduced set of coding tools, and with or without tighter constraints, to meet its targeted goals. For this reason, profiles, levels, and sublevels are defined in this document. These three concepts facilitate partial and reduced complexity implementations of ISO/IEC 21122-1 for such specific application use cases, while also safeguarding interoperability.

This document specifies a limited number of profiles to represent interoperability subsets of the codestream syntax specified in ISO/IEC 21122-1 with each profile serving specific application use cases. In other words, profiles select a subset of the available coding tools. In addition, levels and sublevels provide limits to the maximum throughput in respectively the encoded (codestream) and the decoded (spatial/pixel) domains. In this way, profiles, levels and sublevels allow designing cost-efficient implementations that serve the needs of the desired applications.

In addition to being light-weight, another major requirement of JPEG XS is to allow low end-to-end latency, limited to a fraction of the frame size. To ensure this low-latency property, this document also specifies a buffer model, consisting of a decoder model and a transmission channel model. The models show the interaction of a hypothetical reference decoder, including its smoothing buffer with a constant bitrate channel feeding this buffer. The size of the decoder smoothing buffer is computed from the profile, level, and sublevel. Codestreams are formed such that the buffer of a decoder, operating according to this buffer model, never overflows or underflows. In effect, the buffer model provides encoders with the necessary information to generate codestreams that can be decoded by an arbitrary decoder implementation, ensuring system interoperability.

In addition to the size of the decoder smoothing buffer, end-to-end latency also depends on the latency inherent to each processing step of the encoding-decoding chain whose methods are described in ISO/IEC 21122-1. To help implementers estimate the latency of their device, this document gives extra information on the minimum latency that can be achieved by the different methods described in ISO/IEC 21122-1.

Information technology — JPEG XS low-latency lightweight image coding system —

Part 2: Profiles and buffer models

1 Scope

This document defines a number of subsets of the syntax specified in ISO/IEC 21122-1 as profiles. It also defines lower bounds on the throughput in the decoded domain via levels and the encoded domain via sublevels that a conforming decoder implementation shall support. Furthermore, it defines a buffer model to ensure interoperability between implementations in the presence of a latency constraint.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 21122-1, *JPEG XS low-latency lightweight image coding system — Part 1: Core coding system*