



Edition 1.0 2017-10

TECHNICAL REPORT



Information technology – Sensor network – Guidelines for design in the aeronautics industry: active air-flow control

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 35.110; 49.060

ISBN 978-2-8322-4920-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD						
IN	INTRODUCTION					
1	Scop	e	7			
2	Normative references					
3	Term	s and definitions	7			
4	Symb	ools (and abbreviated terms)	9			
5	Motiv	vations for active air-flow control (AFC)	.11			
	5.1	Skin drag	. 11			
	5.2	Approaches for Aircraft Skin Drag Reduction	.12			
6	Obje	ctives	. 13			
	6.1	General	. 13			
	6.2	Fuel efficiency	. 13			
	6.3	Hybrid dense wired-wireless sensor and actuator networks				
	6.4	Standardized and service oriented wireless sensor architecture				
	6.5	Re/auto/self- configuration				
	6.6	Communication protocols and scalability				
	6.7	Smart actuation profiles and policies	. 14			
	6.8	High rate sensor measurement, synchronous operation and data compression	. 14			
	6.9	Troubleshooting and fail safe operation	. 14			
	6.10	Enabling of wireless communication technologies in aeronautics industry	.14			
	6.11	Integration of wireless technologies with the internal aeronautical communication systems	.14			
	6.12	Design of bidirectional wireless transmission protocols for relaying of				
	C 10	aeronautical bus communication traffic				
	6.13 6.14	Matching of criticality levels of aeronautics industry Internetworking and protocol translation between wireless and wireline	. 14			
	0.14	aeronautical networks	. 14			
7	Syste	em description	. 15			
	7.1	Overview of system operation	. 15			
	7.2	Patch design	. 16			
	7.3	Internal aeronautics network	. 17			
8	Micro	o-sensors and actuators	. 18			
	8.1	Micro-sensors	. 18			
	8.2	Actuators				
9	High	level architecture for aeronautical WSANs				
	9.1	Bubble concept				
	9.2	Layered model				
	9.3	Mapping to ISO/IEC 29182 Sensor Networks Reference Architecture (SNRA)				
10	•	irements for AFC design				
	10.1	Sensing and actuation				
	10.1.					
	10.1.					
	10.1.					
	10.1.					
10.1.5						
	10.1.	6 Sensors synchronicity	.30			

10.1.7 Low power sensor-actuator (patch) consumption	30		
10.1.8 Patch data rate and traffic constraints	30		
10.1.9 Patch low complexity	30		
10.2 Sensor Network Communications	31		
10.2.1 Interference	31		
10.2.2 Wireless range and connectivity	31		
10.3 Aeronautical Network and On-Board Systems			
10.3.1 Full-duplex communications			
10.3.2 Compatibility with avionics internal network (ARINC 664)			
10.3.3 AFC interface			
10.3.4 GS interface			
11 Testing platform and prototype development	32		
12 Scalability	33		
Annex A (informative) System level simulation	36		
A.1 Architecture of the simulator and module description	36		
A.1.1 Fluid modelling domain	36		
A.1.2 Sensor and actuators configuration: patches	36		
A.1.3 Wing design, aircraft configuration, and propagation modelling	36		
A.1.4 Radio resource management	37		
A.2 Simulation metrics	38		
A.2.1 AFC metrics	38		
A.2.2 WSN metrics	39		
Annex B (informative) Turbulent flow modeling	40		
Bibliography	44		
Figure 1 – Drag breakdown in commercial aircraft	11		
Figure 2 – Boundary layer (BL) transition exemplified with a wing profile	12		
Figure 3 – Operation mode of the AFC system	15		
Figure 4 – Architecture of the AFC system			
Figure 5 – Array(s) of patches of sensors/actuators			
Figure 6 – Interaction with internal avionics networks	18		
Figure 7 – Flow control actuators classified by function [22]2			
Figure 8 – Flow control actuators: a) SJA; b) Fliperon2			
Figure 9 – HLA mapping AFC system	22		
Figure 10 – Mapping AFC system to the ISO domain reference architecture view	24		
Figure 11 – Mapping AFC system to the ISO layered reference architecture view	25		
Figure 12 – Mapping AFC system to the ISO sensor node reference architecture	25		
Figure 13 – Mapping AFC system to the ISO physical reference architecture	26		
Figure 14 – Prototype implementation AFC system	33		
Figure 15 – Data rate vs patch size	35		
Figure A.1 – Simulator architecture	38		
Figure B.1 – Characteristics of turbulent flow with different Reynolds numbers (reproduced from [31])	41		

Table 1 – Mapping of AFC system to the HLA layered model	.23
Table 2 – Mapping of AFC architecture to ISO architecture entity and functional models	.27
Table 3 – Mapping of AFC system to ISO architecture interface model	.28

INFORMATION TECHNOLOGY – SENSOR NETWORK – GUIDELINES FOR DESIGN IN THE AERONAUTICS INDUSTRY: ACTIVE AIR-FLOW CONTROL

FOREWORD

- ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of the joint technical committee is to prepare International Standards. However, the joint technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 22560, which is a Technical Report, has been prepared by subcommittee 41: Internet of Things and related technologies, of ISO/IEC joint technical committee 1: Information technology.

This Technical Report has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The number of wireless connections is growing exponentially around the world. Wireless communications are expanding to areas previously reluctant to use this type of technology. In the field of aeronautics, wireless intra-avionics applications are just recently gaining acceptance both in industrial and academic arenas. This late adoption is mainly because wireless transmissions have been conventionally associated with reliability and interference issues. Aeronautics applications on board aircraft are highly critical and therefore the inherent randomness of wireless technologies created lots of skepticism, particularly for sensing, monitoring and control of critical aeronautical subsystems. In addition, uncontrolled wireless transmissions can potentially create interference to other aeronautical subsystems, thus leading to malfunctions and unsafe operation. However, recent interference and reliability studies with state-of-the-art wireless standards suggest safe operation and thus the feasibility of a relatively new research area called wireless avionics intra-communications (WAICs). In the last few years, wireless technology has started to be used on board for systems that conventionally used only wire-line infrastructure (i.e., as replacement of cables). It is also being used for applications which are now only possible thanks to the wireless component (e.g., indoor localization, tracking and wireless power transfer). Examples of potential applications of wireless avionics intra-communications are the following: structure health monitoring, avionics bus communications, smoke sensors, interference monitoring, logistics, identification, replacing of cables, fuel tank sensors, automatic route control based on optimized fuel consumption and weather monitoring, automatic turbulence reduction or active air-flow control, EMI (electromagnetic interference) monitoring, and flexible wiring redundancy design.

The avionics industry will experience a wireless revolution in the years to come. The concept of "fly-by-wireless" opens several issues in design, configuration, security, spectrum management, and interference control. There are several advantages in the use of wireless technologies for the aeronautics industry. They permit reduction of cables in aircraft design, thus reducing weight. Reduction of weight also leads to increased payload capacity, longer ranges, faster speeds, and mainly savings in fuel consumption. The reduction of cables can also improve the flexibility of aircraft design (less manpower for designing complex cabling infrastructure). Additionally, wireless technologies can reach places of aircraft that are difficult to reach by cables, while being relatively immune to electrical cable malfunctions. Wireless technology also provides improved configuration and troubleshooting with over-the-air functionalities of modern radio standards.

This document presents the application of wireless sensor and actuator networks for the dynamic tracking and compensation of turbulent flows across the surface of aircraft. Turbulent flow formation and the associated skin drag effect are responsible for the inefficiency of airplane design and thus act as major factors in increased fuel consumption. The area of active air-flow control represents the convergence of several scientific fields such as: fluid mechanics, sensor networks, control theory, computational fluid dynamics, and actuator design. Due to the high speeds experienced by modern commercial aircraft, dense networks of sensors and actuators are necessary to accurately track the formation of turbulent flows and for counteracting their effects by convenient actuation policies. The use of wireless technologies in this field aims to facilitate the management of the information generated by the large number of sensors, and reduce the need for cables to interconnect all the nodes or groups of nodes (patches) in the network. Additionally, the use of the wireless components opens new issues in joint propagation and turbulence flow modelling. This document presents the design principles of active air-flow control systems using dense wireless/wired sensor networks compliant with the ISO sensor network reference architecture (SNRA). Standardized interfaces will help developers create smart cloud avionics applications that will improve fleet management, optimized route traffic, and computation of actuation profiles for different moments of an aircraft mission. This also lies within the context of future technological concepts such as Internet of things, Big Data, and cloud computing.

INFORMATION TECHNOLOGY – SENSOR NETWORK – GUIDELINES FOR DESIGN IN THE AERONAUTICS INDUSTRY: ACTIVE AIR-FLOW CONTROL

1 Scope

This document describes the concepts, issues, objectives, and requirements for the design of an active air-flow control (AFC) system for commercial aircraft based on a dense deployment of wired/wireless sensor and actuator networks. The objective of this AFC system is to track gradients of pressure across the surface of the fuselage of aircraft. This collected information will be used to activate a set of actuators that will attempt to reduce the skin drag effect produced by the separation between laminar and turbulent flows. This will be translated into increased lift-off forces, higher vehicle speeds, longer ranges, and reduced fuel consumption. The document focuses on the architecture design, module definition, statement of objectives, scalability analysis, system-level simulation, as well as networking and implementation issues using standardized interfaces and service-oriented middleware architectures. This document aims to serve as guideline on how to design wireless sensor and actuator networks compliant with ISO/IEC 29182.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 29182-2:2013, Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 2: Vocabulary and terminology

ISO/IEC 29182-3:2014, Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 3: Reference architecture views

ISO/IEC 29182-4:2013, Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 4: Entity models

ISO/IEC 29182-5:2013, Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 5: Interface definitions