

International Standard

ISO/IEC 22592-2

First edition 2024-01

Office equipment — Print quality measurement methods for colour prints —

Part 2: Registration and magnification accuracy



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: <u>www.iso.org</u> Published in Switzerland

© ISO/IEC 2024 – All rights reserved

Contents

Fore	word		v
Intr	oductio)n	vi
1	Scop	Je	
2	-	native references	
3		ns and definitions	
4		t preparation procedures	
5	4.1 4.2 4.3 4.4 4.5 Gene 5.1	Printing environment. Printing materials Printer settings Printing operations Conditioning the prints after printing eral requirements for measurements Measurement environmental conditions	3 3 3 4 4 4 4
	5.2	Scanner conformance5.2.1General5.2.2Test chart for scanner conformance5.2.3Scanning equipment5.2.4Scanning procedures5.2.5Magnification accuracy of scanner5.2.6Local magnification deviation of scanner5.2.7Goal values5.2.8Compensation for magnification accuracy and local magnification deviationReporting for scanner conformance	
6	Regi 6.1 6.2 6.3 6.4	stration and magnification measurementsGeneralTest chart for registration and magnification for each primary colourTest chart for colour-to-colour variation in registrationRegistration measurement for each primary colour6.4.1Print preparations6.4.2Scanning procedures6.4.3Calculation of side-to-side registration variation6.4.4Calculation of sheet-to-sheet registration variation	9 9 9 10 10 10 10 11
	6.5	 Colour-to-colour registration variation measurement	13 13 13 13 14 14 15 16
	6.6	 Magnification measurement for each primary colour 6.6.1 Print preparations 6.6.2 Scanning procedures 6.6.3 Calculation of magnification variations within printed image 6.6.4 Calculation of side-to-side magnification variation 6.6.5 Calculation of sheet-to-sheet magnification variation 	
	6.7	Reporting for registration and magnification measurements	
7	Repo 7.1 7.2	orting General requirements for reporting Reporting items	
Ann	ex A (in	Iformative) Flatness of prints	
Ann	ex B (in	iformative) Test charts for colour-to-colour variation in registration	

Annex C (normative) Compensation procedure for scanner conformance	1
Annex D (informative) Examples of local magnification measurement on flat bet scanning	
systems	4
Bibliography	80

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iso.org/directiv

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and https://patents.iec.ch. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <u>www.iso.org/iso/foreword.html</u>. In the IEC, see <u>www.iec.ch/understanding-standards</u>.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 28, *Office equipment*.

A list of all parts in the ISO/IEC 22592 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u> and <u>www.iec.ch/national-committees</u>.

Introduction

Measurement methods that quantitatively evaluate geometric property attributes of duplex print sets need to be standardized, as most of the office documents are currently printed as duplex print sets comprising several sheets printed colour images on both surface of substrates.

There are several standard measurement methods to evaluate image quality attributes of printed images formed by office equipment, i.e. colour reproductions, line reproductions, image structures of sharpness and graininess, gloss properties. Included are ISO/IEC 19799, ISO/IEC 24790 and ISO/IEC 29112. ISO/IEC 24790 specifies the measurement methods for large area density uniformity of graininess, mottle and banding, as well as line qualities. ISO/IEC 29112 specifies methods for measuring sharpness attributes of edge blurriness and raggedness, special frequency response, etc. ISO/IEC 19799 specifies the methods for gloss uniformity. By utilizing those documents, users can obtain consistent test results when they comply with the protocols specified in the documents.

While there are no standard methods to measure colour reproduction consistencies and geometrical accuracies in consecutive printing, and image stabilities in typical use case of print images formed by office equipment and used in office environments. In the current state, each printer distributer and its user can provide test results for those attributes measured by its own test methods and procedures, which are often convenient for its product, resulting in misleading customers in the selection of a printing system suitable for their use cases. The ISO/IEC 22592 series can provide standard methods and procedures for those print image attributes: ISO/IEC 22592-1 for colour consistency, this document for geometrical accuracies, and ISO/IEC 22592-3¹) for image stabilities. By using these International Standards, consistent and comparable test results suitable for typical use cases of office prints can be obtained independent of data providers.

The measurement methods described in this document are used to access geometric properties of a print set formed by a printing system on a substrate. When test results are compared among various printing systems, it is essential to use the same product of substrates and set equivalent printing conditions under default printer settings among the printing systems.

As for the metrics for registration and magnification based on images captured by an RGB scanner, prints with four primary colourants other than cyan, magenta, yellow and black are not suitable for the measurement methods described in this document. For example, if a print includes a light colourant image of a primary colour in addition to a standard colourant image, registration and magnification of this print will not be measured correctly because the complementary colour channel of the primary in a scanned image of the print includes two kinds of sources for registration and magnification.

Electrophotography, thermal inkjet, or piezoelectric inkjet technologies are commonly used to form such prints. The main purpose of this document is to provide objective measurement methods for geometric property attributes of duplex print sets, however, some attributes are also applicable for a set of simplex prints.

This document prescribes the following:

- digital test charts for the measurements in which colour codes and locations in page to be measured are specified,
- a test chart to measure the positional accuracy of a scanner,
- conformance requirements for the positional accuracy of a scanner to utilize registration and magnification measurements,
- measurement methods relating to the registration including accuracy of printed positions to substrate for each colour and printed position variations among colours,
- measurement methods relating to the magnification including absolute magnitude of printed size to input and relative difference in the magnitude among colours,

¹⁾ Under preparation. Stage at the time of publication: ISO/IEC DIS 22592-3:2023.

 measurement methods for the variations of the registration and magnification within a page (withinpage variation), between front and back sides (side-to-side variation), among the sheets in the same print set (sheet-to-sheet variations).

Some attributes, such as the attribute "within a printed image", "sheet-to-sheet variations", are also applicable for a simplex print set comprising several sheets which are printed colour images on one surface of a substrate and no image on the other surface.

Some prints show uneven surfaces caused by thermal fusing process of electrophotographic printers or drying process in ink jet printers as well as by storage humidity changes from a highly humid condition to dry condition. Flatness of a print surface is an important aspect for print integrity. On the other hand, there is no proper measure standardized corresponding well with visual impression of flatness. <u>Annex A</u> describes one of the methods to quantify degree of flatness. A further study needed to include this method into the scope of this document.

In this document, colour codes for the test charts are defined in sRGB colour space specified in IEC 61966-2-1 as is common in office documents.

© ISO/IEC 2024 – All rights reserved

Office equipment — Print quality measurement methods for colour prints —

Part 2: Registration and magnification accuracy

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of this document. Users should therefore consider printing with a colour printer.

1 Scope

This document specifies test methods as well as test charts to measure the geometric property attributes and those variations in duplex colour prints typically used in office environment. This document is applicable to duplex prints comprising several sheets which are printed colour images on both surfaces of a substrate.

"Within-page variation" and "sheet-to-sheet variation" are also applicable for a simplex print set comprising several sheets, which are printed colour images on one surface of a substrate and no image on the other surface.

Prints with four primary colourants other than cyan, magenta, yellow and black are outside the scope of this document.

Included are digital prints formed by using a multifunction or single function printer. When a duplex print set is evaluated, duplex printers which are capable to print images on both sides of substrate automatically are applicable, while simplex printers which require a manual arrangement of substrates between the front side and back side printing to form duplex prints are out of scope of this document. The printers of the maximum applicable substrate size of A4 or larger are suitable for the measurements.

The geometric property attributes included are registration and magnification of a print set.

Microscopic geometrical density variations, such as graininess, mottle and line raggedness, are outside the scope of this document.

The sources of variations considered are locations in a page, print side in a sheet, print order of sheets in a print set, and variations among primary colours.

2 Normative references

There are no normative references in this document.