



**International
Standard**

ISO/IEC 24079

Information technology — Network Controller Sideband Interface (NC-SI) specifications collection

Technologies de l'information — Collection de spécifications pour l'interface entre contrôleur réseau et contrôleur de gestion système (NC-SI)

**First edition
2024-07**



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by DMTF [as DMFT Network Controller Sideband Interface (NC-SI) Specifications Collection] and drafted in accordance with its editorial rules. It was adopted, under the JTC 1 PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Contents

Foreword	xi
Introduction	xiii
1 Scope	1
2 Normative references	2
3 Terms and definitions	3
3.1 Requirement term definitions	3
3.2 NC-SI term definitions	4
3.3 Numbers and number bases	6
3.4 Reserved fields	6
4 Symbols and abbreviated terms	6
5 Network Controller Sideband Interface (NC-SI) Specification (DSP0222)	8
5.1 NC-SI overview	8
5.2 Operational behaviors	14
5.3 Arbitration in configurations with multiple Network Controller packages	35
5.4 Packet definitions	45
5.5 Packet-based and op-code timing	105
5.6 RBT Electrical specification	107
6 Network Controller Sideband Interface (NC-SI) Collection (DSP0261)	114
6.1 NC-SI over MCTP overview	114
6.2 NC-SI over MCTP specific considerations	116
6.3 Supported NC-SI commands	126
6.4 Message types	128
6.5 NC-SI support specific to MCTP transport	132
6.6 Packet-Based Timing Specific to MCTP Binding	135
ANNEX A (normative) Extending the model	136
A.1 Commands extension	136
A.2 Design considerations	136
ANNEX B (informative) Relationship to RMII Specification	137
ANNEX C (informative) Notation and conventions	139
Bibliography	140

Figures

Figure 1 – NC-SI functional block diagram.....	9
Figure 2 – NC-SI traffic flow diagram.....	10
Figure 3 – Example topologies supported by the NC-SI	11
Figure 4 – Network Controller integration options	12
Figure 5 – NC-SI transport stack	13
Figure 6 – NC-SI operational state diagram.....	18
Figure 7 – NC-SI operational state diagram for hardware arbitration operation	19
Figure 8 – MC steps when the MC does not have prior knowledge of hardware arbitration	27
Figure 9 – NC-SI packet filtering flowchart	32
Figure 10 – Basic multi-drop block diagram	36
Figure 11 – Multiple Network Controllers in a ring format	37
Figure 12 – Op-code to RXD relationship	39
Figure 13 – Example TOKEN to transmit relationship	42
Figure 14 – Hardware arbitration state machine	43
Figure 15 – Ethernet frame encapsulation of NC-SI packet data without VLAN tag.....	45
Figure 16 – Example NC-SI signal interconnect topology.....	107
Figure 17 – DC measurements.....	109
Figure 18 – AC measurements.....	110
Figure 19 – Overshoot measurement.....	112
Figure 20 – Undershoot measurement	113
Figure 21 – NC-SI over RBT traffic flow diagram	115
Figure 22 – NC-SI over MCTP traffic flow diagram	116
Figure 23 – Single MCTP EID to multiple NC-SI channels mapping	117
Figure 24 – Multiple MCTP EIDs to multiple NC-SI channels mapping.....	118
Figure 25 – Multiple MCTP transport bindings example.....	121

Tables

Table 1 – Component documents	xi
Table 2 – NC-SI operating state descriptions.....	15
Table 3 – Channel ID format	20
Table 4 – Channel Ready state configuration settings	21
Table 5 – Hardware arbitration di-bit encoding	38
Table 6 – Hardware arbitration op-code format	38
Table 7 – Hardware arbitration states.....	44
Table 8 – Hardware arbitration events.....	44
Table 9 – Ethernet header format	46
Table 10 – Control packet header format	47
Table 11 – Generic example of control packet payload	48
Table 12 – Generic example of response packet payload format	50
Table 13 – Reason code ranges	51
Table 14 – Standard response code values	51
Table 15 – Standard reason code values	52
Table 16 – AEN packet format	52
Table 17 – AEN types	53
Table 18 – Command and response types	53
Table 19 – Example of complete minimum-sized NC-SI command packet	55
Table 20 – Example of complete minimum-sized NC-SI response packet.....	55
Table 21 – Clear Initial State command packet format	56
Table 22 – Clear Initial State response packet format.....	56
Table 23 – Select Package command packet format.....	57
Table 24 – Hardware arbitration disable byte.....	58
Table 25 – Select Package response packet format	58
Table 26 – Deselect Package command packet format.....	59
Table 27 – Deselect Package response packet format	59
Table 28 – Enable Channel command packet format.....	59
Table 29 – Enable Channel response packet format	60
Table 30 – Disable Channel command packet format.....	60
Table 31 – Disable Channel response packet format	61
Table 32 – Reset Channel command packet format	61
Table 33 – Reset Channel response packet format	61

Table 34 – Enable Channel Network TX command packet format.....	62
Table 35 – Enable Channel Network TX response packet format	62
Table 36 – Disable Channel Network TX command packet format.....	62
Table 37 – Disable Channel Network TX response packet format	63
Table 38 – AEN Enable command packet format.....	63
Table 39 – Format of AEN control	64
Table 40 – AEN Enable response packet format	64
Table 41 – Set Link command packet format	65
Table 42 – Set Link bit definitions.....	65
Table 43 – OEM Set Link bit definitions.....	66
Table 44 – Set Link response packet format.....	66
Table 45 – Set Link command-specific reason codes	66
Table 46 – Get Link Status command packet format	67
Table 47 – Get Link Status response packet format	67
Table 48 – Link Status field bit definitions.....	67
Table 49 – Other Indications field bit definitions	71
Table 50 – OEM Link Status field bit definitions (optional)	71
Table 51 – Get Link Status command-specific reason code	71
Table 52 – IEEE 802.1q VLAN fields	72
Table 53 – Set VLAN Filter command packet format	72
Table 54 – Possible settings for Filter Selector field (8-bit field).....	72
Table 55 – Possible settings for Enable (E) field (1-bit field)	72
Table 56 – Set VLAN Filter response packet format	73
Table 57 – Set VLAN Filter command-specific reason code	73
Table 58 – Enable VLAN command packet format	73
Table 59 – VLAN Enable modes	73
Table 60 – Enable VLAN response packet format	74
Table 61 – Disable VLAN command packet format	74
Table 62 – Disable VLAN response packet format.....	75
Table 63 – Set MAC Address command packet format.....	76
Table 64 – Possible settings for MAC Address Number (8-bit field)	76
Table 65 – Possible settings for Address Type (3-bit field).....	76
Table 66 – Possible settings for Enable Field (1-bit field).....	77
Table 67 – Set MAC Address response packet format	77

Table 68 – Set MAC Address command-specific reason code.....	77
Table 69 – Enable Broadcast Filter command packet format	77
Table 70 – Broadcast Packet Filter Settings field.....	78
Table 71 – Enable Broadcast Filter response packet format.....	79
Table 72 – Disable Broadcast Filter command packet format	79
Table 73 – Disable Broadcast Filter response packet format	79
Table 74 – Enable Global Multicast Filter command packet format	80
Table 75 – Bit definitions for Multicast Packet Filter Settings field.....	81
Table 76 – Enable Global Multicast Filter response packet format.....	82
Table 77 – Disable Global Multicast Filter command packet format	83
Table 78 – Disable Global Multicast Filter response packet format.....	83
Table 79 – Set NC-SI Flow Control command packet format	84
Table 80 – Values for the Flow Control Enable field (8-bit field).....	84
Table 81 – Set NC-SI Flow Control response packet format.....	85
Table 82 – Set NC-SI Flow Control command-specific reason code	85
Table 83 – Get Version ID command packet format	85
Table 84 – Get Version ID response packet format.....	85
Table 85 – Get Capabilities command packet format	87
Table 86 – Get Capabilities response packet format.....	88
Table 87 – Capabilities Flags bit definitions.....	88
Table 88 – VLAN Mode Support bit definitions	90
Table 89 – Get Parameters command packet format	90
Table 90 – Get Parameters response packet format.....	91
Table 91 – Get Parameters data definition	92
Table 92 – MAC Address Flags bit definitions	92
Table 93 – VLAN Tag Flags bit definitions	92
Table 94 – Configuration Flags bit definitions	93
Table 95 – Get Controller Packet Statistics command packet format.....	93
Table 96 – Get Controller Packet Statistics response packet format	94
Table 97 – Get Controller Packet Statistics counters	95
Table 98 – Counters Cleared from Last Read Fields format	96
Table 99 – Get NC-SI Statistics command packet format	97
Table 100 – Get NC-SI Statistics response packet format	97
Table 101 – Get NC-SI Statistics counters.....	98

Table 102 – Get NC-SI Pass-through Statistics command packet format.....	98
Table 103 – Get NC-SI Pass-through Statistics response packet format	99
Table 104 – Get NC-SI Pass-through Statistics counters	99
Table 105 – Get Package Status packet format.....	100
Table 106 – Get Package Status response packet format	101
Table 107 – Package Status field bit definitions.....	101
Table 108 – OEM command packet format.....	101
Table 109 – OEM response packet format	102
Table 110 – PLDM Request packet format	102
Table 111 – PLDM Response packet format.....	102
Table 112 – Get Package UUID command packet format	103
Table 113 – Get Package UUID response packet format.....	103
Table 114 – UUID format.....	104
Table 115 – Link Status Change AEN packet format.....	104
Table 116 – Configuration Required AEN packet format	105
Table 117 – Host Network Controller Driver Status Change AEN packet format.....	105
Table 118 – Host Network Controller Driver Status format	105
Table 119 – NC-SI packet-based and op-code timing parameters	106
Table 120 – Physical NC-SI signals	108
Table 121 – DC specifications	109
Table 122 – AC specifications	111
Table 123 – MCTP Message types for NC-SI over MCTP	116
Table 124 – Ordering rules	120
Table 125 – Supported NC-SI commands	126
Table 126 – NC-SI messages encapsulation.....	129
Table 127 – MCTP Transport Header fields	129
Table 128 – MCTP Specific Message Header field	129
Table 129 – Ethernet messages encapsulation	130
Table 130 – MCTP Transport Header fields	131
Table 131 – MCTP Specific Message Header field	131
Table 132 – Get Supported Media Command packet format	132
Table 133 – Get Supported Media Response packet format	132
Table 134 – Get Supported Media Response media descriptors format	133
Table 135 – Transport Specific AENs Enable Command packet format	133

ISO/IEC 24079:2024(en)

Table 136 – Transport Specific AENs Enable field format	134
Table 137 – Transport-specific AENs Enable Response packet format	134
Table 138 – Medium change AEN format.....	134
Table 139 – NC-SI Timing Parameters Specific to MCTP Binding	135

Foreword

The *Network Controller Sideband Interface (NC-SI) Specification* was prepared by the PMCI Working Group. DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability.

Component documents

Table 1 lists the component documents for this specification:

Table 1 – Component documents

Document number	Document title	Version
DSP0222	Network Controller Sideband Interface (NC-SI) Specification (DSP0222)	1.1.1
DSP0261	Network Controller Sideband Interface (NC-SI) Collection (DSP0261)	1.2.3

Acknowledgments

The DMTF acknowledges the following individuals for their contributions to this document:

Editors:

- Eiel Louzoun – Intel Corporation
- Hemal Shah – Broadcom Corporation
- Bob Stevens – Dell
- Tom Slight – Intel Corporation

Contributors:

- Alan Berenbaum – SMSC
- Patrick Caporale – Lenovo
- Philip Chidester – Dell Technologies
- Kelly Couch – Intel Corporation
- Benzi Friedman – Intel Corporation
- Yuval Itkin – Mellanox Technologies and NVIDIA Corporation
- Ira Kalman – Intel Corporation
- Ed Kłodnicki – IBM
- Joe Kozlowski – Dell Technologies
- Patrick Kutch – Intel Corporation
- John Leung – Intel Corporation
- Eiel Louzoun – Intel Corporation
- Patrick Schoeller – Hewlett-Packard Company and Intel Corporation

- Hemal Shah – Broadcom Inc.
- Tom Slaight – Intel Corporation
- Bob Stevens – Dell Technologies

Introduction

Network Controller Sideband Interface (NC-SI) Specification (DSP0222)

In out-of-band management environments, the interface between the out-of-band Management Controller and the Network Controller is critical. This interface is responsible for supporting communication between the Management Controller and external management applications. Currently there are multiple such proprietary interfaces in the industry, leading to inconsistencies in implementation of out-of-band management.

The goal of this specification is to define an interoperable sideband communication interface standard to enable the exchange of management data between the Management Controller and Network Controller. The Sideband Interface is intended to provide network access for the Management Controller, and the Management Controller is expected to perform all the required network functions.

This specification defines the protocol and commands necessary for the operation of the sideband communication interface. This specification also defines physical and electrical characteristics of a sideband binding interface that is a variant of RMII targeted specifically for sideband communication traffic.

The specification is primarily intended for architects and engineers involved in the development of network interface components and Management Controllers that will be used in providing out-of-band management.

NC-SI over MCTP Binding Specification (DSP0261)

The *NC-SI over MCTP Binding Specification* defines new MCTP messages used to convey NC-SI Control packets and Ethernet traffic over MCTP to allow NC-SI Pass-through traffic over MCTP. This specification is based on the [DSP0222 1.1](#) specification and uses the same NC-SI Control packet definitions.

Document conventions

Typographical conventions

The following typographical conventions are used in this document:

- Document titles are marked in *italics*.
- Important terms that are used for the first time are marked in *italics*.
- Terms include a link to the term definition in Terms and definitions, enabling easy navigation to the term definition.
- ABNF rules are in monospaced font.

ABNF usage conventions

Format definitions in this document are specified using ABNF (see [RFC5234](#)), with the following deviations:

- Literal strings are to be interpreted as case-sensitive Unicode characters, as opposed to the definition in [RFC5234](#) that interprets literal strings as case-insensitive US-ASCII characters.

Reserved and unassigned values

Unless otherwise specified, any reserved, unspecified, or unassigned values in enumerations or other numeric ranges are reserved for future definition by the DMTF.

Unless otherwise specified, numeric or bit fields that are designated as reserved shall be written as 0 (zero) and ignored when read.

Byte ordering

Unless otherwise specified, byte ordering of multibyte numeric fields or bit fields is "Big Endian" (that is, the lower byte offset holds the most significant byte, and higher offsets hold lesser significant bytes).

Other conventions

See ANNEX C
(informative)

Notation and conventions for other conventions.

Information technology — Network Controller Sideband Interface (NC-SI) Specifications Collection

1 Scope

Network Controller Sideband Interface (NC-SI) Specification (DSP0222)

This specification defines the functionality and behavior of the Sideband Interface responsible for connecting the Network Controller to the Management Controller. It also outlines the behavioral model of the network traffic destined for the Management Controller from the Network Controller.

This specification defines the following two aspects of the Network Controller Sideband Interface (NC-SI):

- behavior of the interface, which include its operational states as well as the states of the associated components
- the payloads and commands of the communication protocol supported over the interface

The scope of this specification is limited to addressing only a single Management Controller communicating with one or more Network Controllers.

This specification also defines the following aspects of a 3.3V RMII Based Transport (RBT) based physical medium:

- transport binding for NC-SI over RBT
- electrical and timing requirements for the RBT
- an optional hardware arbitration mechanism for RBT

Only the topics that may affect the behavior of the Network Controller or Management Controller, as it pertains to the Sideband Interface operations, are discussed in this specification.

NC-SI over MCTP Binding Specification (DSP0261)

This specification defines the bindings between NC-SI protocol elements and MCTP elements in order for NC-SI Control and Pass-Through traffic to be transported using MCTP.

Portions of this specification rely on information and definitions from other specifications, which clause 2 identifies. Two of these references are particularly relevant:

- DMTF [DSP0222](#), *Network Controller Sideband Interface (NC-SI) Specification*, provides the NC-SI base control that is to be bound over MCTP by this specification.
- DMTF [DSP0236](#), *Management Component Transport Protocol (MCTP) Base Specification*, defines the MCTP transport on which the NC-SI Control and Pass-through packets are to be conveyed.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated or versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies. For references without a date or version, the latest published edition of the referenced document (including any corrigenda or DMTF update versions) applies.

ACPI, *Advanced Configuration and Power Interface Specification Revision 4.0a*, April 5, 2010,
<http://www.acpi.info/DOWNLOADS/ACPIspec40a.pdf>

DMTF DSP0004, *CIM Infrastructure Specification 3.0*,
http://www.dmtf.org/standards/published_documents/DSP0004_3.0.pdf

DMTF DSP0222, *Network Controller Sideband Interface (NC-SI) Specification 1.1*,
http://www.dmtf.org/sites/default/files/standards/documents/DSP0222_1.1.0.pdf

DMTF DSP0223, *Generic Operations 1.0*,
http://www.dmtf.org/standards/published_documents/DSP0223_1.0.pdf

DMTF DSP0236, *Management Component Transport Protocol (MCTP) Base Specification 1.3*,
http://www.dmtf.org/standards/published_documents/DSP0236_1.3.pdf

DMTF DSP0237, *Management Component Transport Protocol (MCTP) SMBus/I2C Transport Binding Specification 1.1*,
http://www.dmtf.org/standards/published_documents/DSP0237_1.1.pdf

DMTF DSP0238, *Management Component Transport Protocol (MCTP) PCIe VDM Transport Binding Specification 1.0*,
http://www.dmtf.org/standards/published_documents/DSP0238_1.0.pdf

DMTF DSP0239, *Management Component Transport Protocol (MCTP) IDs and Codes 1.4*,
http://www.dmtf.org/standards/published_documents/DSP0239_1.4.pdf

DMTF DSP0240, *Platform Level Data Model (PLDM) Base 5 Specification 1.1.0*,
https://www.dmtf.org/sites/default/files/standards/documents/DSP0240_1.1.0.pdf

DMTF DSP0261, *NC-SI over MCTP Binding Specification 1.0*,
http://www.dmtf.org/standards/published_documents/DSP0261_1.0.pdf

DMTF DSP1001, *Management Profile Specification Usage Guide 1.2*,
http://www.dmtf.org/standards/published_documents/DSP1001_1.2.pdf

IEEE 802.3, *802.3™ IEEE Standard for Information technology— Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*, December 2005,
<http://www.ieee.org/portal/site>

IEEE 802.1Q, *IEEE 802.1Q-2005 IEEE Standard for Local and Metropolitan Area Networks—Virtual Bridged Local Area Networks*,
<http://www.ieee.org/portal/site>. This standard defines the operation of Virtual LAN (VLAN) Bridges that permit the definition, operation and administration of Virtual LAN topologies within a Bridged LAN infrastructure.

IETF RFC2131, *Dynamic Host Configuration Protocol (DHCP)*, March 1997, <http://www.ietf.org/rfc/rfc2131.txt>

IETF RFC2373, *IP Version 6 Addressing Architecture*, July 1998, <http://www.ietf.org/rfc/rfc2373.txt>

IETF RFC2461, *Neighbor Discovery for IP Version 6 (IPv6)*, December 1998, <http://www.ietf.org/rfc/rfc2461.txt>

ISO/IEC 24079:2024(en)

IETF RFC2464, *Transmission of IPv6 Packets over Ethernet Networks*, December 1998,
<http://www.ietf.org/rfc/rfc2464.txt>

IETF RFC3315, *Dynamic Host Configuration Protocol for IPv6 (DHCPv6)*, July 2003,
<http://www.ietf.org/rfc/rfc3315.txt>

IETF, RFC4122, *A Universally Unique Identifier (UUID) URN Namespace*, July 2005,
<http://datatracker.ietf.org/doc/rfc4122/>

IETF RFC5234, *ABNF: Augmented BNF for Syntax Specifications, January 2008*, <http://tools.ietf.org/html/rfc5234>

ISO/IEC Directives, Part 2, *Rules for the structure and drafting of International Standards*,
<http://isotc.iso.org/livelink/livelink.exe?func=ll&objId=4230456&objAction=browse&sort=subtype>

Reduced Media Independent Interface (RMII) Consortium, *RMII Specification*, revision 1.2, March 20, 1998,
http://ebook.pldworld.com/_eBook/-Telecommunications,Networks-/TCP/IP/RMII/rmii_rev12.pdf