INTERNATIONAL STANDARD

ISO/IEC 24091

First edition 2019-11

Information technology — Power efficiency measurement specification for data center storage



ISO/IEC 24091:2019(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <u>www.iso.org/patents</u>) or the IEC list of patent declarations received (see <u>https://patents.iec.ch</u>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by SNIA (as SNIA Emerald™ Power Efficiency Measurement Specification V3.0.3) and drafted in accordance with its editorial rules. It was adopted, under the JTC 1 PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Contents

1	In	ntroduction	vii
2	S	cope	1
	2.1	Abstract	1
	2.2	Introduction	1
	2.3	Current Revision	1
	2.4	Purpose	1
	2.5	Disclaimer	2
3	N	Iormative References	3
4	D	Pefinitions, Symbols, Abbreviations, and Conventions	4
	4.1	Overview	4
	4.2	Definitions	4
	4.3	Symbols and Abbreviated Terms	9
	4.4	Expression of Provisions	9
	4.5	Conventions	10
5	Ta	axonomy	11
	5.1	Introduction	11
	5.2	Taxonomy Categories	12
	5.3	Taxonomy Classifications	12
	5.4	Taxonomy Rules	12
	5.5	Online Category	13
	5.6	Near-Online Category	15
	5.7	Removable Media Library Category	15
	5.8	Virtual Media Library Category	16
6	C	apacity Optimization	17
	6.1	Introduction	17
	6.2	Space Consuming Practices	17
	6.3	COMs Characterized	17
7	Te	est Definition and Execution Rules	18
	7.1	Overview	18
	7.2	General Requirements and Definitions	18
	7.3	Block Access Online and Near-Online Tests	30
	7.4	File Access Online and Near-Online Active Test	33
	7.5	Block and File Access Ready Idle Test	37
	7.6	Block and File Access Capacity Optimization Test	37
	7.7	Removable Media Library Testing	42
	7.8	Virtual Media Library Testing	46

8	Met	trics	50
8	3.1	Taxonomy Considerations	50
8	3.2	Block Access Primary Metrics	50
8	3.3	File Access Primary Metrics	50
8	3.4	Power Efficiency Metric for Online and Near-Online Systems	50
8	3.5	Power Efficiency Metric for Removable Media Library Systems	52
8	3.6	Storage Power Efficiency Metric for Virtual Media Library Systems	52
8	3.7	Secondary Metrics	52
9	Dis	sclosure Requirements	54
Ś	9.1	General	54
Ś	9.2	Product Identification	54
Ś	9.3	Test Metrics	54
Ş	9.4	Test Characterization	56
Ş	9.5	Product Under Test Description	57
An	nex	A (Normative) Suggested Power and Environmental Meters	59
,	۹.1	Overview	59
,	٩.2	Alternate Meter Usage	59
An	nex	B (Normative) Measurement Requirements	60
E	3.1	Online and Near-Online Block Access Data Collection and Processing Requireme	nts60
_	3.2 Requi	Removable and Virtual Media Library Block Access Data Collection and Processir	
E	3.3	Online and Near-Online File Access Data Collection and Processing Requirement	s60
An	nex	C (Normative) Stable Storage	62
An	nex	D (Normative) Vdbench	63
An	nex	E (Normative) Vdbench Test Scripts	64
An	nex	F (Normative) SPEC SFS® 2014 Benchmark	65
An	nex	G (Normative) File Access IO Load Driver Configuration File	66
An	nex	H (Informative) sFlow [®]	67
An	nex	I (Normative) COM Test Data Set Generator	68
An	nex	J (Informative) gzip	69
Bil	blioa	araphy	70

ISO/IEC 24091:2019(E)

List of Tables, Figures and Equations

Table 1 – Normative References	3
Table 2 – Taxonomy Overview	11
Table 3 – Common Category Attributes	12
Table 4 – Online Classifications	14
Table 5 – Near-Online Classifications	15
Table 6 – Removable Media Library Classifications	16
Table 7 – Virtual Media Library Classifications	16
Figure 1 - Sample Configuration Block Access	19
Figure 2 - Sample Configuration File Access	19
Table 8 – Example RAS Features	20
Table 9 – Input Power Requirements (Products with Nameplate Rated Power ≤ 1 500 W)	21
Table 10 – Input Power Requirements (Products with Nameplate Rated Power > 1 500 W)	21
Table 11 – Power Meter Resolution	22
Equation 7-1: Sequential Transfer Offset	24
Figure 3 - Percentage of Address Hit vs. Cache Size	24
Table 12 – Workloads within the Hot Band IO Profile	25
Table 13 – IO Transfer Size within the Hot Band IO Profile for 512 Byte Native Devices	25
Table 14 – IO Transfer Size within the Hot Band IO Profile for 4 KiB Native Devices	26
Equation 7-2: Average Power	27
Equation 7-3: Periodic Power Efficiency	28
Equation 7-4: Least Squares Linear Fit Calculation	29
Equation 7-5: Weighted Moving Average Calculation	29
Table 15 – Pre-fill Test IO Profile	30
Table 16 – Online and Near-Online Testing: Conditioning Test IO Profiles	31
Table 17 – Online and Near-Online Testing: Active Test Phase IO Profiles	32
Table 18 – Business Metrics for Workload Type	35
Table 19 – Business Metrics for File Access Active Test Sequence	36
Table 20 – Data Sets	38
Table 21 – Drive Counts	42
Table 22 – Removable Media Library Testing: Conditioning Test IO Profiles	43
Table 23 – Removable Media Library Testing: Active Test Phase IO Profiles	44
Equation 7-6: Sequential Transfer Offset	45
Table 24 – Virtual Media Library Testing: Conditioning Test IO Profiles	47
Table 25 – Virtual Media Library Testing: Active Test Phase IO Profiles	48
Equation 7-7: Sequential Transfer Offset	48
Equation 8-1: Power Efficiency, Ready Idle	51
Equation 8-2: Power Efficiency, Active (Block Access)	51
Equation 8-3: Power Efficiency, Active (File Access)	51
Table B-1 Online and Near-Online Block Access Summary	60
Table B-2 Removable and Virtual Media Library Summary	60
Table B-3 Online and Near-Online File Access Summary	

1 Introduction

There is a growing awareness of the environmental impact of IT equipment use. This impact takes several forms: the energy expended in equipment manufacture and distribution, the impact of materials reclamation, and the energy consumed in operation and cooling of the equipment. IT equipment users of all kinds now wish to make their IT operations as energy efficient as possible. This new priority can be driven by one or more of several requirements:

- Rising energy costs have made power and cooling expenses a more significant percentage of total cost of ownership of server and storage equipment;
- Some data centers are physically unable to add more power and cooling load, which means that new
 applications and data can only be brought on if old ones are retired or consolidated onto new, more
 efficient configurations;
- Increased regulatory and societal pressures provide incentives for companies to lower their total energy footprints. For many companies, IT is a significant portion of overall energy consumption, and corporate Green goals can only be achieved by reducing IT's energy needs or by making operations more efficient.

IT equipment users will seek advice on the most energy efficient approach to getting their work done. It is not practical for customers to test a wide range of storage products and architectures for themselves. A more effective approach is to create a collection of standard metrics that allow IT architects to objectively compare a range of possible solutions. This objective, metric-based approach has a dual impact:

- Users can select the mode of storage usage that accomplishes their work objectives with the lowest overall energy consumption;
- Companies will be driven to innovate and compete in the development of energy efficient products as measured by the standard yardsticks.

2 Scope

2.1 Abstract

This document describes a standardized method to assess the energy efficiency of commercial storage products in both active and idle states of operation. A taxonomy is defined that classifies storage products in terms of operational profiles and supported features. Test definition and execution rules for measuring the power efficiency of each taxonomy category are described; these include test sequence, test configuration, instrumentation, benchmark driver, IO profiles, measurement interval, and metric stability assessment. Qualitative heuristic tests are defined to verify the existence of several capacity optimization methods. Resulting power efficiency metrics are defined as ratios of idle capacity or active operations during a selected stable measurement interval to the average measured power.

2.2 Introduction

This document defines methodologies and metrics for the evaluation of the related performance and energy consumption of storage products in specific active and idle states.

Storage products and components are said to be in an "active" state when they are processing externally initiated, application-level requests for data transfer between host(s) and the storage product(s). For purposes of this document, idle is defined as "ready idle", in which storage systems and components are configured, powered up, connected to one or more hosts and capable of satisfying externally initiated, application-level initiated IO requests within normal response time constraints, but no such IO requests are being submitted.

2.3 Current Revision

This document addresses storage products supporting block or file data access. Block access and file access refer to the type of service provided typically by Storage Area Network (SAN) and Network Attached Storage (NAS) systems, respectively. It is not appropriate to use this document to ascertain power efficiency for anything other than these two access modes. This document includes:

- A generalized taxonomy for storage products (clause 5);
- An assessment mechanism for software-based Capacity Optimization Methods (clause 6);
- Measurement and data collection guidelines for assessing the power efficiency of block- and filebased storage products in both active and ready idle states (clause 7);
- Metrics describing storage product power efficiency (clause 8);
- Required disclosures for a test result published as a SNIA Emerald^{™1} Power Efficiency Measurement test result (clause 9).

2.4 Purpose

The purpose of a SNIA Emerald™ Power Efficiency Measurement is to provide a reproducible and standardized assessment of the energy efficiency of commercial storage products in both active and ready idle states.

- 1. Tested systems shall be comprised of commercially released products and components;
- 2. Tested systems shall employ settings, parameters, and configurations that would allow end-users to achieve power efficiency levels equivalent to the published result;
- 3. All data published as an SNIA Emerald™ Power Efficiency Measurement test result shall be gathered from test execution conducted according to this document;

¹ SNIA Emerald[™] is a trademark of the Storage Networking Industry Association. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the product named.

ISO/IEC 24091:2019(E)

- 4. Test execution shall complete in its entirety and without test failure or test error messages;
- 5. Software features which invoke, generate, or use software designed specifically for the test shall not be used. Configuration options chosen for test execution shall be options that are generally recommended for the customer;
- 6. Energy for powering the equipment shall be provided by the power mains that are being monitored (not by an internal UPS).

A SNIA Emerald™ Power Efficiency Measurement shall be a good faith effort to accurately characterize the power requirements of the tested system. The precise configuration used in a SNIA Emerald™ Power Efficiency Measurement is left to the sponsor of a test. Any commercially released components may be used, and a focus on new or emerging components or technologies is encouraged.

2.5 Disclaimer

A SNIA Emerald™ Power Efficiency Measurement test result provides a high-level assessment of the energy efficiency of the tested system in specific ready idle and active states. It is not an attempt to precisely model or reproduce any specific installation.

Actual performance and energy consumption behavior is highly dependent upon precise workload, environmental and usage parameters. While a SNIA Emerald™ Power Efficiency Measurement test result is intended to provide a realistic and reproducible assessment of the relative power efficiency of a system across a broad range of configurations and usage patterns, it cannot completely match the precise needs of any one specific installation.

3 Normative References

The following documents are referred to in the text in a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Table 1 lists these documents.

Table 1 - Normative References

Author/Owner	Title	Revision	URL
ISO/IEC	ISO/IEC Directives Part II	Eighth edition, 2018	https://www.iso.org/directives- and-policies.html