
**Information technology —
Telecommunications and information
exchange between systems — PHY/MAC
specifications for short-range wireless
low-rate applications in the ISM band**

*Technologies de l'information — Téléinformatique — Spécifications
PHY/MAC pour applications à bas débit sans fil à courte portée
dans la bande ISM*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	2
5 Overview	3
6 Interlayer service specification	5
6.1 Overview	6
6.2 General format of management primitives	6
6.2.1 MLME-GET.request and PLME-GET.request	7
6.2.2 MLME-GET.confirm and PLME-GET.confirm	7
6.2.3 MLME-SET.request and PLME-SET.request	8
6.2.4 MLME-SET.confirm and MLME-SET.confirm	8
6.3 MLME-SAP	9
6.3.1 MLME-GET.request	10
6.3.2 MLME-GET.confirm	10
6.3.3 MLME-MASTER-START.request	10
6.3.4 MLME-MASTER-START.confirm	11
6.3.5 MLME-RESET.request	11
6.3.6 MLME-RESET.confirm	12
6.3.7 MLME-SCAN.request	12
6.3.8 MLME-SCAN.confirm	13
6.3.9 MLME-SET.request	13
6.3.10 MLME-SET.confirm	14
6.4 MAC-SAP	14
6.4.1 MAC-DATA.request	15
6.4.2 MAC-DATA.confirm	15
6.4.3 MAC-DATA.indication	16
6.5 PLME-SAP	16
6.5.1 PLME-GET.request	17
6.5.2 PLME-GET.confirm	17
6.5.3 PLME-SET.request	18
6.5.4 PLME-SET.confirm	18
6.5.5 PLME-RESET.request	19
6.5.6 PLME-RESET.confirm	19
6.6 PD-SAP	20
6.6.1 PD-DATA.request	20
6.6.2 PD-DATA.confirm	21
6.6.3 PD-DATA.indication	21
7 MAC PDU format	22
7.1 MPDU of beacon frame (BF)	22
7.1.1 Open flag (OF, 2 bits)	22
7.1.2 MAC version (6 bits)	23
7.1.3 Address mode (ADDM, 2 bits)	23
7.1.4 PHY version (6 bits)	23
7.1.5 Frame type (8 bits)	23
7.1.6 Superframe mode control (SFMC, 2 bits)	23
7.1.7 Upper layer frame size (ULPS, 6 bits)	24
7.1.8 Source MAC address (64 bits)	24
7.1.9 Superframe counter (SFC, 4 bits)	24
7.1.10 Middleframe counter (FC, 4 bits)	24

7.1.11	Hopping sequence (32 bits)	24
7.1.12	Beacon frequency table (BFT, 16 bytes)	24
7.1.13	Upper layer data (16 bytes)	24
7.1.14	TCRC16 (16 bits), MCRC16 (16 bits)	24
7.2	MPDU of fast beacon frame (FBF)	24
7.2.1	Open flag (OF, 2 bits)	24
7.2.2	MAC version (6 bits)	25
7.2.3	Address mode (ADDM, 2 bits)	25
7.2.4	PHY version (6 bits)	25
7.2.5	Frame type (8 bits)	25
7.2.6	Superframe mode control (SFMC, 2 bits)	25
7.2.7	Upper layer frame size (ULPS, 6 bits)	26
7.2.8	Source MAC address (64 bits)	26
7.2.9	Superframe counter (SFC, 4 bits)	26
7.2.10	Middleframe counter (SC, 4 bits)	26
7.2.11	Hopping sequence (32 bits)	26
7.2.12	Beacon frequency table (BFT, 16 bytes)	26
7.2.13	Upper layer data (16 Bytes)	26
7.2.14	TCRC16 (16 bits), MCRC16 (16 bits)	26
7.3	MPDU of request control frame (RCF)	26
7.3.1	Open flag (OF, 2 bits)	26
7.3.2	MAC version (6 bits)	26
7.3.3	Address mode (ADDM, 2 bits)	27
7.3.4	PHY version (6 bits)	27
7.3.5	Frame type (8 bits)	27
7.3.6	Upper layer frame size (ULPS, 6 bits)	27
7.3.7	Source MAC address (64 bits)	27
7.3.8	Destination MAC address (64 bits)	27
7.3.9	Upper layer data	28
7.3.10	TCRC16 (16 bits), MCRC16 (16 bits)	28
7.4	MPDU of master control frame (MCF)	28
7.4.1	Open flag (OF, 2 bits)	28
7.4.2	MAC version (6 bits)	28
7.4.3	Address mode (ADDM, 2 bits)	28
7.4.4	PHY version (6 bits)	28
7.4.5	Frame type (8 bits)	28
7.4.6	Upper layer frame size (ULPS, 6 bits)	28
7.4.7	Source MAC address (64 bits)	28
7.4.8	Destination MAC address (64 bits)	29
7.4.9	Upper layer data	29
7.4.10	TCRC16 (16 bits), MCRC16 (16 bits)	29
7.5	MPDU of RCF acknowledge control frame (RACF)	29
7.6	MPDU of MCF acknowledge control frame (MACF)	29
7.7	MPDU of payload frame (PF)	30
7.7.1	Open flag (OF, 2 bits)	30
7.7.2	MAC version (6 bits)	30
7.7.3	Address mode (ADDM, 2 bits)	30
7.7.4	PHY version (6 bits)	30
7.7.5	Frame type (8 bits)	30
7.7.6	Upper layer frame size (ULPS, 6 bits)	30
7.7.7	Source MAC address (64 bits)	30
7.7.8	Destination MAC address (64 bits)	30
7.7.9	Upper layer data	30
7.7.10	TCRC16 (16 bits), MCRC16 (16 bits)	30
8	MAC functional description	31
8.1	General description	31
8.2	System state diagram	32
8.3	Protocol structure	34

8.3.1	Middleframe structure.....	35
8.3.2	Superframe structure	35
8.4	Frequency operation.....	37
8.4.1	Frequency hopping control	37
8.4.2	Frame frequency mapping	37
8.4.3	Frequency diversity and time diversity	38
8.4.4	Orthogonal frequency offset.....	38
8.4.5	Frequency selection	38
9	PHY specification	41
9.1	General requirements.....	41
9.1.1	Operating frequency range	41
9.1.2	Frequency assignment.....	41
9.1.3	Frequency synthesizer stabilisation time	41
9.1.4	Frequency synthesizer turn off time	41
9.2	PHY protocol data unit (PPDU) format.....	42
9.2.1	Lock time	42
9.2.2	Preamble.....	42
9.2.3	Header (48 bits)	43
9.2.4	Message.....	43
9.2.5	EoF delimiter.....	43
9.3	Modulation and codes.....	43
9.3.1	Modulation	43
9.3.2	Codes.....	44
9.4	Transmitter specification.....	45
9.4.1	Pulse shaping filter	45
9.4.2	Transmitter power spectrum mask	45
	Annex A (informative) Pico-net Light-weight Architecture Security (PLAS)	46

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/IEC JTC 1, *Information technology, SC 6, Telecommunications and information exchange between systems*.

This second edition cancels and replaces the first edition (ISO/IEC 29157:2010), which has been technically revised.

Introduction

This International Standard is the revision of ISO/IEC 29157. This International Standard was established to provide a unified platform for services of data rates up to 1 Mbps: control data, voice, audio, and video. The purpose of the revision is to accommodate the advancement of technology for higher-quality services in the mobile applications.

The direction of the revision is three-fold: to enhance throughput, to facilitate co-existence with other technologies such as time-division LTE (long term evolution) and WiMAX II, and to increase data rate. For the higher throughput, the length of the preamble of the payload frames is made variable up to the user's need (see [9.2.2](#)). For the co-existence, the duration of the middle frames is reduced to 4 ms from 16 ms to make align with those of the other technologies (see [8.3](#)). With the shorter middleframes, the International Standard does not only harmonise with other technologies, but also attains advantages of shorter communication delay and less paring time. To increase the data rate, the message part of the payload frames may be modulated with QPSK. The modulation format is indicated by the 'PHY version' of the header (see [Clause 7](#) and [9.3](#)). With the addition of the new option, the data rate can be increased to 2 Mbps. In addition, to protect communications against security challenges due to the loss of protection provided by wires, this International Standard provides the optional security mechanism (See [9.3.2](#) and [Annex A](#)).

Information technology — Telecommunications and information exchange between systems — PHY/MAC specifications for short-range wireless low-rate applications in the ISM band

1 Scope

This International Standard specifies the PHY characteristics and MAC procedures used for short-range, low-data-rate, wireless communications with very low latency and point-to-multipoint connection capability.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 9798-3, *Information technology — Security techniques — Entity authentication — Part 3: Mechanisms using digital signature techniques*