



Edition 1.0 2008-11

INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture – Part 13-11: Device Security Device Control Protocol – Security Console Service

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 35.200

ISBN 2-8318-1012-9

CONTENTS

FOREWORD	3
ORIGINAL UPNP DOCUMENTS (informative)	5
1. Overview and Scope	7
1.1. Security Console Actions	7
1.1.1. Control Point Discovery	
1.1.2. Local Dictionary Communication1.1.3. Certificate Processing	
2. Service Modeling Definitions	
2.1. Service Type	
2.2. Namespaces	
2.3. State Variables	
2.3.1. PendingCPList	
2.3.2. NameListVersion	
2.3.3. A_ARG_TYPE_string 2.3.4. A_ARG_TYPE_base64	
2.4. Eventing and Moderation	
2.5. Actions	11
2.5.1. PresentKey	11
2.5.2. GetNameList	
2.5.3. GetMyCertificates 2.5.4. RenewCertificate	
2.6. Relationships between Actions	
2.7. Common Error Codes	
3. Theory of Operation	18
3.1. Control Point Discovery	18
3.2. "My Domain" and Component Naming	
3.2.1. Hardware alternatives	
3.3. Certificates	19
3.4. Certificate Delivery	19
3.5. Certificate Renewal	19
3.6. BASE32 Encoding	20
3.7. XML Strings as UPnP Arguments	21
4. XML Service Description	22

LIST OF TABLES

Table 1: State variable	10
Table 2: Event Moderation	11
Table 3: Actions	11

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 13-10: Device Security Device Control Protocol – Security Console Service

FOREWORD

- ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation Standards Licensing Department 5200 NE Elam Young Parkway MS: JFS-98 USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation One Microsoft Way USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S High Tech campus, building 44 3A21 NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL) High Tech campus 60 NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd. 1-3-7 Shiromi, Chuoh-ku JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company 1501 Page Mill Road USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd. 416 Maetan-3 Dong, Yeongtang-Gu, KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-13-11 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play* (*UPnP*) architecture, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

ORIGINAL UPNP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title

ISO/IEC 29341 Part

UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-2
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-13
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
	ISO/IEC 29341-6-16
UPnP TemperatureSetpoint:1 Service	
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-12
	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-12
UPnP QoS Architecture:1.0	ISO/IEC 29341-9-13 ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

UPnP Document Title

UPnP QosDevice:2 Service
UPnP QosManager:2 Service
UPnP QosPolicyHolder:2 Service
UPnP RemoteUIClientDevice:1 Device
UPnP RemoteUIServerDevice:1 Device
UPnP RemoteUIClient:1 Service
UPnP RemoteUIServer:1 Service
UPnP DeviceSecurity:1 Service
UPnP SecurityConsole:1 Service

ISO/IEC 29341 Part

ISO/IEC 29341-11-10
ISO/IEC 29341-11-11
ISO/IEC 29341-11-12
ISO/IEC 29341-12-1
ISO/IEC 29341-12-2
ISO/IEC 29341-12-10
ISO/IEC 29341-12-11
ISO/IEC 29341-13-10
ISO/IEC 29341-13-11

1. Overview and Scope

This service is offered by a Security Console (SC). The Security Console offers a user interface for administration of access control on security-aware UPnP devices. [See DeviceSecurity:1 for a description of the actions used in the creation and editing of Access Control Lists (ACLs) and in taking security ownership of Devices.] As a device the Security Console is self-owned. If it has any access controlled actions, then those are to be administered by the human user and not by some other Security Console. Therefore, a Security Console does not need to include a DeviceSecurity service. It does have a certificate cache, but it is an outgoing cache, rather than an incoming cache.

A network built of the user's own components with no connection to anything outside the user's personal domain and with no control points belonging to anyone other than the user ever attached to the network would not require the features of UPnP Security. Network isolation would already have achieved a level of physical security. We are concerned in UPnP Security with networks in which more than the user's own Control Points are present on the physical network and able to reach the user's Devices with control messages. These situations can include:

- 1. use of wireless, power-line networking or cable modem without a firewall, allowing an attacker to join the network without the user's knowledge or permission
- 2. shared infrastructure networks, such as a college dorm or a condominium building wired for Ethernet as one network segment serving more than one person's residence
- 3. households of multiple adults or teens, in which each individual wants to establish a private security domain, in addition to any domain of devices or control points shared among them, while using a shared network domain
- 4. connections to the Internet via devices or services that create single network segments of multiple subscribers as a side effect of offering network connectivity (such as some cable modems and some ISP connections)
- 5. households in which guests might bring mobile devices or control points into the network temporarily

In such networks of intentional or accidental sharing, one cannot rely on physical network security to protect devices or on discovery methods (e.g., multicast SSDP) to compile a list of "My Devices" or "My Control Points". This leaves it up to the user manually to select from physically accessible devices and control points, choosing those of interest to that user. One primary function of the SC is to enable the user to make that selection. This process requires two operations that were not anticipated in the original design of UPnP:

- 1. discovery of control points; and
- 2. naming of devices and control points on a per-user basis.

The actions provided in this service allow the SC to perform those two functions.

In addition, the sharing of devices across security domains sometimes calls for the use of authorization certificates, as described in sections 1.1.3 and 3.3. This service provides actions for the delivery of such certificates (or certificate chains) (see 2.5.3) and for the revocation (via renewal) of certificates (see 2.5.4).