

This is a preview - click here to buy the full publication



ISO/IEC 29341-17-10

Edition 1.0 2011-09

# INTERNATIONAL STANDARD



---

**Information technology – UPnP device architecture –  
Part 17-10: Quality of Service Device Control Protocol – Level 3 – Quality of  
Service Device Service**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

X

---

ICS 35.200

ISBN 978-2-88912-657-6

## CONTENTS

1	Overview and Scope.....	5
1.1	Referenced Specifications .....	5
1.1.1	Normative References .....	5
1.1.2	Informative References .....	6
2	Service Modeling Definitions.....	6
2.1	ServiceType .....	6
2.2	State Variables.....	7
2.2.1	XML Fragments as UPnP Arguments.....	7
2.2.2	A_ARG_TYPE_TrafficDescriptor .....	8
2.2.3	A_ARG_TYPE_TrafficDescriptorsPerInterface.....	8
2.2.4	A_ARG_TYPE_TrafficHandle .....	10
2.2.5	A_ARG_TYPE_NumTrafficDescriptors .....	10
2.2.6	A_ARG_TYPE_QosDeviceCapabilities .....	10
2.2.7	A_ARG_TYPE_QosDeviceState .....	11
2.2.8	PathInformation .....	12
2.2.9	A_ARG_TYPE_QosDeviceInfo .....	14
2.2.10	A_ARG_TYPE_QosStateId.....	14
2.2.11	A_ARG_TYPE_NumRotameterObservations .....	14
2.2.12	A_ARG_TYPE_RotameterInformation .....	15
2.2.13	A_ARG_TYPE_ConfRotameterObservations .....	20
2.2.14	MostRecentStreamAction .....	21
2.2.15	A_ARG_TYPE_MaxPossibleRotameterObservations .....	22
2.2.16	A_ARG_TYPE_Resource .....	22
2.2.17	A_ARG_TYPE_AdmitTrafficQosExtendedResult.....	23
2.2.18	A_ARG_TYPE_ListOfAdmittedTraffic .....	26
2.2.19	A_ARG_TYPE_PREFERREDQPH .....	28
2.2.20	UnexpectedStreamChange.....	29
2.2.21	A_ARG_TYPE_PreemptingTrafficInfo.....	29
2.2.22	A_ARG_TYPE_ListOfMostRecentUnexpectedStreamChanges.....	30
2.2.23	A_ARG_TYPE_QosDeviceExtendedState.....	33
2.2.24	A_ARG_TYPE_Layer2Mapping .....	38
2.2.25	A_ARG_TYPE_AdmitTrafficQosSucceeded .....	38
2.2.26	A_ARG_TYPE_TrafficDescriptorsWanted.....	38
2.2.27	A_ARG_TYPE_SetPreferredQphResults .....	38
2.2.28	A_ARG_TYPE_NumberOfUnexpectedStreamChangesRequested.....	39
2.2.29	A_ARG_TYPE_NumberOfUnexpectedStreamChangesReported .....	39
2.2.30	A_ARG_TYPE_NewTrafficLeaseTime .....	39
2.2.31	A_ARG_TYPE_TrafficDescriptorContainer .....	39
2.2.32	A_ARG_TYPE_Layer2MappingContainer .....	41
2.2.33	A_ARG_TYPE_QosDeviceInfoContainer .....	41
2.3	Eventing and Moderation .....	43
2.3.1	Event Model.....	43
2.4	Actions.....	44
2.4.1	GetQosDeviceCapabilities() .....	45
2.4.2	GetQosState() .....	46

2.4.3	SetupTrafficQos()	47
2.4.4	ReleaseTrafficQos()	49
2.4.5	GetPathInformation	50
2.4.6	GetQosDeviceInfo()	51
2.4.7	ConfigureRotameterObservation()	52
2.4.8	GetRotameterInformation()	53
2.4.9	AdmitTrafficQos()	54
2.4.10	UpdateAdmittedQos()	62
2.4.11	ReleaseAdmittedQos()	65
2.4.12	GetExtendedQosState()	67
2.4.13	SetPreferredQph()	68
2.4.14	GetUnexpectedStreamChanges()	70
2.4.15	VerifyTrafficHandle()	71
2.4.16	UpdateTrafficLeaseTime()	71
2.4.17	SetL2Map()	72
2.4.18	Non-Standard Actions Implemented by a UPnP Vendor	73
2.4.19	Error Code Summary	73
2.4.20	Reason Code Summary	74
2.5	Theory of Operation (Informative)	75
2.5.1	Parameterized QoS	77
2.5.2	Prioritized QoS	80
2.5.3	Hybrid QoS	81
3	XML Service Descriptions	82
4	Test	88
Annex A (informative) Additional Examples for State Variables		89
A.1	Additional <i>PathInformation</i> Examples	89
A.1.1	Sample argument XML string – PC with two network interfaces that are both end point device and bridged	89
A.1.2	Sample argument XML string –Four port Ethernet Switch	89
A.1.3	Sample argument XML string – Wireless AP with one Ethernet Interface	90
A.1.4	Sample argument XML string – Bridge device between Wireless station and Ethernet	90
A.2	Additional A_ARG_TYPE_RotameterInformation Examples	91
A.2.1	Sample argument XML string – PC with two network interfaces that are both end point devices	91
A.2.2	Sample argument XML string – PC with two network interfaces that are both end point device with TrafficImportanceNumber reporting	94
A.2.3	Sample argument XML string –Four port Ethernet Switch	95
A.2.4	Sample argument XML string – Wireless AP with one Ethernet Interface	95
A.2.5	Sample argument XML string – Bridge device between Wireless station and Ethernet	96
Annex B (normative) Template for Requirements on the QosDevice Service implementation that are specific for the underlying Network Technologies		98
B.1	<Technology Name>	98
B.1.1	References	98
B.1.2	Priority Mapping	98
B.1.3	<i>QosSegmentId</i> formation	98
B.1.4	<i>Layer2StreamId</i> representation	99

B.1.5	Mapping of UPnP-QoS Parameters to <i>&lt;technology&gt;</i> Parameters .....	99
B.1.6	Blocking traffic stream identification .....	100
B.1.7	Responsibility for QoS Setup .....	100
B.1.8	Mapping of <i>&lt;technology&gt;</i> Returned Parameters to <i>ProtoTspec</i> Parameters .....	101
B.1.9	Mapping of <i>&lt;technology&gt;</i> Returned Parameters to <i>AdmitTrafficQosExtendedResult and AllocatedResources</i> Parameters .....	102
Figure 2-1	— Relationship between ROPeriod and MonitorResolutionPeriod .....	16
Figure 2-2	— PC with Two Network Interfaces .....	18
Figure 2-3	— Example of a PC connected to an active network .....	19
Figure 2-4	— Relationship between End-to-End Delay and QoS Segment Delay .....	57
Figure 2-5	— Relationship between QoS Segment Delay And MaxCommittedDelay .....	58
Figure 2-6	— Components of <i>MaxCommittedDelay</i> .....	59
Figure 2-7	— Containers and How They Nest .....	78
Figure A.1	— Example of a PC connected to an active network .....	91
Table 2-1	— State Variables .....	7
Table 2-2	— Reason Codes For AdmissionStatusNet .....	24
Table 2-3	— Reason Codes For AdmissionStatusDev .....	25
Table 2-4	— Containers In Which A Parameter Can Appear .....	34
Table 2-5	— Reason Codes For <i>A_ARG_TYPE_SetPreferredQphResults</i> .....	39
Table 2-6	— Event Moderation .....	43
Table 2-7	— Actions .....	45
Table 2-8	— Arguments for <i>GetQosDeviceCapabilities()</i> .....	45
Table 2-9	— Error Codes for <i>GetQosDeviceCapabilities()</i> .....	46
Table 2-10	— Arguments for <i>GetQosState()</i> .....	46
Table 2-11	— Error Codes for <i>GetQosState()</i> .....	47
Table 2-12	— Arguments for <i>SetupTrafficQos()</i> .....	47
Table 2-13	— Error Codes for <i>SetupTrafficQos()</i> .....	49
Table 2-14	— Arguments for <i>ReleaseTrafficQos()</i> .....	49
Table 2-15	— Error Codes for <i>ReleaseTrafficQos()</i> .....	50
Table 2-16	— Arguments for <i>GetPathInformation()</i> .....	50
Table 2-17	— Error Codes for <i>GetPathInformation</i> .....	50
Table 2-18	— Arguments for <i>GetQosDeviceInfo()</i> .....	51
Table 2-19	— Error Codes for <i>GetQosDeviceInfo()</i> .....	51
Table 2-20	— Arguments for <i>ConfigureRotameterObservation()</i> .....	52
Table 2-21	— Error Codes for <i>ConfigureRotameterObservation()</i> .....	53
Table 2-22	— Arguments for <i>GetRotameterInformation()</i> .....	53
Table 2-23	— Error Codes for <i>GetRotameterInformation()</i> .....	54
Table 2-24	— Arguments for <i>AdmitTrafficQos()</i> .....	54
Table 2-25	— Error Codes for <i>AdmitTrafficQos()</i> .....	61
Table 2-26	— Reason Codes for <i>AdmitTrafficQos()</i> .....	61
Table 2-27	— Arguments for <i>UpdateAdmittedQos()</i> .....	62

Table 2-28 — Error Codes for <a href="#"><u>UpdateAdmittedQos()</u></a> .....	65
Table 2-29 — Reason Codes for <a href="#"><u>UpdateAdmittedQos()</u></a> .....	65
Table 2-30 — Arguments for <a href="#"><u>ReleaseAdmittedQos()</u></a> .....	65
Table 2-31 — Error Codes for <a href="#"><u>ReleaseAdmittedQos()</u></a> .....	67
Table 2-32 — Arguments for <a href="#"><u>GetExtendedQosState()</u></a> .....	67
Table 2-33 — Error Codes for <a href="#"><u>GetExtendedQosState()</u></a> .....	68
Table 2-34 — Arguments for <a href="#"><u>SetPreferredQph()</u></a> .....	68
Table 2-35 — <a href="#"><u>SetPreferredQphResults</u></a> for <a href="#"><u>SetPreferredQph()</u></a> .....	69
Table 2-36 — Arguments for <a href="#"><u>GetUnexpectedStreamChanges()</u></a> .....	70
Table 2-37 — Error Codes for <a href="#"><u>GetUnexpectedStreamChanges()</u></a> .....	70
Table 2-38 — Arguments for <a href="#"><u>VerifyTrafficHandle()</u></a> .....	71
Table 2-39 — Error Codes for <a href="#"><u>VerifyTrafficHandle()</u></a> .....	71
Table 2-40 — Arguments for <a href="#"><u>UpdateTrafficLeaseTime()</u></a> .....	72
Table 2-41 — Error Codes for <a href="#"><u>UpdateTrafficLeaseTime()</u></a> .....	72
Table 2-42 — Arguments for <a href="#"><u>SetL2Map()</u></a> .....	73
Table 2-43 — Error Codes for <a href="#"><u>SetL2Map()</u></a> .....	73
Table 2-44 — Error Code Summary .....	73
Table 2-45 — Common Reason Codes .....	75
Table 2-46 — Actions in Version 3 and Version 2 .....	76
Table 2-47 — State Variables in Version 3 and Version 2 .....	77
Table B.1 — Priority Mapping .....	98
Table B.2 — Traffic Specification Parameters .....	100
Table B.3 — ProtoTspec Parameters .....	102
Table B.4 — AllocatedResources Parameters .....	103

## INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

### Part 17-10: Quality of Service Device Control Protocol – Level 3 – Quality of Service Device Service

#### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-17-10 was prepared by UPnP Forum Steering committee<sup>1</sup>, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

---

<sup>1</sup> UPnP Forum Steering committee, UPnP Forum, 3855 SW 153<sup>rd</sup> Drive, Beaverton, Oregon 97006 USA. See also "Introduction".

[This is a preview - click here to buy the full publication](#)

29341-17-10 © ISO/IEC:2011(E)

**IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.**

## 1 Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0.[DEVICE]

This service-type enables modeling of the 'QosDevice' function capabilities. The QosDevice:3 Service is a function typically implemented in source, sink and intermediate network. The [QosDevice](#) Service is responsible for providing the appropriate network resources to traffic streams and information about the state of the device as requested by the QosManager as defined in the QosManager:3 Service. [QM]

Several L2 Technologies were considered during the design of UPnP-QoS v3. These technologies are described in UPnP QosDevice:3 Underlying Technology Interface Addendum [QD\_Add] . Every attempt was made to ensure that the design of version 3 would accommodate other L2 Technologies as well. Each L2 Technology on which UPnP-QoS version 3 is implemented is recommended to have a document that is compliant to the template in Annex B which specifies how the L2 Technology defines certain state variables, maps parameters, etc.

This document does not address the procedures for end-to-end set up of a new traffic stream or end-to-end revocation of an existing traffic stream. This procedure is defined in the UPnP QosManager:3 Service Document [QM] .

### 1.1 Referenced Specifications

Unless explicitly stated otherwise herein, implementation of the mandatory provisions of any standard referenced by this specification shall be mandatory for compliance with this specification.

#### 1.1.1 Normative References

This clause lists the normative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[Annex\_G] – IEEE 802.1D-2004, Annex G, IEEE Standard for Information technology - Telecommunications and information exchange between systems - IEEE standard for local and metropolitan area networks - Common specifications - Media access control (MAC) Bridges, 2004.

[XML] – *Extensible Markup Language (XML) 1.0 (Second Edition)*, T. Bray, J. Paoli, C. M. Sperberg-McQueen, E. Maler, eds. W3C Recommendations, 6 October 2000.

[QM] – UPnP QosManager:3 Service Document: This reference is informative except for the definitions of the following state variables, which are normative: [A\\_ARG\\_TYPE\\_TrafficDescriptor](#), [A\\_ARG\\_TYPE\\_NumTrafficDescriptors](#) and [A\\_ARG\\_TYPE\\_TrafficHandle](#).

Available at: <http://www.upnp.org/specs/qos/UPnP-qos-QosManager-v3-Service-20081130.pdf>

Latest version available at: <http://www.upnp.org/specs/qos/UPnP-qos-QosManager-v3-Service.pdf>

[QPH] - *UPnP QosPolicyHolder:3 Service Document*  
Available at: <http://www.upnp.org/specs/qos/UPnP-qos-QosPolicyHolder-v3-Service-20081130.pdf>

Latest version available at: <http://www.upnp.org/specs/qos/UPnP-qos-QosPolicyHolder-v3-Service.pdf>

[DEVICE] - *UPnP Device Architecture, version 1.0.*



[RFC3339] – Date and Time on the Internet: Timestamps, G. Klyne, July 2002.  
<http://www.ietf.org/rfc/rfc3339.txt>

[IANA] - IANA Interface Type (IANAifType)-MIB <http://www.iana.org/assignments/ianaiftype-mib>

[QD\_Add] –UPnP QoSDevice:3 Underlying Technology Interface Addendum  
Available at: <http://www.upnp.org/specs/qos/UPnP-qos-QoSDevice-v3-Addendum-20081130.pdf>

Latest version available at: <http://www.upnp.org/specs/qos/UPnP-qos-QoSDevice-v3-Addendum.pdf>

### 1.1.2 Informative References

This clause lists the informative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[QoS Architecture] – UPnP QoS Architecture V3.0  
Available at: <http://www.upnp.org/specs/qos/UPnP-qos-Architecture-v3-20081130.pdf>  
Latest version available at: <http://www.upnp.org/specs/qos/UPnP-qos-Architecture-v3.pdf>

[HomePlug AV] – HomePlug AV Specification, version 1.1.00, Homeplug Powerline Alliance, [www.HomePlug.org](http://www.HomePlug.org).

[MoCA1.0] MoCA MAC/PHY SPECIFICATION v1.0, 2006.

[MoCA1.1] MoCA MAC/PHY SPECIFICATION v1.1 EXTENSIONS. 2007.

[IEEE802.3] – IEEE Standard for Information technology— Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications IEEE Std 802.3™-2005.  
<http://standards.ieee.org/getieee802/802.3.html>

[IEEE11] - 802.11-2007 IEEE Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks— Specific requirements Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications [http://shop.ieee.org/ieeestore/Product.aspx?product\\_no=SS95708](http://shop.ieee.org/ieeestore/Product.aspx?product_no=SS95708)

[DSCP] - IETF RFC 2474, Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers, K. Nichols et al., December 1998.  
Available at: <http://www.ietf.org/rfc/rfc2474.txt>