

ISO/IEC 29341-17-11

Edition 1.0 2011-08

INTERNATIONAL STANDARD



Information technology – UPnP device architecture –
Part 17-11: Quality of Service Device Control Protocol – Level 3 – Quality of Service Manager Service

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE



CONTENTS

1	Overview and Scope			
	1.1	Refere	nces & Terms	3
		1.1.1	References	3
		1.1.2	Terms and Abbreviations	5
2	Service Modeling Definitions			
	2.1 ServiceType			.12
	2.2	State Variables		
		2.2.1	XML Fragments as UPnP Arguments	.12
		2.2.2	A_ARG_TYPE_TrafficDescriptor	.13
		2.2.3	A_ARG_TYPE_TrafficHandle	.33
		2.2.4	A_ARG_TYPE_NumTrafficDescriptors	.33
		2.2.5	A_ARG_TYPE_NumPolicyHolders	.33
		2.2.6	A_ARG_TYPE_ ListOfTrafficDescriptors	.33
		2.2.7	A_ARG_TYPE_QmCapabilities	.35
		2.2.8	A_ARG_TYPE_ExtendedTrafficQosInfo	.36
		2.2.9	A_ARG_TYPE_ResultedQosType	.38
		2.2.10	Relationships Between State Variables	.38
	2.3	Eventin	ng and Moderation	.39
		2.3.1	Event Model	.39
	2.4	Actions		.39
		2.4.1	RequestTrafficQos()	.39
		2.4.2	UpdateTrafficQos()	.51
		2.4.3	ReleaseTrafficQos()	.59
		2.4.4	BrowseAllTrafficDescriptors()	.59
		2.4.5	GetQmCapabilities()	.60
		2.4.6	RequestExtendedTrafficQos()	.61
		2.4.7	UpdateExtendedTrafficQos()	.66
		2.4.8	Common Error Codes	.70
	2.5	Theory	of Operation (Informative)	.72
		2.5.1	Overview	.72
		2.5.2	Recovery from Failures	.73
3	XML	Service	Description	.75
4	Test			.79
Anr	nex A	(normati	ive) Traffic Descriptor Matrix	.80
	nex B	(informa	tive) Methods for determining candidate streams for preemption	
۸۰۰			ive) The res@tspec property in the ContentDirectory Service	
AIII		•		
	C.1	Definiti	on of the XML Fragment	.84
Figure 1 — An example traffic stream				
Fig	ure 2	— A traf	fic stream with a constant bit rate	.24
			non-constant bit-rate traffic (left) can be viewed as a constant bit-rate constant bit-rate	24
uul	110 01	a mynich	- vonotant of 14to D (Hyllt)	

This is a preview - click here to buy the full publication

29341-17-11 © ISO/IEC:2011(E)

Table 1-1 — Abbreviations	5
Table 2-1 — State Variables	13
Table 2-2 — Meaning of <u>PolicyHolderConsultedType</u> parameter	18
Table 2-3 — Traffic Specification Parameters	21
Table 2-4 — Meaning of <u>RequestedQosType</u> parameter	22
Table 2-5 — Meaning of <u>Res<i>ulted</i>QosType</u> parameter	38
Table 2-6 — Event Moderation	39
Table 2-7 — Actions	39
Table 2-8 — Arguments for <u>RequestTrafficQos()</u>	40
Table 2-9 — Elements that MUST equal those of the original TrafficDescriptor	42
Table 2-10 — Default Priorities used by the QoS Manager based on 802.1D (Annex G)	44
Table 2-11 — Error Codes for <u>RequestTrafficQos()</u>	50
Table 2-12 — Elements that are allowed to be updated when calling UpdateTrafficQos()	52
Table 2-13 — Arguments for UpdateTrafficQos()	53
Table 2-14 — Error Codes for UpdateTrafficQos	58
Table 2-15 — Arguments for ReleaseTrafficQos	
Table 2-16 — Error Codes for ReleaseTrafficQos	59
Table 2-17 — Arguments for BrowseAllTrafficDescriptors	60
Table 2-18 — Error Codes for BrowseAllTrafficDescriptors	60
Table 2-19 — Arguments for GetQmCapabilities	60
Table 2-20 — Error Codes for GetQmCapabilities	61
Table 2-21 — Arguments for RequestExtendedTrafficQos	61
Table 2-22 — Error Codes for RequestExtendedTrafficQos	65
Table 2-23 — Arguments for UpdateExtendedTrafficQos	66
Table 2-24 — Error Codes for UpdateExtendedTrafficQos	69
Table 2-25 — Common Error Codes	70

29341-17-11 © ISO/IEC:2011(E)

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 17-11: Quality of Service Device Control Protocol – Level 3 – Quality of Service Manager Service

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-17-11 was prepared by UPnP Forum Steering committee¹, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

UPnP Forum Steering committee, UPnP Forum, 3855 SW 153rd Drive, Beaverton, Oregon 97006 USA. See also "Introduction"

This is a preview - click here to buy the full publication

29341-17-11 © ISO/IEC:2011(E)

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

1 Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0.

This service-type enables modeling of 'Quality of Service Manager' function capabilities. QosManager functionality is the combination of QosManager service and control point functionality that discovers and controls QosDevice and QosPolicyHolder services running on the network. The QosManager function is responsible for requesting, updating, releasing and in general controlling the Quality of Service assigned by networking devices to various traffic streams. The QosManager service is invoked from an UPnP Control Point to perform the functions related to setting up QoS2 for that traffic stream. Once the network is configured with respect to the QosManager service will hand back control to the Control Point. This service provides a mechanism for a Control Point to:

- Be agnostic of the QoS capabilities and associated details about the various QoS Devices on the network at the expense of potential network inefficiency.
- Abstract the tasks of setting up, modifying and revoking the QoS associated with every traffic stream
- QosManager:3 defines new capabilities to set up Parameterized QoS. Control Points may now request reservations for specific resources for the exclusive use of individual streams. Successful resource reservation ensures that streams will always have the bandwidth and other resources to transport time critical data.
- QosManager:3 defines a method for Control Points to request preemption of existing reservations on the UPnP-QoS network if necessary to admit a new stream.
- QosManager:3 supports a mechanism for providing a list of blocking streams to a Control Point so that it can handle preemption on its own, if desired.

A <u>QosManager</u> is a dual-role entity that exposes a <u>QosManager</u> Service to the Control Point while acting as a Control Point for the <u>QosPolicyHolder</u> Service and <u>QosDevice</u> Services running on the network. This document describes the components of the UPnP <u>QosManager</u> Service and the <u>Qos Manager</u>. The <u>Qos Manager</u> provides the Control Point functionality that discovers and controls <u>QosDevice</u> Services and the <u>Qos PolicyHolder</u> Services running on the network. Additional information concerning the <u>Qos Manager</u> may be found in:

- UPnP QoS Architecture document [QoS Architecture]
- UPnP QosDevice Service Definition Document [QOS DEVICE]
- UPnP QosPolicyHolder Service Definition Document [POLICY HOLDER]

1.1 References & Terms

1.1.1 References

Unless explicitly stated otherwise herein, implementation of the mandatory provisions of any standard referenced by this specification shall be mandatory for compliance with this specification. This clause lists the normative references used in this document and includes the tag inside square brackets that is used for each sub reference:

1.1.1.1 Normative References

[XML] - Extensible Markup Language (XML) 1.0 (Second Edition), T. Bray, J.Paoli, C. M. Sperberg McQueen, E Maler, eds. W3C Recommendations, 6 October 2000.

[DEVICE] - UPnP Device Architecture, version 1.0, UPnP Forum, July 20, 2006. Available at: http://upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0-20060720.pdf

-

² Quality of Service

— 4 — 29341-17-11 © ISO/IEC:2011(E)

Latest version available at: http://upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf

[POLICY HOLDER] – UPnP QosPolicyHolder:3 Service Document. Available at: http://www.upnp.org/specs/qos/UPnP-qos-QosPolicyHolder-v3-Service-20081130.pdf

Latest version available at: http://www.upnp.org/specs/qos/UPnP-qos-QosPolicyHolder-v3-Service.pdf

[QOS DEVICE] – UPnP QosDevice:3 Service Document. Available at: http://www.upnp.org/specs/qos/UPnP-qos-QosDevice-v3-Service-20081130.pdf Latest version available at: http://www.upnp.org/specs/qos/UPnP-qos-QosDevice-v3-Service.pdf

[QDA:3] - UPnP QosDevice:3 Underlying Technology Interface Addendum Available at: http://www.upnp.org/specs/qos/UPnP-qos-QosDevice-v3-Addendum-20081130.pdf

Latest version available at: http://www.upnp.org/specs/qos/UPnP-qos-QosDevice-v3-Addendum.pdf

[IANA Portnumbers] – *Port Numbers*, IANA, Available at: http://www.iana.org/assignments/port-numbers

[IANA Protocols] – Assigned Internet Protocol Numbers, IANA, Available at: http://www.iana.org/assignments/protocol-numbers

[RFC 2141] – *URN Syntax*, R. Moats, May 1997, Available at: http://www.ietf.org/rfc/rfc2141.txt

[RFC 2211] - Specification of the Controlled-Load Network Element Service, J. Wroclawski, September 1997. Available at: http://www.ietf.org/rfc/rfc2211.txt

[RFC 2212] - Specification of Guaranteed Quality of Service, S. Shenker et al., September 1997. Available at: http://www.ietf.org/rfc/rfc2212.txt

[RFC 3339] – Date and Time on the Internet: Timestamps, G. Klyne, July 2002. Available at: http://www.ietf.org/rfc/rfc3339.txt

[RFC 3927] – Dynamic Configuration of IPv4 Link-Local Addresses, Internet Engineering Task Force, S. Cheshire et al., March 2005. Available at: http://www.ietf.org/rfc/rfc3927.txt

[RFC 3986] —Uniform Resource Identifiers (URI): Generic Syntax, T. Berners-Lee et al., January 2005. Available at: ftp://ftp.rfc-editor.org/in-notes/rfc3986.txt

1.1.1.2 Informative References

This clause lists the informative references used in this document and includes the tag inside square brackets that is used for each sub reference:

[CDS:2] - UPnP AV ContentDirectory Service Definition document version 2.0. Available at: http://www.upnp.org/specs/av/UPnP-av-ContentDirectory-v2-Service.pdf Latest version available at: http://www.upnp.org/specs/av/UPnP-av-ContentDirectory-v2-Service-20060531.pdf

[IEEE 802.3-2002] – IEEE Std 802.3, 2000 Edition, Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, LAN MAN Standards Committee of the IEEE Computer Society, 2000.

This is a preview - click here to buy the full publication

29341-17-11 © ISO/IEC:2011(E)

— 5 **—**

[IEEE 802.1D] - IEEE Std 802.1D - 2004, Media Access Control (MAC) Bridges, IEEE Computer Society, 2004.

[QoS Architecture] – *UPnP QoS Architecture V3.0* Available at: http://www.upnp.org/specs/qos/UPnP-qos-Architecture-v3-20081130.pdf Latest version available at: http://www.upnp.org/specs/qos/UPnP-qos-Architecture-v3.pdf

[HPAV] – HomePlug AV Specfication v1.1, HomePlug Power Alliance, 2007.

[PACKETC] – PacketCable Specification Multimedia Specification, Available at: http://www.packetcable.com/downloads/specs/PKT-SP-MM-I03-051221.pdf

[RFC 1363] - A Proposed Flow Specification, C. Partridge, September 1992, Available at: http://www.ietf.org/rfc/rfc1363.txt